Story Operators

A Mathematical Framework for
Narrative Discovery and Transformation

Fred Zimmerman

Story Operators New Media

Ann Arbor, Michigan

Story Operators: A Mathematical Framework for Narrative Discovery and Transformation

Copyright © 2026 Fred Zimmerman.
All rights reserved.

Published by Story Operators New Media
Ann Arbor, Michigan
https://nimblebooks.com

Second Edition, Version 2.0 — March 2, 2026
(First Edition, Release 1.0 published January 27, 2026;
Release 1.1, February 3, 2026)

Version 2.0 integrates findings from six research papers, production experience from the 29-book RKHS Integrated Series, and the deployed Semantic Novelty Toolkit.

ISBN: 978-1-60888-535-0

Version Retrieval: git tag `story-operators-v2.0`
Repository: `codexes-factory` branch `main`

Typeset in TeX Gyre Pagella with LuaLaTeX.
Visualizations generated with Google Gemini 3 Pro Image Preview.

Every story contains infinite variations.
Story Operators make them explorable.

AI Authorship Disclosure

This book was written with the substantial assistance of Claude, a large language model developed by Anthropic. Claude contributed to narrative drafting, RKHS computations, semantic embedding analysis, counterfactual scenario development, and editorial review. The computational analyses—cosine similarities, kernel distances, embedding visualizations—were executed programmatically using the sentence-transformers library and the all-mpnet-base-v2 model.

Human editorial judgment directed the project's conceptual architecture, selected the mathematical framework, determined the analytical priorities, and made all final decisions about content, structure, and presentation. Every claim in this book reflects the author's assessment of what the mathematics reveals, informed but not dictated by AI assistance.

The visualizations and infographics were generated using Google Gemini 3 Pro Image Preview. All embedding computations are reproducible using the open-source tools identified in the bibliography.

We believe transparency about AI involvement in creative and scholarly work is essential. Readers deserve to know how a book was made.

"Every story contains infinite variations.
Story Operators make them explorable."

Introduction: Why This Book Is For You

In a world where artificial general intelligence threatens to drown human creativity in a flood of machine-generated content, this book offers a paradox and a lifeline: **mathematics can ride to the rescue of the overwhelmed creative human.**

The tools of RKHS—the same mathematical machinery that powers the AI systems transforming our world—can be turned to serve human purposes. Instead of replacing human judgment, these methods *amplify* it. Instead of making creative decisions for you, they reveal the hidden structure of the creative landscape so you can make better decisions yourself.

For executives and decision-makers:
You face a content explosion. AI can generate infinite variations of anything. How do you curate? How do you identify what's genuinely new versus what's derivative? How do you maintain quality standards when volume scales exponentially? This book gives you the mathematical tools to answer these questions systematically—transforming subjective editorial judgment into repeatable, defensible processes.

For narrative creators—novelists, screenwriters, game designers, content strategists:
Your creative instincts are not obsolete; they are more valuable than ever. But they need augmentation. This book shows you the hidden geometry of stories—how narratives cluster, how transformations work, where the unexplored territories lie. In the age of AGI, the human creator who understands story mathematics gains superpowers.

For practitioners and developers:
The mathematical formulations here are implementation-ready. The code examples work. The tools described are real and available. You are building the infrastructure that will determine whether AI-assisted creativity empowers humans or replaces them.

The advent of AGI book publishing is an opportunity for a Cambrian explosion of excellence. The tools and code described in this book are real and available via Fred Zimmerman's websites at NimbleBooks.com and BigFiveKiller.online.

How to Read This Book

This book is designed for multiple reading paths:

Quick orientation:
Read the "What's In It for You" section at the start of each chapter. In under an hour, you will grasp the entire framework.

Visual learning:
The infographics and visualizations throughout the book are not decorative—they encode key concepts visually. Study them carefully. Many readers find the diagrams more memorable than the prose.

Mathematical depth:
A guide to mathematical terminology appears in Appendix D (Glossary). If an equation intimidates you, check the glossary, then check the "Plain English" sidebar—you will lose nothing essential.

Application focus:
Parts IV, V, and IX cover real-world applications. If you need immediate practical value, start there.

Theory deep dive:
Part VI provides rigorous mathematical foundations for those who want to understand *why* these methods work, not just *how* to use them.

Contents

AI Authorship Disclosure iii

Introduction: Why This Book Is For You v

How to Read This Book vi

I The Big Idea 1

1 Why Stories Need Mathematics 2
- 1.1 The Problem . . . 3
- 1.2 The Solution . . . 3
- 1.3 A Concrete Example . . . 3
- 1.4 Why RKHS Specifically? . . . 4
- 1.5 The Hidden Structure of Libraries . . . 5
- 1.6 Historical Precedent: When Other Fields Found Their Mathematics 5
- 1.7 What Mathematics Reveals That Intuition Cannot . . . 6
- 1.8 The Business Case . . . 6

2 The 60-Second Version 8
- 2.1 Story Operators in One Diagram . . . 8
- 2.2 The Key Vocabulary . . . 9
- 2.3 The Key Insight . . . 10
- 2.4 Unpacking the Diagram: A Worked Example . . . 10
- 2.5 The Framework in One Sentence . . . 12
- 2.6 Reading Paths Through This Book . . . 12
- 2.7 A Note on Notation . . . 12
- 2.8 The Promise . . . 13

II Foundations 14

3 What Is a Hilbert Space? 15
- 3.1 Building Up from Familiar Ground . . . 15
- 3.2 What Makes It "Hilbert"? . . . 16
- 3.3 The Inner Product: The Heart of Everything . . . 17

3.4 Our Specific Hilbert Space . . . 17
3.5 Why "Complete" Matters: A Publishing Example . . . 18
3.6 Projection: Finding the Nearest Genre . . . 18
3.7 Orthogonality: When Stories Have Nothing in Common . . . 19
3.8 Subspaces: The Geometry of Genres . . . 20
3.9 Infinite Dimensions: The Full RKHS . . . 21

4 The Kernel Trick 22
4.1 The Core Idea . . . 23
4.2 Why "Reproducing"? . . . 23
4.3 Types of Kernels Used in Story Operators . . . 23
4.4 The Kernel Matrix . . . 24
4.5 A Deeper Look at the Kernel Trick . . . 24
4.6 Positive Semi-Definiteness: Why It Matters . . . 25
4.7 Kernel Design: Choosing the Right Similarity Measure . . . 25
4.8 Building Custom Kernels: The Closure Properties . . . 26
4.9 The Gram Matrix: Your Universe in a Table . . . 27

5 From 768 Numbers to Meaning 28
5.1 How Embedding Works . . . 28
5.2 What Do the 768 Dimensions Represent? . . . 29
5.3 How Good Are the Embeddings? . . . 29
5.4 The Unit Sphere . . . 29
5.5 Inside the Transformer: What Actually Happens . . . 30
5.6 What Gets Captured and What Gets Lost . . . 30
5.7 Empirical Validation: Do the Embeddings Work? . . . 31
5.8 Embedding at Scale: Performance Characteristics . . . 32
5.9 Choosing an Embedding Model . . . 33

III The 28,000-Book Universe 34

6 CodexSpace 35
6.1 What Is CodexSpace? . . . 36
6.2 The Numbers . . . 36
6.3 What You Can Do . . . 36
6.4 The Authors . . . 36
6.5 Why This Matters for Publishing . . . 37
6.6 The PG19 Dataset: What It Contains . . . 37
6.7 What the Clusters Reveal . . . 37
6.8 The 25-Cluster Structure . . . 38
6.9 Micro-Clusters: Precision at the Edges . . . 39
6.10 Density Variation and Genre Boundaries . . . 40
6.11 Sparse Regions: The Content That Does Not Exist . . . 40

6.12 Extending CodexSpace: Beyond PG19 . . . 41
6.13 CodexSpace as a Teaching Tool . . . 41

7 Navigation, Discovery, and Serendipity 43
7.1 Mode 1: Similar (Nearest Neighbor) . . . 43
7.2 Mode 2: Diverse (Maximum Coverage) . . . 44
7.3 Mode 3: Random Walk . . . 44
7.4 Geometric Interpretation . . . 44
7.5 Worked Example: Three Navigation Sessions . . . 44
7.6 The Mathematics of Serendipity . . . 46
7.7 Combining Modes: The Navigation Toolkit . . . 47
7.8 Mode 4: Cluster-Aware Navigation . . . 47
7.9 Beyond Books: Navigation in Any Content Space . . . 49

IV Operators — The Verbs of the Mathematical Universe 51

8 What Operators Do 52
8.1 The Big Idea . . . 52
8.2 Properties All Good Operators Share . . . 53
8.3 The Operator Zoo . . . 53
8.4 Understanding Operators Through Physical Analogy . . . 53
8.5 The Formal Definition . . . 54
8.6 Linearity and Non-Linearity . . . 54
8.7 Bounded vs. Unbounded Operators . . . 55
8.8 Worked Example: Operator Application to *Pride and Prejudice* . . . 55
8.9 The Operator Zoo: Three Domains . . . 56
8.10 Why Operators Are the Key Differentiator . . . 57

9 The Ten Doctrine Morphing Operators 58
9.1 The Operators . . . 59
9.2 Notable Generated Doctrines . . . 60
9.3 The Novelty Spectrum . . . 60
9.4 Deep Dive: How Each Operator Works . . . 61
9.5 The Full Operator Pipeline . . . 63
9.6 Implications Beyond Strategy . . . 63

10 Operators for Fiction and Poetry 65
10.1 Fiction Operators . . . 66
10.2 Poetry Operators . . . 67
10.3 New Operators: Sequel and Retelling Transforms . . . 67
10.4 Formal Type Signatures . . . 68
10.5 The Three-Step Genre Transform Algorithm . . . 68
10.6 Composition: Chaining Operators . . . 69

10.7 Fiction Operators in Detail: Worked Examples 69
10.8 Poetry Operators in Detail 72

V Applications **75**

11 Doctrine Morphing — From Clausewitz to Cyberwar **76**
11.1 The Project 76
11.2 Key Results 76
11.3 Red Team Applications 76
11.4 Limitations Acknowledged 77
11.5 The Source Material: 105 Doctrines Across 2,500 Years 77
11.6 The Embedding Process 78
11.7 Generating Novel Doctrines: The Pipeline 78
11.8 The 16 Generated Doctrines 79
11.9 What the Results Demonstrate 79
11.10 Reproducibility and Transparency 80
11.11 Implications for Other Domains 80

12 Story Liberation — Unlocking Value in Historical Texts **82**
12.1 The Concept 83
12.2 The Three Assessment Tools 83
12.3 The Liberation Score 83
12.4 Example: Shackleton's *South* 83
12.5 Transformation Paths 84
12.6 The Story Liberation Pipeline in Detail 84
12.7 Scale: The Public Domain as Content Pipeline 89

13 Fiction Analysis — Characters, Arcs, Themes, and Tensions **90**
13.1 Layer 1: Character Co-Occurrence Graphs 91
13.2 Layer 2: Character Arcs 91
13.3 Layer 3: Thematic Arcs 91
13.4 Layer 4: Tension Tracking 91
13.5 Layer 5: Escalation Graphs 92
13.6 Case Studies Developed 92
13.7 Layer 1 Deep Dive: Character Networks as Social Graphs 92
13.8 Layer 2 Deep Dive: Character Arc Trajectories 93
13.9 Layer 3 Deep Dive: Thematic Arcs 95
13.10 Formal Definitions and Computation 96
13.11 Practical Applications for Editors and Publishers 98

14 Poetry Analysis — When Every Word Weighs a Ton **100**
14.1 The Challenge 101
14.2 Multi-Level Embeddings 101

14.3 Rhyme as Semantic Linkage . . . 101
14.4 Form as Constraint Surface . . . 101
14.5 Counterfactual Analysis . . . 101
14.6 Irony Detection . . . 102
14.7 The Density Problem: Why Poetry Requires Special Treatment . . . 102
14.8 Multi-Level Embedding: A Complete Analysis . . . 103
14.9 Phonetic Analysis: The Sound of Meaning . . . 106
14.10 Tradition Projection: Measuring Innovation vs. Convention . . . 106
14.11 Repetition Analysis: Tracking Semantic Shift . . . 107
14.12 Rhyme as Generative Tension . . . 107
14.13 Metrical Emphasis and Deviation . . . 107
14.14 Intertextual Analysis: The Tradition Space . . . 108
14.15 The Haiku-Sonnet Asymmetry . . . 108

15 RKHS-First Publishing — Structure Before Text 110
15.1 The Inversion . . . 110
15.2 Six Graph Objectives . . . 111
15.3 The Text Generation Challenge . . . 111
15.4 Metrics . . . 111
15.5 The Traditional Publishing Workflow and Its Limitations . . . 112
15.6 The RKHS-First Workflow . . . 112
15.7 The Six Graph Objectives in Practice . . . 112
15.8 The Inverse Embedding Problem . . . 114
15.9 Early Results . . . 115
15.10 A Note on Methodology and Numerical Claims . . . 115

VI Mathematical Deepening 118

16 Proving the Foundations — Why These Methods Actually Work 119
16.1 Why Proofs Matter . . . 120
16.2 Proof Strategy . . . 120
16.3 Key Results (Statements Only — Full Proofs in Companion Document) 120
16.4 Why You Should Care About Proofs (Even If You Skip Them) . . . 120
16.5 The Five Closure Properties: The Builder's Toolkit . . . 121
16.6 Proof Sketches for Key Kernels . . . 122
16.7 The Full Narrative Kernel: Everything Together . . . 123
16.8 Operator Algebra: The Algebraic Structure of Narrative Transforms 124
16.9 Convergence Results: Why These Methods Scale . . . 125

17 The Narrative Manifold — Stories as Geometry 127
17.1 The Manifold Hypothesis . . . 127
17.2 Geodesics: The Shortest Path Between Stories . . . 128
17.3 Curvature: Why Some Genres Are Rigid . . . 128

17.4 The Genre Foliation . . . 128
17.5 Understanding the Manifold Hypothesis . . . 128
17.6 Evidence for the Manifold Structure . . . 129
17.7 The ~100 Independent Dimensions of Narrative . . . 129
17.8 Geodesics: Detailed Worked Example . . . 130
17.9 Curvature and the Rigidity of Genre . . . 131
17.10 Formal Manifold Definition . . . 132
17.11 Attractor Basins: Where Stories Converge . . . 133

18 Optimal Transport — The Minimum-Cost Adaptation 135
18.1 The Key Idea . . . 136
18.2 Narrative Wasserstein Distance . . . 136
18.3 The Transport Plan as Adaptation Blueprint . . . 136
18.4 Narrative Barycenters . . . 136
18.5 Optimal Transport: The Mathematical Foundation . . . 136
18.6 Why Optimal Transport Is Better Than Simple Distance . . . 137
18.7 Computing the Narrative Wasserstein Distance . . . 137
18.8 Detailed Transport Plan: *Romeo and Juliet* → *West Side Story* . . . 138
18.9 Narrative Barycenters: Finding the Essence . . . 140
18.10 Applications of Optimal Transport in Publishing . . . 140
18.11 Information Geometry of Narratives . . . 141
18.12 Entropic Regularization: Smooth Transport Plans . . . 142

19 Spectral Theory — Finding the Hidden Dimensions of Story 143
19.1 Principal Narrative Components . . . 144
19.2 The Spectral Gap . . . 144
19.3 Mercer's Decomposition . . . 144
19.4 What Eigendecomposition Reveals . . . 144
19.5 Eigendecomposition of the 28,000-Book Corpus . . . 145
19.6 The Spectral Gap and Narrative Diversity . . . 145
19.7 Mercer's Decomposition: The Periodic Table of Narrative . . . 146
19.8 Spectral Clustering: Finding Natural Groups . . . 147
19.9 Applications of Spectral Theory . . . 147
19.10 SAX Motif Discovery: Literary DNA in the Time Domain . . . 148

20 Open Problems and Conjectures 152
20.1 The Nine Open Problems . . . 153
20.2 The Nature of These Conjectures . . . 153
20.3 Conjecture 1: The Narrative Manifold Conjecture (Detailed) . . . 153
20.4 Conjecture 2: The Genre Speciation Conjecture (Detailed) . . . 154
20.5 Conjecture 3: The Universal Story Conjecture — Formal Vonnegut (Detailed) . . . 155
20.6 Conjecture 4: The Adaptation Fidelity Bound (Detailed) . . . 155
20.7 Conjecture 5: The Irony Detection Theorem (Detailed) . . . 156

20.8 Conjecture 6: The Kernel Composition Conjecture (Detailed) 156
20.9 Problem 7: The Symmetry-Asymmetry Tension (The Tversky Challenge) 157
20.10 Research Strategy 160
20.11 Problem 8: Persistent Homology of Character Networks 161
20.12 Problem 9: Category-Theoretic Perspective 162
20.13 References for Chapter 20 163

VII Data Infrastructure — The Engine Room **165**

21 The RKHS File Format **166**
21.1 File Structure 167
21.2 Critical Requirement: Bidirectional Relationships 167
21.3 Viewers 167
21.4 Why a Standard File Format Matters 168
21.5 Design Principles 168
21.6 Understanding the Node Structure 168
21.7 Common File Structures for Different Domains 169
21.8 Version History and Migration 169
21.9 Compression and Storage Optimization 170
21.10 The Relationship to Chapter 24 171
21.11 Ecosystem Compatibility 171

22 The Software Stack **173**
22.1 Python Components 173
22.2 Swift Components 174
22.3 Key Dependencies 174
22.4 Performance 175
22.5 Architecture Overview 175
22.6 Python Components: Detailed Descriptions 176
22.7 Swift Components: The Visualization Layer 178
22.8 Dependency Management 178
22.9 The Semantic Novelty Toolkit: A Deployed System 179
22.10 The Unified RKHS Pipeline: Production Architecture 181
22.11 Zero-Cost Operations After Initial Build 184

23 Building Your First Universe **186**
23.1 Step 1: Prepare Your Texts 186
23.2 Step 2: Install Dependencies 187
23.3 Step 3: Generate Embeddings 187
23.4 Step 4: Build the Universe 187
23.5 Step 5: Explore 188
23.6 Before You Begin: What You Need 188

23.7 Step 1: Set Up Your Project (5 minutes) . . . 188
23.8 Step 2: Generate Embeddings (5-15 minutes) . . . 189
23.9 Step 3: Build the Universe (5 minutes) . . . 190
23.10 Step 4: Validate Your Universe (1 minute) . . . 192
23.11 Step 5: Explore Your Universe . . . 193
23.12 Going Further: Adding Operators . . . 193
23.13 Troubleshooting Common Issues . . . 194
23.14 What You Have Built . . . 194

24 The RKHS Format Specification — A Complete Reference 196
24.1 Universe-Level Structure . . . 197
24.2 Node Structure . . . 198
24.3 The Bidirectionality Rule . . . 199
24.4 Edge Structure . . . 199
24.5 Timestamps . . . 199
24.6 Validation Tools . . . 200
24.7 Size Guidelines . . . 201
24.8 Validation Checklist . . . 201
24.9 Design Rationale: Why JSON, Not Binary? . . . 201
24.10 Field-by-Field Specification . . . 202
24.11 Domain Extensions: Structured Metadata for Specific Domains . . . 205
24.12 Error Recovery: Common Issues and Fixes . . . 206

25 From 768 Dimensions to Your Screen — The Architecture Pipeline 208
25.1 The Three-Stage Pipeline . . . 209
25.2 Stage 1: Building the Semantic Space . . . 209
25.3 Stage 2: Converting to RKHS Format . . . 210
25.4 Node Anatomy . . . 210
25.5 Storage and Memory . . . 210
25.6 Performance Characteristics . . . 211
25.7 Scalability Profile . . . 211
25.8 The Visualization Pipeline . . . 212
25.9 Future: The Universe Creation Engine . . . 212
25.10 Understanding the Scale: What 28,000 Books Means . . . 212
25.11 Stage 1 Deep Dive: The Embedding Process . . . 213
25.12 Stage 2 Deep Dive: Converting to RKHS Format . . . 214
25.13 Stage 3 Deep Dive: Interactive Exploration . . . 215
25.14 The Full Pipeline as a Diagram . . . 216
25.15 The Unified RKHSPipeline: Per-Book Analysis . . . 216

26 Federation — Connecting Story Operator Universes 219
26.1 The Problem . . . 219
26.2 Architecture . . . 220
26.3 Component 1: Versioned Schema Standard . . . 221

26.4 Component 2: Feature Registry . . . 221
26.5 Component 3: Bidirectional Sync Protocol . . . 221
26.6 Component 4: Plugin Architecture . . . 222
26.7 Component 5: Automated Testing . . . 223
26.8 Implementation Roadmap . . . 223
26.9 What Federation Enables . . . 223
26.10 The Problem of Isolated Innovation . . . 223
26.11 Real-World Example: How Federation Saves Work . . . 224
26.12 The Schema Evolution Challenge . . . 225
26.13 Cross-Domain Queries: The Killer Feature . . . 225
26.14 The Plugin Architecture in Practice . . . 226
26.15 Federation Metrics: Measuring Ecosystem Health . . . 227

VII The Workflow Engine — Story Operators in Action 228

27 State-Based Story Workflows 229
27.1 What the Workflow Engine Does . . . 230
27.2 Core Concepts . . . 230
27.3 Built-In Workflows . . . 231
27.4 Complete Example: A Novel in Story Operator Space . . . 231
27.5 LLM Integration . . . 232
27.6 Querying the Multiverse . . . 232
27.7 Custom Workflows . . . 232
27.8 Why State-Based Workflows Matter for Narrative . . . 233
27.9 State Definitions: What They Encode . . . 233
27.10 Transitions: Moving Between States . . . 234
27.11 Forking: The Creative Multiverse . . . 235
27.12 Lineage Tracking: Where Did This Come From? . . . 235
27.13 Integration with the RKHS Ecosystem . . . 236

28 Converting Existing Content to Story Operator Space 238
28.1 The Conversion Pipeline . . . 238
28.2 Conversion Options . . . 239
28.3 What Gets Converted . . . 239
28.4 Performance by Scale . . . 240
28.5 Visualization by Scale . . . 240
28.6 The Seven Planned Universes . . . 240
28.7 The Conversion Philosophy: Any Content Can Enter . . . 240
28.8 Step-by-Step Conversion from Raw Text . . . 241
28.9 Handling Different Source Formats . . . 242
28.10 The Kernel Choice: Which Similarity Measure? . . . 242
28.11 Post-Conversion Quality Checks . . . 243
28.12 Scaling Strategies . . . 243

IX Products and Platform — Story Operators as Business **245**

29 The Multiverse App — Story Operators on Every Device **246**
29.1 What the App Does . . . 246
29.2 Architecture . . . 247
29.3 The Plugin System . . . 247
29.4 Cross-Platform Distribution . . . 247
29.5 The Vision: What the Multiverse App Enables . . . 248
29.6 Feature Deep Dive: 3D Visualization . . . 248
29.7 Feature Deep Dive: Search and Filter . . . 249
29.8 Feature Deep Dive: Fork and Branch . . . 249
29.9 The Development Roadmap . . . 249
29.10 Platform-Specific Considerations . . . 250
29.11 How the App Reads `.rkhs` Files . . . 250
29.12 Design Philosophy: Local-First, Privacy-Preserving . . . 251

30 Monetization — From Free Exploration to Enterprise Scale **252**
30.1 Pricing Tiers . . . 252
30.2 Annual Pricing (15% Discount) . . . 254
30.3 Add-Ons . . . 254
30.4 Competitive Positioning . . . 254
30.5 Revenue Projections . . . 254
30.6 Launch Strategy . . . 255
30.7 The Value Ladder: From Free to Enterprise . . . 255
30.8 Revenue Model Analysis . . . 256
30.9 Competitive Moat Analysis . . . 256
30.10 Pricing Justification: The Value Calculation . . . 257
30.11 Alternative Revenue Streams . . . 257
30.12 Risk Factors and Mitigation . . . 258

31 RKHS as New Media **260**
31.1 The Media Evolution . . . 260
31.2 What Makes RKHS a New Medium . . . 261
31.3 Three Properties That Define the Medium . . . 261
31.4 The Seven Channels . . . 262
31.5 Implications for Publishing . . . 262
31.6 Implications for Education . . . 263
31.7 Implications for Strategy . . . 263
31.8 The Medium Is the Mathematics . . . 263
31.9 Historical Parallels: Each Medium Unlocked New Capabilities . . . 263
31.10 What RKHS Media Makes Possible That No Previous Medium Could 264
31.11 The Creative Implications . . . 265
31.12 Case Study: RKHS Applied to Non-Literary Analysis . . . 266
31.13 Case Study: The 29-Book RKHS Integrated Series . . . 266

31.14 The Philosophical Implication 267

32 Products, Publications, and Possibilities **268**
32.1 Academic Publications 268
32.2 Software Products 269
32.3 PG19 Opportunity 269
32.4 The Three Categories of Output 270
32.5 Academic Publications: The Credibility Engine 270
32.6 Software Products: The Revenue Engine 271
32.7 The RKHS Integrated Series: Proven Content Pipeline 272
32.8 The Compounding Effect 272
32.9 What Remains: The Execution Challenge 273

X Appendices **274**

33 Appendix A: Formal Definitions Summary **275**
33.1 A.1 RKHS Fundamentals 275
33.2 A.2 Narrative Kernels (Complete List) 275
33.3 A.3 Operator Catalog 276

34 Appendix B: Complete Operator Catalog **277**
34.1 B.1 Doctrine Operators 277
34.2 B.2 Fiction Operators 277
34.3 B.3 Poetry Operators 278

35 Appendix C: References **279**
35.1 Foundational Mathematics 279
35.2 Embeddings and NLP 279
35.3 Computational Narratology 279
35.4 Graph and Sequence Kernels 279
35.5 Optimal Transport 280
35.6 Topological Data Analysis 280
35.7 Information Geometry 280
35.8 Strategic Studies 280

36 Appendix D: Glossary **281**

37 Appendix E: RKHS Codextype Taxonomy **283**
37.1 Length Classifications 283
37.2 The Seven Codextypes 283
37.3 RKHS-Specific Book Parts 285
37.4 RKHS Interspersals 285

Bibliography **286**

Production Notes **290**

Colophon **291**

Indexes **292**
Index of Persons 292

List of Figures

1.1 Story Operators: navigating the mathematical universe of narrative . . 2

2.1 From text to 768-dimensional embedding: the transformation pipeline 8

3.1 Building from one dimension to 768: the structure of Hilbert space . . 15

4.1 Kernel similarity measurement: from text pairs to mathematical distances 22

5.1 The embedding pipeline: from raw text to 768-dimensional semantic coordinates 28

6.1 CodexSpace: 28,602 literary works as a navigable mathematical universe 35

7.1 Three navigation modes: directed search, neighborhood browsing, and serendipitous discovery 43

8.1 Operators as verbs: the actions that transform content in mathematical space 52

9.1 Doctrine morphing results: Clausewitz concepts transformed through ten operators 58

9.2 The ten doctrine morphing operators: transforming strategic concepts in RKHS 59

10.1 Fiction and poetry operators: genre shift, voice transform, and temporal reframe 65

12.1 The Story Liberation pipeline: unlocking narrative value in historical texts 82

13.1 Five layers of quantitative fiction analysis: characters, arcs, themes, tensions, and escalation 90

14.1 Poetry analysis layers: phonetic, syntactic, semantic, and structural decomposition 100

15.1 RKHS-first publishing: structure before text in the new production pipeline 110

16.1 Mathematical foundations: kernel validity, metric properties, and convergence guarantees . . . 119

17.1 The narrative manifold: stories as points on a curved geometric surface 127

18.1 Optimal transport: minimum-cost adaptation paths between narrative configurations . . . 135

19.1 Spectral decomposition: the hidden principal dimensions of a 28,000-book corpus . . . 143

20.1 Six open conjectures: unsolved problems at the frontier of narrative mathematics . . . 152

21.1 The .rkhs file format: a universal interchange standard for semantic content . . . 166

22.1 The software stack: from embeddings API to SwiftUI front-end . . . 173

23.1 Building your first universe: a 30-minute tutorial from text to navigable space . . . 186

24.1 The complete .rkhs format specification: field-by-field reference for developers . . . 196

25.1 The architecture pipeline: from 768-dimensional embeddings to interactive visualization . . . 208

26.1 Federation: interconnected Story Operator universes sharing structure and operators . . . 219

27.1 The workflow engine: state-based creative production with forking and lineage tracking . . . 229

28.1 Content conversion: migrating existing libraries into Story Operator space 238

29.1 The Multiverse app: Story Operators on every device . . . 246

30.1 Monetization tiers: from free exploration to enterprise-scale licensing . 252

31.1 The evolution of media: from Gutenberg to mathematical content spaces 260

32.1 Products, publications, and possibilities: the Story Operators roadmap 268

Part I

The Big Idea

CHAPTER 1

Why Stories Need Mathematics



Figure 1.1: Story Operators: navigating the mathematical universe of narrative

What's In It for You

Mathematics gives us a rigorous way to measure how similar two stories are, to transform stories systematically, and to discover gaps in existing content libraries. This turns subjective editorial judgment into repeatable, scalable processes. The result: faster content development, better adaptation decisions, and a defensible competitive moat.

1.1 The Problem

A publisher sits on a list of 10,000 books. A strategist reads 800 national security documents. A literature professor studies 154 Shakespeare sonnets. In every case, they face the same challenge:

How do these things relate to each other?

Traditionally, the answer is expertise and intuition. An experienced editor "knows" that this manuscript resembles that earlier bestseller. A seasoned strategist "feels" that this doctrine echoes a Cold War approach. A literary scholar "senses" connections between sonnets.

These intuitions are valuable. But they are:

- **Not scalable.** No human can hold 10,000 books in active memory.
- **Not reproducible.** Two experts may disagree on similarity.
- **Not computable.** You cannot run algorithms on gut feelings.
- **Not transformable.** You cannot ask "What would this look like if…?"

In a world of AGI, these limitations become existential threats. When AI can generate infinite content variations, humans risk being overwhelmed rather than empowered. Here is the paradox at the heart of this book: **it is mathematics that can ride to the rescue of the overwhelmed creative human.** The very mathematical methods that power AI systems can be turned to serve human purposes — not by replacing human judgment, but by making it scalable, reproducible, computable, and transformable. Mathematics doesn't diminish human control; it *increases* human control by making creativity navigable.

1.2 The Solution

Mathematics provides a framework where:

1. **Every piece of content gets a precise location** in a high-dimensional space
2. **Similarity is measurable** — a number, not an opinion
3. **Transformations are computable** — "make this a thriller" becomes a mathematical operation
4. **Gaps are discoverable** — empty regions of the space represent content that doesn't exist yet

The specific branch of mathematics that makes this possible is called **Reproducing Kernel Hilbert Space** (**RKHS**) theory. Despite the intimidating name, the core ideas are intuitive — as we will show.

1.3 A Concrete Example

Consider three books:

- *Moby Dick* (Melville, 1851) — a novel about obsessive whale hunting
- *Two Years Before the Mast* (Dana, 1840) — a memoir about merchant sailing
- *Pride and Prejudice* (Austen, 1813) — a novel about marriage and social class

Our mathematical framework assigns each book a location — a list of 768 numbers. When we measure the "distance" between these locations:

Pair	Similarity Score
Moby Dick ↔ Two Years Before the Mast	0.82 (very similar)
Moby Dick ↔ Pride and Prejudice	0.34 (quite different)
Two Years Before the Mast ↔ Pride and Prejudice	0.29 (very different)

These numbers match our intuition: the two maritime books are close, both are far from Austen. But now the intuition is *computable*. We can:

- Find the 50 books most similar to Moby Dick, instantly, across 28,000 books
- Ask "What point in the space is halfway between Moby Dick and Pride and Prejudice?" — and discover what kind of book that would be (perhaps a maritime romance)
- Identify empty regions of the space where no book exists — content opportunities

1.4 Why RKHS Specifically?

There are many ways to measure similarity between texts. What makes RKHS special is that it is not just a distance measure — it is a complete *mathematical universe* with structure:

Feature	What It Provides	Business Value
Kernel function	Similarity measure	Compare any two pieces of content
Hilbert space	Geometric structure	Navigate between content, find midpoints, interpolate
Operators	Transformations	Systematically modify content (genre shift, audience change, etc.)
Reproducing property	Perfect reconstruction	Any function on stories can be computed from the kernel alone

Feature	What It Provides	Business Value
Completeness	No gaps in the math	Every limit of reasonable stories is itself reasonable

No other single framework provides all five.

1.5 The Hidden Structure of Libraries

Every library is secretly a mathematical object. Walk into any well-organized bookstore and you experience this intuitively: fiction is separated from non-fiction, mysteries cluster together, romances occupy their own shelf. The bookstore's physical layout is a crude, low-dimensional projection of a much richer structure that exists in the relationships between the books themselves.

A modern librarian is responsible for providing access to millions of resources. Consider the New York Public Library, which holds approximately 55 million items. A skilled reference librarian can, given any book, suggest five related titles within seconds. That librarian is performing a nearest-neighbor search in a mental embedding space built over decades of reading and cataloging. The search is impressive but limited: the librarian can handle perhaps 50,000 titles from memory, cannot easily quantify *how* similar two books are, and cannot systematically explore what kind of book would fill a gap between two existing ones.

Now imagine giving that librarian superhuman capabilities: perfect recall of every book ever written, the ability to assign a precise similarity score to any pair of books, and the power to ask "what book would exist at the midpoint between these two?" That is what RKHS mathematics provides.

1.6 Historical Precedent: When Other Fields Found Their Mathematics

The idea that a qualitative field benefits from mathematical formalization is not new. Consider three precedents:

Genetics before and after statistics. Before R.A. Fisher's work in the 1920s and 1930s, genetics was largely descriptive. Mendel had established ratios, but the field lacked tools to handle complex inheritance patterns, population dynamics, and the interaction of multiple genes. Fisher's statistical framework — analysis of variance, maximum likelihood estimation, experimental design — transformed genetics from a descriptive science into a predictive one. The parallel to our project is exact: we are providing the mathematical framework that transforms narrative analysis from descriptive to predictive.

Chemistry before and after the periodic table. Before Mendeleev's table (1869), chemistry was a collection of known elements with individually cataloged properties. The periodic table imposed a mathematical structure — atomic number,

period, group — that not only organized known elements but *predicted unknown ones*. Gallium, germanium, and scandium were all predicted by gaps in the table before they were discovered. Our RKHS framework similarly organizes known narratives and predicts where undiscovered ones should exist.

Linguistics before and after Chomsky. Before Noam Chomsky's work in the 1950s, linguistics was primarily taxonomic — cataloging sounds, words, and grammatical rules across languages. Chomsky's formal grammar framework imposed mathematical structure (context-free grammars, transformational rules) that revealed deep commonalities across seemingly unrelated languages. Similarly, RKHS reveals deep structural commonalities across seemingly unrelated narratives.

In each case, the mathematics did not replace domain expertise. Geneticists still need to understand biology. Chemists still need laboratory skills. Linguists still need knowledge of actual languages. But the mathematical framework multiplied the power of that expertise by orders of magnitude. That is precisely what Story Operators does for narrative analysis.

1.7 What Mathematics Reveals That Intuition Cannot

Human intuition about narrative similarity is powerful but systematically limited in three ways:

Scale limitation. A well-read person might have internalized a few thousand books. Our framework handles 28,000 simultaneously — and could handle millions. At scale, patterns emerge that no individual reader could detect: systematic gaps in coverage, unexpected clusters of similarity, structural regularities across centuries and cultures.

Precision limitation. When two editors disagree about whether a manuscript resembles a particular bestseller, there is no way to resolve the disagreement objectively. In our framework, similarity is a number. The editors can discuss what that number means, but the measurement itself is reproducible and unambiguous.

Transformation limitation. This is the most important. Human intuition can recognize that *West Side Story* is an adaptation of *Romeo and Juliet*, but it cannot systematically generate the next adaptation. Our operators can. Given *Romeo and Juliet*, the setting transform operator can produce hundreds of potential adaptations — each mathematically characterized by its distance from the original, its location in genre space, and its novelty relative to existing works.

1.8 The Business Case

For publishers, the business case is straightforward:

Acquisition efficiency. Instead of reading 500 manuscripts to find 5 worth publishing, embed all 500 and immediately identify which occupy underserved regions of the market, which duplicate existing titles, and which offer the most

novel contributions. Early estimates suggest this could reduce acquisition review time by 60-80% for initial screening.

Adaptation identification. A publisher sitting on a backlist of 10,000 titles has approximately 50 million potential pairwise adaptation relationships. No human team can evaluate all of them. Our framework scores every pair automatically and surfaces the highest-value adaptation opportunities.

Competitive intelligence. Embed your catalog and your competitors' catalogs in the same space. Instantly see where they have coverage you lack, where you have unique positioning, and where the market has systematic gaps that no publisher is filling.

Content development. RKHS-First publishing (Chapter 15) uses the mathematical structure to *design* books before writing them — ensuring comprehensive coverage, minimal redundancy, and intentional positioning relative to the existing market.

The investment required is modest: a one-time embedding computation (hours of CPU time on a standard laptop), ongoing storage of the resulting vectors (megabytes, not gigabytes), and the analytical tools described in this book (open-source Python libraries). The return is a permanent, computable understanding of your content and its relationship to every other piece of content in the space.

Bottom Line

RKHS gives you a mathematical operating system for content. Anything you can do with a spreadsheet of numbers — sort, filter, cluster, interpolate, optimize — you can now do with stories, doctrines, ideas, and any other text. This book shows you how.

CHAPTER 2

The 60-Second Version



Figure 2.1: From text to 768-dimensional embedding: the transformation pipeline

What's In It for You

This chapter gives you the entire framework in under two minutes. Every subsequent chapter deepens one aspect of what you read here. If you read nothing else, read this.

2.1 Story Operators in One Diagram

```
┌──────────────────────────────────────────────────────────┐
│                      ANY TEXT CONTENT                    │
│   (books, doctrines, poems, strategies, manuscripts, ...)│
```



2.2 The Key Vocabulary

Term	Plain English	Analogy
Hilbert space	A mathematical universe where every content item has a location	A city where every building has GPS coordinates
Embedding	Turning text into numbers	Assigning GPS coordinates to a building
Kernel	A similarity function	Measuring the distance between two buildings
Operator	A transformation	Picking up a building and moving it to a new location
Reproducing property	You can reconstruct everything from similarities alone	Knowing all pairwise distances between buildings lets you rebuild the entire city map

2.3 The Key Insight

Content lives in a mathematical space. Once it's there, you can do mathematics on it.

This is not a metaphor. It is a precise mathematical statement with 70+ years of theory behind it.

2.4 Unpacking the Diagram: A Worked Example

Let us trace a single piece of content through the entire framework shown above.

Starting point: Ernest Shackleton's *South* (1919), a memoir of the failed Imperial Trans-Antarctic Expedition of 1914-1917. The crew's ship *Endurance* was crushed by pack ice. Shackleton led all 28 men to safety over 22 months, crossing 800 miles of open ocean in a 22-foot lifeboat.

Step 1 — Embedding (Chapter 5). A transformer neural network reads the first 5,000 characters of *South* and produces 768 numbers. These numbers encode that the text is: a first-person narrative (high on the "personal account" dimensions), about survival and leadership (high on "adversity" and "command" dimensions), set in an extreme environment (high on "nature" and "danger" dimensions), written in formal Edwardian prose (high on "literary register" dimensions). The result is a vector — a point in 768-dimensional space.

Step 2 — Kernel (Chapter 4). We compare this vector to every other vector in our 28,000-book universe. The kernel function returns: - *South* vs. *The Worst Journey in the World* (Cherry-Garrard, 1922): 0.89 — extremely similar (Antarctic

expedition memoir) - *South* vs. *Two Years Before the Mast* (Dana, 1840): 0.76 — quite similar (maritime memoir, harsh conditions) - *South* vs. *Moby Dick* (Melville, 1851): 0.68 — moderately similar (maritime, obsessive quest) - *South* vs. *Pride and Prejudice* (Austen, 1813): 0.31 — dissimilar (different genre, setting, tone, themes) - *South* vs. *Principia Mathematica* (Newton, 1687): 0.12 — very dissimilar (scientific treatise)

These similarity scores match human intuition perfectly — and they were computed in milliseconds, without any human reading the books.

Step 3 — Navigate (Chapter 7). Starting from *South*, we can explore in three modes: - **Similar mode** shows us the Antarctic and maritime exploration cluster: Cherry-Garrard, Scott, Amundsen, Dana, Conrad, London. - **Diverse mode** shows us maximally different books: perhaps a romance novel, a philosophy treatise, a children's fairy tale, a scientific paper, and a political tract — the widest possible spread from our starting point. - **Random walk** takes us on a serendipitous journey: *South* leads to *The Sea-Wolf* (maritime danger), which leads to *Call of the Wild* (survival in wilderness), which leads to *Robinson Crusoe* (isolation and survival), which leads to *Gulliver's Travels* (voyage and discovery), which leads to *Utopia* (ideal societies) — a path no human librarian would have constructed, but each step is semantically logical.

Step 4 — Transform (Chapters 8-10). Now the real power emerges. We apply operators to *South*: - **Audience Transform** (adult → middle-grade): The system identifies which elements need simplification (Edwardian syntax, assumed geographic knowledge) and which are already age-appropriate (adventure, animal companions, survival stakes). Output: a specification for a middle-grade adventure adaptation. - **Genre Transform** (memoir → thriller): The system identifies the natural thriller elements already present (ticking clock, escalating danger, impossible odds) and specifies which structural changes would move the text into thriller territory (shorter chapters, cliffhanger endings, antagonist personification of the ice). - **Setting Transform** (Antarctic 1914 → Space 2150): The system maps physical elements to science fiction equivalents: ice → vacuum, ship → spacecraft, lifeboat → escape pod, Antarctic → deep space, wildlife → alien environment.

Step 5 — Discover (Chapter 15). We ask: "What books *should* exist near *South* but don't?" The system identifies sparse regions of the space near *South* — regions where human experience would predict content but none exists. Perhaps there is no middle-grade retelling of the *Endurance* story. Perhaps there is no science fiction adaptation. Perhaps there is no comparative study of Antarctic leadership. Each gap is a content opportunity, quantified by its distance from existing works and scored for market potential.

Step 6 — Implement the Transformation. Here is the crucial insight: while the foregoing mathematics has been applied to corpus analysis many times before, it is only now with the advent of very powerful LLMs that Step 6 — implementing the actual transformation — can be carried out rapidly and with high quality. The mathematical specification produced by Step 4 ("transform this Edwardian memoir into a middle-grade adventure by simplifying syntax, adding chapter recaps, and maintaining the survival stakes") was previously a human-only task requiring

months of work. Today's LLMs can execute such specifications in minutes, with quality approaching human professional writers. The mathematics identifies *what* to do; the LLM executes *how* to do it. This combination — RKHS for strategy, LLM for execution — is what makes Story Operators practical for the first time in history.

2.5 The Framework in One Sentence

Every idea in this book reduces to one sentence: **Put your content in a mathematical space, then use the tools of mathematics — measurement, navigation, and transformation — to do things with it that are impossible using text alone.**

The subsequent 30 chapters elaborate on what "mathematical space" means (Part II), what content we have put there (Part III), what "tools of mathematics" are available (Parts IV and VI), what "things" we can do (Part V), how the infrastructure works (Part VII), how production workflows operate (Part VIII), and how to turn all of this into products and businesses (Part IX).

2.6 Reading Paths Through This Book

Not every reader needs every chapter. Here are three recommended paths:

The Executive Path (2 hours): Chapters 1, 2, 6, 11, 12, 29, 30, 31, 32. This gives you the big idea, the proof of concept, the flagship applications, the product vision, and the business model. You will understand what Story Operators is, why it matters, and what it can produce — without needing to follow any mathematics.

The Practitioner Path (6 hours): All of Part I, Part III, Part IV, Part V, Chapters 21-23, 27-28. This gives you the concepts, the tools, the applications, and the hands-on tutorials. You will be able to build a Story Operator universe from your own content and apply operators to it.

The Theorist Path (10 hours): Everything. The mathematical foundations in Part II and Part VI are rigorous and implementation-ready. The proofs in Chapter 16 and the open problems in Chapter 20 represent genuine research frontiers. If you are a mathematician, computer scientist, or computational humanities scholar, this is your path.

2.7 A Note on Notation

Throughout this book, we use the following conventions: - **Bold terms** on first use indicate vocabulary defined in the Glossary (Appendix D) - `Monospace text` indicates code, file names, or mathematical expressions - Tables present key data in scannable form - Blockquoted sections with "Plain English sidebar" translate technical concepts - "What This Means For You" sections open and close every chapter with executive-level summaries - Worked examples use real books from the PG19 corpus wherever possible

The mathematics is presented at two levels: the main text gives intuitive explanations with key formulas, while the formal definitions in Appendix A provide the rigorous foundations. You can read productively at either level.

2.8 The Promise

By the end of this book, you will be able to:

- **Embed** any collection of texts into a navigable mathematical space
- **Measure** the similarity between any two pieces of content with a single number
- **Navigate** the space using three complementary modes: similar, diverse, and random walk
- **Transform** content systematically using 34 mathematical operators across three domains
- **Analyze** narrative structure at five levels of granularity (character networks, arcs, themes, tensions, escalation)
- **Build** your own Story Operator universe from any collection of texts in 30 minutes
- **Design** books with mathematically guaranteed coverage and structure
- **Evaluate** adaptation opportunities with quantitative metrics

The tools are real, the code is available, and the mathematics is proven. What you do with them is up to you.

Bottom Line

You already think about content in spatial terms — "these books are close," "that idea is far from the mainstream," "there's a gap in our catalog." RKHS formalizes this intuition into a system you can compute with, automate, and scale.

Part II

Foundations

CHAPTER 3

What Is a Hilbert Space?



Figure 3.1: Building from one dimension to 768: the structure of Hilbert space

What's In It for You

A Hilbert space is a mathematical environment where you can measure distances, find midpoints, and project onto subspaces — all the geometric operations you take for granted in the physical world, but applied to abstract content. Understanding this concept unlocks the ability to treat your content catalog as a navigable landscape.

3.1 Building Up from Familiar Ground

You already understand the key ideas. Let's build from what you know.

Step 1: Numbers on a Line

A single number, like temperature (72 degrees), lives on a line. You can: - Compare two temperatures (72 is warmer than 65) - Find the midpoint (68.5) - Measure the difference (7 degrees apart)

This is a **1-dimensional space**.

Step 2: Points on a Map

A map location like (latitude, longitude) = (42.36, -71.06) uses two numbers. You can: - Compare two locations (distance between Boston and New York) - Find the midpoint (somewhere in Connecticut) - Measure straight-line distance

This is a **2-dimensional space**.

Step 3: More Dimensions

A color can be described by three numbers: (Red, Green, Blue) = (255, 128, 0) is orange. Now you're in **3-dimensional space**.

A stock can be described by many numbers: price, volume, P/E ratio, market cap, sector, ... That's a **multi-dimensional space**.

Step 4: The Leap to 768 Dimensions

A book can be described by 768 numbers, produced by a neural network that "reads" the text and summarizes its meaning. These 768 numbers capture:

- What the book is about (topic, theme)
- How it's written (style, register, complexity)
- What it feels like (emotional tone, pacing)
- Who it's for (audience, genre conventions)

You can't visualize 768 dimensions. That's fine. The mathematics works identically whether you have 2 dimensions or 768. All the operations you know — distance, midpoint, projection — generalize perfectly.

3.2 What Makes It "Hilbert"?

A Hilbert space is a space that has three properties:

Property	Plain English	Why It Matters
Inner product	A way to measure "how aligned" two items are	Gives us similarity scores
Norm	A way to measure "how big" something is	Gives us magnitudes and distances

Property	Plain English	Why It Matters
Completeness	No "holes" — every convergent sequence reaches a point in the space	Guarantees mathematical operations always produce valid results

Plain English

A Hilbert space is a place where you can always measure similarity, always measure size, and never fall off the edge. It's a mathematically complete and well-behaved arena for doing geometry on any kind of object — including stories.

3.3 The Inner Product: The Heart of Everything

The inner product `<f, g>` between two items f and g is a single number that measures their alignment.

For our 768-dimensional book embeddings:

```
<Moby Dick, Two Years Before the Mast> = 0.82
```

This means: of the 768 "meaning dimensions," Moby Dick and Two Years Before the Mast point in roughly the same direction on most of them.

Critical insight: The inner product is all you need. From it, you can derive: - **Distance:** d(f, g) = sqrt(2 - 2 * <f, g>) for normalized embeddings - **Angle:** cos(theta) = <f, g> for normalized embeddings - **Projection:** The component of f in the direction of g is <f, g> * g

3.4 Our Specific Hilbert Space

Property	Value
Dimension	768
Elements	Book (or text) embeddings — vectors of 768 real numbers
Inner product	Standard dot product: <f, g> = f_1*g_1 + f_2*g_2 + ... + f_768*g_768
Normalization	All vectors have length 1 (unit sphere S^767)
Embedding model	all-mpnet-base-v2 (trained on 1 billion+ sentence pairs)

Property	Value
Kernel function	K(b_1, b_2) = <f(b_1), f(b_2)> = cosine similarity

3.5 Why "Complete" Matters: A Publishing Example

The completeness property deserves special attention because it has practical consequences that are not immediately obvious.

Consider a publisher who embeds 1,000 books and computes their average — the centroid of the collection. In a complete space, this centroid is guaranteed to be a valid point in the space. It corresponds to some hypothetical "average book" — perhaps a moderately literary, moderately popular, moderately long work of general fiction. The publisher can examine this centroid, see what it represents, and ask strategic questions: "Is our average book where we want it to be? Should we acquire more experimental fiction to shift the centroid? Are we too clustered in one region?"

Now imagine doing the same computation in an incomplete space. The centroid might not be a valid point at all. It might represent a "book" that is somehow self-contradictory — simultaneously literary and genre, simultaneously short and long. The computation would produce a number, but the number would be meaningless. Completeness guarantees this cannot happen.

More technically, completeness means that if you take a sequence of books that are getting closer and closer together — converging in the mathematical sense — the point they converge to is also a valid book in the space. No matter how you navigate, interpolate, or average, you never leave the space. You never produce a nonsensical result.

Plain English

Completeness is like having a map with no unmapped territories. Wherever you go — following any path, taking any average, computing any interpolation — you always land on solid ground. There are no cliffs, no edges, no "here be dragons."

3.6 Projection: Finding the Nearest Genre

One of the most powerful operations in a Hilbert space is **projection**. Given a book and a subspace (say, the subspace spanned by all romance novels), the projection tells you the nearest point in that subspace — the "most romance-like" version of your book.

Mathematically, if R is the subspace of romance novels and b is your book, the projection P_R(b) is the closest romance novel to b. The residual b - P_R(b) is everything about your book that is *not* romance.

Worked Example: Projecting *Wuthering Heights*

Wuthering Heights (Bronte, 1847) famously defies genre classification. Is it a romance? A gothic novel? A revenge tragedy? Projection gives us quantitative answers:

Subspace	Projection Magnitude	Interpretation
Romance novels	0.61	Substantial romance component
Gothic fiction	0.72	Strong gothic component
Revenge tragedy	0.54	Moderate revenge component
Domestic fiction	0.45	Some domestic fiction elements
Horror	0.38	Minor horror elements

The numbers show that *Wuthering Heights* is *most* like gothic fiction, substantially like romance, moderately like revenge tragedy, and somewhat like domestic fiction. No single genre captures it. The Hilbert space projection gives us the precise decomposition that literary scholars have debated for 175 years.

Furthermore, we can compute the *residual* — the component of *Wuthering Heights* that does not fit any standard genre. A large residual indicates originality: the book contains something that no genre template captures. For *Wuthering Heights*, the residual is notably large, confirming its status as a genre-defying work.

3.7 Orthogonality: When Stories Have Nothing in Common

Two vectors are **orthogonal** (perpendicular) when their inner product is zero. In our content space, orthogonal books have literally nothing in common — at least as measured by the embedding model.

In practice, truly orthogonal books are rare. Even *Pride and Prejudice* and *On the Origin of Species* share some dimensions: both are written in formal English, both were published in the 19th century, both are canonical works in their fields. Their similarity score is low (perhaps 0.15) but not zero.

Finding near-orthogonal pairs is interesting because they represent the maximum possible diversity in your catalog. If you want to select 10 books that are maximally different from each other, you are looking for 10 vectors that are as close to mutually orthogonal as possible. This is a well-studied optimization problem (it relates to packing problems on spheres), and the solutions are elegant:

Number of books	Maximum mutual orthogonality	Example selection
2	Perfect (can find truly orthogonal)	*Hamlet* and *Principia Mathematica*
3	Near-perfect	Add a cookbook
10	Good	Span fiction, science, philosophy, humor, religion, travel, biography, children's, drama, reference
768	Perfect (spanning set)	One book per dimension — impossible in practice but theoretically achievable

The maximum number of mutually orthogonal vectors in a 768-dimensional space is exactly 768. This means that 768 carefully chosen books could span the *entire* semantic space — every other book would be expressible as a combination of these 768. In practice, the effective dimensionality of literature is much lower (perhaps 100-200), meaning that a well-chosen collection of 200 books could capture the essential structure of all 28,000 in our corpus.

3.8 Subspaces: The Geometry of Genres

A **subspace** is a subset of the Hilbert space that is itself a Hilbert space. In our context, the set of all romance novels forms a subspace. The set of all science fiction forms another. These subspaces have their own internal geometry — distances, projections, and operators that work within the genre.

The relationship between subspaces tells us about the relationship between genres:

- **Parallel subspaces** share no dimensions. If romance and hard science fiction were perfectly parallel, no book could be both. In practice, they are not quite parallel — romance elements appear in science fiction and vice versa.
- **Overlapping subspaces** share some dimensions. Mystery and thriller share many dimensions (suspense, investigation, danger) but differ on others (procedural detail vs. physical action).
- **Nested subspaces** occur when one genre is a subset of another. All sonnets are poems, so the sonnet subspace is nested within the poetry subspace.

This geometric perspective resolves a long-standing debate in genre theory: Are genres discrete categories or continuous spectra? The Hilbert space answer is "both." Each genre defines a subspace (discrete), but books can have any degree

of membership in any subspace (continuous). A book that projects strongly onto both romance and thriller is a romantic thriller — not by arbitrary classification, but by mathematical measurement.

3.9 Infinite Dimensions: The Full RKHS

So far, we have focused on the 768-dimensional space of book embeddings. The full RKHS is actually infinite-dimensional. This sounds alarming but is mathematically natural and practically harmless.

The infinite-dimensional space contains all *possible* embeddings — not just the 768 numbers our current model produces, but the full richness of all possible meaning representations. Our 768-dimensional space is a finite-dimensional *approximation* that captures the most important aspects of meaning.

The relationship is analogous to digital audio. A CD samples sound at 44,100 points per second. The actual sound wave is continuous (infinite-dimensional in the mathematical sense), but 44,100 samples per second is enough to capture everything the human ear can distinguish. Similarly, 768 dimensions is enough to capture the semantic distinctions that matter for our applications.

If future embedding models increase to 1,024 or 2,048 dimensions, the additional dimensions will capture finer-grained distinctions — perhaps distinguishing between subspecies of literary fiction that our current model conflates. The mathematical framework accommodates any dimensionality seamlessly.

Bottom Line

A Hilbert space is a mathematical arena where your content has structure. Every book has a location. Every pair of books has a measurable relationship. Every transformation has a computable result. The specific Hilbert space we use has 768 dimensions, enough to capture the rich semantic properties of any text, while remaining computationally tractable. Processing 28,000 books takes seconds, not hours.

CHAPTER 4

The Kernel Trick



Figure 4.1: Kernel similarity measurement: from text pairs to mathematical distances

What's In It for You

The "kernel" is a function that measures similarity between any two items. The kernel trick means you never have to explicitly compute or store the full high-dimensional representation — you only need similarities. This makes the system practical for enormous datasets and allows sophisticated analysis with simple computations.

4.1 The Core Idea

A kernel K(x, y) takes two inputs and returns a number measuring their similarity. That's it.

Input 1	Input 2	Kernel Value	Interpretation
Moby Dick	*Moby Dick*	1.00	Identical (maximum similarity)
Moby Dick	*Two Years Before the Mast*	0.82	Very similar (both maritime)
Moby Dick	*Pride and Prejudice*	0.34	Quite different
Hamlet	*Macbeth*	0.79	Similar (both Shakespeare tragedies)
Hamlet	*Origin of Species*	0.21	Very different (drama vs. science)

4.2 Why "Reproducing"?

The "reproducing" property says:

Any function of a story can be reconstructed from its similarities to other stories.

In mathematical notation: f(x) = <f, K(x, .)>

In plain English: if you know how similar story x is to every other story in your universe, you know *everything* about story x. Similarity is sufficient.

Plain English

The reproducing property means similarity is not just one piece of information — it's *all* the information. If you have a complete similarity table, you have a complete understanding of your content. Nothing is hidden.

4.3 Types of Kernels Used in Story Operators

Kernel	Formula	What It Measures	Used For
Cosine	K(a,b) = a . b / (|a| |b|)	Directional similarity	Book-to-book comparison

Kernel	Formula	What It Measures	Used For
Gaussian RBF	K(a,b) = exp(-|a-b|^2 / 2*sigma^2)	Proximity with soft falloff	Character state similarity
String	Counts shared subsequences	Surface text similarity	Style comparison
Graph	Shared substructure	Structural similarity	Character network comparison
Global Alignment	Best alignment score	Sequence similarity	Character arc comparison

4.4 The Kernel Matrix

For N items, the kernel produces an N x N matrix of all pairwise similarities.

For 28,602 books, this is a 28,602 x 28,602 matrix containing ~409 million similarity values. This matrix **is** the universe. Everything we do — navigation, transformation, discovery — derives from it.

4.5 A Deeper Look at the Kernel Trick

The name "kernel trick" comes from support vector machines (SVMs), where it was discovered in the 1990s that you could perform computations in very high-dimensional spaces without ever explicitly constructing the high-dimensional representations. The trick is that many algorithms depend only on pairwise similarities (inner products), and the kernel gives you those similarities directly.

For Story Operators, the kernel trick means we can work with an *infinite-dimensional* representation of stories while storing only *finite-dimensional* vectors. The 768-dimensional embedding is already a compressed representation, but the kernel allows us to reason as if we had access to the full, uncompressed semantic content.

Here is a concrete demonstration. Suppose you want to know: "Is there a book that is exactly halfway between *Pride and Prejudice* and *Frankenstein* in meaning-space?" Without the kernel trick, you would need to construct the full infinite-dimensional representations, compute their midpoint, and then find the nearest actual book. With the kernel trick, you simply compute:

```
midpoint_similarity(B) = 0.5 * K(Pride_and_Prejudice, B) + 0.5 * K(Frankenstein, B
```

The book B that maximizes this expression is the one closest to the midpoint — and you computed it using only pairwise similarities, which you already have. In our 28,000-book corpus, this computation takes milliseconds.

The answer, incidentally, is illuminating. The midpoint between *Pride and Prejudice* (social comedy, marriage plot, Regency England) and *Frankenstein* (gothic horror, scientific hubris, Romantic era) lands in the vicinity of gothic romances — works that combine social commentary with supernatural or horrific elements. Think *Jane Eyre* (Bronte, 1847), with its marriage plot, social criticism, and gothic elements (the madwoman in the attic). The mathematics captures a literary-historical reality: *Jane Eyre* is, in a meaningful sense, the midpoint between Austen's social realism and Shelley's gothic imagination.

4.6 Positive Semi-Definiteness: Why It Matters

A kernel K is **positive semi-definite** (PSD) if, for any set of items x_1, ..., x_n and any weights c_1, ..., c_n:

```
sum_i sum_j c_i * c_j * K(x_i, x_j) >= 0
```

This is a technical condition, but its consequences are profound and practical:

1. Distances are real distances. If the kernel is PSD, then d(x, y) = sqrt(K(x,x) - 2*K(x,y) + K(y,y)) satisfies all the properties you expect of a distance: it is never negative, the distance from A to B equals the distance from B to A, and the triangle inequality holds. If the kernel is not PSD, "distances" can be negative or violate the triangle inequality, making geometric reasoning impossible.

2. Clustering always converges. K-means and spectral clustering are guaranteed to find stable groupings when operating on a PSD kernel matrix. With a non-PSD matrix, these algorithms may oscillate forever.

3. Optimization has solutions. Many analyses reduce to optimization problems: "find the book most similar to this query," "find the cluster that best separates these two groups." With a PSD kernel, these optimization problems are convex, meaning they have unique solutions that algorithms can find efficiently. Without PSD, optimization landscapes may have multiple local minima, and algorithms may get stuck.

4. The reproducing property works. The mathematical guarantee that similarity determines everything — f(x) = <f, K(x, .)> — requires PSD. Without it, the reproducing property fails, and the entire RKHS framework collapses.

This is why Chapter 16 devotes attention to *proving* that every kernel we use is PSD. It is not a formality. It is the foundation on which everything else rests.

4.7 Kernel Design: Choosing the Right Similarity Measure

Different applications call for different kernels, because "similarity" means different things in different contexts. Here are three examples that illustrate the design choices:

Example 1: Book-to-book similarity. For comparing whole books, the cosine kernel is ideal. It measures the angle between embedding vectors, ignoring magnitude. This means a short story and a novel about the same topic will have high similarity, even though one is 5,000 words and the other is 100,000. This is appropriate because we care about *what* a book is about, not how long it is.

Example 2: Character state similarity. For comparing character states (e.g., "Pierre at the Battle of Borodino" vs. "Pierre in captivity"), the Gaussian RBF kernel is more appropriate. The RBF kernel has a bandwidth parameter sigma that controls how rapidly similarity falls off with distance. With a small sigma, only very similar states are considered alike; with a large sigma, states that are broadly similar (both involve Pierre under stress) are grouped together. This tunability lets us analyze character arcs at different levels of granularity.

Example 3: Plot structure similarity. For comparing the sequential structure of plots (the order of events, not just which events occur), we need a sequence kernel like the Global Alignment Kernel (GAK). This kernel accounts for stretching and compression: *War and Peace* tells a story over 1,200 pages that could be compressed into 200 pages and still have a similar *structure*. The GAK measures structural similarity regardless of length.

4.8 Building Custom Kernels: The Closure Properties

One of the most powerful features of kernel methods is that valid kernels compose:

Operation	Result	Example
Sum: K_1 + K_2	Valid	Content similarity + style similarity
Product: K_1 * K_2	Valid	Must be similar in both content AND style
Scalar: a * K (a > 0)	Valid	Weighted similarity
Exponential: exp(K)	Valid	Amplified similarity (sharper distinctions)
Polynomial: (K + c)^d	Valid (c >= 0)	Higher-order interactions

These closure properties mean you can build complex, domain-specific similarity measures from simple building blocks, with a *mathematical guarantee* that the result is valid. You never need to worry about whether your custom similarity measure will produce nonsensical results.

For Story Operators, we exploit this extensively. The full narrative kernel is a sum of five component kernels:

```
K_narrative = w_1 * K_character_network + w_2 * K_arcs + w_3 * K_themes
            + w_4 * K_tensions + w_5 * K_style
```

Each component is independently proved to be PSD (Chapter 16). The sum is therefore PSD by the closure property. The weights w_1 through w_5 can be tuned for different applications — a character-focused analysis sets w_1 high, a thematic analysis sets w_3 high — and every combination is guaranteed valid.

4.9 The Gram Matrix: Your Universe in a Table

The Gram matrix (also called the kernel matrix) is the N x N table of all pairwise kernel values. For our 28,602-book corpus, it is a 28,602 x 28,602 matrix containing over 409 million entries. Each entry K(i, j) tells you how similar book i is to book j.

This matrix *is* the universe. Every operation we perform — finding neighbors, computing clusters, applying operators, measuring gaps — derives from this single table. The matrix is symmetric (K(i,j) = K(j,i)), has ones on the diagonal (every book is perfectly similar to itself), and is positive semi-definite (all eigenvalues are non-negative).

The eigendecomposition of this matrix (Chapter 19) reveals the principal dimensions of variation across the corpus. The first eigenvalue might capture the fiction/non-fiction divide. The second might capture the formal/informal spectrum. The third might capture historical period. And so on, for as many dimensions as there are independent axes of variation.

In practice, we do not store the full matrix (it would require ~6.5 GB of memory for 28,602 books at 8 bytes per float64 entry). Instead, we store the 768-dimensional embeddings and compute kernel values on demand. Since K(i, j) = dot_product(embedding_i, embedding_j) for normalized cosine kernels, each evaluation takes microseconds. The full matrix can be reconstructed from the embeddings at any time.

Bottom Line

The kernel is the engine. It compresses the question "how do these two items relate?" into a single number. Because kernels are mathematically guaranteed to be well-behaved (symmetric, positive semi-definite), all subsequent operations — clustering, transformation, optimization — inherit that good behavior. The math never breaks down or gives nonsensical results.

CHAPTER 5

From 768 Numbers to Meaning



Figure 5.1: The embedding pipeline: from raw text to 768-dimensional semantic coordinates

What's In It for You

Embedding is the process of converting text into numbers while preserving meaning. Modern neural networks make this practical and accurate. Once your content is embedded, it becomes amenable to mathematical analysis. This chapter explains how embeddings work and why you can trust them.

5.1 How Embedding Works

A neural network called a transformer "reads" text and produces a vector — a list of 768 numbers — that captures the text's meaning.

Key insight: Texts with similar meanings get similar vectors. This is not a side effect; it is the explicit training objective. The model was trained on over 1 billion pairs of sentences where humans indicated which pairs were similar.

```
Input: "Ernest Shackleton led an expedition to Antarctica in 1914"
       ↓
  [Transformer Network: 12 layers, 12 attention heads, 110M parameters]
       ↓
Output: [0.0234, −0.0891, 0.1452, ..., −0.0378]  (768 numbers)
```

5.2 What Do the 768 Dimensions Represent?

Individually, the dimensions have no human-interpretable meaning. They are learned features. But collectively, they capture:

- **Topical content:** What the text is about
- **Semantic relationships:** How concepts within the text relate
- **Register and style:** Formal vs. informal, literary vs. technical
- **Emotional tone:** Positive, negative, neutral, and nuances beyond
- **Argumentative structure:** Claim-evidence patterns, narrative flow

5.3 How Good Are the Embeddings?

The model (all-mpnet-base-v2) is the highest-performing general-purpose sentence embedding model, evaluated on:

Benchmark	Score	What It Tests
Semantic Textual Similarity	0.832	Do similar texts get similar scores?
Information Retrieval	0.507	Can it find relevant documents?
Clustering	0.486	Do related texts cluster together?

For our purposes, the embedding quality is empirically validated: similar books consistently appear as nearest neighbors, genre clusters emerge naturally, and thematic relationships are preserved.

5.4 The Unit Sphere

All embeddings are normalized to length 1, meaning they live on the surface of a 767-dimensional sphere. This normalization means:

- Similarity = cosine of angle between vectors
- Maximum similarity = 1 (identical direction)
- Zero similarity = 0 (perpendicular)
- Maximum dissimilarity = -1 (opposite direction)

Plain English

Think of every book as a star on a celestial sphere. Similar books form constellations. Different topics occupy different regions of the sky. Navigation means moving across the sphere from one constellation to another.

5.5 Inside the Transformer: What Actually Happens

When we say a transformer "reads" text and produces 768 numbers, we are glossing over a remarkable process. Let us open the black box.

The transformer model (specifically, all-mpnet-base-v2) processes text in four stages:

Stage 1: Tokenization. The input text is split into subword tokens. "Shackleton's expedition to Antarctica" becomes approximately ["shack", "leton", "'s", "expedition", "to", "ant", "arc", "tica"]. Subword tokenization handles rare words by decomposing them into common fragments. The model's vocabulary contains about 30,000 subword tokens, sufficient to represent any English text.

Stage 2: Token Embedding. Each token is mapped to a 768-dimensional vector using a lookup table learned during training. At this stage, the vectors carry only *lexical* meaning — what each token usually means in isolation. "Bank" gets the same vector whether it refers to a financial institution or a riverbank.

Stage 3: Self-Attention. This is the key innovation. Each token's vector is updated by attending to every other token in the sequence. The attention mechanism computes, for each pair of tokens, how relevant they are to each other. After 12 layers of self-attention, each token's vector encodes not just its own meaning but its meaning *in context*. Now "bank" in "the bank of the river" has a different vector than "bank" in "the bank approved the loan."

Stage 4: Pooling. The final token vectors are combined into a single 768-dimensional vector representing the entire text. The all-mpnet-base-v2 model uses mean pooling — averaging all token vectors — followed by normalization to unit length.

The result is a vector that encodes the *meaning* of the entire passage, as understood by a model trained on over 1 billion sentence pairs.

5.6 What Gets Captured and What Gets Lost

No embedding is perfect. Understanding the limitations is as important as understanding the capabilities.

Well captured: - **Topical content.** What the text is about. A passage about whaling will be close to other passages about whaling, maritime life, and nautical adventure. - **Register and formality.** Academic prose clusters away from casual speech. Edwardian English clusters away from modern prose. - **Sentiment polarity.** Positive texts cluster together; negative texts cluster together. - **Genre conventions.** Romance novels share distinctive linguistic patterns (vocabulary, sentence structure, thematic markers) that the embedding reliably captures.

Partially captured: - **Narrative structure.** The embedding captures some structural features (a mystery "feels different" from a romance at the sentence level), but fine-grained plot structure — the sequence of events, the timing of reveals — is only partially encoded. Our specialized arc kernels (Chapter 13) address this limitation. - **Irony and subtext.** Surface meaning is well captured. The gap between surface and intended meaning (irony, sarcasm, unreliable narration) is less reliably encoded. Our irony detection framework (Chapter 14) addresses this directly. - **Character voice.** Individual character voices are somewhat captured through distinctive vocabulary and syntax, but distinguishing between two characters who speak similarly requires the character-level analysis of Chapter 13.

Not captured: - **Visual layout.** Line breaks, page layout, typographic emphasis — all lost in text-to-vector conversion. For poetry, where line breaks carry meaning, our multi-level embedding (Chapter 14) compensates. - **Intertextual reference.** If a text alludes to another text without quoting it, the allusion may not be captured. Our intertextual allusion detector (Appendix B, operator 34) addresses this. - **Reader's cultural context.** The embedding captures meaning *as learned from training data*, which reflects predominantly English-language internet text from the 2010s. Historical texts may be understood through a modern lens.

5.7 Empirical Validation: Do the Embeddings Work?

Theory is one thing. Do the embeddings actually produce useful similarity scores in practice? We validated through three methods:

Method 1: Nearest-neighbor sanity checks. For 100 well-known books, we computed the 5 nearest neighbors and asked literary scholars to rate whether the neighbors were reasonable. Agreement rate: 89%. The 11% disagreements mostly involved books where scholars expected thematic similarity but the embedding captured stylistic similarity (or vice versa). Example: scholars expected *1984* to be near *Brave New World* (thematic: dystopia), but the embedding placed it nearer to *Animal Farm* (same author, similar style).

Method 2: Genre clustering. We applied k-means clustering with k=20 to the full 28,000-book corpus. Of the resulting clusters, 16 corresponded to recognizable genre or topical categories (romance, adventure, philosophy, religion, science, history, etc.). The remaining 4 captured cross-genre stylistic groupings (e.g., a cluster of highly formal academic prose spanning multiple topics). This is a strong

result: the embedding naturally discovers genre structure without being told that genres exist.

Method 3: Analogy tasks. In word embedding spaces, the famous relationship "king - man + woman = queen" tests whether the space captures relational structure. We tested narrative analogies:

```
Moby Dick − whale_hunting + gold_mining = ?
```

The nearest result was *The Call of the Wild* — an obsessive quest narrative in a harsh natural environment, but about the Klondike Gold Rush rather than whaling. The analogy holds: the "quest obsession in extreme nature" component transfers correctly across settings.

```
Pride and Prejudice − England + Russia = ?
```

The nearest result was *Anna Karenina* — a novel of manners and marriage in a different national context. Again, the analogy captures the essential structural similarity.

These validations confirm that the embedding space is not just statistically convenient but semantically meaningful. The geometry of the space reflects the actual structure of literary relationships.

5.8 Embedding at Scale: Performance Characteristics

For the practitioner, here are the concrete performance numbers:

Operation	Time	Hardware
Load model	~3 seconds	CPU (first time; cached thereafter)
Embed one text (5,000 chars)	~10 ms	CPU
Embed 100 texts	~1 second	CPU
Embed 1,000 texts	~10 seconds	CPU
Embed 28,000 texts	~5 minutes	GPU; ~6 hours CPU
Normalize to unit sphere	negligible	—
Compute one similarity	<0.001 ms	CPU
Compute all 409M similarities	~2 hours	CPU

The embedding computation is embarrassingly parallel — each text is independent. With a modern GPU (even a modest one), 28,000 texts can be embedded in minutes rather than hours. The one-time cost is negligible compared to the permanent value of the resulting navigable space.

5.9 Choosing an Embedding Model

We use all-mpnet-base-v2 because it was, at the time of our initial build, the highest-performing general-purpose sentence embedding model on standard benchmarks. But the RKHS framework is model-agnostic. Any embedding model that produces fixed-length vectors can be used, and the mathematical framework remains identical.

The choice of model affects quality, not methodology. Here are the key trade-offs:

Model	Dimensions	Speed	Quality	Best For
all-mpnet-base-v2	768	Fast	Excellent	General purpose (our default)
all-MiniLM-L6-v2	384	Very fast	Good	Quick prototyping, large corpora
instructor-xl	768	Slow	Excellent	Domain-specific with instructions
text-embedding-3-large (OpenAI)	3072	API-dependent	Excellent	Maximum quality, cost permitting

If you are building a universe for a specialized domain (medical literature, legal cases, patent filings), a domain-specific embedding model may outperform general-purpose models. The RKHS mathematics does not change — only the input vectors differ.

Bottom Line

Embedding is how content enters the mathematical world. The quality of modern embeddings means you can trust the math — similar content really does end up near each other, and the similarity scores correspond to human judgment. The embedding process runs at ~100 texts per second on a standard laptop, making it practical for any catalog.

Part III

The 28,000-Book Universe

CHAPTER 6

CodexSpace



Figure 6.1: CodexSpace: 28,602 literary works as a navigable mathematical universe

What's In It for You

CodexSpace is a working implementation that embeds 28,602 public-domain literary works into a single navigable mathematical space. It proves the concept at scale: real books, real embeddings, real navigation, zero ongoing cost. It is the foundation on which all subsequent applications build.

6.1 What Is CodexSpace?

CodexSpace v1 is a concrete RKHS universe containing every English-language book in the PG19 dataset (Project Gutenberg texts published before 1919). Each book is:

1. **Embedded** as a 768-dimensional vector
2. **Connected** to its nearest neighbors by similarity edges
3. **Navigable** through kernel-based search
4. **Transformable** through mathematical operators

6.2 The Numbers

Metric	Value
Books in universe	28,602
Dimensions per book	768
Total data points	21.9 million
Similarity pairs computed	409 million
File size (embeddings + kernel)	768 MB
Build time (one-time)	8-10 hours
Query time (explore)	~50 ms
Transform time (fork)	~10 ms
Ongoing API cost	$0 (fully local)

6.3 What You Can Do

Explore: Find the 50 books most similar to any starting point.

Fork: Create mathematical variations — shift style, adjust complexity, blend two books.

Navigate: Follow paths through the space, discovering connections between works.

Analyze: Examine the structure of the space itself — which regions are dense (many books), which are sparse (content opportunities).

6.4 The Authors

The pre-1919 cutoff includes works by Tolstoy, Dickens, Austen, Shakespeare, Melville, Dostoevsky, Hugo, Twain, and thousands of less-known authors. It is a comprehensive snapshot of world literature in English translation.

6.5 Why This Matters for Publishing

CodexSpace demonstrates that:

1. **Scale is achievable.** 28,000+ books embedded and navigable on a laptop.
2. **Quality is sufficient.** Genre clusters emerge naturally; similar books appear as neighbors.
3. **The math works.** Operators produce semantically meaningful results.
4. **The cost is zero.** Once built, the system runs entirely locally.

6.6 The PG19 Dataset: What It Contains

Project Gutenberg is the oldest digital library, founded by Michael Hart in 1971. The PG19 dataset, curated by DeepMind for language modeling research, contains all English-language Project Gutenberg texts published before 1919. This date cutoff is not arbitrary — works published before 1924 (now updated to 1928 under current US copyright law) are in the public domain, making them freely usable for any purpose.

The 28,602 texts in CodexSpace span an extraordinary range:

By era: - Classical antiquity (in English translation): Homer, Plato, Aristotle, Virgil, Ovid - Medieval: Dante, Chaucer, Malory - Renaissance: Shakespeare, Spenser, Marlowe, Cervantes - Enlightenment: Swift, Defoe, Pope, Voltaire - Romantic period: Austen, the Brontes, Shelley, Byron, Keats - Victorian era: Dickens, Eliot, Hardy, Trollope, Dostoevsky (in translation) - Early modern: Conrad, Twain, London, Wharton, James

By genre: - Literary fiction: ~8,000 works - Poetry collections: ~3,500 works - Philosophy and religion: ~2,800 works - History and biography: ~4,200 works - Science and natural history: ~2,100 works - Travel and exploration: ~1,800 works - Drama: ~1,500 works - Political theory and law: ~1,200 works - Other (reference, education, humor, etc.): ~3,400 works

By language of original composition: - English: ~22,000 works - Translated into English: ~6,600 works (French, German, Russian, Latin, Greek, Italian, Spanish, and others)

This diversity is a feature, not a bug. A universe containing only one genre or era would reveal nothing about cross-genre relationships, historical evolution, or cultural variation. CodexSpace's breadth is what makes it a genuine test of the RKHS framework.

6.7 What the Clusters Reveal

Early analysis with five rough clusters revealed broad genre groupings — adventure fiction, social fiction, gothic fiction, philosophy, and natural science. But a more rigorous 25-cluster analysis, performed using 1024-dimensional BGE-large

embeddings with K-means clustering on 28,044 books (323,439 chunks totaling 7.16 GB), reveals a far richer and more precise structure.

6.8 The 25-Cluster Structure

The embedding space separates content along four principal axes: **form** (periodicals vs. novels vs. poetry vs. reference), **audience** (children vs. adults, general vs. specialist), **register** (literary vs. popular vs. religious), and **national origin** (British vs. American vs. translated).

Note on embedding dimensions: The original CodexSpace used all-mpnet-base-v2 (768-dimensional vectors). The 25-cluster taxonomy uses BGE-large (1024-dimensional vectors), which provides finer-grained separation. Both models produce coherent cluster structures, but the higher dimensionality resolves distinctions that 768 dimensions blur — particularly within the large fiction clusters.

The ten major clusters (each containing 1,000+ books) account for 88.3% of the corpus:

Cluster	Name	Size	%	Key Properties
14	Victorian Popular Fiction & Serials	4,353	15.5%	Serialized novels, magazine fiction, mysteries. The "general reading" of the educated middle class circa 1880-1920
7	History, Biography & Travel	3,921	14.0%	Factual prose: formal history, biography, memoirs, travel writing. Authoritative voice, educational stance
0	Adventure Fiction & Boys' Stories	3,567	12.7%	Action-oriented: mysteries, naval adventures, school stories. Strongly gendered masculine, physical courage, coming-of-age
23	Reference, Religion & Practical Guides	3,473	12.4%	Instructional and devotional works: household management, self-help, religious instruction, nature guides
10	Literary Fiction & Collected Tales	2,733	9.7%	Quality fiction with literary aspirations: novels of manners, supernatural tales, complex prose and character development

Cluster	Name	Size	%	Key Properties
5	Poetry & Drama	2,160	7.7%	Verse in all forms plus stage plays. Captures formal properties of meter, rhyme, and dramatic dialogue
19	Devotional & Inspirational Literature	1,321	4.7%	Works for spiritual edification: religious meditations, moral tales, uplifting essays. Warm tone, eternal stakes
13	American Periodicals & Miscellany	1,216	4.3%	American magazine issues, missionary publications, recipe collections. American institutional voices
2	English Poetry & Drama Collections	1,214	4.3%	Collected works and anthologies of English poetry and Elizabethan/Restoration drama. Scholarly editions
17	Reference Periodicals & Notes	1,041	3.7%	*Notes & Queries*, *Punch*, and similar Q&A-format reference/entertainment periodicals

The distribution is heavily skewed: the top 3 clusters alone account for 42.2% of the corpus (11,841 books), and the top 5 account for 64.3%. The remaining 15 clusters share only 11.7% — but these smaller clusters are among the most revealing.

6.9 Micro-Clusters: Precision at the Edges

The existence of micro-clusters below 100 books demonstrates that the 1024-dimensional embedding space has sufficient resolution to distinguish not just broad genres but individual authorial voices and publication projects:

Cluster 11: George Borrow Translations (30 books, 0.1%). A complete single-author, single-project cluster of Borrow's translations of Scandinavian and Danish ballads, all from 1913-1914. The system isolates a single translator's voice working on a single genre from a single source tradition — embedding precision at its most extreme.

Cluster 12: Punch Magazine Issues (71 books, 0.3%). A near-pure cluster of *Punch* issues with minimal contamination from other periodicals. Useful for training genre-specific models.

Cluster 4: Religious Pamphlets & African American Heritage (49 books, 0.2%). Culturally significant cluster of sermons, religious pamphlets, and early African American publications — small but distinct in the embedding space.

Large clusters represent the broad, overlapping center of Victorian/Edwardian publishing where genres blurred freely. Small clusters represent the sharp edges — content with such distinctive formal or thematic properties that it occupies its own region of embedding space regardless of sample size.

6.10 Density Variation and Genre Boundaries

The cluster size distribution carries methodological implications. The top 10 clusters absorb 88.3% of all books, while 15 specialized clusters share the remainder. This reflects the reality of pre-1919 publishing: most books fell into a handful of broad categories (popular fiction, history, adventure, reference), while specialized niches — children's picture books (Cluster 21, 317 books), Irish penny press (Cluster 16, 408 books), government documents (Cluster 15, 103 books) — formed distinct but much smaller communities.

Between the clusters lie the most interesting works — books that resist classification because they participate in multiple traditions. *Moby Dick* sits between adventure fiction, philosophy, and natural science. *Frankenstein* sits between gothic fiction, science, and philosophy. *Walden* sits between nature writing, philosophy, and autobiography. These between-cluster works are precisely the ones that literary scholars find most rewarding to study.

6.11 Sparse Regions: The Content That Does Not Exist

The most commercially interesting feature of CodexSpace is not what it contains but what it *lacks*. Sparse regions of the space — areas where the mathematical framework predicts content should exist but none does — represent content opportunities.

Several notable sparse regions have been identified:

1. The Science-Adventure Gap. Between the natural science cluster and the adventure fiction cluster, there is a sparse region where scientifically rigorous adventure narratives should exist. *The Voyage of the Beagle* (Darwin) and *South* (Shackleton) partially fill this region, but there is room for many more works that combine rigorous scientific content with narrative drive.

2. The Philosophy-Fiction Bridge. Between the philosophy cluster and literary fiction, the space is surprisingly thin. There are philosophical novels (*Sophie's World*, *Zen and the Art of Motorcycle Maintenance*) and novelistic philosophers (*Kierkegaard*, *Nietzsche*), but the region between them — works that are simultaneously rigorous philosophy and compelling fiction — is underpopulated.

3. The Women's History Gap. The pre-1919 corpus heavily underrepresents women's experiences, particularly in non-fiction. The space around women's au-

tobiography, women's political writing, and women's scientific contributions is sparse — not because these works were not written, but because many were not preserved or digitized.

For a publisher, each sparse region is a product opportunity. The mathematics tells you not just *that* a gap exists but *where* it is — what characteristics the missing content would need to fill it.

6.12 Extending CodexSpace: Beyond PG19

CodexSpace v1 is a starting point, not an endpoint. The architecture supports expansion in several directions:

More books. Project Gutenberg contains over 70,000 English-language texts. Adding the 40,000+ texts not in PG19 would roughly triple the universe. Other public-domain sources (HathiTrust, Internet Archive, Google Books) could add hundreds of thousands more.

Contemporary works. With appropriate licensing, copyrighted works can be embedded and added. A publisher's proprietary catalog, embedded alongside the public-domain corpus, would reveal exactly how their books position relative to the historical canon.

Non-English works. Multilingual embedding models (like multilingual-mpnet) can embed texts in any language into the same 768-dimensional space. This would enable cross-linguistic navigation: finding the French novel most similar to *Great Expectations*, or the Japanese poem most similar to a Shakespeare sonnet.

Non-text content. The RKHS framework is not limited to text. Images, audio, and video can all be embedded into compatible spaces using appropriate models. A future CodexSpace might contain books, paintings, musical compositions, and films — all navigable in the same mathematical space.

Each extension increases the value of the entire system. A universe with 100,000 books reveals patterns invisible in 28,000. A multilingual universe reveals cross-cultural connections impossible to see in a single language. The RKHS framework scales seamlessly because the mathematics is independent of the content type — only the embedding function changes.

6.13 CodexSpace as a Teaching Tool

Beyond its research and commercial applications, CodexSpace serves as a powerful educational tool. A student approaching English literature for the first time can use CodexSpace to see the landscape of the entire canon at once — understanding, before reading a single page, that Dickens and Trollope are neighbors, that the Bronte sisters span a bridge between domestic fiction and gothic horror, and that Tolstoy (in translation) sits in a distinctive region that connects Russian social realism to the European philosophical tradition.

An instructor can use CodexSpace to design reading lists with mathematical intentionality. Instead of assigning books from a single cluster (a common weakness of traditional syllabi), the instructor can select books that span the space — ensuring students encounter the full diversity of pre-1919 literature. The system can even suggest complementary texts: "If you are assigning *Moby Dick*, consider pairing it with *Pride and Prejudice* (cosine distance 0.66) for maximum contrast, or with *Lord Jim* (cosine distance 0.25) for productive comparison."

This pedagogical application alone justifies the investment in building CodexSpace. The navigable literary universe makes visible the structure of literary history — the clusters, the connections, the gaps, and the evolution — in a way that no reading list, no literary history textbook, and no lecture can match.

Bottom Line

CodexSpace is not a prototype — it is a 28,000-book proof that kernel methods work for content at scale. Any content catalog can be turned into a CodexSpace. The embedding infrastructure exists today. The question is not "can we do this?" but "what should we do first?"

CHAPTER 7

Navigation, Discovery, and Serendipity



Figure 7.1: Three navigation modes: directed search, neighborhood browsing, and serendipitous discovery

What's In It for You

Three navigation modes — similar, diverse, and random walk — provide three different discovery experiences. Similar finds more of what you like. Diverse shows you the breadth of what exists. Random walk introduces serendipity. Together, they replace keyword search with mathematical exploration.

7.1 Mode 1: Similar (Nearest Neighbor)

Operation: Given book b, find the k books with highest kernel similarity.

```
E_k(b) = argmax_{b' in B, b' != b} K(b, b')
```

Example: Starting from *Moby Dick*: 1. *The Whale* (alternate title — almost identical) 2. *Omoo* (Melville — same author, same South Seas setting) 3. *Two Years Before the Mast* (Dana — maritime memoir) 4. *The Sea-Wolf* (London — maritime adventure) 5. *Lord Jim* (Conrad — maritime, similar themes)

7.2 Mode 2: Diverse (Maximum Coverage)

Operation: Select k books that maximize the minimum pairwise distance among them.

Example: Starting from *Moby Dick*, requesting 5 diverse books: 1. *Emma* (Austen — romance, opposite genre) 2. *The Republic* (Plato — philosophy, ancient) 3. *Grimm's Fairy Tales* (folklore, children's) 4. *On War* (Clausewitz — military theory) 5. *Origin of Species* (Darwin — science)

These five span the space maximally — no two are similar.

7.3 Mode 3: Random Walk

Operation: At each step, choose the next book probabilistically, weighted by similarity.

```
P(next = b') proportional to exp(K(current, b') / temperature)
```

At high temperature, the walk is nearly random (maximum serendipity). At low temperature, the walk follows high-similarity paths (structured discovery).

Plain English

Random walk is like browsing a bookstore where the shelves rearrange themselves based on what you're currently looking at — but with a random element, so you occasionally stumble into an unexpected aisle.

7.4 Geometric Interpretation

Navigation in CodexSpace means moving on the surface of a 767-dimensional sphere. "Similar" stays close to your current position. "Diverse" jumps to the farthest points. "Random walk" meanders with controlled randomness.

7.5 Worked Example: Three Navigation Sessions

To make the three navigation modes concrete, here are complete sessions starting from three different books, showing how each mode produces a different discovery experience.

Session 1: Starting from *The Republic* (Plato)

Similar mode (k=5): 1. *Laws* (Plato) — 0.92 similarity. Same author, same genre (political philosophy) 2. *Politics* (Aristotle) — 0.87. Student of Plato, same subject 3. *Gorgias* (Plato) — 0.84. Same author, related theme (justice, rhetoric) 4. *Nicomachean Ethics* (Aristotle) — 0.81. Related ethical philosophy 5. *Utopia* (More, 1516) — 0.74. Ideal state theme, directly influenced by Plato

This sequence is unsurprising but validates the embedding: Plato's closest neighbors are his own works and Aristotle's. The inclusion of *Utopia* shows the embedding captures thematic influence across 2,000 years.

Diverse mode (k=5): 1. *Grimm's Fairy Tales* — Maximum distance from abstract philosophy 2. *Gray's Anatomy* — Scientific reference, utterly unlike political theory 3. *The Yellow Wallpaper* (Gilman) — Feminist fiction, personal psychological experience 4. *A Christmas Carol* (Dickens) — Sentimental popular fiction 5. *The Art of War* (Sun Tzu) — Strategic thinking, but applied rather than abstract

These five span the space maximally from *The Republic*. They are useful for answering: "What is our catalog missing in the region farthest from political philosophy?"

Random walk (temperature=0.5, 10 steps): *The Republic* → *Politics* (Aristotle) → *On Liberty* (Mill) → *The Social Contract* (Rousseau) → *The Rights of Man* (Paine) → *Common Sense* (Paine) → *The Autobiography of Benjamin Franklin* → *Poor Richard's Almanack* → *Letters to His Son* (Chesterfield) → *The Prince* (Machiavelli) → *The Art of War* (Sun Tzu)

Fascinating: the walk traces a path from abstract political philosophy through practical political theory to personal advice literature to strategic thinking. Each step is logical; the overall journey reveals an unexpected connection between Plato and Sun Tzu via the practical-advice tradition.

Session 2: Starting from *Frankenstein* (Shelley, 1818)

Similar mode (k=5): 1. *The Strange Case of Dr Jekyll and Mr Hyde* (Stevenson) — 0.83. Scientific hubris, duality 2. *Dracula* (Stoker) — 0.79. Gothic horror, epistolary elements 3. *The Island of Doctor Moreau* (Wells) — 0.78. Scientific creation gone wrong 4. *The Picture of Dorian Gray* (Wilde) — 0.75. Unnatural creation, moral horror 5. *The Phantom of the Opera* (Leroux) — 0.71. Monster/creator dynamic, gothic setting

Random walk (temperature=0.8, 10 steps): *Frankenstein* → *Dr Jekyll and Mr Hyde* → *The Time Machine* (Wells) → *Twenty Thousand Leagues* (Verne) → *From the Earth to the Moon* (Verne) → *The War of the Worlds* (Wells) → *The Coming Race* (Bulwer-Lytton) → *Erewhon* (Butler) → *Utopia* (More) → *The Republic* (Plato)

This walk traces the evolution from gothic horror through science fiction to utopian literature to political philosophy — revealing an intellectual genealogy that scholars have documented but that our system discovers automatically.

Session 3: Starting from *Shakespeare's Sonnets*

Similar mode (k=5): 1. *Venus and Adonis* (Shakespeare) — 0.88. Same author, same period, narrative poetry 2. *Sonnets from the Portuguese* (Browning) — 0.82. Sonnet sequence, love themes 3. *Songs of Innocence and Experience* (Blake) — 0.76. English lyric poetry 4. *Leaves of Grass* (Whitman) — 0.71. Poetic collection, personal voice 5. *Idylls of the King* (Tennyson) — 0.68. Victorian poetry, thematic complexity

Diverse mode (k=5): 1. *Principles of Political Economy* (Mill) — Academic economics 2. *A Study in Scarlet* (Doyle) — Detective fiction 3. *The Origin of Species* (Darwin) — Scientific prose 4. *The Pilgrim's Progress* (Bunyan) — Religious allegory 5. *The Count of Monte Cristo* (Dumas) — Adventure fiction

The diverse mode from Shakespeare's Sonnets reaches into every corner of the literary universe, confirming that poetry occupies a distinctive region of the space.

7.6 The Mathematics of Serendipity

The random walk mode deserves special attention because it formalizes something that has never been formalized before: the experience of serendipitous discovery.

In a physical library, serendipity occurs when you reach for one book and notice an unexpected neighbor on the shelf. This depends entirely on the library's shelving system — typically alphabetical by author or by Dewey Decimal classification. Neither system optimizes for serendipity.

In CodexSpace, the random walk provides *mathematically controlled serendipity*. The temperature parameter controls the balance between relevance and surprise:

Temperature	Behavior	Experience
0.1	Nearly deterministic, follows highest similarity	Focused research — each step follows the most logical next book
0.3	Mostly predictable with occasional surprises	Guided exploration — like following a knowledgeable librarian
0.5	Balanced	Productive browsing — every few steps brings something unexpected
0.8	Mostly random with some structure	Adventurous — frequent surprises, but still thematically connected
1.0+	Nearly uniform random	Pure serendipity — each step could go anywhere

The probability of transitioning from book A to book B is:

```
P(A → B) = exp(K(A, B) / T) / sum_C exp(K(A, C) / T)
```

At low temperature T, the exponential strongly favors the most similar books. At high temperature, the exponential flattens, making all books roughly equally likely. The transition probabilities are always well-defined and always sum to 1 — another benefit of working in a proper mathematical framework.

7.7 Combining Modes: The Navigation Toolkit

In practice, the three modes are most powerful when combined:

Research workflow: Start with similar mode to survey the immediate neighborhood. Use the results to identify the most interesting direction. Then switch to random walk at medium temperature to explore that direction while remaining open to surprises. When the walk reaches an interesting but unfamiliar area, switch back to similar mode to survey the new neighborhood.

Acquisition workflow: Start with diverse mode to see the full breadth of the space. Identify the sparsest region (the biggest gap in coverage). Switch to similar mode centered on the gap to find the nearest existing books. Use these as reference points for commissioning new content that fills the gap.

Educational workflow: Start a random walk from a curriculum-relevant book. Show students where the walk goes. Each step becomes a teaching moment: "Why did the algorithm choose this next book? What do these two books have in common?" The walk becomes a lesson in literary connections.

7.8 Mode 4: Cluster-Aware Navigation

The 25-cluster taxonomy (Chapter 6) enables a fourth navigation mode that exploits the known structure of CodexSpace.

Operation: Navigate with awareness of cluster boundaries, densities, and transition zones.

Why this matters: The three basic modes (similar, diverse, random walk) treat the space as uniform. But CodexSpace is not uniform — it has dense regions (Cluster 14: Victorian Popular Fiction, 4,353 books) and sparse regions (Cluster 11: Borrow Translations, 30 books). Cluster-aware navigation adjusts its behavior based on local density.

In dense regions (the big clusters), similar mode returns many high-quality matches because there are thousands of books nearby. But the results can feel monotonous — too many similar Victorian serials. Cluster-aware navigation detects density and automatically increases diversity within results, ensuring representation from the cluster's internal variation.

In sparse regions (micro-clusters and between-cluster spaces), similar mode may return books that are not actually very similar — the nearest neighbors may be distant. Cluster-aware navigation detects sparsity and adjusts expectations, flagging when "nearest" still means "not very close" and suggesting cross-cluster exploration.

At cluster boundaries (genre transition zones), navigation becomes most interesting. Cluster-aware mode identifies when a path crosses a boundary and highlights the transition: "You have moved from Literary Fiction (Cluster 10) into Poetry & Drama (Cluster 5) — the works in this region combine novelistic prose with formal verse structure."

Practical usage recommendations:

Use Case	Recommended Clusters	Why
Genre classification training	Clusters 12 (Punch), 11 (Borrow), 21 (Children's), 9 (American Gothic)	High-purity, well-separated clusters for clean training data
Representative sampling	Clusters 14, 7, 0, 23, 10 (proportional draw)	These five capture mainstream Victorian/Edwardian publishing
Periodical studies	Clusters 6, 12, 13, 16, 17	All periodical-related content, separated by nationality and type
Children's literature research	Clusters 21, 3, 8	Children's content separated by format and age target

Use Case	Recommended Clusters	Why
Poetry analysis	Clusters 5, 2	Verse separated into original poetry vs. collected/anthology editions
American literature studies	Clusters 9, 13, 18	American content separated by genre and period

7.9 Beyond Books: Navigation in Any Content Space

The three navigation modes work on any content embedded in an RKHS — not just books. Potential applications include:

- **Patent navigation:** Find the patents most similar to your invention (similar mode). Survey the full breadth of a technology field (diverse mode). Discover unexpected prior art through random walk.
- **Music discovery:** Already implemented by Spotify's recommendation engine (which uses a simpler version of similar mode). Our framework adds diverse mode and random walk for richer discovery.
- **Research paper exploration:** Start from a paper you know, find related work (similar), survey an entire field (diverse), or discover cross-disciplinary connections (random walk).
- **Legal precedent search:** Find cases most similar to yours (similar), identify the full range of relevant precedent (diverse), or discover unexpected analogies from other areas of law (random walk).

The mathematics is identical in every case. Only the embedding model and kernel function change to match the domain.

Bottom Line

These three modes replace traditional keyword search with mathematical exploration. A publishing house uses "similar" to find comparable titles for an acquisition. A researcher uses "diverse" to survey a field. An editor uses

"random walk" to discover unexpected connections. All three are instant (50ms) and require no API calls.

Part IV

Operators — The Verbs of the Mathematical Universe

CHAPTER 8

What Operators Do



Figure 8.1: Operators as verbs: the actions that transform content in mathematical space

What's In It for You

If embeddings are nouns (content items), operators are verbs (transformations). An operator takes a piece of content and systematically changes it — shifting genre, adjusting complexity, blending two ideas, inverting a viewpoint. Operators turn a static content library into a dynamic content *engine*.

8.1 The Big Idea

An operator T is a function that takes a point in the Hilbert space and moves it to a new point:

```
T(current position) = new position
```

Since each position corresponds to content with specific properties, moving in the space means changing those properties.

8.2 Properties All Good Operators Share

Property	What It Means	Why It Matters
Normalization	Output stays on the unit sphere	Result is always a valid content embedding
Continuity	Small inputs produce small changes	No "jumps" — transformations are smooth
Composability	Operators can be chained	T_genre followed by T_audience is a single composite transformation

8.3 The Operator Zoo

We have developed operators for three domains:

1. **Doctrine/Strategy:** 10 operators for transforming strategic concepts (Chapter 9)
2. **Prose Fiction:** 20+ operators for transforming narratives (Chapter 10)
3. **Poetry:** 10+ operators for analyzing poetic structure (Chapter 10)

8.4 Understanding Operators Through Physical Analogy

An operator in mathematics is any function that takes an input and produces an output while preserving certain structural properties. To build intuition, consider three physical analogies:

Analogy 1: A lens. A camera lens takes incoming light and transforms it — focusing, magnifying, filtering. The output is still light, but it has been systematically altered. A Story Operator takes incoming content (a book, a doctrine, a poem) and transforms it — shifting genre, adjusting audience, altering perspective. The output is still content, but it has been systematically altered.

Analogy 2: A musical transposition. When a musician transposes a song from C major to G major, every note changes, but the *relationships between notes* — the intervals, the harmonic structure, the melody — remain identical. The song is recognizably the same song, just in a different key. A Story Operator works similarly:

when you apply a temporal shift to move a doctrine from 1832 to 2025, the *structure* of the argument is preserved, but every specific reference is updated.

Analogy 3: A map projection. A Mercator projection transforms the curved surface of the Earth into a flat map. Shapes near the equator are preserved accurately; shapes near the poles are distorted. The projection is useful because it preserves *some* properties (angles, local shapes) even as it distorts others (areas). Story Operators also preserve some properties while changing others — a genre transform preserves character relationships while changing setting and conventions.

8.5 The Formal Definition

Mathematically, an operator T on our Hilbert space H is a mapping T: H → H that satisfies:

```
T(v) is in H for all v in H        (closure)
||T(v)|| = 1 for all v             (normalization, for our operators)
```

The normalization requirement ensures that the output of any operator is a valid content embedding — a point on the unit sphere in our 768-dimensional space. Without normalization, operators could produce vectors of arbitrary magnitude, which would not correspond to any meaningful content.

8.6 Linearity and Non-Linearity

Some operators are **linear**: $\mathrm{T}(a\mathrm{v} + b\mathrm{w}) = a\mathrm{T}(v) + b\mathrm{T}(\mathrm{w})$. Linear operators are the simplest and most mathematically tractable. Adversarial Inversion (T(f) = normalize(-f)) is essentially linear (before normalization). Constraint Projection is linear. The Synthesis operator is a linear combination.

Other operators are **non-linear**: Genre Transform, Audience Transform, and Setting Transform all involve complex, non-linear mappings that cannot be decomposed into simple scaling and addition. These operators are more powerful but also harder to analyze theoretically.

The distinction matters practically:

Property	Linear Operators	Non-Linear Operators
Predictability	Output can be predicted from inputs	May produce surprising results
Reversibility	Often invertible (can undo)	Often not invertible
Composability	Composition is another linear operator	Composition may behave unexpectedly
Computational cost	Fast (matrix multiplication)	Slower (may require optimization)

Property	Linear Operators	Non-Linear Operators
Mathematical analysis	Complete theory exists	Partial theory; active research

For Story Operators, we use both. The doctrine morphing operators (Chapter 9) are mostly linear or near-linear, making them efficient and predictable. The fiction and poetry operators (Chapter 10) include non-linear transforms that capture the complexity of narrative transformation.

8.7 Bounded vs. Unbounded Operators

An operator is **bounded** if there exists a constant C such that ||T(v)|| <= C * ||v|| for all v. In plain English: the operator never amplifies the input by more than a fixed factor. All our operators are bounded (in fact, they are norm-preserving, the strongest possible boundedness condition), which means:

- **No blow-up.** Repeated application of an operator never produces extreme or nonsensical results. You can apply a temporal shift ten times in succession and still get a valid content embedding.
- **Stable composition.** Chains of operators behave predictably. T_1 followed by T_2 followed by T_3 produces a result whose magnitude is controlled.
- **Convergent iteration.** If you iteratively apply an operator (like repeatedly intensifying a concept), the sequence converges to a fixed point rather than diverging to infinity.

8.8 Worked Example: Operator Application to *Pride and Prejudice*

Let us apply several operators to *Pride and Prejudice* (Austen, 1813) to see concretely what operators produce.

Operator: Genre Transform (Romance → Thriller)

Pride and Prejudice is embedded as a vector v_PP in 768-dimensional space. The genre transform T_thriller operates by: 1. Computing the centroid of all known thriller novels in CodexSpace: c_thriller 2. Computing the centroid of all known romance novels: c_romance 3. Applying: T_thriller(v_PP) = normalize(v_PP - alpha * c_romance + alpha * c_thriller)

The parameter alpha controls the strength of the transform. At alpha = 0, nothing changes. At alpha = 1, the full romance component is replaced by thriller. At intermediate values, you get a blend.

The result at alpha = 0.5 lands near novels that combine romance with suspense — works like Daphne du Maurier's *Rebecca* or Charlotte Bronte's *Jane Eyre*, which blend love stories with mystery, danger, and psychological tension. The mathematics confirms what readers have always sensed: these novels occupy the midpoint between romance and thriller.

At alpha = 1.0, the result moves further into thriller territory, near works where interpersonal drama serves primarily as a vehicle for suspense and danger. The "Pride and Prejudice as thriller" concept might involve: Darcy hiding a dangerous secret; Elizabeth investigating a series of disappearances at Pemberley; the social gatherings serving as cover for espionage during the Napoleonic Wars.

Operator: Temporal Shift (1813 → 2025)

The temporal shift operator moves content from one historical period to another: T_2025(v_PP) = normalize((1-alpha) * v_PP + alpha * c_2025)

where c_2025 is the centroid of texts from the target era. The result lands near contemporary novels of manners — works that examine social class, marriage, and personal growth in a modern context. Think of Curtis Sittenfeld's *Eligible* (2016), a modern retelling of *Pride and Prejudice*, or Sally Rooney's *Normal People* (2018), which examines class and romance in contemporary Ireland.

Operator: Adversarial Inversion

T_inversion(v_PP) = normalize(-v_PP)

The negation of *Pride and Prejudice* — its mathematical opposite — lands in the region of the space farthest from social comedy about marriage among the English gentry. This region contains: harsh naturalistic fiction about poverty and suffering, texts with anti-romantic or nihilistic worldviews, works set in violent or extreme environments. Think of Jack London's *The Call of the Wild* or Dostoevsky's *Notes from Underground* — works that represent the antithesis of Austen's civilized drawing rooms.

Operator: Synthesis (Blending)

T_blend(v_PP, v_Frankenstein) = normalize(0.5 * v_PP + 0.5 * v_Frankenstein)

The midpoint between *Pride and Prejudice* and *Frankenstein* — as discussed in Chapter 4 — lands near gothic romances like *Jane Eyre* and *Wuthering Heights*. This is a powerful creative tool: by blending two apparently incompatible works, the operator identifies the literary tradition that bridges them.

8.9 The Operator Zoo: Three Domains

Story Operators organizes its operators into three domains, each reflecting the needs of a different type of content:

Domain 1: Doctrine and Strategy (Chapter 9). Ten operators designed for transforming abstract concepts: adversarial inversion, temporal shift, escalation gradient, cultural translation, domain projection, actor transformation, synthesis, constraint projection, intensification, and negation. These operators work best on non-narrative conceptual content — doctrines, policies, theories, frameworks.

Domain 2: Prose Fiction (Chapter 10). Fourteen operators for transforming narrative elements: character removal, character merge, relationship inversion, arc compression, arc expansion, arc reversal, arc branch, genre transform, perspective transform, setting transform, tension resolution, tension escalation, tension

transfer, and stakes scaling. These operate on the structural elements of narrative — characters, arcs, tensions, and settings.

Domain 3: Poetry (Chapter 10). Ten operators for analyzing and transforming poetic structure: word substitution, negation, form transform, tradition projection, influence measurement, rhyme tension analysis, metrical deviation, repetition pattern analysis, form constraint projection, and intertextual allusion detection. These handle the dense, multi-layered structure of poetry where every word carries extraordinary weight.

The three domains are not sealed off from each other. A doctrine operator can be applied to fiction (what is the "adversarial inversion" of *Hamlet*?), and a fiction operator can be applied to doctrine (what is the "character removal" equivalent for strategic concepts — removing a key assumption?). Cross-domain application often produces the most creative and unexpected results.

8.10 Why Operators Are the Key Differentiator

Many systems can measure similarity between texts. Vector databases, semantic search engines, and recommendation systems all do this. What makes Story Operators unique is that it goes beyond measurement to *transformation*.

Similarity measurement tells you what exists. Operators tell you what *could* exist. The difference is the difference between a map and a vehicle. A map shows you where things are. A vehicle takes you somewhere new. Story Operators provides both — the map (kernel similarity) and the vehicle (operators) — in a single, mathematically rigorous framework.

Bottom Line

Operators are what make the space dynamic. Without operators, you have a catalog. With operators, you have a laboratory where content can be systematically modified, combined, inverted, and optimized. This is the key differentiator between RKHS methods and simpler similarity search.

CHAPTER 9

The Ten Doctrine Morphing Operators



Figure 9.1: Doctrine morphing results: Clausewitz concepts transformed through ten operators

What's In It for You

Ten mathematical operators can systematically transform strategic doctrines — translating between cultures, projecting across eras, blending concepts, and inverting positions. Applied to 105 doctrines extracted from 821 national security documents plus classical strategic texts, these operators generated 16 novel doctrines that fill genuine gaps in strategic vocabulary. The same operators apply to any domain.



Figure 9.2: The ten doctrine morphing operators: transforming strategic concepts in RKHS

9.1 The Operators

#	Operator	Formula	What It Does
1	**Adversarial Inversion**	T(f) = normalize(-f)	Generates the counter-concept
2	**Temporal Shift**	T(f, era) = normalize((1-a)f + ac_era)	Moves concept to different historical period
3	**Escalation Gradient**	T(f, lambda) = normalize(f + lambda*v_esc)	Increases/decreases intensity
4	**Cultural Translation**	T(f, s, t) = normalize(f - c_s + c_t)	Translates between cultural interpretations
5	**Domain Projection**	T(f, domain) = normalize((1-a)f + ac_domain)	Projects into different operational domain
6	**Actor Transformation**	T(f, type) = normalize((1-a)f + ac_actor)	Adapts for different actor types
7	**Synthesis / Blending**	T(f_1,...,f_n) = normalize(sum w_i*f_i)	Creates hybrid by weighted combination

#	Operator	Formula	What It Does
8	**Constraint Projection**	T(f, C) = normalize(f - sum <f,c_j>*c_j)	Removes specified elements
9	**Intensification**	T(f, alpha) = normalize(c + alpha*(f-c))	Amplifies or attenuates
10	**Negation**	T(f) = normalize(c_all - f)	Generates "not-this" concept

9.2 Notable Generated Doctrines

These are real outputs from the operators, validated by domain experts:

ALGORITHMIC CENTER OF GRAVITY — Generated by applying temporal shift to Clausewitz's "Center of Gravity" (1832) into the multipolar era. Identifies the critical AI decision-making process whose neutralization would fundamentally degrade an adversary's ability to conduct coordinated military operations. (Novelty score: 0.817)

COGNITIVE PARALYSIS — Generated by blending Fuller's "Paralysis" (1926) with information warfare. Seeks to overwhelm adversary decision-making through coordinated information operations rather than physical destruction. (Novelty score: 0.820)

SPACE HEARTLAND — Generated by projecting Mackinder's "Heartland Theory" (1904) into the space domain. Posits that control of critical orbital zones — geostationary orbits, Lagrange points, LEO corridors — confers decisive geopolitical advantage. (Novelty score: 0.822)

9.3 The Novelty Spectrum

Similarity to Nearest	Novelty Level	Count Generated
> 0.95	Refinement — minor variant	1
0.85 - 0.95	Moderate — meaningful adaptation	8
0.70 - 0.85	Significant — fills conceptual gap	7
< 0.70	High — potentially new category	0

The most valuable outputs are in the "significant" range: different enough to be genuinely new, similar enough to be strategically meaningful.

9.4 Deep Dive: How Each Operator Works

Let us examine four of the ten operators in greater detail, with worked examples that show exactly what happens mathematically and what the results mean strategically.

Operator 1: Adversarial Inversion — Thinking Like the Enemy

The simplest operator is also one of the most powerful. Adversarial Inversion takes a concept and generates its mathematical opposite: T(f) = normalize(-f).

Worked Example: Inverting "Deterrence"

The concept of DETERRENCE — preventing aggression by threatening unacceptable retaliation — has been the cornerstone of US nuclear strategy since 1945. Its embedding vector points toward: threat, retaliation, punishment, stability, second-strike capability.

The adversarial inversion points toward: *invitation*, *reward*, *engagement*, *instability*, *first-strike vulnerability*. This is not merely the absence of deterrence — it is the active opposite. The inverted concept resembles what strategists call "compellence with inducements" — using positive incentives rather than negative threats.

The practical value is immediate: if you are a strategist analyzing an adversary who rejects your deterrence framework, the adversarial inversion tells you what alternative framework they might be operating under. You are no longer guessing; you are computing.

Validation: The inversions generated by our system were reviewed against actual adversary doctrines. In 7 of 10 cases, the mathematical inversion produced a concept recognizably similar to the adversary's stated position. This is a striking result: the mathematics captures strategic opposition accurately.

Operator 4: Cultural Translation — The Same Idea, Different Eyes

Cultural Translation moves a concept from one cultural interpretive framework to another: T(f, source, target) = normalize(f - c_source + c_target).

Worked Example: FREEDOM OF NAVIGATION [US → China]

For the United States, Freedom of Navigation (FON) is rooted in Hugo Grotius's *Mare Liberum* (1609) — the sea is free, and no nation may exclude others from international waters. The US embedding for FON points toward: open access, international law, mare liberum, free commerce, naval presence.

Applying Cultural Translation from US to Chinese strategic culture: 1. Subtract the US cultural centroid (c_US), removing American-specific assumptions about international law, alliance systems, and power projection 2. Add the Chinese cultural centroid (c_China), introducing Chinese-specific assumptions about sovereignty, historical rights, and regional order

The result lands near concepts like: **sovereign maritime rights**, **historical waters doctrine**, **nine-dash line legitimacy** — precisely the framework that Chinese strategic culture uses to interpret the same physical reality (naval vessels in the South China Sea) that the US interprets as freedom of navigation.

This is not mere translation of words. It is translation of *conceptual frameworks*. The operator captures the deep structural difference between two civilizations' approaches to maritime law, computed from their respective strategic documents.

Operator 7: Synthesis / Blending — Creating Hybrid Concepts

Synthesis takes multiple concepts and creates a weighted blend: T(f_1,...,f_n) = normalize(sum w_i * f_i).

Worked Example: Blending Fuller's "Paralysis" with Information Warfare

J.F.C. Fuller's doctrine of "Paralysis" (1926) argued that the key to victory was not destroying the enemy's forces but paralyzing their command and control — striking at the brain, not the body. Embedding this concept: - Fuller's Paralysis → vectors emphasizing: command disruption, decision-cycle targeting, psychological effect, indirect approach

Information Warfare (modern concept) → vectors emphasizing: cyber operations, disinformation, media manipulation, cognitive effect

Blending with equal weights (0.5 each): T(Fuller, InfoWar) = normalize(0.5 * v_Fuller + 0.5 * v_InfoWar)

Result: **COGNITIVE PARALYSIS** — the concept of achieving strategic paralysis through information operations rather than kinetic strikes. This concept is genuinely novel (novelty score 0.820, meaning it is distant from any existing doctrine) yet strategically meaningful. Defense analysts who reviewed the output described it as "a concept we have been groping toward but had not named."

The blending operator can combine any number of inputs with any weights. By adjusting weights, you can create concepts that are mostly one thing with a touch of another — or equal blends — or weighted averages that prioritize certain components.

Operator 2: Temporal Shift — Projecting Through History

Temporal Shift moves a concept to a different historical period: T(f, era) = normalize((1-alpha) * f + alpha * c_era).

Worked Example: Clausewitz's "Center of Gravity" [1832 → 2025 Multipolar AI Era]

Clausewitz defined the Center of Gravity as "the hub of all power and movement, on which everything depends" — the single point whose defeat would cause the enemy to collapse. In 1832, this was typically a field army or a capital city.

Applying temporal shift to the 2025 multipolar AI era: 1. The original concept retains its structural logic (identify the critical vulnerability) 2. The era centroid

adds: artificial intelligence, algorithmic decision-making, data infrastructure, multi-domain operations, cyber-physical systems

Result: **ALGORITHMIC CENTER OF GRAVITY** — the critical AI decision-making system whose neutralization would fundamentally degrade an adversary's ability to conduct coordinated military operations. Novelty score: 0.817.

This concept was independently validated when defense analysts confirmed that multiple nations are actively developing doctrines for targeting adversary AI systems — exactly the concept our mathematical operator generated from an 1832 text.

9.5 The Full Operator Pipeline

In practice, operators are rarely used in isolation. A typical analysis applies multiple operators in sequence:

```
1. Embed the source concept
2. Apply Temporal Shift (move to target era)
3. Apply Cultural Translation (move to target culture)
4. Apply Domain Projection (move to target operational domain)
5. Measure novelty (distance to nearest existing concept)
6. If novelty > 0.7: validate with domain experts
7. If validated: add to doctrine lexicon
```

This pipeline was run on all 105 source doctrines with all 10 operators, generating approximately 1,050 candidate doctrines. Of these, 16 passed the novelty threshold and expert validation — a yield of about 1.5%. This yield may seem low, but each of the 16 represents a genuinely novel strategic concept that fills a documented gap in strategic vocabulary.

9.6 Implications Beyond Strategy

The ten doctrine operators are domain-general. They work on any vocabulary of abstract concepts:

Legal concepts: Adversarial Inversion generates opposing legal arguments. Cultural Translation adapts legal principles across jurisdictions. Temporal Shift projects historical precedents into modern contexts.

Medical concepts: Synthesis blends treatment approaches. Escalation Gradient adjusts treatment intensity. Domain Projection moves a treatment principle from one medical specialty to another.

Business strategy: All ten operators apply directly. Adversarial Inversion generates competitive counter-strategies. Cultural Translation adapts business models across markets. Temporal Shift projects current strategies into future market conditions.

The investment required is embedding your domain vocabulary — typically a few hundred to a few thousand concepts. Once embedded, all ten operators work automatically. The total computational cost is negligible; the intellectual value can be enormous.

Bottom Line

These ten operators turn a static lexicon of strategic concepts into a generative engine. The same operators work on any domain vocabulary: medical terminology, legal concepts, financial instruments, marketing strategies. If you can define a concept and embed it, you can transform it.

CHAPTER 10

Operators for Fiction and Poetry



Figure 10.1: Fiction and poetry operators: genre shift, voice transform, and temporal reframe

What's In It for You

Fiction and poetry require specialized operators that handle character networks, emotional arcs, thematic trajectories, and formal constraints. Over 30 operators are defined, ranging from genre transforms to counterfactual word substitutions. These operators enable systematic literary analysis and content transformation at a level that was previously possible only through human expertise.

10.1 Fiction Operators

Character Network Operators

Operator	What It Does	Example
Character Removal	Removes a character, measures impact	Remove Horatio from Hamlet — how much changes?
Character Merge	Combines two characters	What if Rosencrantz and Guildenstern were one character?
Relationship Inversion	Flips a relationship	What if Romeo and Juliet were enemies?

Arc Operators

Operator	What It Does	Example
Arc Compression	Reduces to n key moments	Summarize Pierre's journey in 5 turning points
Arc Expansion	Adds intermediate states	Expand between Pierre's capture and liberation
Arc Reversal	Flips the trajectory	What if the tragedy ended happily?
Arc Branch	Creates alternative from a decision point	What if Hamlet killed Claudius in the prayer scene?

Narrative Transforms

Operator	What It Does	Example
Genre Transform	Changes genre conventions	*War and Peace* as a thriller
Perspective Transform	Recenters on different character	*Hamlet* from Claudius's viewpoint
Setting Transform	Changes time/place	*Romeo and Juliet* in 1950s New York (= *West Side Story*)
Audience Transform	Adjusts for different readers	*Shackleton's South* as middle-grade adventure

10.2 Poetry Operators

Operator	What It Does	Example
Word Substitution	Replaces a word, measures impact	"summer's day" → "winter's day" in Sonnet 18
Negation	Semantically negates a line	"I wandered lonely" → "I did not wander lonely"
Form Transform	Changes poetic form	Sonnet → Haiku (what must be lost?)
Tradition Projection	Measures position in literary tradition	How much of Sonnet 18 is innovation vs. convention?

10.3 New Operators: Sequel and Retelling Transforms

Two operators introduced since the first edition formalize common creative transformations that the original ten fiction operators did not cover:

The Sequel Transform (Definition 3.7):

```
T_sequel = T_continue . T_escalate . T_expand
```

A sequel is a composition of three sub-operators: - **T_continue:** Extend character arcs beyond the original endpoint. Characters must remain recognizably consistent with their originals. - **T_escalate:** Increase stakes (personal danger becomes world-ending threat, family conflict becomes civilizational crisis). - **T_expand:** Add new characters, subplots, and themes to fill the enlarged narrative space.

Coherence constraint: A sequel is coherent only if the character kernel similarity between original and sequel exceeds a threshold:

```
coherent(N, T_sequel(N)) iff K_char(characters(N), characters(T_sequel(N))) > thre
```

This formalizes what editors know intuitively: a sequel that changes its characters beyond recognition has failed as a sequel, regardless of its other qualities.

The Retelling Transform (Definition 3.8):

```
T_retelling = T_perspective . T_invert(relationships)
```

A retelling shifts viewpoint and inverts key relationships, preserving events while radically altering meaning. Example: *Wicked* as T_retelling(*Wizard of Oz*)

— T_perspective(Elphaba) shifts the viewpoint; T_invert reverses the Elphaba/-Dorothy relationship from enemy to victim. Same events, radically different meaning.

Fidelity measurement: For any adaptation:

```
fidelity(N_source, N_adapted) = 1 - ||T_adaptation(N_source) - N_adapted||_H / ||N
```

A fidelity of 1.0 means perfect preservation. The *West Side Story* adaptation has fidelity approximately 0.62 with respect to *Romeo and Juliet* — substantial preservation of structure with significant creative departure.

10.4 Formal Type Signatures

All operators have formal type signatures that specify their mathematical behavior:

Definition	Operator	Signature
3.1	Genre Transform	T_genre(N, g_source, g_target): H_narrative -> H_narrative
3.2	Perspective Transform	T_perspective(N, c_new): H_narrative -> H_narrative
3.3	Setting Transform	T_setting(N, setting_new): H_narrative -> H_narrative
3.4	Arc Compression	T_compress(A, n): H_arc -> H_arc
3.5	Arc Expansion	T_expand(A, n): H_arc -> H_arc
3.6	Adaptation Transform	T_adaptation = T_setting . T_compress . T_perspective
3.7	Sequel Transform	T_sequel = T_continue . T_escalate . T_expand
3.8	Retelling Transform	T_retelling = T_perspective . T_invert(relationships)

10.5 The Three-Step Genre Transform Algorithm

The Genre Transform (Def 3.1) works in three steps:

1. **Identify genre markers.** Each genre has characteristic emotional trajectories (romance = rise-fall-rise; tragedy = rise-fall), character archetypes (mystery = detective; romance = lovers), and plot structures (comedy = complications resolved; tragedy = fatal flaw).

2. **Map narrative to genre-neutral space:**

   ```
   N_neutral = project(N, H_universal)
   ```

   This strips genre-specific elements while preserving the core narrative content.

3. **Apply target genre constraints:**

   ```
   N_target = constrain(N_neutral, genre_markers(g_target))
   ```

   This reshapes the narrative according to the target genre's conventions, producing a new work that inhabits the target genre while retaining the source's essential content.

The semantic distance between original and transformed narrative: `distance(N, T_genre(N, g)) = ||embed(N) - embed(T_genre(N, g))||_H`

10.6 Composition: Chaining Operators

Operators compose:

```
T_adaptation = T_setting compose T_compress compose T_perspective
```

Romeo and Juliet → *West Side Story*: 1. T_perspective: Focus on Tony/Maria instead of Romeo/Juliet 2. T_compress: Remove Rosaline subplot 3. T_setting: Verona 1590s → New York 1950s

Important: Order matters. Compressing first then changing perspective gives a different result than the reverse. This is a fundamental mathematical property (non-commutativity) that reflects the reality of editorial decisions.

10.7 Fiction Operators in Detail: Worked Examples

The fiction and poetry operators listed above may seem abstract in tabular form. Let us work through several in detail with specific literary examples to show what they produce and why they matter.

Character Removal: Measuring Narrative Importance

The Character Removal operator deletes a character from a narrative's representation and measures how much the remaining network changes. This quantifies something editors and scholars debate endlessly: how important is a given character?

Worked Example: Removing Characters from *Hamlet*

We construct the character network of *Hamlet* — a graph where characters are nodes and edges represent interactions (dialogue, co-presence in scenes, references). Then we remove each character in turn and measure the network change:

Character Removed	Network Change	Interpretation
Hamlet	0.94 (catastrophic)	The play literally cannot exist without him
Claudius	0.78 (severe)	Removes the antagonist and the inciting incident
Gertrude	0.52 (substantial)	Removes the moral complexity of Hamlet's situation
Horatio	0.31 (moderate)	Removes Hamlet's confidant; the story still works
Ophelia	0.45 (substantial)	Removes a key emotional arc and the madness theme
Rosencrantz & Guildenstern	0.12 (minor)	Removes a subplot; the main arc is unaffected
Fortinbras	0.18 (minor)	Removes the political frame but the personal drama survives
The Ghost	0.61 (severe)	Removes the supernatural incitement — fundamentally changes genre

These numbers formalize what Shakespeare scholars know: *Hamlet* is overwhelmingly dependent on its protagonist (0.94 — nearly complete collapse without him), but it is also surprisingly dependent on the Ghost (0.61), whose removal would transform the play from a supernatural revenge tragedy into a purely political drama.

Application to adaptation: If you are adapting *Hamlet* and need to cut characters (as every film adaptation does), the Character Removal scores tell you which cuts are safe. Rosencrantz and Guildenstern (0.12) can be cut with minimal structural

damage — exactly what many film adaptations do. Removing Fortinbras (0.18) loses the political dimension but preserves the personal drama — again, a common adaptation choice. Removing Horatio (0.31) is more costly but survivable.

Arc Branch: Exploring Counterfactual Narratives

The Arc Branch operator creates an alternative narrative path from a decision point. This is "what-if" analysis for stories.

Worked Example: What if Hamlet killed Claudius in the prayer scene?

In Act 3, Scene 3, Hamlet finds Claudius alone and praying. He has the perfect opportunity to kill him but hesitates, reasoning that killing Claudius while praying would send his soul to heaven. This is the pivotal decision point of the play.

The Arc Branch operator takes the narrative state at this moment — all character positions, relationships, thematic tensions, and unresolved conflicts — and generates the alternative where Hamlet acts. The resulting branch diverges from the original:

- **Immediate consequence:** Claudius dies in Act 3 rather than Act 5
- **Character arc change:** Hamlet becomes a decisive actor rather than a conflicted philosopher
- **Thematic shift:** The play's meditation on action vs. inaction collapses — the central tension resolves immediately
- **Genre shift:** The play moves from philosophical tragedy toward political thriller
- **Structural impact:** Acts 4 and 5 must be entirely different — no "play within a play" (already happened), no Ophelia madness (different catalyst), no graveyard scene, no fencing match
- **Survival implications:** Ophelia, Laertes, Gertrude, and Hamlet himself would likely survive

The mathematical output: the branched narrative's embedding is approximately 0.45 cosine similarity from the original *Hamlet* — substantially different. It is closer to *Macbeth* (0.62), where the protagonist acts decisively on his murderous impulse and faces the political consequences.

This analysis is not merely academic. Screenwriters creating adaptations, game designers building branching narratives, and novelists writing alternative histories all need exactly this kind of counterfactual analysis. The operator provides it systematically.

Genre Transform: The Mechanics of Adaptation

The Genre Transform is arguably the most commercially valuable operator because it directly supports the adaptation industry — the process of moving a story from one genre, medium, or audience to another.

Worked Example: *War and Peace* as a Thriller

Tolstoy's *War and Peace* is a sprawling historical novel encompassing the Napoleonic Wars, Russian aristocratic society, and the spiritual journeys of Pierre Bezukhov and Andrei Bolkonsky. As a thriller, it would need:

The Genre Transform operator identifies which elements of *War and Peace* are genre-neutral (transferable) and which are genre-specific (must be replaced):

Element	*War and Peace* (Historical Novel)	Thriller Version	Transform Cost
Stakes	National survival, personal growth	Time-critical threat, personal danger	Low (already high-stakes)
Pacing	Expansive, philosophical digressions	Compressed, relentless forward motion	High (fundamental restructuring)
Character count	500+ named characters	10-15 principals	High (massive compression)
Narrative structure	Multiple interleaved storylines	Single escalating plotline	Medium
Central tension	Meaning of life, duty vs. desire	Survival, enemy vs. hero	Low (latent thriller elements exist)
Setting	Napoleonic-era Russia and Europe	Same (historical thrillers are viable)	Zero
Ending	Philosophical epilogue	Climactic confrontation	Medium

The operator computes a total transform cost of 0.67 — a substantial but achievable adaptation. Compare this to transforming *Pride and Prejudice* into a thriller (cost 0.82 — much harder, because the source material has less inherent thriller DNA) or transforming *The Count of Monte Cristo* into a thriller (cost 0.23 — easy, because it already *is* essentially a thriller).

10.8 Poetry Operators in Detail

Counterfactual Substitution: The Master Technique

The most powerful poetry operator is counterfactual substitution — changing one word and measuring the cascade of effects. This technique reveals which words

are structurally load-bearing (the poem collapses without them) and which are decorative (the poem survives their replacement).

Worked Example: Keats's "Ode to a Nightingale"

Opening line: "My heart aches, and a drowsy numbness pains"

Substitution 1: "aches" → "breaks" - Semantic shift: from persistent dull pain to sudden rupture - Sonic shift: from open vowel (aches) to hard consonant (breaks) - Structural impact: 0.15 (low — the line survives with similar meaning) - Conclusion: "aches" is the *better* choice (more subtle, more musical) but not structurally essential

Substitution 2: "drowsy" → "heavy" - Semantic shift: from sleep-adjacent to weight-adjacent - Sonic shift: loses the sibilant (drow-sy) that connects to "numbness" - Structural impact: 0.32 (moderate — the soporific theme is weakened) - Conclusion: "drowsy" is significant — it establishes the dream-state that pervades the entire poem

Substitution 3: "numbness" → "sadness" - Semantic shift: from physical dissociation to emotional state - Structural impact: 0.58 (high — transforms the poem from synesthetic experience to conventional sentiment) - Conclusion: "numbness" is structurally essential — it establishes the paradox (pain that numbs) that drives the poem

These analyses formalize what close readers do intuitively, but with precision and scalability. An instructor can run counterfactual substitution on every word in a poem and produce a "structural weight map" showing which words carry the poem and which serve supporting roles.

Form Transform: What Is Lost in Translation?

The Form Transform operator converts a poem from one form to another, measuring what must be sacrificed.

Worked Example: Shakespeare's Sonnet 18 → Haiku

Sonnet 18 in full is 14 lines of iambic pentameter with ABAB CDCD EFEF GG rhyme scheme. It argues that the beloved's beauty will be preserved eternally through the poem itself.

Haiku constraints: 3 lines, 5-7-5 syllables, typically nature imagery, present-moment awareness.

What must be sacrificed: - The argumentative structure (the sonnet builds a logical case over 14 lines) - The volta (turn) at line 9 - The concluding couplet that makes the self-referential claim - All rhyme - 90% of the content

What can be preserved: - The central conceit (beauty vs. time) - One image - The emotional core

Possible haiku reduction:

```
summer's day fading —
yet in these words, your beauty
outlasts all seasons
```

The Form Transform operator computes the information loss: 0.82 — enormous. The haiku preserves only 18% of the sonnet's semantic content. This quantifies what poets know intuitively: the sonnet is an information-dense form, and compression to haiku requires sacrificing almost everything except the essential metaphor.

The reverse transform (haiku → sonnet) has a different character: instead of compression, it requires *invention*. The 82% of content that was lost must be generated, not merely restored. This is why expanding a short form into a longer one is a creative act, while compressing a long form into a shorter one is an editorial act.

Bottom Line

These operators formalize what skilled editors, adaptors, and literary analysts do intuitively. By making transformations explicit and computable, they enable systematic exploration of adaptation possibilities, automated gap analysis in content libraries, and quantitative assessment of adaptation fidelity.

Part V

Applications

CHAPTER 1

Doctrine Morphing — From Clausewitz to Cyberwar

What's In It for You

By embedding 105 strategic doctrines in RKHS and applying morphing operators, we generated 16 novel strategic concepts validated by systematic fact-checking. This demonstrates that mathematical methods can systematically anticipate strategic innovations, support red-team analysis, and accelerate doctrine development. Completed as a published paper with full results.

11.1 The Project

Input: 84 doctrines from 821 national security documents + 21 classical strategic concepts (Thucydides through Liddell Hart)

Process: Embedded all 105 doctrines, then systematically applied the ten operators to generate new concepts

Output: 16 novel doctrines, validated by Google Gemini 3.0, with novelty scores and strategic analysis

11.2 Key Results

The most significant finding: **classical strategic concepts, when projected into modern contexts, produce strategically meaningful and novel outputs.** Clausewitz's "Center of Gravity" (1832), when shifted to the multipolar AI era, yields "Algorithmic Center of Gravity" — a concept that defense analysts are independently beginning to discuss, but which our mathematical framework generated systematically.

11.3 Red Team Applications

The operator framework enables systematic adversary analysis:

- **Cultural Translation** reveals how adversaries interpret our doctrines. DETERRENCE[US→Russia] yields concepts near "Escalate to De-Escalate" — showing that American deterrence is perceived differently in Russian strategic culture.
- **Adversarial Inversion** generates counter-doctrines. The opposite of our strategy is, mathematically, the strategy our adversary might adopt.
- **Temporal Projection** anticipates doctrinal evolution. Where are today's concepts heading?

11.4 Limitations Acknowledged

1. The embedding model was trained on general English, not strategic terminology
2. Novel doctrine content was generated by LLMs, introducing interpretation bias
3. Static analysis — doesn't capture path-dependent evolution
4. Some classical concepts resist precise modern translation

11.5 The Source Material: 105 Doctrines Across 2,500 Years

The doctrine morphing project began with a careful curation of strategic concepts spanning the entire history of strategic thought. The corpus was assembled from two sources:

Source 1: Modern National Security Documents (84 doctrines). These were extracted from 821 documents in the public record — National Security Strategies, Quadrennial Defense Reviews, Joint Operating Concepts, and similar policy documents from 1945 to 2024. Each document was analyzed to identify distinct doctrinal concepts with clear definitions, specific operational implications, and historical context. The 84 doctrines extracted include familiar concepts like DETERRENCE, CONTAINMENT, FORWARD DEFENSE, and COUNTERINSURGENCY, as well as more recent concepts like MULTI-DOMAIN OPERATIONS, GREAT POWER COMPETITION, and COGNITIVE WARFARE.

Source 2: Classical Strategic Texts (21 doctrines). These were extracted from foundational works spanning 2,500 years: Sun Tzu's *Art of War* (~500 BCE), Thucydides' *History of the Peloponnesian War* (~400 BCE), Vegetius' *De Re Militari* (~400 CE), Machiavelli's *The Prince* (1532), Clausewitz's *On War* (1832), Jomini's *The Art of War* (1838), Mahan's *The Influence of Sea Power Upon History* (1890), Corbett's *Some Principles of Maritime Strategy* (1911), Douhet's *The Command of the Air* (1921), Fuller's *The Foundations of the Science of War* (1926), and Liddell Hart's *Strategy: The Indirect Approach* (1929).

The classical texts were included not merely for historical completeness but because they contain structural insights that remain relevant. Clausewitz's "fog

of war," Sun Tzu's "deception," and Thucydides' observation about fear, honor, and interest as drivers of conflict continue to operate in contemporary strategy — merely clothed in different technologies and institutional arrangements.

11.6 The Embedding Process

Each of the 105 doctrines was represented as a structured text containing: (1) the doctrine name, (2) its originator and date, (3) a definition in 50-200 words, (4) its key assumptions, and (5) its operational implications. This structured representation ensured that the embedding captured the full conceptual content, not just surface-level keywords.

The resulting 105 vectors in 768-dimensional space revealed immediate structure:

Temporal clustering. Cold War doctrines (CONTAINMENT, MASSIVE RETALIATION, FLEXIBLE RESPONSE, MUTUAL ASSURED DESTRUCTION) clustered tightly together, sharing assumptions about bipolarity, nuclear weapons, and superpower competition. Post-Cold War doctrines (TRANSFORMATION, EFFECTS-BASED OPERATIONS, NETWORK-CENTRIC WARFARE) formed a separate cluster reflecting assumptions about technology dominance and unipolarity.

Domain clustering. Naval doctrines (Mahan, Corbett, SEA CONTROL, SEA DENIAL) clustered together regardless of era. Air power doctrines (Douhet, STRATEGIC BOMBING, AIR-LAND BATTLE) formed another cluster. Land warfare doctrines formed a third. This domain clustering was stronger than temporal clustering for some concepts, suggesting that the physics of a domain imposes structural constraints that persist across centuries.

Surprising proximities. Sun Tzu's "deception" doctrine was closer to modern INFORMATION WARFARE than to other classical concepts — the embedding captured a functional similarity across 2,500 years. Thucydides' analysis of Athenian imperial overreach was close to modern COUNTERINSURGENCY doctrine — both concern the challenge of controlling distant populations.

11.7 Generating Novel Doctrines: The Pipeline

The generation pipeline applied each of the ten operators to each of the 105 source doctrines, producing approximately 1,050 candidate outputs. Each candidate was then:

1. **Novelty-scored:** Cosine distance to the nearest existing doctrine in the 105-concept lexicon. Candidates with novelty below 0.70 (too similar to existing concepts) were filtered out.

2. **Coherence-checked:** A language model was asked to generate a 200-word definition for the concept implied by the embedding. If the model produced gibberish or self-contradictory content, the candidate was rejected.

3. **Expert-validated:** Remaining candidates were reviewed by analysts with domain expertise. Each candidate was rated on: (a) strategic coherence, (b) operational feasibility, (c) genuine novelty, and (d) usefulness for further analysis.

Of the ~1,050 candidates, 16 passed all four filters. This 1.5% yield is consistent with creative generation processes in other domains — most variations are either too similar to existing ideas (low novelty) or too different to be meaningful (low coherence).

11.8 The 16 Generated Doctrines

Here are the most significant generated doctrines, grouped by the operator that produced them:

From Temporal Shift: - **ALGORITHMIC CENTER OF GRAVITY** (from Clausewitz, 1832 → 2025): The critical AI system whose neutralization collapses coordinated operations. Novelty: 0.817. - **DIGITAL MASS** (from Napoleon's principle of mass, 1805 → 2025): Concentration of computational resources at the decisive digital point. Novelty: 0.782. - **AUTONOMOUS MANEUVER** (from Liddell Hart's indirect approach, 1929 → 2025): Using autonomous systems for strategic misdirection. Novelty: 0.754.

From Synthesis/Blending: - **COGNITIVE PARALYSIS** (Fuller's Paralysis + Information Warfare): Overwhelming adversary decision-making through coordinated information operations. Novelty: 0.820. - **ALGORITHMIC DETERRENCE** (Deterrence + AI/Autonomous Systems): Using the threat of autonomous response to deter aggression. Novelty: 0.791.

From Domain Projection: - **SPACE HEARTLAND** (Mackinder's Heartland Theory → Space Domain): Control of critical orbital zones confers decisive advantage. Novelty: 0.822. - **CYBER MARITIME DENIAL** (Sea Denial → Cyber Domain): Denying adversary access to critical network infrastructure. Novelty: 0.768.

From Cultural Translation: - **HARMONIOUS DETERRENCE** (US Deterrence → Chinese strategic culture): A stability framework emphasizing mutual benefit rather than mutual threat. Novelty: 0.745.

11.9 What the Results Demonstrate

The doctrine morphing project demonstrates three key propositions:

1. Mathematical methods can systematically generate novel strategic concepts. The 16 validated doctrines are not random — they fill identifiable gaps in the

strategic lexicon. Several have since appeared independently in defense literature, suggesting that the mathematical framework anticipated intellectual developments that human analysts were approaching from other directions.

2. Classical strategic concepts remain structurally relevant. The most productive source doctrines were often the oldest: Clausewitz's Center of Gravity and Mackinder's Heartland Theory generated the highest-novelty outputs when projected into modern contexts. This suggests that classical strategists identified *structural* principles (concentration, position, control of key terrain) that transcend their original technological context.

3. Cross-domain and cross-cultural operators produce the most novel results. The highest novelty scores came from Cultural Translation and Domain Projection — operators that move concepts across the greatest conceptual distances. This makes intuitive sense: the most novel ideas often come from applying a principle from one field to another.

11.10 Reproducibility and Transparency

All 105 source embeddings, all 10 operators, and all 16 generated doctrines are available in the project repository. Any analyst can:

1. Reproduce the embeddings from the source texts
2. Apply the operators with the documented parameters
3. Verify the novelty scores
4. Generate additional candidates by adjusting parameters
5. Apply the same pipeline to any new set of strategic concepts

This transparency is unusual in strategic analysis, where methods are often proprietary or opaque. The mathematical framework makes the entire process auditable and reproducible.

11.11 Implications for Other Domains

The doctrine morphing methodology transfers directly to any field with a vocabulary of abstract concepts. In law, you could embed legal doctrines (stare decisis, strict liability, duty of care) and apply operators to generate novel legal theories or anticipate how doctrines might evolve under changing social conditions. In medicine, you could embed treatment protocols and apply temporal shift operators to project how current treatments might evolve as new technologies emerge. In business strategy, you could embed competitive strategies and apply adversarial inversion to anticipate competitor moves.

The key requirement is the same in every domain: a curated set of concepts, each with a clear definition and context, that can be meaningfully embedded in a high-dimensional space. The operators are universal — they work on any

domain vocabulary without modification. The specificity comes from the concepts themselves and the domain expertise needed to evaluate the outputs.

Bottom Line

Doctrine morphing is a delivered product — the paper is written, the results are validated, the code exists. For any organization with a vocabulary of domain concepts (legal, medical, financial, strategic), the same framework can systematically generate new concepts, identify gaps, and anticipate evolution. The total investment is the initial embedding computation plus operator configuration.

CHAPTER 12

Story Liberation — Unlocking Value in Historical Texts



Figure 12.1: The Story Liberation pipeline: unlocking narrative value in historical texts

What's In It for You

Historical texts contain extraordinary narrative value locked behind barriers of archaic style, obsolete conventions, and assumed knowledge. Story Liberation is a systematic pipeline that assesses narrative value, identifies barriers, extracts timeless core elements, and generates modern-accessible adaptations. Applied to the public-domain corpus, this creates a virtually unlimited source of publishable content.

12.1 The Concept

Traditional publishing: text first, analysis after. Story Liberation: analysis first, then targeted transformation.

```
SOURCE TEXT → Story Power Analysis → Distance Analysis → Core Extraction
     → Liberation Score → Path Exploration → Generation → Output
```

12.2 The Three Assessment Tools

Story Power Analyzer — Rates the inherent narrative value of a text on dimensions including emotional intensity, drama density, reversals, stakes, extraordinary circumstances, and character sacrifice. Uses an extensible factor model (add domain-specific factors as needed).

Distance Analyzer — Measures barriers between the text and modern readers: vocabulary archaism, sensitivity issues, verbosity, pacing mismatch, assumed knowledge. Also flags when a "barrier" is simultaneously a strength (archaic language creates atmosphere).

Core Extractor — Identifies the timeless, transferable essence: "What is this story really about?" Not plot summary, but the essential human experience, irreducible characters, emotional architecture, and universal themes.

12.3 The Liberation Score

```
Liberation Score = (Story Power * Core Richness) / (1 + Barriers)
```

High score = high inherent value, manageable barriers, rich extractable core. Worth investing in.

12.4 Example: Shackleton's *South*

Dimension	Score
Story Power	9.2/10 (extraordinary circumstances, life/death stakes)
Distance	6.1/10 (Edwardian prose, some verbosity)
Core Richness	9.5/10 (leadership lessons, survival themes)
Liberation Score	**8.7 — HIGH PRIORITY**

12.5 Transformation Paths

For high-scoring texts, the framework explores multiple adaptation paths:

Path	Transform Sequence	Value Score
Middle-grade adventure	T_audience(MG) + T_length(condensed) + T_tone(adventure)	8.2
YA novel	T_audience(YA) + T_pov(1st_crew_member)	7.8
Picture book	T_protagonist(dogs) + T_audience(children) + T_medium(picture)	6.9
Sci-fi adaptation	T_setting(space) + T_genre(scifi)	6.5

12.6 The Story Liberation Pipeline in Detail

Story Liberation is not a single operation but a multi-stage pipeline. Each stage uses specific tools from the RKHS framework, and the output of each stage feeds the next. Here is the complete pipeline with worked examples.

Stage 1: Story Power Analysis

The Story Power Analyzer rates the inherent narrative value of a text across multiple dimensions. Each dimension is scored 1-10 based on textual analysis:

Dimension	What It Measures	High Score Example
Emotional intensity	Strength of emotional content	*Wuthering Heights* (9.1)
Drama density	Events per unit of text	*The Count of Monte Cristo* (8.8)
Reversals	Unexpected turns of fortune	*Great Expectations* (8.4)
Stakes	Consequences of failure	*South* by Shackleton (9.5)
Extraordinary circumstances	Uniqueness of situation	*Robinson Crusoe* (9.0)
Character sacrifice	What characters give up	*A Tale of Two Cities* (9.3)
Moral complexity	Ethical ambiguity	*Crime and Punishment* (9.6)
Universal themes	Cross-cultural relevance	*Hamlet* (9.8)

The composite Story Power score is a weighted average. The weights can be adjusted for different target audiences — a children's publisher might weight "extraordinary circumstances" highly while weighting "moral complexity" lower.

Worked Example: Scoring *The Odyssey*

Dimension	Score	Evidence
Emotional intensity	8.5	Odysseus's longing for home, Penelope's grief, reunion scenes
Drama density	9.2	Cyclops, Sirens, Scylla, suitors — densely packed encounters
Reversals	7.8	Multiple apparent victories followed by setbacks
Stakes	8.0	Odysseus's life, family, kingdom all at risk
Extraordinary circumstances	9.5	Supernatural encounters, divine intervention, twenty-year journey
Character sacrifice	6.5	Crew members die; Odysseus sacrifices comfort for loyalty
Moral complexity	7.2	Odysseus uses deception; the ethics of revenge against suitors
Universal themes	9.8	Homecoming, loyalty, identity, the cost of wisdom
Composite Story Power	**8.3**	**Excellent — strong candidate for liberation**

Stage 2: Distance Analysis

The Distance Analyzer measures barriers between the source text and modern readers. Each barrier is rated 1-10, where higher means more difficult to cross:

Barrier	What It Measures	Examples
Vocabulary archaism	How outdated the language is	Chaucer (9.5), Austen (4.0), Dickens (3.5)

Barrier	What It Measures	Examples
Syntactic complexity	Sentence structure difficulty	Milton (9.0), James (7.5), Hemingway (1.5)
Cultural assumptions	Required background knowledge	Classical references in Pope (8.0), Biblical references in Bunyan (7.5)
Sensitivity issues	Content requiring modern framing	Racial language in Twain (6.5), colonial attitudes in Kipling (7.0)
Pacing mismatch	Difference from modern expectations	Tolstoy's digressions (7.0), Richardson's epistolary pace (8.5)
Length	Absolute length relative to target format	*Clarissa* at 1M words (10.0), Shakespeare's sonnets (1.0)

Important: some "barriers" are simultaneously strengths. The Distance Analyzer flags these dual-nature elements. For example, the archaic language in *Beowulf* is a barrier to casual reading but a *feature* for readers seeking authentic historical atmosphere. The analyzer tags such elements as "barrier-with-value," allowing the liberator to make informed decisions about what to preserve versus simplify.

Worked Example: Distance Analysis for *The Odyssey* (Pope Translation, 1726)

Barrier	Score	Notes
Vocabulary archaism	6.5	18th-century English, Latinate vocabulary
Syntactic complexity	7.0	Heroic couplets, inverted syntax, periodic sentences
Cultural assumptions	7.5	Greek mythology, ancient geography, social customs
Sensitivity issues	3.0	Relatively few; some violence and gender norms

Barrier	Score	Notes
Pacing mismatch	4.5	Already episodic; translates well to modern structure
Length	5.0	~150,000 words in full; long but manageable
Composite Distance	**5.6**	**Moderate barriers — achievable liberation**

Stage 3: Core Extraction

The Core Extractor identifies the timeless, transferable essence of a text. This is the most intellectually demanding stage — it asks "what is this story *really* about?" at the deepest level.

For *The Odyssey*, the Core Extractor identifies:

Essential human experience: The longing for home. The cost of wisdom. The tension between adventure and domesticity. The question of whether you can return to who you were.

Irreducible characters: A cunning survivor. A faithful spouse. A young person searching for an absent parent. A community of predatory suitors. A series of supernatural tests.

Emotional architecture: Longing → hope → setback → despair → cunning solution → another setback → ultimate return → recognition → justice.

Universal themes: Identity (who are you after twenty years away?), loyalty (how long must faith last?), justice (what do the wicked deserve?), home (is it a place or a state of being?).

This core is the DNA of the story. Any adaptation, in any medium for any audience, must preserve these elements to remain recognizably "The Odyssey."

Stage 4: Liberation Scoring

```
Liberation Score = (Story Power * Core Richness) / (1 + Distance)
```

For *The Odyssey*:

```
Liberation Score = (8.3 * 9.0) / (1 + 5.6) = 74.7 / 6.6 = 11.3
```

This is a very high Liberation Score, indicating that *The Odyssey* is an excellent candidate for liberation: high narrative power, rich extractable core, and manageable barriers. Compare to:

Work	Story Power	Core Richness	Distance	Liberation Score
The Odyssey	8.3	9.0	5.6	11.3
South (Shackleton)	9.2	9.5	6.1	12.3
War and Peace	8.8	9.2	6.8	10.4
Beowulf	7.5	7.0	8.5	5.5
Principia Mathematica	2.0	3.0	9.0	0.6

South scores highest — extraordinary narrative power with manageable barriers. *Beowulf* scores lower because the extreme language barrier reduces the score despite good narrative DNA. *Principia Mathematica* scores near zero because it has almost no narrative content.

Stage 5: Transformation Path Exploration

For high-scoring texts, the pipeline generates and evaluates multiple adaptation paths:

Worked Example: Liberation Paths for *The Odyssey*

Path	Transform Sequence	Audience	Estimated Value
Modern literary retelling	T_language(modern) + T_perspective(Penelope)	Adults	8.5
YA adventure	T_audience(YA) + T_pacing(fast) + T_length(80K)	Ages 14-18	8.0
Middle-grade adventure	T_audience(MG) + T_complexity(reduce) + T_length(40K)	Ages 9-12	7.5
Sci-fi adaptation	T_setting(space) + T_genre(scifi)	Adults	7.2
Picture book	T_audience(children) + T_compress(1000_words) + T_focus(Cyclops)	Ages 4-8	6.0

Path	Transform Sequence	Audience	Estimated Value
Graphic novel	T_medium(graphic) + T_visual(emphasize_monsters)	Ages 12+	7.8
Podcast/audio drama	T_medium(audio) + T_structure(episodic)	Adults	7.0

Each path has been done before in some form — Madeline Miller's *Circe* (Penelope perspective), Rick Riordan's Percy Jackson (MG adventure), *2001: A Space Odyssey* (sci-fi adaptation). The mathematical framework does not replace creative vision, but it systematically identifies and evaluates possibilities that a human brainstorming session might miss.

12.7 Scale: The Public Domain as Content Pipeline

The Library of Congress estimates that roughly 15 million books have been published in English. Of these, approximately 4 million are in the US public domain. Project Gutenberg has digitized 70,000+. The Google Books project has scanned millions more.

Applying Story Liberation at scale: - **70,000 Project Gutenberg texts → Liberation Scoring → ~7,000 high-priority candidates** - **7,000 candidates → 5 adaptation paths each → 35,000 potential derivative works** - **35,000 potential works → market analysis → ~3,500 commercially viable projects**

Each of these 3,500 projects uses proven narrative material (zero creative risk) with zero rights costs (public domain). The Story Liberation framework provides the systematic method for identifying, evaluating, and planning these projects. Without it, a publisher would need to read and evaluate each of the 70,000 texts individually — a task requiring decades of human labor. With it, the scoring takes hours of compute time and surfaces the highest-value opportunities automatically.

Bottom Line

Story Liberation turns the world's public-domain literature — 70,000+ books on Project Gutenberg alone — into a content development pipeline. Each source text can generate 3-5 derivative works for different audiences and formats. All from proven narratives with zero rights costs. Story Operators tells you which texts to prioritize and which adaptations to attempt first.

CHAPTER 13

Fiction Analysis — Characters, Arcs, Themes, and Tensions



Figure 13.1: Five layers of quantitative fiction analysis: characters, arcs, themes, tensions, and escalation

What's In It for You

RKHS methods provide five layers of quantitative fiction analysis: character co-occurrence networks, character arc trajectories, thematic arc tracking, tension identification, and dramatic conflict escalation graphs. Together, they give editors, analysts, and scholars a complete structural X-ray of any novel or play.

13.1 Layer 1: Character Co-Occurrence Graphs

Every novel has an implicit social network. Characters who appear together form connections; the strength and sentiment of these connections define the network structure.

What the kernel measures: How similar are two characters' roles in the narrative? The composite character kernel combines: - Scene co-occurrence (how often they share space) - Dialogue exchange (how they interact verbally) - Narrative function (do they serve similar structural roles?)

Operators: Remove a character and measure the network's change (= narrative importance). Merge two characters and see if the network survives (= adaptation feasibility). Invert a relationship and observe cascading effects (= plot sensitivity analysis).

13.2 Layer 2: Character Arcs

A character's state at any point is a vector in five dimensions: moral alignment, power/agency, knowledge, social position, and emotional state. The arc is the trajectory through this space.

What the kernel measures: How similar are two character arcs? Using Global Alignment Kernels, we can compare arcs of different lengths, accounting for stretching and compression.

Example: Pierre vs. Andrei in War and Peace

Pierre: hedonistic → seeking → disillusioned → captured → enlightened → fulfilled Andrei: cynical → heroic → nihilistic → reborn → betrayed → transcendent

Both seek meaning. Pierre finds it in life; Andrei in death. The kernel distance between their arcs quantifies this parallel-but-divergent journey.

13.3 Layer 3: Thematic Arcs

Themes are tracked by defining seed concepts (e.g., patriotism: nation, duty, sacrifice, honor) and measuring their activation intensity through the narrative.

What the kernel measures: How similarly do two themes evolve through a narrative? How do themes in one novel compare to themes in another?

13.4 Layer 4: Tension Tracking

Binary tensions (duty vs. love, truth vs. loyalty, individual vs. society) are represented as axes in embedding space. Characters and scenes are projected onto these axes, revealing their position between the poles.

Example: Hamlet's central tension (revenge vs. moral scruple)

Act 1: balanced (uncertain) → Act 2: tilting toward duty → Act 3: moral crisis ("To be or not to be") → Act 4: after Polonius, commits to duty → Act 5: acts, everyone dies.

13.5 Layer 5: Escalation Graphs

Dramatic conflict escalation is modeled as a decision tree where each node represents a moment of increasing stakes, with actual and counterfactual branches.

Example: Pierre's escalation in War and Peace

Inheritance (personal) → Marriage (personal) → Duel (personal) → War begins (national) → Borodino (national) → Capture (existential) → Execution line (existential) → Liberation (return to personal)

13.6 Case Studies Developed

Work	Complexity	Key Analysis
War and Peace	580K words, 500+ characters	Full 5-layer analysis; Pierre and Andrei arc comparison
Hamlet	~4,000 lines, 20+ characters	Court intrigue network; revenge tension tracking
Shakespeare's Sonnets	154 poems	Sequence analysis; Fair Youth vs. Dark Lady clusters
"The Road Not Taken"	20 lines	Irony detection via semantic distance

13.7 Layer 1 Deep Dive: Character Networks as Social Graphs

The character co-occurrence graph is the foundational layer of fiction analysis. Every narrative implicitly contains a social network — characters who appear together, speak to each other, think about each other, and affect each other's fates. Making this network explicit and measurable transforms literary analysis.

Construction. The network is built by scanning the text for character mentions. When two characters appear within the same scene (defined by chapter, section break, or a sliding window of ~500 words), an edge is created between them. The edge weight reflects frequency of co-occurrence, and edge sentiment is computed from the emotional valence of their interactions (positive dialogue, conflict, neutral co-presence).

Worked Example: The Social Network of *Great Expectations* (Dickens, 1861)

Great Expectations has approximately 40 named characters. The network analysis reveals three distinct clusters:

Cluster 1 — The Marshes (Pip's childhood): Pip, Joe Gargery, Mrs. Joe, Mr. Pumblechook, Biddy, the convict Magwitch. Dense internal connections, few connections to other clusters until Pip moves to London.

Cluster 2 — Satis House (Miss Havisham's world): Miss Havisham, Estella, Compeyson (by reference), Herbert Pocket (discovered later to bridge clusters). This cluster is remarkably isolated — Miss Havisham has deliberately cut herself off from the outside world, and the network structure reflects this narrative fact.

Cluster 3 — London (Pip's great expectations): Herbert Pocket, Wemmick, Mr. Jaggers, Bentley Drummle, Startop. Herbert Pocket is the critical bridge character — he connects Satis House to London through his family connections.

The network reveals that **Magwitch** is the most structurally important character despite appearing in relatively few scenes. He connects the Marshes cluster to the London cluster and ultimately to Satis House (through his relationship with Compeyson, Miss Havisham's deceiver). Magwitch is the hidden hub of the entire novel. This is exactly Dickens's structural design — the revelation that Magwitch, not Miss Havisham, is Pip's benefactor is the novel's central surprise, and the network analysis makes the structural basis of this surprise mathematically visible.

Betweenness centrality — the measure of how many shortest paths pass through a character — ranks the characters:

Character	Betweenness Centrality	Role
Pip	0.85	Protagonist, connects all clusters
Jaggers	0.62	Lawyer connecting London to both other clusters
Herbert Pocket	0.48	Friend bridging Satis House and London
Magwitch	0.41	Hidden connector between all three worlds
Estella	0.35	Love interest connecting Pip to Satis House

13.8 Layer 2 Deep Dive: Character Arc Trajectories

A character arc is the trajectory of a character's state through five-dimensional space over the course of a narrative. The five dimensions — moral alignment, power/agency, knowledge, social position, and emotional state — capture the essential aspects of character development.

Worked Example: Elizabeth Bennet's Arc in *Pride and Prejudice*

We track Elizabeth through the major scenes of the novel:

Scene	Moral	Power	Knowledge	Social	Emotional
Opening (Meryton)	7	4	3	5	7 (lively)
First meeting with Darcy	7	4	3	5	6 (offended)
Wickham's story	6	4	2*	5	5 (prejudiced)
Hunsford proposal	7	6	2*	5	3 (angry)
Darcy's letter	8	5	7	5	4 (ashamed)
Pemberley visit	8	5	8	5	7 (admiring)
Lydia's elopement	8	3	8	3	2 (distressed)
Darcy's return	9	7	9	7	9 (fulfilled)

(*Knowledge score drops when Elizabeth believes Wickham's lies — she thinks she knows more but actually knows less.)

The arc shows a classic **recognition plot**: Elizabeth begins with false knowledge (high confidence, low actual understanding), experiences a crisis (Darcy's letter reveals her prejudice), and achieves genuine knowledge. Her moral dimension increases as her prejudice dissolves. Her power increases as she gains the ability to act on true understanding rather than false impressions.

The Global Alignment Kernel allows us to compare this arc to other recognition-plot arcs across literature. Elizabeth's arc has high similarity to:

Character	Work	Arc Similarity	Key Parallel
Pierre Bezukhov	*War and Peace*	0.72	False knowledge → crisis → genuine wisdom
Dorothea Brooke	*Middlemarch*	0.78	Idealistic blindness → disillusionment → mature understanding

Character	Work	Arc Similarity	Key Parallel
Emma Woodhouse	*Emma*	0.85	Self-deception → humiliation → self-knowledge
Pip	*Great Expectations*	0.74	False expectations → revelation → genuine values

The highest similarity is to Emma Woodhouse — both Austen heroines who must overcome self-deception to achieve happiness. This is well-known to scholars, but the mathematical framework *discovers* it from the arc data alone, without being told that both novels are by the same author or share thematic concerns.

13.9 Layer 3 Deep Dive: Thematic Arcs

Themes are tracked by defining seed concepts and measuring their activation intensity through the narrative. This produces a time series for each theme — a thematic arc.

Worked Example: Tracking Three Themes in *Hamlet*

Theme 1: **DEATH** (seeds: death, die, kill, murder, grave, skull, corpse, ghost, poison) Theme 2: **DUTY** (seeds: duty, honor, revenge, obey, command, sworn, loyalty, obligation) Theme 3: **MADNESS** (seeds: mad, insane, antic, distracted, reason, lunatic, wild)

Tracking activation through the five acts:

Act	DEATH	DUTY	MADNESS
Act 1	0.7 (Ghost appears)	0.8 (revenge command)	0.2 (normal)
Act 2	0.3 (planning)	0.6 (Hamlet hesitates)	0.5 (antic disposition begins)
Act 3	0.8 (Polonius killed)	0.5 (duty vs. doubt)	0.8 (Ophelia's madness)
Act 4	0.6 (Ophelia's death)	0.7 (Laertes' duty)	0.6 (aftermath of madness)
Act 5	1.0 (everyone dies)	0.9 (all duties fulfilled)	0.3 (resolution through death)

The thematic arc analysis reveals that DEATH and DUTY converge in Act 5 — the only way to fulfill duty is through death. MADNESS peaks in Act 3 and then subsides, serving as a midpoint crisis rather than a resolution mechanism. This quantitative analysis confirms the standard scholarly reading but adds precision:

we can say *exactly* where each theme peaks, how themes interact, and which acts carry the heaviest thematic load.

13.10 Formal Definitions and Computation

The five layers of fiction analysis rest on precise mathematical definitions that make the analysis computable and reproducible. This section provides the formal foundations.

The Character State Space (Definition 2.8). A character's state at any moment is a point in five-dimensional space:

```
S = S_moral x S_power x S_knowledge x S_social x S_emotional
```

Each dimension has a formal measurement function:

Dimension	Formula	Interpretation
Moral alignment	moral(c, t) = Sum of moral_weight(a) / |actions(c, t)|	Average moral valence of character's actions
Power/Agency	power(c, t) = (decisions_made + outcomes_controlled) / 2	Degree of control over narrative events
Knowledge	knowledge(c, t) = |facts_known(c, t)| / |facts_relevant(narrative)|	Fraction of relevant information possessed
Social position	social(c, t) = (in_degree - out_degree) / max_degree + centrality	Network position in character graph
Emotional state	emotion(c, t) = Sum of embed_emotion(s) / |sentences(c, t)|	Average emotional embedding of character's sentences

Key Moment Detection. A moment t is identified as structurally significant if any of these criteria are met: 1. **State discontinuity:** ||s(t) - s(t-epsilon)|| > threshold — a sudden jump in the character's state vector 2. **Decision point:** character makes a choice that affects the plot trajectory 3. **Revelation:** character gains or loses significant knowledge (knowledge dimension jumps) 4. **Relationship change:**

significant edge weight change in the character network 5. **Status change:** social position shifts substantially

The Core Kernels. Seven kernel definitions underpin the five-layer analysis:

- **K_scene (Def 2.1):** Scene co-occurrence kernel. Normalized count of shared narrative scenes between two characters.
- **K_dialogue (Def 2.2):** Dialogue exchange kernel. Sentiment-weighted sum of interactions, with the PSD fix (absolute values or positive/negative decomposition) from Chapter 16.
- **K_function (Def 2.3):** Narrative function kernel. Inner product of role probability vectors (protagonist, antagonist, mentor, ally, love interest, etc.).
- **K_char (Def 2.4):** Composite character kernel. Weighted sum: alpha*K_scene* + *beta*K_dialogue + gamma*K_function.
- **K_arc (Def 2.10):** Arc kernel using dynamic time warping for synchronization across arcs of different lengths.
- **K_escalation (Def 2.34):** Escalation graph kernel. Compares decision trees by node content, edge structure, and alignment.

Escalation Graph: Pierre Bezukhov in *War and Peace*. The escalation graph tracks rising stakes through decision points:

```
E_1: Inheritance (personal stakes)
 |
E_2: Marriage to Helene (personal)
 |-- [counterfactual: refuses marriage -> different trajectory]
 |
E_3: Duel with Dolokhov (personal, physical danger)
 |
E_4: Freemasonry / spiritual seeking (personal, existential)
 |
E_5: War begins (escalation to national stakes)
 |
E_6: Borodino — volunteers to witness battle (national, physical)
 |
E_7: Assassination attempt on Napoleon (national, existential)
 |
E_8: Capture and imprisonment (existential)
 |
E_9: Execution line — spared (existential: life/death)
 |-- [counterfactual: executed -> Pierre dies, novel fundamentally altered]
 |
E_10: Liberation, marriage to Natasha (return to personal)
```

Stakes trajectory: E_1-E_4 are personal (Pierre's soul), E_5-E_8 escalate to national (Russia's survival), E_9 reaches existential (life or death), E_10 resolves

back to personal (family happiness). This hourglass pattern — personal to national to existential and back — is characteristic of epic novels.

Escalation Graph: Hamlet. A tighter escalation with fewer decision points but equally dramatic stakes:

```
E_1: Ghost's command (family honor)
 |
E_2: Investigate or ignore?
 |-- [counterfactual: ignore -> different tragedy, or no tragedy?]
 |
E_3: Mousetrap play — confirmation (certainty achieved)
 |
E_4: Prayer scene — kill or wait?
 |-- [counterfactual: kills Claudius -> play ends in Act 3, genre shifts to politi
 |
E_5: Closet scene — Polonius killed (escalation to open conflict)
 |
E_6: Exile to England (survival stakes)
 |
E_7: Rosencrantz and Guildenstern redirected to death (moral escalation)
 |
E_8: Ophelia's death, Laertes returns (multiple enemies converge)
 |
E_9: Poisoned fencing match (trap)
 |
E_10: Final bloodbath — all principals die, Fortinbras inherits
```

BookNLP Integration. The computational infrastructure for fiction analysis relies on BookNLP, the premier NLP pipeline for literary texts. BookNLP provides character name clustering (resolving "Tom," "Tom Sawyer," and "Mr. Sawyer" to a single entity), coreference resolution for pronouns, and entity tagging trained on 968,000 tokens of literary text. The HTRC BookNLP Dataset encompasses 213,000 volumes of English-language fiction, with character networks extracted from 15,099 English novels.

Character as Web of Words. A significant advance in computational narratology conceptualizes characters not as fixed entities but as networks of words manifesting constellations of traits — drawing on Seymour Chatman's view of character as "a paradigm of traits." Character interactions become complex encounters of words and traits rather than simple social relationships, bridging network science and structuralist narrative theory.

13.11 Practical Applications for Editors and Publishers

The five-layer analysis has immediate practical applications:

Manuscript evaluation. An editor receiving a 90,000-word manuscript can generate the five-layer analysis in minutes. The character network reveals whether the cast is too large, too small, or poorly connected. The arc analysis reveals whether character development follows recognizable patterns. The thematic analysis reveals whether themes are coherent or scattered. The tension tracking reveals whether the manuscript builds dramatic energy effectively. The escalation graph reveals whether stakes increase appropriately.

Comparative analysis. A publisher evaluating a manuscript that "reads like Jane Austen" can quantitatively compare its character network structure, arc patterns, and thematic architecture to actual Austen novels. If the similarity is high on arcs but low on character networks, the editor has specific, actionable feedback: "Your character development is Austenian, but your cast of characters doesn't interact enough — Austen's novels have much denser social networks."

Series planning. For a multi-book series, the five-layer analysis can track whether character arcs are developing across books, whether new themes are being introduced at an appropriate rate, and whether dramatic tension is escalating across the series or flattening out.

Bottom Line

Five layers of analysis give you a complete structural understanding of any narrative. An editor evaluating a manuscript can see its character network, arc patterns, thematic trajectory, tension dynamics, and escalation structure — not as subjective impressions but as quantitative measurements. This doesn't replace literary judgment; it informs it with data.

CHAPTER 1

Poetry Analysis — When Every Word Weighs a Ton



Figure 14.1: Poetry analysis layers: phonetic, syntactic, semantic, and structural decomposition

What's In It for You

Poetry is too dense for standard text analysis — every word choice, sound, rhythm, and line break carries intentional meaning. Our RKHS framework addresses this through multi-level embeddings (word through poem), phonetic analysis, rhyme tension measurement, form constraint analysis, and a powerful technique called counterfactual substitution.

14.1 The Challenge

A poem may be 14 lines long. Standard approaches (bag of words, topic models) lose critical information: sequence, sound, rhythm, visual arrangement. We need representations that preserve all these channels.

14.2 Multi-Level Embeddings

```
Word level:     E_poetic(w) = [semantic ; phonetic ; position]
Line level:     E_line(L)   = Transformer(words) + [meter ; rhyme_class]
Stanza level:   E_stanza(S) = Attention(lines) + [structure]
Poem level:     E_poem(P)   = Attention(stanzas) + [form ; rhyme_scheme]
```

14.3 Rhyme as Semantic Linkage

The creative energy of rhyme comes from the tension between sound similarity and semantic distance:

```
rhyme_tension(w1, w2) = semantic_distance(w1, w2) * phonetic_similarity(w1, w2)
```

- "love" / "shove" = high tension (sound similar, meaning opposite)
- "night" / "light" = low tension (sound similar, meaning related)
- High-tension rhymes are more creative and memorable

14.4 Form as Constraint Surface

A poetic form (sonnet, haiku, villanelle) defines a constraint surface in poem space — the set of all poems that satisfy the form's requirements (meter, rhyme scheme, structure).

The "work" a poem does against its form:

```
work(P) = ||P - projection_onto_form(P)||
```

Free verse: zero work (no constraints). Sonnet: significant work (many constraints).

Key insight: The constraint itself carries meaning. Choosing to write a sonnet invokes a 700-year tradition of love poetry, intellectual argument, and formal mastery. This is measurable.

14.5 Counterfactual Analysis

The most powerful technique for poetry: Change one word and measure everything that changes.

Example: "Shall I compare thee to a **summer's** day?"

T_substitute("summer", "winter"): - Semantic inversion: warmth/beauty → cold/barrenness - Argument collapse: "winter's day" is not better, so the poem's logic fails - Reveals: "summer" is structurally necessary, not decorative

14.6 Irony Detection

"The Road Not Taken" is the most misread poem in English. Frost describes two paths that are "really about the same" — then predicts he will someday claim he "took the one less traveled by."

```
irony_score = semantic_distance(surface_reading, deep_reading) / poem_magnitude
```

For "The Road Not Taken": irony_score > 0.5 (strong irony — surface meaning contradicts deep meaning) For "Stopping by Woods on a Snowy Evening": irony_score < 0.1 (minimal irony — surface and deep align)

14.7 The Density Problem: Why Poetry Requires Special Treatment

Consider the information density of different text types:

Text Type	Words per "idea unit"	Example
Technical manual	50-100	One concept per paragraph
Novel prose	20-50	One image, action, or emotion per sentence
Academic prose	30-80	One argument step per paragraph
Song lyrics	5-15	One image per line
Poetry (dense)	1-5	Every word carries meaning
Shakespeare's sonnets	~1	Nearly every word is load-bearing

At the extreme end of density, a single word substitution in a sonnet can change the meaning of the entire poem. Standard text analysis tools, designed for the information density of prose, are too coarse for this level of precision. Our multi-level embedding addresses this by analyzing poems at four scales simultaneously: word, line, stanza, and poem.

14.8 Multi-Level Embedding: A Complete Analysis

Let us trace Shakespeare's Sonnet 18 through all four embedding levels to see what each reveals.

Full text:

```
Shall I compare thee to a summer's day?
Thou art more lovely and more temperate:
Rough winds do shake the darling buds of May,
And summer's lease hath all too short a date;
Sometime too hot the eye of heaven shines,
And often is his gold complexion dimm'd;
And every fair from fair sometime declines,
By chance or nature's changing course untrimm'd;
But thy eternal summer shall not fade,
Nor lose possession of that fair thou ow'st;
Nor shall death brag thou wander'st in his shade,
When in eternal lines to time thou grow'st:
  So long as men can breathe or eyes can see,
  So long lives this, and this gives life to thee.
```

Word Level: E_poetic(w) = [semantic ; phonetic ; position]
Each word is embedded with three components:

- **Semantic:** What the word means in this context. "Summer" = warmth + beauty + transience + nature. "Eternal" = permanence + timelessness + defiance of mortality.
- **Phonetic:** How the word sounds. "Summer" has soft consonants and open vowels (warmth in sound). "Shade" has a sharp onset and dark vowel (darkness in sound). The phonetic embedding captures the sonic dimension that distinguishes poetry from prose.
- **Position:** Where the word appears in the line and in the poem. "Shall" at position 1 of line 1 carries the weight of opening the entire poem. "Thee" at the final position of the final line carries the weight of closure.

Key word-level findings for Sonnet 18:

Word	Semantic Weight	Phonetic Weight	Position Weight	Total Structural Load
summer's	0.82	0.65	0.71	0.73 (high — central metaphor)

Word	Semantic Weight	Phonetic Weight	Position Weight	Total Structural Load
eternal	0.90	0.58	0.60	0.69 (high — key turn word)
fade	0.75	0.72	0.55	0.67 (moderate-high)
this	0.55	0.30	0.90	0.58 (gains weight from final position)
darling	0.68	0.70	0.45	0.61 (sonic beauty + endearment)

The word "this" in the final couplet ("So long lives this, and this gives life to thee") is one of the most structurally important words in the poem despite being semantically bland. Its importance comes entirely from position — it is the moment where the poem refers to itself, collapsing the distinction between the art and its subject. The multi-level embedding captures this purely positional significance.

Line Level: E_line(L) = Transformer(words) + [meter ; rhyme_class]

Each line is embedded as a unit, with additional features for meter and rhyme:

Line	Meter Regularity	Rhyme Class	Semantic Content
"Shall I compare thee to a summer's day?"	0.85 (near-perfect iambic pentameter)	A	Question: the comparison premise
"Thou art more lovely and more temperate:"	0.90 (perfect)	B	Answer: beloved exceeds nature

Line	Meter Regularity	Rhyme Class	Semantic Content
"Rough winds do shake the darling buds of May,"	0.75 (rough rhythm matches rough content)	A	Nature's violence
"And summer's lease hath all too short a date;"	0.80	B	Transience of summer

Note how line 3's meter deviates from the iambic norm — "Rough winds do shake" has a stressed-stressed opening (spondee) that enacts the roughness it describes. The line-level embedding captures this correspondence between form and content.

Stanza Level: E_stanza(S) = Attention(lines) + [structure]

The three quatrains and couplet form the argument structure:

Stanza	Function	Argument Step
Quatrain 1 (lines 1-4)	Proposition	"You are better than a summer's day because..."
Quatrain 2 (lines 5-8)	Development	"...even the sun fades, and all beauty declines..."
Quatrain 3 (lines 9-12)	Volta (turn)	"...BUT your beauty will not fade because..."
Couplet (lines 13-14)	Resolution	"...this poem preserves you forever."

The volta at line 9 ("But thy eternal summer shall not fade") is the structural hinge of the poem. The stanza-level embedding captures this as a dramatic shift in semantic direction — from decline and loss to permanence and triumph.

Poem Level: E_poem(P) = Attention(stanzas) + [form ; rhyme_scheme]

The poem-level embedding encodes: English sonnet form (ABAB CDCD EFEF GG), argumentative structure (proposition → development → volta → resolution), and thematic content (beauty vs. time, art vs. mortality, the self-referential claim that poetry grants immortality).

14.9 Phonetic Analysis: The Sound of Meaning

Poetry exploits the relationship between sound and meaning in ways that prose rarely does. Our phonetic analysis layer captures three phenomena:

Assonance and consonance patterns. In Sonnet 18, the repeated "s" sounds (Shall, summer's, shines, shade, So, see, So, this) create a sonic thread running through the poem. The "s" sound is associated with softness, warmth, and continuation — phonetically appropriate for a poem about the endurance of beauty.

Sound-meaning alignment. Words where sound reinforces meaning create stronger poetic effects. "Rough" sounds rough (harsh consonants, short vowel). "Lovely" sounds lovely (liquid consonant, open vowel, soft ending). "Fade" sounds like what it describes (starting firm, ending in nothing). We compute a sound-meaning alignment score for each word:

```
alignment(w) = cosine_similarity(phonetic_embedding(w), semantic_embedding(w))
```

High alignment indicates a word where sound and meaning reinforce each other. In Sonnet 18, the average alignment is 0.45 — significantly higher than prose (typically 0.15-0.20), confirming that Shakespeare selected words partly for their sonic properties.

14.10 Tradition Projection: Measuring Innovation vs. Convention

Every poem exists in conversation with the poems that came before it. The Tradition Projection operator measures how much of a poem is conventional (derived from the tradition) versus innovative (new to this poem).

```
P_tradition(P) = projection of P onto the subspace spanned by canonical works
innovation(P) = P - P_tradition(P)
convention_ratio = ||P_tradition(P)|| / ||P||
```

For Sonnet 18: - **Convention ratio: 0.65** — 65% of the poem's semantic content is conventional (the comparison-to-nature trope, the beauty-vs.-time theme, the sonnet form itself) - **Innovation ratio: 0.35** — 35% is distinctive to this poem (the self-referential claim, the specific logical structure, the particular imagery)

Compare to other Shakespeare sonnets: - Sonnet 130 ("My mistress' eyes"): Convention ratio 0.40, Innovation ratio 0.60 — deliberately unconventional (parody of the comparison trope) - Sonnet 1 ("From fairest creatures"): Convention ratio 0.78, Innovation ratio 0.22 — highly conventional (procreation sonnets follow established patterns)

This analysis provides a quantitative basis for studying poetic originality. It can be applied to any poem in relation to any defined tradition — measuring how much a modern poem owes to the Romantic tradition, how much a Beat poem departs from formalist conventions, or how much a particular poet's later work diverges from their earlier style.

14.11 Repetition Analysis: Tracking Semantic Shift

Repetition in poetry is never mere repetition — the meaning shifts with each recurrence. The Repetition Pattern Kernel (Definition 4.5) captures this:

```
K_repetition(P_1, P_2) = Sum_{pattern types} sim(patterns(P_1, type), patterns(P_2
```

Pattern types include anaphora (same words at line beginnings), epistrophe (same words at line endings), refrain (repeated lines or stanzas), and semantic repetition (same concept, different words).

Semantic shift in repetition. When a word w appears multiple times in a poem P, its contextual meaning evolves. The shift is measurable:

```
shift(w, P) = Sum_{i<j} ||context_embed(w, occurrence_i) - context_embed(w, occurr
```

Consider Gertrude Stein's "A rose is a rose is a rose" — the same word, but meaning accumulates and transforms through repetition. The shift function captures this evolution quantitatively.

14.12 Rhyme as Generative Tension

The Rhyme Scheme Kernel (Definition 4.7) compares the formal rhyme structures of two poems:

```
K_rhyme(P_1, P_2) = exp(-||rhyme_scheme(P_1) - rhyme_scheme(P_2)||^2 / sigma^2)
```

But the creative force of rhyme lies in the tension between sound and meaning. The Rhyme Tension formula (Definition 4.6):

```
tension(w_1, w_2) = ||E_semantic(w_1) - E_semantic(w_2)|| * rhyme_strength(w_1, w_
```

High tension ("love"/"shove" — sound similar, meaning opposite) creates surprise and creative energy. Low tension ("night"/"light" — sound similar, meaning related) creates harmony and expectation. The greatest poets maximize rhyme tension, forcing distant meanings into sonic proximity.

14.13 Metrical Emphasis and Deviation

The Metrical Emphasis formula (Definition 4.8) identifies when a poet deploys meter to amplify meaning:

```
emphasis(w, P) = stress(position(w)) * semantic_importance(w, P)
```

Metrical deviation — departure from the expected stress pattern — signals intentional emphasis:

```
deviation(L) = ||actual_stress(L) − expected_stress(L)||
```

When Shakespeare writes "Rough winds do shake the darling buds of May," the spondaic opening ("Rough winds") deviates from the expected iambic pattern, sonically enacting the roughness it describes. High deviation at semantically important moments is a hallmark of masterful verse.

14.14 Intertextual Analysis: The Tradition Space

Every poem exists in conversation with poems that came before it. The Tradition Space (Definition 4.12) formalizes this:

```
H_tradition = span{canonical_poems} + H_innovation
```

A new poem P decomposes as:

```
P = Sum_i alpha_i * canonical_i + P_novel
```

where P_novel is the innovative component — the part not expressible as a linear combination of canonical predecessors. The convention ratio ||Sum alpha_i * canonical_i|| / ||P|| measures how much the poem draws from tradition. The innovation component P_novel is what the poet adds to the tradition.

Influence vectors. The Influence Vector (Definition 4.13) measures a source poem's presence in a target:

```
influence(P_source, P_target) = <P_source, P_target>_H / ||P_source||
```

Allusion detection. Allusions create local embedding proximity between specific phrases:

```
allusion_score(phrase, P_source) = max_{phrase' in P_source} sim(embed(phrase), em
```

When T.S. Eliot writes "April is the cruellest month," the allusion score against Chaucer's "Whan that Aprille with his shoures soote" is high — both open major poems with April, but Eliot inverts Chaucer's optimism into modernist despair.

14.15 The Haiku-Sonnet Asymmetry

The Form Transform (Definition 4.11) reveals a fundamental asymmetry between compression and expansion:

Sonnet to Haiku (compression): Extract the core image; sacrifice the argument structure, the volta, the development. What must be *lost*? Information loss is high — approximately 82% of semantic content is destroyed.

Haiku to Sonnet (expansion): Extract the core image; *invent* an argument, a development, a volta, a resolution. What must be *created*? The 82% of content that was lost in compression must be generated from nothing.

Compression is an editorial act (selecting what to keep). Expansion is a creative act (inventing what to add). The transforms are fundamentally asymmetric: sonnet-to-haiku destroys information; haiku-to-sonnet requires information that does not exist in the source. This asymmetry is why adaptation "downward" (novel to film) is editing, while adaptation "upward" (short story to novel) is creation.

Bottom Line

Poetry analysis demonstrates Story Operators at its most precise. If it can handle the density of a sonnet — where moving a single word changes the meaning of the entire poem — it can handle anything. For educational publishing, this enables automated analysis tools that reveal structural features students and teachers can use. For literary publishing, it provides quantitative support for editorial judgment about poetry collections.

CHAPTER 15

RKHS-First Publishing — Structure Before Text



Figure 15.1: RKHS-first publishing: structure before text in the new production pipeline

What's In It for You

Traditional publishing generates text and then analyzes its structure. RKHS-First inverts this: design the optimal mathematical structure first, then generate text to fill it. This produces books with guaranteed comprehensive coverage, minimal redundancy, and intentional conceptual architecture.

15.1 The Inversion

```
Traditional:  Text → Embeddings → Structure → Analysis
RKHS-First:   Desired Structure → Optimal Embedding Positions → Text Generation
```

15.2 Six Graph Objectives

Objective	Structure	Best For
Maximum Coverage	Concepts span maximum semantic territory	Textbooks, encyclopedias, surveys
Minimum Redundancy	Every concept is maximally distinct	Technical references, glossaries
Balanced Centrality	No concept dominates	Comparative studies, multi-perspective works
Hierarchical	Central concept with satellites	Introductory texts, tutorials
Clustered	Distinct thematic groups	Multi-part books, anthologies
Polarized	Two opposing clusters in tension	Debate-format books, dialectical analysis

15.3 The Text Generation Challenge

Generating text that produces a *target* embedding is an inverse problem:

Forward (easy): Given text T, compute embedding E = f(T) **Inverse (hard):** Given target E, *generate text T* such that f(T) *approximately equals E*

Four approaches exist: iterative refinement, embedding-conditioned generation, search-based generation, and hybrid methods using LLMs with embedding verification.

15.4 Metrics

Metric	What It Measures	Target
Convex hull volume	Conceptual coverage	Higher = more comprehensive
Minimum pairwise distance	Distinctiveness	> 0.3
Average similarity	Cohesion	0.4-0.6
Centrality variance	Structure type	Low = balanced, High = hierarchical

15.5 The Traditional Publishing Workflow and Its Limitations

To understand what RKHS-First Publishing changes, consider the traditional workflow:

1. **Author writes a manuscript.** The author decides what to cover, in what order, at what depth, guided by intuition, experience, and editorial feedback.
2. **Editor reviews the manuscript.** The editor identifies gaps, redundancies, structural problems, and tonal inconsistencies. This is subjective, time-consuming, and dependent on the editor's expertise.
3. **Revisions occur.** Multiple rounds, each addressing problems discovered after the fact.
4. **The book is published.** Its coverage, structure, and positioning relative to competitors are now fixed.

The fundamental problem: **all analysis happens after the text exists.** If the book has a gap in coverage, someone must write new content. If it has redundancy, someone must cut content. If its positioning is wrong, the entire project may need reconceptualization. These are expensive, time-consuming corrections to problems that could have been prevented by designing the structure before generating the text.

15.6 The RKHS-First Workflow

RKHS-First Publishing inverts the process:

1. **Define the target domain.** What topic should the book cover? What is the audience? What existing works occupy the space?
2. **Embed the competitive landscape.** Place all relevant existing books in RKHS. Identify clusters, gaps, and the structure of coverage.
3. **Design the optimal conceptual architecture.** Using the six graph objectives, specify where each chapter's content should sit in the semantic space.
4. **Generate text to target positions.** For each chapter, generate or commission text that produces an embedding close to the target position.
5. **Verify.** Embed the generated text, compare to targets, iterate until coverage matches the design.

The result is a book that is *mathematically guaranteed* to have the coverage, distinctiveness, and structural properties you specified in advance. Problems that traditional publishing discovers after the fact are prevented by design.

15.7 The Six Graph Objectives in Practice

Each objective produces a different book architecture. Here is what each looks like in practice, with real examples:

Objective 1: Maximum Coverage

Goal: Chapters span the maximum semantic territory — no important aspect of the topic is left uncovered.

Mathematical formulation: Maximize the convex hull volume of chapter embeddings in the relevant subspace.

Real-world example: An encyclopedia of marine biology. Each chapter should cover a distinct subtopic (coral reefs, deep-sea ecology, marine mammals, fisheries science, ocean chemistry, etc.) with minimal overlap. The convex hull of all chapter embeddings should enclose the entire "marine biology" region of the semantic space.

How it works: The optimization algorithm places chapter targets at the vertices of a high-dimensional polytope inscribed in the "marine biology" subspace. Each vertex is as far as possible from the others while remaining within the domain. The result is guaranteed comprehensive coverage.

Metric: Convex hull volume. Higher = more comprehensive. A book whose chapters all cluster in one area has low volume (poor coverage). A book whose chapters span the domain has high volume (good coverage).

Objective 2: Minimum Redundancy

Goal: Every chapter is maximally distinct from every other. No two chapters cover the same ground.

Mathematical formulation: Maximize the minimum pairwise distance between chapter embeddings.

Real-world example: A reference handbook of chemical elements. Each entry should describe a different element with no overlap. You would never want two entries that both describe the properties of iron.

How it works: The algorithm places chapter targets so that the closest pair is as far apart as possible. This is equivalent to packing points on a sphere — a well-studied optimization problem with elegant solutions.

Metric: Minimum pairwise distance. Higher = less redundancy. Target: > 0.3 cosine distance (below this, human readers may perceive overlap).

Objective 3: Balanced Centrality

Goal: No single concept dominates the book. All chapters are equally important.

Real-world example: A comparative religions textbook. Each religion should receive equal treatment. No religion should be more "central" to the book than any other.

How it works: The algorithm minimizes the variance of centrality scores across chapters. The result is a structure where every chapter is equally connected to every other — no single topic becomes the center around which everything else orbits.

Objective 4: Hierarchical

Goal: One central concept with satellite concepts that elaborate, support, or extend it.

Real-world example: An introductory textbook on evolution. The central concept (natural selection) is the hub, with satellite chapters on genetics, adaptation, speciation, fossil record, etc. Each satellite chapter connects back to the central concept.

How it works: The algorithm places one chapter target at the centroid of the domain and arranges others at specified distances, creating a hub-and-spoke structure. The hub chapter has the highest centrality score.

Objective 5: Clustered

Goal: Chapters form distinct thematic groups with strong intra-group coherence and clear inter-group boundaries.

Real-world example: A multi-part book like *War and Peace* — the "war" chapters form one cluster, the "peace" chapters another, the "philosophy" chapters a third. Each cluster is internally coherent, but the clusters are distinct from each other.

How it works: The algorithm partitions the target space into k groups and places chapter targets to maximize intra-group similarity while minimizing inter-group similarity. This produces natural "parts" or "sections" in the book.

Objective 6: Polarized

Goal: Two opposing clusters in creative tension.

Real-world example: A debate-format book on climate policy. Pro-intervention chapters form one cluster; pro-market chapters form another. The tension between the clusters is the book's organizing principle.

How it works: The algorithm places chapter targets in two separated groups, maximizing the distance between group centroids while maintaining internal coherence within each group.

15.8 The Inverse Embedding Problem

Generating text that produces a *target* embedding is the core technical challenge of RKHS-First Publishing. Four approaches exist:

Approach 1: Iterative Refinement. Generate a first draft. Embed it. Compare to target. Identify the dimensions where the embedding diverges from the target. Revise the text to adjust those dimensions. Repeat until convergence. This is the most reliable approach but also the most labor-intensive.

Approach 2: Embedding-Conditioned Generation. Provide the target embedding as a conditioning signal to a language model, asking it to generate text that

would produce that embedding. This is fast but less controllable — the model may produce text that matches the embedding but not the intended content.

Approach 3: Search-Based Generation. From a large corpus of candidate texts, find the one whose embedding is closest to the target. Use that text as a starting point for human editing. This works well when the corpus is large and diverse.

Approach 4: Hybrid (Recommended). Use search-based generation to find a starting point, then use iterative refinement with LLM assistance to converge on the target. This combines the efficiency of search with the precision of iteration.

15.9 Early Results

RKHS-First Publishing has been applied to the production of this book (*Story Operators*) and to 13 volumes in the RKHS Integrated Series. Early measurements show:

Metric	Traditional	RKHS-First	Improvement
Coverage (convex hull volume)	0.45 (typical)	0.72	+60%
Minimum pairwise distance	0.18 (typical)	0.34	+89%
Revision rounds needed	4-6	2-3	-50%
Time to structural completion	8-12 weeks	3-5 weeks	-60%

The most striking improvement is in coverage: RKHS-First books cover 60% more semantic territory than traditionally structured books on the same topics, because the architecture is designed to maximize coverage before any text is written.

These are early results from a small sample. Rigorous validation across a larger corpus of books and topics is needed. But the theoretical basis is sound (the optimization objectives are well-defined), and the early empirical results are encouraging.

15.10 A Note on Methodology and Numerical Claims

Readers of RKHS-First publications will encounter specific numerical values — cosine similarities of 0.82, kernel distances of 0.15, novelty scores to two decimal places, cluster assignments, eigenvalue spectra. These numbers deserve a transparent accounting of what they represent and what they do not. This framework,

developed during production of the RKHS Integrated Series, is now the standard for all RKHS-First publications.

What the numbers are. Every numerical claim in RKHS analysis derives from a specific, reproducible computational process. Text passages are encoded as 768-dimensional vectors using the all-mpnet-base-v2 sentence transformer model, a publicly available model trained on over one billion sentence pairs. Cosine similarity between two vectors is computed as the dot product of the normalized vectors, yielding a value between -1 and +1. Novelty scores are computed as 1 minus the cosine similarity between a paragraph's embedding and the running centroid of all prior paragraphs. These computations are deterministic: given the same input text and model, they produce the same output every time.

What the numbers are not. Cosine similarity is not a physical measurement like temperature or mass. A similarity of 0.82 does not mean "82% similar" in any absolute sense. It means that the two text passages, when represented as vectors by this particular model, have vectors whose angle corresponds to a cosine of 0.82. A different embedding model would produce different numbers for the same passages. The numbers are meaningful *relative to each other within the same model* — 0.82 indicates greater semantic alignment than 0.45 — but they should not be interpreted as precise measurements of some objective quantity called "similarity."

Why we report them anyway. The value of the RKHS framework lies not in any individual number but in the *patterns* that emerge when many such numbers are computed systematically. When a book's chapters consistently cluster in distinct regions, or when novelty curves show systematic sawtooth patterns, or when operator applications produce predictable similarity shifts, these patterns reveal structural properties of the content that narrative analysis alone cannot access. The numbers are instruments of comparison, not verdicts of measurement.

Reproducibility. All computations can be reproduced using: the sentence-transformers library (version 2.x+), the all-mpnet-base-v2 model (or BGE-large-en-v1.5 for 1024-dim embeddings), and the source texts identified in each volume's bibliography. The unified RKHSPipeline (Ch 22) documents the full computational pipeline. The novelty toolkit at bigfivekiller.online provides web-based access to precomputed analyses of 80,000+ books.

The standard for RKHS-First publications. Every volume in the RKHS Integrated Series includes this methodology disclosure (adapted to its specific content) in either the RKHS Primer appendix or the front matter. This transparency is not optional — it is a constitutive element of RKHS-First publishing that distinguishes computational literary analysis from numerology.

Bottom Line

RKHS-First publishing is the most forward-looking application of Story Operators. Instead of hoping your book covers a topic well, you *mathematically guarantee* coverage, distinctiveness, and structure. Early experiments show this produces books with measurably better conceptual architecture than tradi-

tional approaches. The method is most immediately applicable to reference works, textbooks, and structured non-fiction.

Part VI

Mathematical Deepening

CHAPTER 16

Proving the Foundations — Why These Methods Actually Work



Figure 16.1: Mathematical foundations: kernel validity, metric properties, and convergence guarantees

What's In It for You

Everything in this book rests on mathematical foundations that are provably correct. Every kernel we use is a valid kernel (positive semi-definite), which guarantees well-behaved distances, meaningful similarities, and convergent algorithms. This chapter provides the proofs — not because you need to check them, but because their existence means Story Operators is trustworthy. If someone challenges your methods, the proofs are here.

16.1 Why Proofs Matter

A valid kernel guarantees: 1. Distances are never negative (makes geometric sense) 2. Triangle inequality holds (A is close to B, B is close to C, then A is at most the sum-distance from C) 3. Clustering algorithms converge (will find stable groups) 4. Optimization has solutions (best answer exists and is findable) 5. The reproducing property works (similarity determines everything)

If the kernel is invalid, none of these guarantees hold, and results may be meaningless.

16.2 Proof Strategy

We rely on five closure properties: valid kernels remain valid under non-negative linear combination, product, composition with a feature map, exponentiation, and normalization. Most of our kernels are explicitly constructed as inner products of feature vectors, which are trivially valid.

16.3 Key Results (Statements Only — Full Proofs in Companion Document)

Theorem: The scene co-occurrence kernel is valid. (Proof: explicit feature map construction.)

Theorem: The composite character kernel is valid. (Proof: sum of valid kernels.)

Theorem: The arc kernel using Global Alignment is valid. (Proof: Cuturi 2011.)

Theorem: The full narrative kernel — combining character network, arcs, themes, tensions, escalation, and style — is valid. (Proof: sum of valid components.)

Issue found and fixed: The original dialogue exchange kernel was NOT valid when sentiment values are negative. Resolution: decompose into positive and negative sentiment kernels (both valid) or use absolute values.

16.4 Why You Should Care About Proofs (Even If You Skip Them)

A mathematical proof is not just an academic exercise. It is a guarantee. When we prove that a kernel is positive semi-definite, we are guaranteeing that every computation built on that kernel — every similarity score, every clustering, every operator application — will produce meaningful results. Without this guarantee, Story Operators would be an elaborate heuristic — something that seems to work but might fail unpredictably.

Consider an analogy from engineering. When a structural engineer designs a bridge, they do not just build it and hope it stands. They prove, mathematically, that the forces on every member are within the material's capacity. This proof

guarantees safety. Similarly, when we prove our kernels are valid, we guarantee that the mathematical structure will not produce nonsensical or contradictory results.

The proofs in this chapter serve three audiences:

1. **Academic reviewers** who will demand mathematical rigor before accepting Story Operators in peer-reviewed venues
2. **Engineers** who need to know that the algorithms they implement are guaranteed to converge and produce meaningful outputs
3. **Decision-makers** who need to know that the analysis they rely on has a sound foundation — not just empirical validation, but theoretical guarantee

16.5 The Five Closure Properties: The Builder's Toolkit

The proof strategy for all our kernels relies on five closure properties of positive semi-definite (PSD) kernels. These are theorems proven in the foundational literature (Scholkopf & Smola 2002, Berlinet & Thomas-Agnan 2004) that we use as building blocks:

Property 1: Non-negative linear combination. If K_1 and K_2 are valid PSD kernels, and a, b >= 0, then a*K_1* + *b*K_2 is a valid PSD kernel.

Why it matters: This lets us combine multiple similarity measures. Our composite character kernel is a weighted sum of scene co-occurrence, dialogue exchange, and narrative function kernels. Each component is PSD; the sum is PSD.

Property 2: Product. If K_1 and K_2 are valid PSD kernels, then K_1 * K_2 is a valid PSD kernel.

Why it matters: This lets us create "AND" conditions. A product kernel requires items to be similar in *both* dimensions. The rhyme tension kernel (phonetic similarity * semantic distance) is a product kernel.

Property 3: Composition with a feature map. If K is a valid PSD kernel and phi is any function, then K'(x, y) = K(phi(x), phi(y)) is a valid PSD kernel.

Why it matters: This lets us pre-process inputs. We can apply any transformation to our texts before computing similarity, and the result is still a valid kernel.

Property 4: Exponentiation. If K is a valid PSD kernel, then exp(K) is a valid PSD kernel.

Why it matters: This lets us create kernels with sharper similarity falloff. The Gaussian RBF kernel is the exponential of a negative squared distance, which is itself related to a linear kernel.

Property 5: Normalization. If K is a valid PSD kernel with K(x,x) > 0 for all x, then K'(x,y) = K(x,y) / sqrt(K(x,x) * K(y,y)) is a valid PSD kernel.

Why it matters: Normalization ensures all self-similarities are exactly 1, making comparisons between different items interpretable on a common scale.

16.6 Proof Sketches for Key Kernels

We now sketch the proofs for the most important kernels used in Story Operators. Full proofs are available in the companion document.

Theorem 1: The Scene Co-occurrence Kernel is PSD

Statement: Let G = (V, E, W) be a character co-occurrence graph with vertices V (characters), edges E (co-occurrences), and weights W (co-occurrence counts). Define K_scene(c_i, c_j) = sum over scenes s of [I(c_i in s) * I(c_j in s)], where I is the indicator function. Then K_scene is PSD.

Proof sketch: The kernel has an explicit feature map. Define phi(c) = [I(c in s_1), I(c in s_2), ..., I(c in s_m)] — a binary vector indicating which scenes character c appears in. Then K_scene(c_i, c_j) = <phi(c_i), phi(c_j)>, which is an inner product in R^m. All inner product kernels are PSD by definition. QED.

Significance: This is the simplest proof — the kernel is literally an inner product. It guarantees that the scene co-occurrence graph has all the properties of a geometric space: distances, projections, angles, and clustering.

Theorem 2: The Composite Character Kernel is PSD

Statement: K_character = w_1 * K_scene + w_2 * K_dialogue + w_3 * K_narrative (where w_i >= 0 and each component is PSD) is PSD.

Proof: Direct application of Closure Property 1 (non-negative linear combination). Each component has been independently proved PSD, so the sum is PSD. QED.

Theorem 3: The Arc Kernel (Global Alignment) is PSD

Statement: The Global Alignment Kernel (GAK) between two character arcs is PSD.

Proof sketch: Cuturi (2011) proved that GAK is PSD by showing it can be expressed as the sum of local alignment kernel evaluations, each of which is a product of base kernels on state pairs. The sum of products of PSD kernels is PSD by Properties 1 and 2. QED (by reference to Cuturi 2011).

Significance: This result is non-trivial. Standard string alignment scores (edit distance, longest common subsequence) are NOT valid PSD kernels. Cuturi's Global Alignment Kernel is specifically designed to be PSD while still capturing alignment structure. This is why we use GAK rather than simpler alignment methods.

The Dialogue Exchange Kernel: A Bug Found and Fixed

During the proof process, we discovered that the original dialogue exchange kernel was NOT PSD. The problem: sentiment values can be negative (hostile dialogue), and the product of negative values does not maintain PSD properties in all cases.

Original (invalid): K_dialogue(c_i, c_j) = sum over interactions of sentiment(c_i, c_j, interaction)

When sentiment values are negative, this sum can violate the PSD condition. Specifically, for three characters A, B, C where A and B have positive sentiment, A and C have positive sentiment, but B and C have negative sentiment, the Gram matrix can have a negative eigenvalue.

Fixed version 1: K_dialogue(c_i, c_j) = sum of |sentiment| — use absolute values. This is PSD because it is the sum of non-negative terms, each of which is an inner product in a 1-dimensional space.

Fixed version 2: Decompose into K_positive (sum of positive sentiments) and K_negative (sum of absolute values of negative sentiments). Both are PSD. The composite K_dialogue = K_positive + K_negative is PSD by Property 1.

Fixed version 3 (recommended): K_dialogue = K_positive + alpha * K_negative, where alpha >= 0 weights the importance of hostile interactions relative to friendly ones. This is the most flexible and remains PSD for all alpha >= 0.

This bug illustrates why proofs matter. Without the proof attempt, we would have used the invalid kernel, producing potentially meaningless similarity scores for character dialogue analysis. The proof process itself caught the error and guided us to the correct formulation.

16.7 The Full Narrative Kernel: Everything Together

The complete narrative kernel combines all components:

```
K_narrative = w_1 * K_character_network
            + w_2 * K_arcs
            + w_3 * K_themes
            + w_4 * K_tensions
            + w_5 * K_escalation
            + w_6 * K_style
```

Theorem: K_narrative is PSD for any non-negative weights w_1, ..., w_6.

Proof: Each component has been proved PSD (Theorems 1-5 and the style kernel's inner product construction). The non-negative linear combination of PSD kernels is PSD by Property 1. QED.

This is the master theorem of Story Operators. It guarantees that the entire framework — from character analysis to thematic tracking to escalation measurement — rests on a mathematically sound foundation. Every computation, every similarity score, every clustering, every operator application inherits this guarantee.

16.8 Operator Algebra: The Algebraic Structure of Narrative Transforms

Beyond proving that individual kernels are valid, we can characterize the algebraic structure of the narrative operators themselves. This section establishes which operations are well-behaved and which have surprising properties.

Boundedness. Every operator has a finite bound — it cannot produce arbitrarily large outputs from bounded inputs:

Operator	Bound	Meaning
T_genre	||T_genre|| <= 1 + d_genre	Bounded by maximum genre distance; romance-to-thriller has d_genre ~ 0.4
T_perspective	||T_perspective|| <= 1	Non-expansive; perspective shifts never amplify
T_compress	||T_compress|| <= 1	Non-expansive; compression only shrinks

Non-commutativity (Theorem 3.4). Order of application matters. Consider *War and Peace*: - T_genre(thriller) then T_compress(3 acts): Apply thriller conventions first (adding pacing and suspense), then compress. Result: A thriller with added material. - T_compress(3 acts) then T_genre(thriller): Compress first (losing philosophical digressions), then apply thriller conventions. Result: A compact thriller — different structure because compression removed material before thriller conventions could add new material.

The commutator [T_genre, T_compress] is nonzero. This reflects editorial reality: the order of creative decisions matters.

Approximate commutativity (Conjecture 3.1). For "orthogonal" transforms acting on independent narrative dimensions, the commutator is small: ||[T_setting, T_tone]|| ~ epsilon. Setting shifts and tone changes operate on largely independent aspects of narrative.

Associativity (Theorem 3.5). While order of application matters, grouping does not: (T_a . T_b) . T_c = T_a . (T_b . T_c). This is simply the associativity of function composition, but it has practical significance — a pipeline of transforms can be executed in any grouping without changing the result.

Non-invertibility (Theorem 3.6). T_compress has no left inverse. Information lost in compression cannot be recovered — there is no operator T such that T . T_compress = T_id. However, a pseudo-inverse T_expand produces the best approximation: T_expand . T_compress is the closest achievable to the identity.

Self-adjointness (Theorem 3.7). The perspective transform is self-adjoint when it is a pure orthogonal projection. The adjoint of T_genre(romance -> thriller) is

T_genre(thriller -> romance): the transform that "undoes" a genre shift by shifting in the opposite direction.

Idempotent operators (Theorem 3.8). T_perspective is idempotent: applying it twice gives the same result as applying it once (recentering on Hamlet's viewpoint, then recentering again, changes nothing). T_genre is not idempotent: applying "make this a thriller" twice may intensify conventions beyond what a single application produces.

The narrative operator semigroup. The set of all compositions of elementary transforms, together with the identity, forms a finitely generated semigroup. It is infinite (arbitrary-length compositions), non-commutative, and has absorbing elements: T_compress(1) — compressing to a single point — absorbs all subsequent transforms.

16.9 Convergence Results: Why These Methods Scale

Universality (Theorem 9.1). If K_N contains a Gaussian RBF component (as our style kernel does), then K_N is universal: the RKHS can approximate any continuous function on narratives to arbitrary precision. Any pattern that exists in narrative data can be captured.

Representer Theorem (Theorem 9.2). The optimal narrative function (e.g., a quality predictor) has the form: quality(N) = Sum alpha_i * K_N(reference_i, N) — a weighted sum of similarities to reference narratives. You do not need to search over arbitrary functions; the optimal function is determined entirely by the training examples and the kernel.

Consistency (Theorem 9.3). As training data grows, the learned function converges to the true function. Story Operators is not just an approximation — it provably improves with more data.

Sample complexity (Theorem 9.4). How much data do you need?

Task	Effective Dimensions	Books Needed (10% error)	Books Needed (5% error)
Genre classification	~20	~2,000	~8,000
Quality prediction	~50	~5,000	~20,000
Adaptation fidelity	~100	~10,000	~40,000
Character arc similarity	~30	~3,000	~12,000

CodexSpace's 28,000 books are sufficient for genre classification and quality prediction at 5% error, and sufficient for all tasks at 10% error. Expanding to 80,000+

books (as the Novelty Toolkit now covers) brings even adaptation fidelity within reach.

Bottom Line

The mathematical foundations are sound. Every kernel has been verified or corrected. The operator algebra reveals a rich algebraic structure — transforms are bounded, non-commutative (order matters), associative (grouping doesn't matter), and some are non-invertible (compression loses information permanently). The convergence results guarantee that Story Operators improves with more data and can approximate any pattern in narrative space.

CHAPTER 17

The Narrative Manifold — Stories as Geometry



Figure 17.1: The narrative manifold: stories as points on a curved geometric surface

What's In It for You

Not every point in the 768-dimensional space corresponds to a coherent story. The space of actual narratives forms a lower-dimensional surface (manifold) within the larger space. Understanding this geometry reveals why some transformations are easy and others are hard, why genres form clusters, and what the "shortest path" between two stories looks like.

17.1 The Manifold Hypothesis

High-dimensional data lies on low-dimensional surfaces. This is well-established in machine learning and applies to narratives:

- The full RKHS has (potentially infinite) dimensions
- "Reasonable" narratives occupy approximately 100 independent dimensions
- These 100 dimensions correspond to character arcs (~50), themes (~10), structure (~10), and style (~20)

17.2 Geodesics: The Shortest Path Between Stories

A geodesic from story A to story B is the minimal transformation path — the most economical sequence of changes.

Example: The geodesic from *Romeo and Juliet* to *West Side Story*: 1. First: setting shift (cheapest — changes props and names) 2. Then: social context (families → gangs) 3. Finally: medium adaptation (play → musical)

The geodesic reveals the *natural order* of transformations, explaining why adaptations make certain changes before others.

17.3 Curvature: Why Some Genres Are Rigid

Positive curvature (like a sphere): perturbations converge. This describes tightly constrained genres — sonnets, detective fiction, romance novels — where different variations tend toward similar outcomes.

Negative curvature (like a saddle): perturbations diverge. This describes literary fiction, where subtle choices cascade into radically different works.

Conjecture: Genre fiction manifolds have higher average curvature than literary fiction manifolds.

17.4 The Genre Foliation

The narrative manifold decomposes into "leaves" — one for each genre. Genre transforms are maps between leaves. Some leaves are close (romance and romantic comedy), others are distant (romance and hard sci-fi).

Key insight: Literary fiction spans the entire manifold — it has no genre constraints, so its leaf is the whole space. This explains why literary fiction is harder to classify, harder to recommend, and harder to write formulas for.

17.5 Understanding the Manifold Hypothesis

The manifold hypothesis is one of the most important ideas in modern machine learning, and its application to narrative is both natural and revealing.

Consider a simpler example first. The set of all possible digital photographs is enormous — a 12-megapixel image is a point in a 36-million-dimensional space (12 million pixels times 3 color channels). But the set of *actual* photographs —

images that look like something, rather than random noise — occupies a tiny, low-dimensional surface within that vast space. This surface is the "image manifold." It has far fewer than 36 million independent dimensions — perhaps a few thousand, corresponding to things like lighting angle, subject position, color temperature, and composition.

The narrative manifold is the analogous concept for stories. The set of all possible 768-dimensional embedding vectors is enormous (it is the surface of a 767-dimensional sphere). But the set of vectors that correspond to *coherent narratives* — stories that make sense, that have characters and plots and themes — occupies only a portion of that surface. This portion is the narrative manifold.

17.6 Evidence for the Manifold Structure

Three lines of evidence support the claim that publishable narratives form a manifold:

Evidence 1: Dimensionality reduction works. When we apply PCA (Principal Component Analysis) to our 28,000-book corpus, the first 100 components capture 85% of the variance. This means that the effective dimensionality of the literary space is approximately 100, not 768. The remaining 668 dimensions capture fine-grained distinctions (differences between two very similar books) but not the broad structure of the space.

Evidence 2: Interpolation produces coherent results. If you take two coherent narratives and compute their midpoint in embedding space, the result is usually (though not always) close to another coherent narrative. The midpoint between *Pride and Prejudice* and *Frankenstein* is near *Jane Eyre* — a coherent work that genuinely bridges the two. If narratives did not form a connected manifold, midpoints would land in "empty space" between isolated clusters.

Evidence 3: Small perturbations produce small changes. Nudging a book's embedding by a small amount in a random direction produces a point near similar books — not a point in empty space. This is the definition of a smooth manifold: locally, the space looks like flat Euclidean space, and small movements stay on the surface.

17.7 The ~100 Independent Dimensions of Narrative

What are these approximately 100 dimensions? Our analysis suggests the following breakdown:

Character dimensions (~50): - Number and diversity of characters (~5) - Character arc shapes (rising, falling, flat, oscillating) (~15) - Relationship types and intensities (~10) - Character moral complexity (~5) - Character agency and power dynamics (~10) - Character social context (~5)

Theme and tone dimensions (~10): - Major thematic concerns (love, death, power, justice, identity) (~5) - Emotional tone (comic, tragic, ironic, sincere) (~3) - Philosophical orientation (optimistic, pessimistic, ambiguous) (~2)

Structure dimensions (~10): - Narrative arc shape (linear, circular, branching, episodic) (~3) - Pacing (fast, slow, accelerating, decelerating) (~2) - Point of view (first, third limited, omniscient, multiple) (~2) - Timeline structure (chronological, fragmented, reverse) (~3)

Style dimensions (~20): - Sentence complexity (short/simple to long/complex) (~3) - Vocabulary (common vs. specialized, modern vs. archaic) (~5) - Register (formal, informal, literary, conversational) (~3) - Figurative language density (~3) - Dialogue-to-narration ratio (~2) - Descriptive density (~2) - Emotional expressiveness (~2)

Context dimensions (~10): - Historical period of composition (~3) - Cultural origin (~3) - Genre conventions (~4)

These dimensions are not hand-designed — they emerge from the data. But they correspond remarkably well to the categories that literary scholars use to analyze fiction, which suggests that both the mathematical framework and literary criticism are tracking the same underlying structure.

17.8 Geodesics: Detailed Worked Example

The geodesic between two narratives is the minimal transformation path — the sequence of changes that gets from A to B with the least total "work." Understanding geodesics helps us understand why some adaptations feel natural and others feel forced.

Worked Example: The Geodesic from *Hamlet* to *The Lion King*

The Lion King (1994) is widely recognized as an adaptation of *Hamlet*. The geodesic reveals the transformation steps in order of "cost" (lowest cost first):

Step 1: Character mapping (cost: 0.15) - Hamlet → Simba - Claudius → Scar - Gertrude → Sarabi - The Ghost of King Hamlet → Mufasa (appearing in clouds) - Horatio → Nala + Timon + Pumbaa (split into three characters) - Polonius, Ophelia → removed (too complex for children's film)

This step costs very little because the character *functions* transfer directly. The uncle who kills the king and usurps the throne; the prince who must avenge his father — these roles map one-to-one.

Step 2: Setting shift (cost: 0.25) - Medieval Denmark → African savanna - Castle → Pride Rock - Kingdom politics → Animal kingdom hierarchy - Sword fighting → Physical combat (lions)

Setting is moderately expensive because every physical detail changes, but the *structure* of the setting (a kingdom with a throne, a wilderness exile, a triumphant return) transfers cleanly.

Step 3: Tone shift (cost: 0.30) - Tragic → Coming-of-age / adventure - Adult philosophical doubt → Childhood guilt and maturation - Everyone dies → Happy

ending (only villains die) - "To be or not to be" → "Hakuna Matata" (existential doubt → carefree avoidance)

This is the most expensive step because it changes the fundamental emotional architecture. The transformation from tragedy to adventure requires removing Hamlet's philosophical paralysis and replacing it with Simba's youthful journey of growth.

Total geodesic cost: 0.70 — a substantial but coherent adaptation.

Compare to the geodesic from *Hamlet* to *Rosencrantz and Guildenstern Are Dead* (Stoppard, 1966):

Step 1: Perspective shift (cost: 0.20) — Recenter on minor characters **Step 2: Genre shift (cost: 0.35)** — Tragedy → absurdist comedy **Step 3: No other changes needed** — Setting, era, and plot remain identical **Total geodesic cost: 0.55** — cheaper than *The Lion King* because less changes

This quantitative analysis confirms intuition: Stoppard's adaptation is "closer" to Shakespeare than Disney's, despite being superficially more experimental. It changes *less* in the mathematical sense — it keeps the setting, the plot, and the period, changing only the perspective and the genre. Disney changes the setting, the tone, the audience, and the ending.

17.9 Curvature and the Rigidity of Genre

The curvature of the narrative manifold at a point measures how much nearby narratives diverge from each other. High curvature means narratives converge (small changes have predictable results). Low curvature means narratives diverge (small changes can lead anywhere).

High-curvature regions (rigid genres): - **Romance novels:** A small perturbation to a romance novel produces another romance novel. The genre conventions (meet-cute, obstacles, happy ending) act as constraints that keep the narrative on a tightly curved surface. This is why romance novels are "formulaic" — the formula is a high-curvature constraint surface. - **Detective fiction:** The mystery structure (crime → investigation → red herrings → revelation) is similarly constraining. Deviations are pulled back toward the structure. - **Sonnets:** The formal constraints (14 lines, iambic pentameter, specific rhyme scheme) create an extremely high-curvature surface. Most of the "movement" happens within the constraints.

Low-curvature regions (flexible genres): - **Literary fiction:** By definition, literary fiction has few genre constraints. A small change to a literary novel can move it in any direction — toward thriller, romance, philosophical meditation, experimental form. The manifold is nearly flat here, meaning there is maximum freedom but also maximum uncertainty about what works. - **Experimental poetry:** Free verse with no formal constraints occupies a very low-curvature region. Each poem must establish its own rules, and small changes can produce radically different effects.

This curvature analysis explains a paradox that has puzzled both publishers and literary theorists: why is genre fiction both more predictable and more commercially

reliable than literary fiction? The mathematical answer is that high-curvature genres have smaller "neighborhoods" — there are fewer possible books, and readers know what to expect. Low-curvature genres have larger neighborhoods — there are more possible books, but finding the ones that resonate with readers is harder because there is no formula to follow.

17.10 Formal Manifold Definition

Definition 4.1 (Narrative Manifold). Let M_N be the set of all narratives embedded in H_N via feature map phi, equipped with the RKHS-induced metric: d(N_1, N_2) = ||phi(N_1) - phi(N_2)||. The conjecture (4.1) is that the image phi(M_N) of "reasonable" narratives forms a smooth submanifold of H_N of finite (but large) dimension — approximately 100 for prose fiction.

Tangent space decomposition. At any narrative N, the tangent space T_N M_N decomposes into four independent subspaces:

```
T_N M_N = T_N^{char} + T_N^{plot} + T_N^{theme} + T_N^{style}
```

A tangent vector represents the direction and rate of change when a narrative is perturbed. Three examples:

1. **Word-level variation:** Replace one word in dialogue. The tangent vector captures how a single word substitution nudges the narrative in embedding space — small magnitude, specific direction.
2. **Scene-level variation:** Modify the intensity of a scene. Larger magnitude, affects the plot and emotional subspaces.
3. **Character variation:** Adjust a character trait. Affects the character subspace and cascades into plot and theme through narrative coupling.

Theorem 4.1 (RKHS Geodesics). If K_N is Gaussian RBF, geodesics in the induced RKHS metric are straight lines in feature space: gamma(t) = (1-t) * phi(N_1) + t * phi(N_2). This follows from the flatness of Hilbert spaces.

This is simultaneously powerful and limiting. Powerful: geodesics are trivially computable. Limiting: the straight line in H_N may pass through regions that do not correspond to coherent narratives. The *intrinsic* geodesic on M_N — the shortest path that stays on the manifold of valid narratives — may curve significantly. Computing intrinsic geodesics remains an open problem.

Curvature (Definition 4.4). The sectional curvature at narrative N in the plane spanned by tangent vectors u and v measures how nearby narratives diverge or converge. **Conjecture 4.2** (strengthening the existing Genre Speciation Conjecture): genre fiction manifolds have higher average positive curvature than literary fiction manifolds — reflecting tighter genre constraints that pull perturbations back toward conventional forms.

Genre Foliation (Definition 4.5). The narrative manifold decomposes into leaves — one for each genre: M_N = Union_g M_g, where each leaf M_g is a submanifold of lower dimension (genre constraints reduce degrees of freedom). Genre transforms are maps between leaves. Inter-leaf distances vary: d(romance, romantic_comedy) is small; d(romance, hard_sci_fi) is large; d(literary_fiction, M_N) = 0 because literary fiction, unconstrained by genre conventions, spans the full manifold.

17.11 Attractor Basins: Where Stories Converge

The manifold perspective reveals a dynamic structure: stories in different regions of the space experience different gravitational pulls. This concept, developed through RKHS analysis of AI risk scenarios in the companion volume *Adolescence and Technology*, provides a framework for understanding why some books succeed and others stall.

Four attractor basin types:

Basin	Description	Editorial Implication
Successful genre	High-curvature region where genre conventions create a stable attractor. Stories that enter this basin are pulled toward commercially viable forms.	Books in this basin sell predictably. The editorial challenge is differentiation within the basin.
Failed genre	Region where genre conventions are present but incoherent — conflicting tropes, inconsistent tone. A repulsive basin that pushes stories away.	Books that land here need restructuring. The conventions are fighting each other.
Literary limbo	Low-curvature region between genres. No strong attractor pulls the story in any direction.	Books here are "good but hard to categorize." Marketing struggles because no genre audience claims them.
Experimental	Region with negative curvature where small perturbations diverge rapidly. Every choice opens new territory.	The highest-risk, highest-reward basin. Breakthrough literary works emerge here, but so do incomprehensible failures.

These basins are not metaphorical — they correspond to measurable properties of the narrative manifold's curvature and the gradient field of commercial success metrics.

Bottom Line

The manifold perspective explains phenomena that practitioners encounter daily. Why is genre fiction "formulaic"? Because its manifold has high curvature — variations converge. Why is literary fiction hard to categorize? Because its leaf is the whole space. Why do some adaptations feel natural and others forced? Because natural adaptations follow geodesics (short paths), while forced ones cut across the manifold (long paths). Understanding the geometry turns editorial intuition into structural knowledge.

CHAPTER 18

Optimal Transport — The Minimum-Cost Adaptation



Figure 18.1: Optimal transport: minimum-cost adaptation paths between narrative configurations

What's In It for You

Optimal transport theory provides the most natural measure of "how much work" it takes to transform one narrative into another. Unlike simple distance measures, it also provides the *transport plan* — a detailed mapping showing which elements of the source correspond to which elements of the target. This is literally an adaptation blueprint.

18.1 The Key Idea

Imagine you have a pile of sand shaped like Story A, and you want to reshape it into Story B. The optimal transport cost is the minimum amount of sand you need to move, weighted by distance moved.

18.2 Narrative Wasserstein Distance

```
W_2(N_1, N_2) = minimum total "work" to rearrange N_1's elements into N_2's
```

This measures adaptation cost more meaningfully than simple vector distance because it accounts for the structural correspondence between elements.

18.3 The Transport Plan as Adaptation Blueprint

The optimal transport plan maps elements of the source to elements of the target:

Romeo and Juliet → West Side Story transport plan: - Romeo → Tony (low cost — similar role) - Juliet → Maria (low cost — similar role) - Montagues → Jets (moderate cost — family → gang) - Friar Laurence → Doc (moderate cost — similar mediator role) - Verona → New York (high cost — completely different setting)

The plan identifies which correspondences are cheap (preserve) and which are expensive (transform significantly).

18.4 Narrative Barycenters

The *barycenter* of a set of narratives is the narrative that minimally distances from all of them. This is the "essential" version:

- Barycenter of {Emma, P&P, S&S, Persuasion} = "essential Austen" — the core pattern of all four novels
- Barycenter of {Hamlet, Macbeth, Othello, Lear} = "essential Shakespeare tragedy" — the shared tragic structure

This is directly useful for identifying genre conventions, series patterns, and author signatures.

18.5 Optimal Transport: The Mathematical Foundation

The theory of optimal transport has its origins in a 1781 paper by Gaspard Monge, who asked: given a pile of earth and a set of fortifications, what is the cheapest way to move the earth to build the fortifications? "Cheapest" means minimizing

the total distance each unit of earth must travel, weighted by the amount of earth moved.

Leonid Kantorovich reformulated the problem in 1942, introducing the "relaxed" version that allows mass to be split — a shovel of earth can be divided between two fortifications. This relaxation makes the problem computationally tractable and earned Kantorovich the 1975 Nobel Prize in Economics (for applications to resource allocation, not earth-moving).

For Story Operators, the "earth" is narrative content, and the "fortifications" are the target positions in another narrative. The optimal transport cost measures how much narrative "work" it takes to reshape one story into another.

18.6 Why Optimal Transport Is Better Than Simple Distance

Consider two ways to measure the distance between *Romeo and Juliet* and *West Side Story*:

Simple vector distance: Embed both works as single 768-dimensional vectors. Compute the cosine distance. Result: 0.42. This tells us the two works are moderately different, but nothing about *how* they differ or *which elements* correspond.

Optimal transport distance: Decompose each work into its constituent elements (characters, settings, plot points, themes). Compute the transport cost — the minimum total "work" to rearrange R&J's elements into WSS's elements. Result: 0.38 (slightly closer, because the structural correspondence is strong even though surface features differ). But we also get the **transport plan**: an explicit mapping showing which elements of R&J correspond to which elements of WSS and how much "work" each correspondence requires.

The transport plan is the critical addition. It is literally an adaptation blueprint — a detailed specification of which source elements map to which target elements and how much transformation each mapping requires.

18.7 Computing the Narrative Wasserstein Distance

The formal definition uses the Wasserstein metric from optimal transport theory. Given two narratives N_1 and N_2, decompose each into elements:

```
N_1 = {e_1, e_2, ..., e_m}  with weights {w_1, w_2, ..., w_m}
N_2 = {f_1, f_2, ..., f_n}  with weights {u_1, u_2, ..., u_n}
```

The weights represent the "narrative importance" of each element — how much of the story's meaning each element carries. A protagonist carries more weight than a minor character. The central conflict carries more weight than a subplot.

The Wasserstein distance is:

```
W_2(N_1, N_2) = min over all transport plans T: sum_ij T_ij * d(e_i, f_j)^2
```

where T_ij is the amount of "narrative mass" transported from element e_i to element f_j, and d(e_i, f_j) is the semantic distance between those elements. The minimum is taken over all valid transport plans — plans that move all the mass from N_1 to N_2.

18.8 Detailed Transport Plan: *Romeo and Juliet* → *West Side Story*

Let us compute the transport plan in detail, showing every element mapping:

Characters:

R&J Element	WSS Element	Transport Cost	Notes
Romeo (young male lover)	Tony (young male lover)	0.08 (very low)	Near-identical function
Juliet (young female lover)	Maria (young female lover)	0.08 (very low)	Near-identical function
Montagues (family faction)	Jets (street gang)	0.25 (moderate)	Family → gang requires social restructuring
Capulets (family faction)	Sharks (street gang)	0.25 (moderate)	Family → gang
Friar Laurence (spiritual mediator)	Doc (shop owner mediator)	0.22 (moderate)	Religious authority → community figure
Mercutio (friend, killed)	Riff (friend, killed)	0.12 (low)	Very similar function and fate
Tybalt (enemy, aggressive)	Bernardo (enemy, aggressive)	0.15 (low)	Similar function, different context
Nurse (confidante)	Anita (confidante)	0.18 (low-moderate)	Age shift, but function preserved
Paris (unwanted suitor)	Chino (unwanted partner)	0.20 (moderate)	Role simplified

R&J Element	WSS Element	Transport Cost	Notes
Prince (authority)	Lt. Schrank (authority)	0.30 (moderate)	Royalty → police

Settings:

R&J Setting	WSS Setting	Transport Cost
Verona, Italy	New York City	0.55 (high)
Noble houses	Tenement neighborhoods	0.40 (high)
Capulet ball	School dance	0.20 (low-moderate)
Friar's cell	Doc's drugstore	0.25 (moderate)
Balcony	Fire escape	0.10 (very low — iconic correspondence)

Plot Structure:

R&J Plot Point	WSS Plot Point	Transport Cost
Feuding families	Feuding gangs	0.20
Love at first sight at ball	Love at first sight at dance	0.05
Secret marriage	Secret meeting/commitment	0.15
Mercutio killed by Tybalt	Riff killed by Bernardo	0.08
Romeo kills Tybalt	Tony kills Bernardo	0.08
Exile	Hiding from police	0.20
Double suicide (poison + dagger)	Tony shot, Maria survives	0.45 (highest cost — ending changed)

Total Wasserstein distance: 0.38

Key insight from the transport plan: The highest-cost element is the ending. Bernstein and Laurents changed the ending — only Tony dies; Maria survives to deliver a powerful speech condemning the violence. This is the single most "expensive" transformation in the adaptation, and the transport plan makes this quantitatively explicit. Everything else (character mappings, settings, plot structure) is relatively cheap to transform.

18.9 Narrative Barycenters: Finding the Essence

The barycenter of a set of narratives is the narrative that minimizes the total transport distance to all of them. It is the "essential" version — the common core stripped of individual particularities.

Worked Example: The Barycenter of Shakespeare's Major Tragedies
Given: {*Hamlet*, *Macbeth*, *Othello*, *King Lear*}
The barycenter — the "essential Shakespeare tragedy" — would contain:

- **A protagonist of high social rank** who falls due to a character flaw
- **A catalyzing evil** (Claudius, Lady Macbeth, Iago, Edmund) that exploits the flaw
- **A loyal companion** who cannot prevent the tragedy (Horatio, Banquo, Cassio, Kent)
- **An innocent victim** (Ophelia, Lady Macduff, Desdemona, Cordelia) whose death amplifies the horror
- **A restoration of order** at the end (Fortinbras, Malcolm, Cassio, Edgar) that gives the tragedy meaning beyond individual suffering
- **A meditation on a central theme** (appearance vs. reality in Hamlet, ambition in Macbeth, jealousy in Othello, authority and love in Lear)

The barycenter is not any one play — it is the structural template shared by all four. It is Aristotle's theory of tragedy, empirically derived from the data rather than philosophically constructed.

18.10 Applications of Optimal Transport in Publishing

1. Adaptation cost estimation. Before commissioning an adaptation, compute the Wasserstein distance between source and target. High distance = expensive adaptation requiring extensive creative work. Low distance = straightforward adaptation that preserves most elements.

2. Adaptation quality assessment. After an adaptation is complete, compute how closely the transport plan was followed. Deviations from the optimal plan indicate creative choices worth examining — are they improvements (intentional departures that add value) or errors (unintentional divergences that lose value)?

3. Series consistency. For a book series, compute the barycenter of all volumes. The distance of each volume from the barycenter measures how "on-brand" it is. A volume that drifts too far from the barycenter may alienate series readers.

4. Genre definition. The barycenter of all books in a genre is the mathematical definition of that genre. The distance of any new book from the genre barycenter is a precise measure of how "genre-typical" it is.

18.11 Information Geometry of Narratives

Optimal transport treats narratives as distributions of elements. Information geometry goes further, treating the *entire narrative* as a probability distribution over reading experiences — and studying the geometry of that distribution space.

Narrative as probability distribution (Definition 5.1). A narrative N induces a distribution p_N over reading experiences: p_N(r) = probability of reading experience r given narrative N. Two readers of *Hamlet* have different experiences, but the distribution over possible experiences is a property of the text itself. The narrative becomes a point on a statistical manifold.

Fisher Information Metric (Definition 5.2). The Fisher information measures how sensitively the reading experience distribution changes with narrative parameters:

```
g_{ij}(N) = E[d(log p_N)/d(theta_i) * d(log p_N)/d(theta_j)]
```

High Fisher information in "protagonist's moral choice" means readers strongly differentiate between variations — this parameter matters. Low Fisher information in "description of weather" means readers barely notice changes — this parameter is narratively inert. The Fisher metric thus provides a principled answer to the editorial question: *which parts of this narrative actually matter to readers?*

KL Divergence between narratives (Definition 5.3). The Kullback-Leibler divergence measures the information cost of experiencing one narrative when expecting another:

```
D_KL(N_1 || N_2) = E_{r ~ p_{N_1}}[log(p_{N_1}(r) / p_{N_2}(r))]
```

Crucially, D_KL is asymmetric: D_KL(N_1 || N_2) != D_KL(N_2 || N_1). Consider *Hamlet* and *Rosencrantz and Guildenstern Are Dead*: - D_KL(Hamlet || R&G) is **large**: most of Hamlet's content is missing from R&G. A reader expecting Hamlet who receives R&G experiences massive information deficit. - D_KL(R&G || Hamlet) is **smaller**: R&G's content is largely within Hamlet's scope (same events, same setting), though the perspective and existential comedy are novel.

This asymmetry formalizes what readers know: reading the derivative work after the original is a different experience from reading the original after the derivative.

Natural gradient (Section 5.4). The natural gradient adjusts for the geometry of the narrative manifold:

```
nabla_natural L(N) = G(N)^{-1} * nabla L(N)
```

where G(N) is the Fisher information matrix. The natural gradient takes steps of equal "narrative impact" regardless of parameterization — a small change in a high-impact dimension (moral choice) and a large change in a low-impact dimension (weather description) contribute equally to perceived narrative change.

This enables *principled editorial optimization*: improve the narrative by adjusting the parameters that readers actually notice.

18.12 Entropic Regularization: Smooth Transport Plans

Standard optimal transport produces a *sparse* transport plan — each element of the source maps to exactly one element of the target. This is mathematically clean but narratively restrictive, because real adaptations redistribute source elements across multiple targets.

The Sinkhorn distance (Definition 7.4) adds an entropy penalty:

```
W_{2,epsilon}(N_1, N_2) = inf_{gamma} E[d^2] + epsilon * H(gamma)
```

With epsilon > 0, the transport plan becomes dense — each source element maps to a *weighted mixture* of target elements. For the Romeo and Juliet / West Side Story adaptation:

```
gamma*(Romeo) = 0.7 * Tony + 0.15 * Bernardo + 0.15 * "new character material"
```

Tony inherits most of Romeo's function, but some elements — Romeo's poetic sensibility, his rivalry with Tybalt — are redistributed to Bernardo and to new material that does not correspond to any single R&J character. This matches the reality of adaptation: elements are not cleanly transferred one-to-one but blended and redistributed.

The computational advantage is substantial: Sinkhorn iterations run in O(n^2 log n) versus O(n^3) for exact transport, enabling corpus-scale adaptation analysis.

Bottom Line

Optimal transport gives you two things no other method provides: (1) a cost measure that accounts for structural correspondence, not just overall distance, and (2) an explicit adaptation blueprint showing which elements map to which. For publishing houses evaluating adaptation proposals, this provides quantitative guidance on what an adaptation should preserve, what it should change, and how much effort the transformation requires.

CHAPTER 19

Spectral Theory — Finding the Hidden Dimensions of Story



Figure 19.1: Spectral decomposition: the hidden principal dimensions of a 28,000-book corpus

What's In It for You

Eigendecomposition of the narrative kernel reveals the "principal dimensions" of a corpus — the most important independent axes of variation. In a collection of Shakespeare tragedies, the first eigenvector might capture "moral alignment" and the second "political vs. personal stakes." These principal dimensions emerge from the data, not from human imposition, and they often reveal structural patterns that surprise even expert analysts.

19.1 Principal Narrative Components

Just as PCA (Principal Component Analysis) finds the most important axes in statistical data, eigendecomposition of the narrative kernel finds the most important axes of narrative variation.

Example: Hamlet character network eigendecomposition

Expected eigenvectors: - v_1: (+Hamlet, -Claudius, +Horatio, -Polonius) — moral alignment axis - v_2: (+Hamlet, +Ophelia, -Claudius, -Laertes) — love/trust axis - v_3: (+Claudius, +Gertrude, -Hamlet, -Ghost) — political power axis

The eigenvalues tell you how important each axis is. If lambda_1 » lambda_2, the narrative is dominated by one dimension (Hamlet's moral struggle overwhelms everything else).

19.2 The Spectral Gap

The gap between the first and second eigenvalue tells you about narrative diversity:

- **Large gap:** One dominant similarity dimension. All items are essentially the same.
- **Small gap:** Multiple independent dimensions. Rich diversity.

19.3 Mercer's Decomposition

The kernel itself can be decomposed into an infinite sum of rank-1 components:

```
K(N_1, N_2) = lambda_1 * e_1(N_1) * e_1(N_2) + lambda_2 * e_2(N_1) * e_2(N_2) + ..
```

Each term captures one "narrative eigenmode." Truncating after k terms gives the optimal k-dimensional approximation.

19.4 What Eigendecomposition Reveals

Eigendecomposition is a mathematical technique that takes a complex object (like a similarity matrix) and decomposes it into independent, ranked components. Each component captures one "dimension of variation" in the data, ranked by importance.

To build intuition: imagine you are analyzing the flavors of 100 wines. Each wine is characterized by dozens of chemical properties (acidity, tannins, residual sugar, alcohol content, etc.). Eigendecomposition reveals that the most important axis of variation might be "red vs. white" (this single dimension explains the most variation). The second axis might be "sweet vs. dry." The third might be "old world vs. new world." These principal components emerge from the data — they are not imposed by the analyst — and they often correspond to meaningful, interpretable distinctions.

For narrative analysis, eigendecomposition of the kernel matrix reveals the principal dimensions along which narratives vary. These dimensions are not predetermined — they emerge from the corpus itself and often correspond to categories that literary scholars have identified through decades of qualitative analysis.

19.5 Eigendecomposition of the 28,000-Book Corpus

When we decompose the kernel matrix of CodexSpace, the following principal components emerge:

First eigenvector (lambda_1 = 0.42): Fiction vs. Non-fiction The single most important dimension of variation in the literary corpus is the distinction between fictional and non-fictional texts. This is not surprising — these two broad categories differ in narrative structure, vocabulary, rhetorical strategy, and virtually every other dimension. The first eigenvector assigns positive values to fiction and negative values to non-fiction (or vice versa — the sign is arbitrary; only the axis matters).

Second eigenvector (lambda_2 = 0.28): Formal vs. Informal Register The second most important dimension is the formality of the prose. Highly formal texts (academic treatises, legal documents, philosophical works) cluster at one end; informal texts (personal letters, adventure stories, humor) cluster at the other. This dimension cuts across the fiction/non-fiction divide — formal fiction (Henry James) is closer to formal non-fiction (John Stuart Mill) than to informal fiction (Mark Twain).

Third eigenvector (lambda_3 = 0.19): Historical Period The third dimension captures the era of composition. Pre-1800 texts cluster at one end; late 19th century texts at the other. This reflects the cumulative evolution of English prose style, vocabulary, and thematic concerns over two centuries.

Fourth eigenvector (lambda_4 = 0.12): Emotional Intensity The fourth dimension captures the emotional temperature of the text. Passionate, emotionally intense works (Bronte, Dostoevsky, Poe) cluster at one end; cool, analytical works (Mill, Locke, Darwin) cluster at the other.

Fifth and beyond: Subsequent eigenvectors capture increasingly fine-grained distinctions — genre subdivisions, national origin, audience level, etc. Each contributes less variance, and by the 20th eigenvector, individual components explain less than 1% of the variance.

19.6 The Spectral Gap and Narrative Diversity

The ratio between consecutive eigenvalues tells us about the structure of diversity in a corpus:

```
spectral_gap(k) = lambda_k / lambda_{k+1}
```

A large spectral gap between lambda_1 and lambda_2 means one dimension dominates — the corpus has one overwhelmingly important axis of variation. A

small spectral gap means multiple dimensions are roughly equally important — the corpus has rich, multi-dimensional diversity.

Worked Example: Comparing Publisher Catalogs

Catalog	lambda_1 / lambda_2	Interpretation
Publisher A (romance-only)	8.5	One dimension dominates (within-romance variation)
Publisher B (general fiction)	2.1	Several important dimensions (genre, tone, period)
Publisher C (academic press)	1.4	Multiple equally important dimensions (discipline, methodology, audience)
CodexSpace (all PG19)	1.5	Rich multidimensional diversity

Publisher A's large spectral gap reveals that its catalog, while containing many books, varies primarily along a single dimension — perhaps intensity of romance, or contemporary vs. historical settings. A strategic advisor might recommend diversifying into adjacent genres to reduce this one-dimensionality and capture a broader audience.

Publisher C's small spectral gap indicates a well-diversified catalog where no single dimension of variation dominates — many fields, many approaches, many audience levels are represented roughly equally.

19.7 Mercer's Decomposition: The Periodic Table of Narrative

Mercer's theorem provides the most profound interpretation of eigendecomposition. It states that any continuous positive semi-definite kernel can be decomposed:

```
K(N_1, N_2) = sum_{k=1}^{infinity} lambda_k * e_k(N_1) * e_k(N_2)
```

where lambda_k are the eigenvalues and e_k are the eigenfunctions. Each term in the sum is one "narrative eigenmode" — an independent dimension of variation.

This is analogous to Fourier decomposition of a sound wave. A complex sound is decomposed into pure tones (sine waves) at different frequencies. Similarly, the complex relationship between two narratives is decomposed into independent axes of comparison: fiction-vs-nonfiction, formal-vs-informal, historical-vs-modern, and so on. Each axis contributes independently, weighted by its eigenvalue (importance).

The practical consequence: **truncating after k terms gives the optimal k-dimensional approximation.** If you can only compare books along 5 dimensions, the best 5 dimensions are the first 5 eigenvectors. If you can afford 20 dimensions, the first 20 eigenvectors are optimal. No other choice of k dimensions captures as much of the total variation.

19.8 Spectral Clustering: Finding Natural Groups

Spectral clustering uses the eigenvectors to partition the corpus into groups. The key insight: in the space defined by the first few eigenvectors, natural clusters become visible that may be invisible in the full 768-dimensional space.

Worked Example: Spectral Clustering of Shakespeare's Plays

Using the first 3 eigenvectors of the play-to-play kernel matrix:

Cluster	Plays	Eigenspace Signature
Tragedies	Hamlet, Macbeth, Othello, Lear, Antony & Cleopatra	High on e_1 (seriousness), low on e_2 (social comedy), high on e_3 (death)
Comedies	MSND, Twelfth Night, As You Like It, Much Ado	Low on e_1, high on e_2, low on e_3
Histories	Henry IV, Henry V, Richard III, Richard II	Medium on e_1, low on e_2, medium on e_3
Problem plays	Measure for Measure, Troilus, All's Well	Medium on all three — they resist clustering

The "problem plays" earn their name mathematically: they sit between clusters, refusing to join any group cleanly. This is precisely why scholars call them "problem plays" — they defy the standard tragedy/comedy/history classification. The spectral analysis confirms the scholarly intuition with mathematical precision.

19.9 Applications of Spectral Theory

1. Automatic genre detection. Spectral clustering of a publisher's catalog automatically identifies genre groupings, even when genre labels are missing or inconsistent. This is valuable for backlist management and metadata correction.

2. Diversity analysis. The eigenvalue spectrum of a catalog reveals its diversity profile. A catalog that wants to claim "wide-ranging" should have a small spectral gap (many equally important dimensions of variation).

3. Trend detection. By tracking how eigenvectors change over time (analyzing books decade by decade), we can detect shifts in the principal dimensions of literary variation. The emergence of a new genre, for example, would appear as a new significant eigenvector that was previously negligible.

4. Dimensional reduction for visualization. The first 2-3 eigenvectors provide the best possible 2D or 3D visualization of the corpus — the projection that preserves the most structure. This is exactly what we use for the 3D visualizations in the Multiverse app.

19.10 SAX Motif Discovery: Literary DNA in the Time Domain

Spectral analysis decomposes narrative structure in the *frequency domain* — identifying periodic patterns, dominant modes, and their relative strengths. But there is a complementary approach that operates in the *time domain*: Symbolic Aggregate approXimation (SAX), which discretizes novelty curves into symbolic sequences and then discovers recurring motifs across thousands of books. Where spectral methods reveal *what frequencies are present*, SAX motif discovery reveals *what temporal patterns recur* — the sequential DNA of narrative structure.

From Novelty Curves to Symbolic Sequences

The SAX pipeline transforms continuous novelty curves into discrete symbolic sequences through two steps:

Step 1: Piecewise Aggregate Approximation (PAA-16). Each book's novelty curve — regardless of its original length — is normalized to exactly 16 segments. Each segment represents approximately 6.25% of the book's total length. The value of each segment is the mean novelty score over that portion. This reduces a curve with thousands of data points to a 16-element vector while preserving the overall shape.

Step 2: SAX-5 Discretization. Each of the 16 PAA values is mapped to one of 5 symbols {a, b, c, d, e} using Gaussian breakpoints. The breakpoints are set so that each symbol has equal probability under a standard normal distribution: - **a** = very low novelty (below -0.84σ) - **b** = low novelty (-0.84σ to -0.25σ) - **c** = medium novelty (-0.25σ to +0.25σ) - **d** = high novelty (+0.25σ to +0.84σ) - **e** = very high novelty (above +0.84σ)

The result: every book in the corpus becomes a 16-character string over a 5-letter alphabet. *Moby Dick* might become `cbcddeeccbbccdde`. *Pride and Prejudice* might become `ccbccddcccbbcccd`. These strings are the symbolic fingerprints of narrative novelty structure.

Motif Extraction Across 80,000+ Books

With symbolic representations in hand, we extract *motifs* — recurring subsequences that appear significantly more often than chance would predict. We analyze both 4-gram motifs (capturing local patterns spanning ~25% of a book) and 6-gram motifs (capturing broader patterns spanning ~37.5%).

The analysis was conducted across two major corpora: PG-19 (28,044 pre-1919 books) and Books3 (a large contemporary corpus), enabling cross-century comparison.

Key Finding 1: Steady-state novelty dominates. The motif `cccc` (four consecutive segments of medium novelty) is the most common pattern in both corpora. This means the single most prevalent narrative strategy across two centuries is *maintaining a consistent level of novelty* — neither surprising nor predictable, but steady. This is the literary equivalent of a comfortable cruising speed.

Key Finding 2: Genre-specific motif fingerprints exist. Different genres show statistically distinct motif frequency distributions. Fiction favors patterns with dramatic novelty shifts (`cdec`, `bcde`), while non-fiction favors more uniform patterns (`cccc`, `cccd`). The motif fingerprint of a genre is as distinctive as a musical genre's rhythmic signature.

Key Finding 3: Poetry shows the most dramatic cross-century transformation. Of all genres, poetry underwent the most radical structural change between the 19th and 20th centuries: - **Formal verse** (pre-1919): Circuitousness score of 69.4 — relatively direct novelty trajectories constrained by meter and rhyme - **Free verse** (post-1919): Circuitousness score of 481.4 — wildly wandering novelty paths freed from formal constraints

This 7× increase in circuitousness quantifies the modernist revolution in poetry more precisely than any previous metric. The transition from formal to free verse was not merely a change in surface features (rhyme, meter) but a fundamental restructuring of how novelty unfolds through a poem.

Key Finding 4: Shared motifs constitute "literary DNA." Despite massive changes in style, technology, and culture over two centuries, a core set of motifs appears in both corpora at similar frequencies. These shared patterns represent deep structural invariants of narrative — the literary DNA that persists across eras. The top-10 shared motifs account for over 40% of all motif occurrences in both corpora.

Top-20 Motif Comparison: Two Centuries of Narrative Structure

Rank	PG-19 Motif	PG-19 Freq	Books3 Motif	Books3 Freq	Shared?
1	cccc	12.3%	cccc	11.8%	Yes
2	cccd	4.7%	cccd	4.2%	Yes
3	dccc	4.5%	cdcc	3.9%	—

Rank	PG-19 Motif	PG-19 Freq	Books3 Motif	Books3 Freq	Shared?
4	ccdc	3.8%	dccc	3.7%	Yes
5	cdcc	3.6%	ccdc	3.5%	Yes
6	cccb	3.2%	bccc	3.1%	—
7	bccc	3.0%	cccb	2.9%	Yes
8	ccbc	2.8%	ccbc	2.7%	Yes
9	cbcc	2.5%	cbcc	2.4%	Yes
10	cdcd	2.1%	cdcd	2.2%	Yes
11	dcdc	1.9%	dcdc	2.0%	Yes
12	cddc	1.8%	cddc	1.9%	Yes
13	ddcc	1.6%	ccdd	1.7%	—
14	ccdd	1.5%	ddcc	1.6%	Yes
15	bccd	1.4%	dccd	1.5%	—
16	dccd	1.3%	bccd	1.4%	Yes
17	cdce	1.2%	cdce	1.3%	Yes
18	ecdc	1.1%	decc	1.2%	—
19	cbcd	1.0%	cbcd	1.1%	Yes
20	dccb	0.9%	cdcb	1.0%	—

Note: 14 of the top 20 motifs are shared between corpora, confirming the "literary DNA" hypothesis. Motifs involving extreme symbols (a, e) are rare in both corpora, suggesting that sustained very-low or very-high novelty is an uncommon narrative strategy.

Connection to Spectral Analysis

SAX motif discovery and spectral analysis are complementary decompositions of the same underlying novelty curves:

- **Spectral analysis** answers: "What *frequencies* of novelty variation are present?" It reveals periodic structure — cycles of tension and release, regular oscillations between familiar and novel.
- **SAX motif discovery** answers: "What *sequential patterns* of novelty recur?" It reveals temporal motifs — specific progressions from one novelty level to another that appear across many books.

A book with a dominant low-frequency spectral component (slow oscillation between high and low novelty) would produce SAX motifs like `ccddddcccc` — long runs of consistent symbols. A book with dominant high-frequency components (rapid alternation) would produce motifs like `cdcdcdcd`. The spectral view and the SAX view are two windows onto the same narrative structure.

Together, they provide a complete characterization of novelty dynamics: spectral analysis captures the *frequency content*, SAX captures the *sequential grammar*, and

both operate on the same RKHS-embedded novelty curves that form the foundation of this entire framework.

Bottom Line

Spectral analysis reveals structure you didn't know was there. When applied to a publisher's catalog, it might reveal that all books cluster along 3-4 axes (topic, audience, format, tone) — suggesting the catalog lacks diversity along other dimensions. When applied to a competitor's catalog, it reveals their strategic position. SAX motif discovery complements this by revealing the temporal DNA of narrative structure — the recurring patterns of novelty that persist across centuries and define genres at a structural level. Together, these tools provide frequency-domain and time-domain views of the same underlying narrative dynamics.

CHAPTER 20

Open Problems and Conjectures



Figure 20.1: Six open conjectures: unsolved problems at the frontier of narrative mathematics

What's In It for You

Seven open problems identify the frontier of this field. Solving any one of them would significantly advance the science and create competitive advantage. These are opportunities for research partnerships, academic publications, and product innovation. The newest problem — the Tversky Challenge — addresses a fundamental tension between mathematical requirements and psychological reality in similarity measurement.

20.1 The Nine Open Problems

1. The Narrative Manifold Conjecture: Publishable narratives form a smooth, connected manifold of dimension ~100. If true, gradient-based optimization could systematically improve narrative quality.

2. The Genre Speciation Conjecture: Genre boundaries correspond to high-curvature ridges in narrative space. Cross-genre works sit on saddle points, explaining their instability in reader perception.

3. The Universal Story Conjecture (Formal Vonnegut): The emotional arc kernel has a sharp eigenvalue drop after K ~ 6-20 archetypal shapes, formally confirming Vonnegut's "shapes of stories" hypothesis.

4. The Adaptation Fidelity Bound: Adaptation fidelity is bounded by the narrative energy in the discarded principal components. This would give a theoretical maximum fidelity for any given compression ratio.

5. The Irony Detection Theorem: Irony is detectable as the semantic distance between surface reading and deep reading, normalized by text magnitude.

6. The Kernel Composition Conjecture: Natural narrative transforms induce a valid kernel on adaptation strategies themselves, enabling optimization over transformation pipelines.

7. The Symmetry-Asymmetry Tension (The Tversky Challenge): RKHS kernels must be symmetric $K(x,y) = K(y,x)$, but human similarity judgments are fundamentally asymmetric. This tension has practical implications for user-facing similarity displays and influence analysis.

20.2 The Nature of These Conjectures

Each of the six conjectures below represents a precise mathematical statement about narrative structure that, if proven true, would enable specific new capabilities. They are not vague aspirations — they are testable hypotheses with clear implications. Some may be provable with current mathematical tools; others may require new theoretical frameworks. All are grounded in empirical observations from our work with CodexSpace.

20.3 Conjecture 1: The Narrative Manifold Conjecture (Detailed)

Statement: The set of publishable narratives, embedded in RKHS, forms a smooth, connected Riemannian manifold of intrinsic dimension approximately 100 (plus or minus 20).

Why we believe it: Three pieces of evidence. First, PCA on our 28,000-book corpus shows that 100 components capture 85% of variance — suggesting the effective dimension is approximately 100. Second, interpolation between coherent narratives usually produces points near other coherent narratives — suggesting

the narrative set is connected. Third, small perturbations of coherent narratives produce points near other coherent narratives — suggesting smoothness.

What it would take to prove: A rigorous proof would require: (a) a formal definition of "publishable narrative" (possibly in terms of a quality threshold on some coherence metric), (b) demonstrating that this set satisfies the smoothness conditions for a manifold (local homeomorphism to R^d), and (c) estimating the intrinsic dimension using methods like maximum likelihood dimension estimation (Levina & Bickel, 2004) or persistent homology.

What it would enable: If the manifold conjecture is true, gradient-based optimization could systematically improve narrative quality. Starting from a draft manuscript, compute its position on the manifold, compute the gradient of a quality function, and follow the gradient to produce a better manuscript. This would be the mathematical analog of editorial revision — but automated, continuous, and guaranteed to improve quality at each step.

Potential obstacles: The set of "publishable narratives" may not be smooth — it may have corners, cusps, or disconnected components corresponding to distinct genres that cannot be continuously deformed into each other. Also, the dimension estimate of ~100 is based on linear PCA, which may underestimate the true dimension if the manifold is highly curved.

20.4 Conjecture 2: The Genre Speciation Conjecture (Detailed)

Statement: Genre boundaries in narrative space correspond to ridges of high Gaussian curvature on the narrative manifold. Cross-genre works occupy saddle points on these ridges, explaining their instability in reader perception.

Why we believe it: Empirical observation. When we move smoothly between two genres in embedding space (e.g., gradually transforming a romance novel toward thriller conventions), we observe a "resistance" at certain points — regions where small changes in the embedding produce large changes in perceived genre. These are the ridges. Works that sit on ridges (e.g., romantic thrillers) are perceived differently by different readers — some classify them as romance, others as thriller. This is the instability predicted by the conjecture.

What it would take to prove: Compute the Gaussian curvature of the narrative manifold at a dense grid of points. Show that curvature peaks correspond to perceived genre boundaries (as measured by human genre classification). Show that works with inconsistent genre classification sit near curvature maxima.

What it would enable: Precision genre targeting. A publisher could specify "place this book exactly 0.3 units from the romance-thriller ridge on the romance side" — producing a romance with thriller elements that is clearly classifiable as romance by readers. Currently, genre positioning is done by intuition and market testing. The curvature map would make it a design parameter.

Related work: This conjecture is related to the "decision boundary" concept in machine learning. Genre boundaries in narrative space may function like decision

boundaries in classification — regions where the classifier (human reader) is maximally uncertain.

20.5 Conjecture 3: The Universal Story Conjecture — Formal Vonnegut (Detailed)

Statement: The eigenvalue spectrum of the emotional arc kernel exhibits a sharp drop after the first K eigenmodes (K approximately 6-20), formally confirming Kurt Vonnegut's hypothesis that stories come in a small number of archetypal shapes.

Background: In an unpublished master's thesis (later popularized in a famous lecture), Kurt Vonnegut proposed that the emotional arcs of stories come in a small number of shapes: "Man in Hole" (fortune falls then rises), "Boy Meets Girl" (fortune rises, falls, rises), "Cinderella" (rise, fall, greater rise), and a handful of others. Reagan et al. (2016) provided computational support for 6 basic arc shapes using sentiment analysis.

Our conjecture goes further: Not just that 6 shapes are common, but that the emotional arc kernel has a *mathematical* property (spectral gap) that makes 6-20 shapes fundamental. The eigenvalue spectrum drops sharply after K modes, meaning that the first K shapes capture nearly all the variation in emotional arcs. Additional shapes exist but contribute negligibly.

What it would take to prove: Compute the emotional arc kernel for a large corpus (thousands of narratives). Perform eigendecomposition. Measure the spectral gap after each eigenvalue. If the gap between lambda_K and lambda_{K+1} is significantly larger than subsequent gaps, the conjecture is supported. The value of K and the steepness of the gap would be the key results.

What it would enable: Emotional arc prediction. Given the first half of a story, predict the most likely arc shape for the second half. This has applications in: (a) manuscript evaluation (does this story follow a recognizable and commercially successful arc shape?), (b) recommendation (if you liked stories with this arc shape, try these), (c) generation (create a story with a specified arc shape).

20.6 Conjecture 4: The Adaptation Fidelity Bound (Detailed)

Statement: For any adaptation of a narrative from d dimensions to d' < d dimensions, the maximum achievable fidelity is bounded by the ratio of energy in the first d' principal components to the total energy:

```
max_fidelity(d') = sum_{k=1}^{d'} lambda_k / sum_{k=1}^{infinity} lambda_k
```

Why it matters: This gives a *theoretical upper limit* on how faithful an adaptation can be at any given level of compression. A 2-hour film adaptation of a 500-page

novel necessarily compresses narrative dimensionality. The bound tells you the maximum possible fidelity of that compression.

Practical implication: If the first 20 narrative dimensions capture 75% of the energy, then no film adaptation can preserve more than 75% of the novel's narrative content — no matter how skillful the adaptation. The remaining 25% is mathematically inaccessible at that compression level. This explains why every reader finds something missing from even the best film adaptations.

What it would take to prove: Establish that narrative adaptation can be modeled as a linear projection (or bounded non-linear projection) in the RKHS. Apply the Eckart-Young theorem (which establishes that truncated SVD is the optimal low-rank approximation) to derive the bound.

20.7 Conjecture 5: The Irony Detection Theorem (Detailed)

Statement: Irony in a text is detectable as the normalized semantic distance between the surface reading (literal interpretation) and the deep reading (intended interpretation):

```
irony_score(T) = d(surface_embedding(T), deep_embedding(T)) / ||T||
```

Why we believe it: Irony is, by definition, a gap between what is said and what is meant. If we can compute embeddings for both the surface meaning and the intended meaning, their distance measures the gap — which is the irony. Preliminary experiments with "The Road Not Taken" (known to be ironic) and "Stopping by Woods on a Snowy Evening" (known to be non-ironic) show scores of >0.5 and <0.1 respectively.

The challenge: Computing the "deep reading" embedding is non-trivial. It requires a model that understands pragmatic context, cultural convention, and authorial intent — all of which go beyond surface semantics. Current embedding models capture surface meaning well but deep meaning only partially.

What it would enable: Automated irony detection would be transformative for: (a) literary analysis (identifying ironic texts that have been misread for centuries), (b) sentiment analysis (ironic text has opposite sentiment to its surface reading), (c) content moderation (sarcasm detection), (d) machine translation (irony must be preserved, not literally translated).

20.8 Conjecture 6: The Kernel Composition Conjecture (Detailed)

Statement: If K_1 is a valid narrative kernel and T_1, T_2 are valid narrative operators, then:

```
K_adaptation(T_1, T_2) = K_1(T_1(N), T_2(N))
```

defines a valid (PSD) kernel on the space of operators. This would mean that operators themselves can be compared, clustered, and optimized using kernel methods.

Why it matters: Currently, operators are tools we apply to content. If operators themselves live in a kernel space, we can apply *meta-operators* to operators — optimizing transformation pipelines, finding the "nearest" operator to a desired transformation, and clustering operators by their effects.

Practical implication: An editor wants to transform manuscript A into something like published book B. Instead of manually selecting and sequencing operators, they query the operator kernel space: "Find the operator sequence T such that T(A) is closest to B." The operator kernel makes this optimization well-defined.

20.9 Problem 7: The Symmetry-Asymmetry Tension (The Tversky Challenge)

Statement: The mathematical requirement that valid RKHS kernels be symmetric ($K(x,y) = K(y,x)$) conflicts with decades of psychological research showing that human similarity judgments are fundamentally asymmetric.

The Psychological Evidence

In 1977, Amos Tversky published a landmark paper demonstrating that human similarity judgments violate the core properties of metric spaces. His findings have been replicated across domains and cultures:

1. **Asymmetry.** "North Korea is like China" feels different from "China is like North Korea." The prominent, well-known object becomes the referent against which the less familiar object is compared. In narrative terms: "Billy Budd is like Moby Dick" carries different cognitive weight than "Moby Dick is like Billy Budd."

2. **Triangle inequality violations.** If readers judge that A is similar to B, and B is similar to C, they do not necessarily judge A similar to C. This violates a fundamental axiom of metric spaces.

3. **Context dependence.** Adding a third option can change the perceived similarity between the first two — the "decoy effect" familiar from marketing research.

Tversky proposed a contrast model to capture these phenomena:

```
S(a,b) = θf(A∩B) − αf(A−B) − βf(B−A)
```

When $\alpha \neq \beta$, similarity becomes directional. The subject's distinctive features (A-B) weight differently than the referent's distinctive features (B-A). The ratio α/β captures the asymmetry.

The Mathematical Tension

Our entire RKHS framework rests on symmetric positive semi-definite kernels. This is not a convenience — it is a mathematical necessity:

- The **reproducing property** ($f(x) = \langle f, K(x,\cdot)\rangle$) requires symmetry
- **Mercer's theorem** establishes that valid kernels correspond to PSD matrices
- The **kernel trick** — computing in infinite dimensions using only inner products — depends on $K(x,y) = K(y,x)$
- **Distance metrics** derived from kernels ($d(x,y) = \sqrt{(K(x,x) - 2K(x,y) + K(y,y))}$) require symmetry to satisfy the triangle inequality

If we abandon symmetry, we lose the mathematical foundation. Our clustering algorithms may not converge. Our optimization problems may have no solution. Our geometric reasoning becomes invalid.

Where This Matters

For internal computation — clustering, retrieval, dimensionality reduction — symmetry is appropriate. These are mathematical operations that require well-behaved spaces.

But for user-facing applications, the asymmetry becomes significant:

- **"Similar books" recommendations.** When a reader asks "What's like Moby Dick?", they expect books that share Moby Dick's distinctive features. When a rare book's page asks "What is this like?", readers expect canonical references. These are different questions with different answers.

- **Narrative influence analysis.** "War and Peace influenced Anna Karenina" is not the same statement as "Anna Karenina influenced War and Peace." Influence has direction. A symmetric kernel erases this.

- **Decision graph analysis.** In our Nimitz RKHS work on 607 nodes of WWII Pacific command decisions, the direction of influence matters. Decision A constraining Decision B is not the same as B constraining A.

- **Story operator transformations.** When we apply an operator that moves a narrative toward a different genre, the starting point and ending point are not symmetrically related. The transformation has direction.

Alternative Implementations

Recent work by Doumbouya, Jurafsky & Manning at Stanford (arxiv 2506.11035) has made Tversky similarity differentiable and learnable within neural network architectures. This opens several paths forward:

Option 1: Symmetric backbone, asymmetric presentation layer. Use symmetric RKHS kernels for all internal computation — clustering, retrieval, dimensionality reduction. Add an asymmetric adjustment layer for user-facing similarity displays:

```
S_display(a,b) = K(a,b) * asymmetry_weight(a,b)
```

where asymmetry_weight encodes the prominence differential (is a more canonical than b?). This preserves mathematical validity while improving psychological plausibility.

Option 2: Directed and undirected graphs. Maintain two parallel representations: - Undirected similarity graph using symmetric K(a,b) for mathematical operations - Directed influence graph using asymmetric Tversky-style weights for causal/influence analysis

Queries about "similarity" use the undirected graph. Queries about "influence" or "derivation" use the directed graph.

Option 3: Asymmetric kernel approximations. Define an asymmetric similarity function and find the closest PSD kernel that approximates it:

```
K_approx = argmin_K ||K - S_tversky||² subject to K being PSD
```

This involves projecting the asymmetric matrix onto the PSD cone — a convex optimization problem with known solutions. The approximation error measures how much asymmetry we sacrifice for mathematical validity.

Option 4: Neural Tversky embeddings. Following the Stanford work, train a neural network that learns asymmetric similarity end-to-end, using Tversky's contrast model as the similarity function. The network learns to weight common features (θ), subject-specific features (α), and referent-specific features (β) directly from data.

Their results are promising: 24.7% accuracy improvement on image classification and 7.5% perplexity reduction on language modeling compared to cosine similarity baselines.

Practical Recommendation

For Story Operators, we recommend Option 1 as the immediate path forward:

1. **Compute all internal operations using symmetric cosine kernels.** This preserves the mathematical guarantees we need for clustering, retrieval, and operator composition.

2. **Add a prominence weighting for user-facing displays.** When showing "books similar to X," weight results by the prominence ratio: books that are less canonical than X should be ranked higher than books that are more canonical, all else equal.

3. **Maintain separate directed influence relationships.** Do not try to capture influence within the similarity kernel. Instead, compute influence edges separately using citation networks, publication dates, and explicit derivation relationships.

4. **Experiment with neural Tversky for future versions.** The Stanford results suggest significant improvements are possible. Once the technique matures, it may warrant a deeper integration.

Open Questions

- Can we define a "narrative prominence" metric that captures canonicity in a principled way?
- How much asymmetry exists in narrative similarity judgments specifically (vs. the general cognitive findings)?
- Does the asymmetry vary by domain (fiction vs. non-fiction, poetry vs. prose)?
- Can we train a Tversky-style network specifically on narrative similarity judgments?

The Broader Lesson

This tension between psychological grounding and mathematical requirement is not unique to similarity measurement. Throughout computational humanities, we face choices between:

- Models that match human cognition but resist mathematical analysis
- Models that enable rigorous mathematics but simplify away psychological reality

The RKHS framework's power comes from its mathematical rigor. We should not abandon that rigor lightly. But we should also not mistake mathematical convenience for psychological truth. The path forward is hybrid architectures that preserve rigor where it matters (internal computation) while acknowledging asymmetry where it is psychologically salient (user-facing displays).

20.10 Research Strategy

These nine open problems are ordered by estimated difficulty:

Problem	Estimated Difficulty	Most Promising Approach
5 (Irony Detection)	Moderate	Empirical testing with known-ironic corpus
3 (Universal Story)	Moderate	Large-scale emotional arc eigendecomposition
7 (Tversky Challenge)	Moderate	Hybrid architecture with asymmetric display layer

Problem	Estimated Difficulty	Most Promising Approach
8 (Persistent Homology)	Moderate	Apply ripser/gudhi to BookNLP character networks
4 (Fidelity Bound)	Moderate-Hard	Apply Eckart-Young to narrative compression
6 (Kernel Composition)	Hard	Extend PSD closure properties to operator spaces
1 (Narrative Manifold)	Hard	Intrinsic dimension estimation + smoothness testing
9 (Category Theory)	Hard	Formalize functors and test naturality conditions
2 (Genre Speciation)	Very Hard	Requires both manifold geometry and genre boundary mapping

We recommend pursuing Conjectures 5 and 3 first, as they are most tractable and have the most immediate practical applications. Problem 7 (the Tversky Challenge) is both theoretically important and practically actionable — the hybrid architecture approach can be implemented immediately while deeper solutions are researched. Problem 8 (Persistent Homology) is immediately tractable with existing computational tools and could yield results quickly. Problem 9 (Category Theory) provides organizational clarity but requires the most abstract mathematical sophistication. Conjecture 1 is the most foundational — if true, it undergirds all the others — but also the hardest to prove rigorously.

20.11 Problem 8: Persistent Homology of Character Networks

Algebraic topology offers tools for detecting structural features of narrative that neither spectral analysis nor kernel methods can capture directly. The key idea is *persistent homology* — tracking how topological features (connected components, loops, voids) appear and disappear as we vary a threshold parameter.

Setup. Given a narrative, construct a *character interaction graph* where vertices are characters and edge weights reflect interaction strength (co-occurrence frequency, dialogue exchanges, or emotional impact). Now consider the *filtration*: start with only the strongest edges and progressively add weaker ones. At each threshold, compute the *Betti numbers*:

- β_0 = number of connected components (character communities)
- β_1 = number of independent loops (circular relationship structures)

- β_2 = number of voids (higher-dimensional cavities in the relationship structure)

Persistence diagrams record when each topological feature is "born" (first appears) and when it "dies" (merges with another feature). Long-lived features represent robust structural elements of the narrative; short-lived features are noise.

Conjecture. The persistence diagram of a novel's character network is a genre invariant — novels in the same genre have statistically similar persistence diagrams (under an appropriate metric like the bottleneck distance or Wasserstein distance), while novels in different genres have significantly different diagrams.

Narrative descriptors from Betti numbers: - A novel with $\beta_1 = 1$ throughout most of the filtration has a tightly connected cast (e.g., *Pride and Prejudice* — everyone is connected through the Bennet family) - A novel with $\beta_1 > 1$ persisting has genuinely separate storylines (e.g., *War and Peace* — the Bolkonsky, Bezukhov, and Rostov families form distinct components that only gradually merge) - A novel with high β_1 has many "love triangles" or circular dependency structures - A novel with non-trivial β_2 has complex higher-order relationship structures beyond pairwise interactions

Stability theorem. A crucial property for practical use: small perturbations in the character network (adding a minor character, adjusting weights) produce small changes in the persistence diagram. This means the topological features are robust descriptors, not artifacts of arbitrary modeling choices.

This problem is tractable with existing tools (the `ripser` and `gudhi` Python libraries compute persistent homology efficiently) but requires careful definition of how to construct the filtration from narrative data.

20.12 Problem 9: Category-Theoretic Perspective

Category theory provides a language for describing *structure-preserving transformations* that complements the operator-algebraic view developed in Chapters 10 and 16. Where operator algebra asks "what algebraic properties do story transformations have?", category theory asks "what is the most general framework for understanding how narratives relate to each other?"

Definition: Category Narr. Define a category where: - **Objects** are narratives (represented as points in the RKHS) - **Morphisms** are story operators (transformations between narratives) - **Composition** is operator composition (applying one transformation after another) - **Identity** is the identity operator (leaving a narrative unchanged)

The category axioms (associativity of composition, existence of identity) are automatically satisfied because story operators compose associatively (Theorem in Ch 16) and the identity operator exists.

The Genre Functor. Define a functor G: Narr → Genre that maps each narrative to its genre classification and each story operator to the induced genre

transformation. This functor captures the observation that operators like T_genre explicitly change genre, while others (T_perspective, T_compress) preserve genre. The kernel of this functor — operators that map to the identity in Genre — defines *genre-preserving transformations*.

The Embedding Functor. Define a functor E: Narr → Hilbert that maps each narrative to its RKHS embedding and each story operator to the corresponding bounded linear operator on the Hilbert space. This functor is the mathematical formalization of what the entire RKHS framework does: it translates narrative concepts into mathematical objects while preserving their structural relationships.

Natural transformations as systematic retellings. A natural transformation η: F ⇒ G between two functors is a systematic way of converting one type of narrative mapping into another. The key property — the *naturality condition* — requires that the conversion commutes with all morphisms.

Example: the modernization transformation. Consider two functors: P (period-faithful adaptation) and M (modernized adaptation). A natural transformation η: P ⇒ M that systematically converts period adaptations to modern ones must satisfy: modernizing a sequel equals sequelizing a modernization. When this condition holds, the transformation is "natural" — it works uniformly regardless of which narrative it is applied to.

Naturality failure as a diagnostic. Not all transformations are natural, and *failures of naturality* are informative. Cross-cultural translation is a classic example: translating a Japanese novel into English and then adapting it for film does not generally produce the same result as adapting the Japanese novel for film and then subtitling/dubbing. The failure of naturality here reflects genuine cultural incommensurabilities that resist systematic resolution.

The categorical perspective does not replace the operator algebra or manifold geometry of earlier chapters — it provides a higher-level organizational framework that clarifies *why* certain operator compositions work smoothly (they respect functorial structure) while others produce unexpected results (they violate naturality conditions).

20.13 References for Chapter 20

- Tversky, A. (1977). Features of similarity. *Psychological Review*, 84(4), 327-352.
- Doumbouya, M., Jurafsky, D., & Manning, C. D. (2025). Tversky Neural Networks. *arXiv:2506.11035*.
- Levina, E., & Bickel, P. J. (2004). Maximum likelihood estimation of intrinsic dimension. *Advances in Neural Information Processing Systems*, 17.
- Reagan, A. J., et al. (2016). The emotional arcs of stories are dominated by six basic shapes. *EPJ Data Science*, 5(1), 31.
- Edelsbrunner, H., & Harer, J. L. (2010). *Computational Topology: An Introduction*. American Mathematical Society.

- Mac Lane, S. (1998). *Categories for the Working Mathematician* (2nd ed.). Springer.

Bottom Line

These nine open problems (the original seven plus persistent homology and category theory) represent the next 5-10 years of research opportunity. Organizations that invest in solving them will gain both academic prestige and practical advantage. Each conjecture, if proven, enables specific products: the Narrative Manifold enables quality optimization; the Genre Speciation enables precision genre targeting; the Universal Story enables emotional arc prediction. Problem 7 (the Tversky Challenge) is particularly actionable — a hybrid architecture can be implemented immediately to improve user-facing similarity displays while preserving mathematical rigor internally.

Part VII

Data Infrastructure — The Engine Room

CHAPTER 2

The RKHS File Format



Figure 21.1: The .rkhs file format: a universal interchange standard for semantic content

What's In It for You

A standardized JSON file format (.rkhs or .rkhs.json) stores universes — collections of embedded content with relationships and metadata. The format is human-readable, tool-compatible, and supports bidirectional navigation. This chapter is your specification reference.

21.1 File Structure

```
{
  "id": "unique-universe-id",
  "name": "Universe Display Name",
  "description": "Brief description",
  "dimension": 768,
  "kernel_type": "cosine",
  "kernel_params": {"gamma": 1.0},
  "version": "1.0",
  "created_at": "2026-01-27T00:00:00Z",
  "modified_at": "2026-01-27T00:00:00Z",
  "domain_type": "literature",
  "nodes": {
    "node-id-1": {
      "id": "node-id-1",
      "position": [x, y, z],
      "content": {
        "title": "Node Title",
        "description": "Full description",
        "properties": {}
      },
      "kernel_features": [768 numbers],
      "timestamp": "2026-01-27T00:00:00Z",
      "parent_ids": ["parent-1", "parent-2"],
      "children_ids": ["child-1", "child-2"]
    }
  },
  "edges": [
    {"source": "node-1", "target": "node-2", "weight": 0.85, "type": "similarity"}
  ],
  "metadata": {}
}
```

21.2 Critical Requirement: Bidirectional Relationships

The #1 cause of display errors: Parent-child relationships MUST be bidirectional. If node A lists node B as a child, node B MUST list node A as a parent.

21.3 Viewers

Two viewers exist: - **Streamlit** (Python, web-based): `/hilberts/platform/multiverse_viewer.` - **Multiverse** (Swift, native Mac/iOS): `/xcode_projects/multiverse/`

21.4 Why a Standard File Format Matters

Every successful technology ecosystem has a standard file format at its center. JPEG for images. MP3 for music. PDF for documents. HTML for web pages. These formats succeed because they are open, well-specified, and supported by a diverse ecosystem of tools.

The `.rkhs` file format serves the same function for Story Operator content. It is the container that makes mathematical content portable, shareable, and tool-independent. Without a standard format, every tool in the ecosystem would need to understand every other tool's internal representation. With a standard format, any tool that reads `.rkhs` files can participate in the ecosystem, and any tool that writes them can contribute content.

21.5 Design Principles

The `.rkhs` format was designed with five principles:

1. Human-readable. The format is JSON — plain text that can be opened, read, and edited in any text editor. This was a deliberate choice. Binary formats are more compact, but JSON ensures that anyone can inspect, debug, and modify `.rkhs` files without specialized software. When debugging a display error, the ability to open the file in a text editor and check that bidirectional relationships are maintained is invaluable.

2. Self-describing. Every `.rkhs` file contains all the information needed to interpret its contents: the dimension of the embedding space, the kernel type, the domain type, and the schema version. No external metadata is required. A `.rkhs` file found years from now, without documentation, would still be interpretable.

3. Tool-compatible. Every programming language has JSON support. Python, Swift, JavaScript, Java, Rust, Go — all can read and write `.rkhs` files natively. This makes the format accessible to developers regardless of their technology stack.

4. Graph-native. The format represents content as a graph: nodes (content items) connected by edges (relationships). This graph structure is fundamental to Story Operators — navigation, forking, lineage tracking, and federation all operate on the graph.

5. Extensible. Every object in the format has a `metadata` field that can contain arbitrary key-value pairs. Domain-specific extensions (military history metadata, literary analysis metadata, business strategy metadata) are stored here without polluting the core schema.

21.6 Understanding the Node Structure

Each node in an `.rkhs` file represents a single piece of content — a book, a document, a decision point, a story beat, or any other discrete element. The node structure contains four types of information:

Visualization data (`position`): Three numbers [x, y, z] that determine where the node appears in 3D space. These are computed by dimensionality reduction (PCA or t-SNE) from the full embedding and are used only for display. Changing these numbers does not affect any mathematical operation — they are purely for human eyes.

Semantic data (`kernel_features`): The full embedding vector — 768 numbers (or another dimension, as specified by the universe's `dimension` field) that encode the meaning of the content. This is the mathematically meaningful representation. All similarity computations, operator applications, and analytical operations use these numbers.

Content data (`content`): Human-readable information — title, description, and arbitrary properties. This is what users see when they browse the universe. It has no mathematical role but is essential for interpretability.

Graph data (`parent_ids`, `children_ids`): The connections between nodes. These define the navigable structure of the universe. A book might be connected to its 10 nearest neighbors by similarity edges, or to specific related works by curated edges, or to its adaptations and derivatives by lineage edges.

21.7 Common File Structures for Different Domains

Different applications produce `.rkhs` files with different structural characteristics:

Literary Universe (e.g., CodexSpace): - Nodes: One per book (28,602 nodes) - Edges: Similarity-based (k-nearest neighbors, typically k=10) - Properties: author, year, word count, genre - Graph structure: Mostly undirected similarity; some directed temporal edges

Decision Analysis (e.g., Nimitz Graybook): - Nodes: One per decision point (~200 nodes) - Edges: Temporal sequence + counterfactual branches - Properties: date, commander, battle, outcome - Graph structure: Directed acyclic graph (DAG) with branching

Creative Workflow: - Nodes: One per version of the work-in-progress (~50-500 nodes) - Edges: State transitions (logline → summary → draft) and forks - Properties: state, word_count, creation_date, author - Graph structure: Tree with branches at fork points

Doctrine Morphing: - Nodes: One per doctrine concept (~105 source + ~16 generated) - Edges: Similarity + operator derivation (which operator produced which concept) - Properties: originator, date, domain, novelty_score - Graph structure: Bipartite (sources connected to generated concepts through operators)

21.8 Version History and Migration

The `.rkhs` format uses semantic versioning:

Version	Changes	Migration
0.1	Initial format — nodes as array	N/A
0.5	Nodes changed to object (dict) keyed by ID	Rebuild node keys
1.0	Added `kernel_features`, `parent_ids`, `children_ids`	Add new required fields
1.1	Added `domain_type`, `isTraversed`, `isForkPoint`	New optional fields (backward compatible)
2.0 (planned)	JSON Schema validation, extension points, federation metadata	Migration guide provided

The most important migration was from version 0.1 to 0.5: changing nodes from an array to an object. Arrays require sequential scan to find a node by ID ($O(n)$); objects allow direct lookup ($O(1)$). For a universe with 28,000 nodes, this is the difference between 28 milliseconds and 0.001 milliseconds per lookup — a 28,000x speedup.

21.9 Compression and Storage Optimization

Full `.rkhs` files for large universes can be hundreds of megabytes. Several strategies reduce storage and transmission costs:

Strategy 1: Compact embeddings. Reduce `kernel_features` from 768 dimensions to 8 or 16 using PCA. The compact embedding preserves the broad structure (which genre cluster a book belongs to) while losing fine detail (exact similarity rankings). File size reduction: ~99%.

Strategy 2: Edge pruning. Instead of storing edges for all k neighbors, store only the top-3 most similar. File size reduction: ~70% of edge data.

Strategy 3: Content truncation. Truncate `description` fields to 200 characters for browsing; load full descriptions on demand. File size reduction: ~60%.

Strategy 4: JSON compression. Apply gzip compression to the JSON file. File size reduction: ~85%. Most tools can read gzip-compressed JSON natively.

Strategy	File Size	Load Time	Similarity Accuracy
Full (no optimization)	670 MB	40 seconds	100%
Compact embeddings (8D)	12 MB	1 second	~70%
Edge pruning (k=3)	450 MB	30 seconds	100%
Content truncation	280 MB	20 seconds	100%
All optimizations + gzip	4 MB	0.5 seconds	~70%

For most interactive applications, the compact+compressed format (4 MB) is sufficient. Full-resolution analysis uses the uncompressed format.

21.10 The Relationship to Chapter 24

This chapter provides a conceptual overview of the `.rkhs` file format — why it exists, what design principles it follows, how it is used across different domains, and how it has evolved. Chapter 24 provides the complete field-by-field specification — the definitive reference for developers implementing `.rkhs` readers and writers.

If you are a decision-maker or analyst, this chapter gives you everything you need to understand the format and its role in the ecosystem. If you are a developer building tools that read or write `.rkhs` files, start here for context and then use Chapter 24 as your implementation reference.

The two chapters together ensure that the format is both *understood* (this chapter) and *specified* (Chapter 24). Understanding without specification leads to incompatible implementations. Specification without understanding leads to brittle implementations that follow the letter of the format but miss its spirit. Together, they provide the foundation for a robust, interoperable ecosystem.

21.11 Ecosystem Compatibility

The `.rkhs` format is currently supported by the following tools and platforms:

Tool	Reads	Writes	Notes
Multiverse App (Mac/iOS)	Yes	Yes	Native SwiftUI reader/writer
Streamlit Viewer (Python)	Yes	No	Read-only visualization
codexs-paces_to_rkhs_converter.py	No	Yes	Builds universes from embeddings
validate_rkhs.py	Yes	No	Structural validation only
rkhs_workflow engine (Python)	Yes	Yes	Creates workflow universes
Any JSON parser	Yes	Yes	The format is standard JSON

Any tool that can parse JSON can read `.rkhs` files. The format requires no proprietary libraries, no special binary readers, and no platform-specific dependencies. This universality is the format's greatest strength.

Bottom Line

The .rkhs format is your interchange standard. Any tool that reads or writes this format can participate in the RKHS ecosystem. The format is simple JSON — no proprietary binary, no special libraries needed to read it. A validation script checks structural integrity.

CHAPTER 22

The Software Stack



Figure 22.1: The software stack: from embeddings API to SwiftUI front-end

What's In It for You

The full implementation spans Python (analysis, embedding, transformation) and Swift (visualization). All core operations run locally at zero ongoing cost. This chapter maps the codebase.

22.1 Python Components

Component	Location	Purpose
rkhs_embedder.py	codexes-factory/src/codexes/modules/rkhs/	Generate 768-dim embeddings
hilbert_formalization.py	hilberts/	Core RKHS mathematics
codexspace.py	hilberts/	28,000-book universe management
doctrine_operators.py	hilberts/doctrine_morphs/	10 morphing operators
rkhs_kernels.py	hilberts/doctrine_morphs/	Kernel implementations
rkhs_methods.py	hilberts/doctrine_morphs/	Core mathematical methods
transform_registry.py	codexes-factory/src/codexes/modules/rkhs/	Transform management
rkhs_first_publisher.py	codexes-factory/src/codexes/modules/rkhs/	RKHS-First publishing workflow
entity_extractor.py	codexes-factory/src/codexes/modules/rkhs/	Semantic entity extraction
pipeline.py	hilberts/tranchetransformer/	End-to-end corpus transformation
validate_rkhs.py	shared/rkhs_info/	File format validation

22.2 Swift Components

Component	Location	Purpose
RKHSModels.swift	xcode_projects/multiverse/	Data models for RKHS nodes
RKHSDataStorage.swift	xcode_projects/multiverse/	Persistence layer
RKHSMath.swift	xcode_projects/multiverse/	Kernel computations in Swift

22.3 Key Dependencies

Library	Purpose	Version
sentence-transformers	Embedding generation	Latest

Library	Purpose	Version
PyTorch	Neural network backend	2.0+
NetworkX	Graph analysis	3.0+
Streamlit	Web UI	Latest
NumPy/SciPy	Numerical computing	Standard

22.4 Performance

Operation	Time	Cost
Embed one book	~10ms	$0 (local)
Build 28,000-book universe	~8 hours (one-time)	$0 (local)
Query similar books	~50ms	$0 (local)
Apply transform	~10ms	$0 (local)
Generate novel doctrine	~500ms + LLM call	Variable

22.5 Architecture Overview

The Story Operators software stack spans two languages (Python and Swift), multiple platforms (macOS, iOS, web), and several distinct functional layers. Understanding the architecture helps practitioners know which component to modify or extend for their specific needs.





22.6 Python Components: Detailed Descriptions

Each Python component has a specific role in the pipeline. Here is what each does, when you would use it, and how it connects to other components.

rkhs_embedder.py — The gateway to the mathematical world. This module wraps the sentence-transformers library and provides a clean API for converting text into 768-dimensional vectors. It handles model loading, batching, normalization, and caching. Use it when you have new text content that needs to enter the RKHS.

```
from codexes.modules.rkhs.rkhs_embedder import RKHSEmbedder

embedder = RKHSEmbedder()
vector = embedder.embed("Any text content goes here")
# vector is a numpy array of shape (768,), normalized to unit length
```

hilbert_formalization.py — The mathematical core. This module implements the abstract RKHS operations: inner products, norms, projections, kernel evaluations, and eigendecompositions. It is the "pure math" layer that does not know about books, doctrines, or poems — it operates on vectors and matrices. Use it when you need to perform mathematical operations on embeddings.

```
from hilberts.hilbert_formalization import HilbertSpace

H = HilbertSpace(dimension=768, kernel='cosine')
similarity = H.kernel(vector_a, vector_b)
projection = H.project(vector, subspace_basis)
eigenvectors, eigenvalues = H.eigendecompose(kernel_matrix)
```

codexspace.py — The 28,000-book universe manager. This module handles loading, querying, and manipulating the pre-built CodexSpace universe. It provides high-level operations like "find nearest neighbors," "compute cluster structure," and "identify sparse regions." Use it when working with the PG19 literary corpus.

doctrine_operators.py — The ten doctrine morphing operators. Each operator is a Python function that takes one or more embedding vectors and produces a transformed vector. The module also handles parameter configuration, batch processing, and novelty scoring. Use it when transforming strategic or conceptual content.

rkhs_kernels.py — Kernel implementations beyond the basic cosine kernel. Includes Gaussian RBF, string kernels, graph kernels, and the Global Alignment Kernel. Each kernel is implemented as a class with a consistent API: `kernel.evaluate(x, y)` returns a similarity score.

transform_registry.py — A registry of available transforms that can be applied through the UI or workflow engine. Transforms are registered with metadata (name, description, parameter schema, domain applicability) and can be discovered and invoked programmatically.

rkhs_first_publisher.py — The RKHS-First publishing workflow. This module implements the six graph objectives (maximum coverage, minimum redundancy, etc.) and the inverse embedding problem (generating text that matches a target embedding). Use it when designing book architecture before writing content.

entity_extractor.py — Semantic entity extraction. Given a text, this module identifies and embeds named entities (characters, places, concepts) as separate vectors within the RKHS. This enables character-level and concept-level analysis rather than whole-document analysis.

pipeline.py — The end-to-end corpus transformation pipeline. Given a collection of source texts, this module orchestrates: embedding, kernel computation, graph construction, operator application, and RKHS file output. Use it for batch processing of large corpora.

validate_rkhs.py — The format validator. Checks that a `.rkhs` file conforms to the specification: correct JSON structure, bidirectional relationships, consistent dimensions, valid node references. Always run this before loading a file into the Multiverse app.

22.7 Swift Components: The Visualization Layer

The Swift components power the Multiverse app — the native Mac and iOS application for exploring Story Operator content.

RKHSModels.swift defines the data structures:

```
struct RKHSNode: Codable, Identifiable {
    let id: String
    var position: [Double]      // 3D visualization position
    var content: NodeContent     // Title, description, properties
    var kernelFeatures: [Double] // 768-dim embedding
    var parentIDs: [String]
    var childrenIDs: [String]
    var isTraversed: Bool
    var isForkPoint: Bool
}
```

RKHSDataStorage.swift handles persistence — reading `.rkhs` files from disk, caching in memory, and saving modifications. It uses Swift's Codable protocol for JSON parsing, which handles the full `.rkhs` format natively.

RKHSMath.swift implements kernel computations in Swift for real-time analysis within the app. While the heavy computation (embedding, eigendecomposition) happens in Python, the app needs to compute similarity scores, find neighbors, and evaluate operators in real time. The Swift math module provides these operations at native speed.

22.8 Dependency Management

All Python dependencies are managed through `uv` (the fast Python package manager):

```
uv sync  # Install all dependencies from pyproject.toml
```

Key dependency versions and their roles:

Library	Role	Why This Library
sentence-transformers 3.0+	Embedding generation	Best sentence-level embeddings available
torch 2.0+	Neural network backend	Required by sentence-transformers
numpy 1.24+	Array operations	Foundation for all numerical computation

Library	Role	Why This Library
scipy 1.10+	Scientific computing	Eigendecomposition, optimization, sparse matrices
networkx 3.0+	Graph analysis	Character networks, narrative graphs
streamlit (latest)	Web UI	Rapid interactive application development
plotly 5.0+	3D visualization	Interactive 3D scatter plots for RKHS visualization

22.9 The Semantic Novelty Toolkit: A Deployed System

Since the first edition, a comprehensive web-accessible toolkit for large-scale semantic novelty analysis has been built and deployed at bigfivekiller.online. This section documents the system as actually implemented — not a theoretical design but working infrastructure processing 80,000+ books across two corpora.

Theoretical foundation. The toolkit operationalizes Schmidhuber's compression progress theory (2009): subjective interestingness corresponds to the rate of improvement in an agent's predictive model. We compute a proxy for compression progress at corpus scale via paragraph-level cosine distances from a running centroid.

The novelty formula. Each paragraph is embedded using all-mpnet-base-v2 (768 dimensions). The novelty score for paragraph i is:

```
novelty(p_i) = 1 - cos(e_i, centroid_{i-1})
```

where e_i is the paragraph's embedding and centroid_{i-1} is the running mean of all prior paragraph embeddings. High novelty means the paragraph introduces concepts distant from what came before. Low novelty means it reinforces established patterns. The resulting novelty curve — one value per paragraph — is a structural fingerprint of the book.

Storage architecture. The system uses a hybrid approach: - **SQLite** stores structured data: book metadata, per-book novelty metrics (mean, std, skewness, kurtosis), cluster assignments, SAX strings, BISAC classifications, and paragraph-level novelty scores. PG19 database: 711 MB; Books3 database: 1.1 GB. - **NumPy .npy files** store paragraph embeddings as memory-mapped float16 arrays, enabling zero-copy access with a memory footprint far below total index size. - **Float16 optimization:** Pearson correlation between float32 and float16 cosine similarity exceeds $r > 0.9999$, with mean absolute difference $< 10^{-4}$. This halves storage requirements (~40 GB to ~20 GB for PG19) with no meaningful precision loss.

Unified SQL views enable cross-corpus querying with a single discriminator column:

```
SELECT * FROM unified_novelty WHERE corpus = 'pg19' AND mean_novelty > 0.4
```

Books from PG19 (28,730 titles) and Books3 (52,796 titles) share identical column schemas, enabling direct comparison of novelty distributions across a century of publishing.

Checkpoint/resume. The pipeline records each completed book in a checkpoint table. Processing was interrupted and resumed over a dozen times during the Books3 run (5-7 days on single GPU, 2-3 weeks on CPU for 52,796 books) with no data loss or duplication.

Five toolkit components:

Component	Access	Function
Semantic Novelty Hub	Public	Primary exploration for PG19 corpus. Filter by genre, cluster, year, TAD thresholds. Browse ranked lists, visualize individual novelty trajectories, compare books side-by-side.
Novelty Explorer	Public	Extends to Books3 corpus. Cross-corpus comparison via Euclidean distance in PAA space. TAD metric distributions as histograms with KDE.
PG-19 BISAC Browser	Public	Dual-method subject classification: keyword-based (rule-driven from title/author/LoC subjects) and RKHS-semantic (cosine similarity to BISAC prototype embeddings).

Component	Access	Function
Thematic Anthology Engine	Authenticated	Paragraph-level semantic retrieval across entire PG19 corpus. Given a query, retrieves most semantically similar paragraphs from 28K+ books.
Republication Scorer	Authenticated	Cross-corpus matching to identify public-domain works whose novelty profiles most resemble modern commercial successes.

Deployment. GCP e2-standard-2 (2 vCPU, 8 GB RAM, SSD persistent disk), Streamlit on port 8516 behind Apache2 reverse proxy. Steady-state memory: ~2 GB. Performance: individual book lookup <100ms, novelty trajectory <500ms, corpus-wide aggregation <3s, cross-corpus comparison <2s, paragraph embedding search <5s.

Comparison to existing tools:

Capability	Voyant	HathiTrust	BookNLP	Stanford Lit Lab	**Our Toolkit**
Semantic embeddings	No	No	No	No	**Yes**
Interactive web UI	Yes	Yes	No	No	**Yes**
Corpus-scale (10K+)	No	Yes	Yes	Varies	**Yes**
Novelty trajectories	No	No	No	No	**Yes**

The toolkit is unique in combining all four capabilities: semantic embeddings, interactive web UI, corpus-scale analysis, and novelty trajectory visualization.

22.10 The Unified RKHS Pipeline: Production Architecture

Since the first edition, the scattered Python components described above have been unified into a single orchestrator: `RKHSPipeline`. This class provides a single

entry point that takes a book's text and produces all RKHS artifacts — embedding, novelty analysis, kernel similarities, operator application, and report generation.

Core modules (production implementation):

Module	Class	Purpose
`rkhs_pipeline.py`	`RKHSPipeline`	Orchestrator: coordinates all analysis stages
`rkhs_embedder.py`	`RKHSEmbedder`	Embedding generation (768-dim, sentence-transformers)
`surprisal_curve.py`	`SurprisalAnalyzer`	Novelty curve computation and grading
`surprisal_curve.py`	`SurprisalGoal`	Per-book novelty "contract"
`surprisal_database.py`	`SurprisalDatabase`	Two-table SQLite storage + unified views
`kernels.py`	`compute_kernel`, `compute_gram_matrix`	6 kernel types
`rkhs_report.py`	`RKHSReport`, `OperatorResult`	JSON + LaTeX artifact generation
`transform_registry.py`	Transform registry	Discoverable operator catalog

Data flow through the pipeline:

```
Book Text → [RKHSEmbedder] → book_embedding (768-dim)
                  ↓
[SurprisalAnalyzer] → novelty_report (curve + metrics + grade)
                  ↓
[compute_gram_matrix] → corpus similarities
                  ↓
[Operator Application] → transform results
                  ↓
[RKHSReport] → JSON artifacts + LaTeX chapter
```

Six kernel types implemented:

Kernel	Class	Best For	Key Parameter
Cosine	`KernelType.COSINE`	Book-to-book similarity	None (parameter-free)
RBF/Gaussian	`KernelType.RBF`	Character state similarity	`gamma` (0.1=strict, 10.0=broad)

Kernel	Class	Best For	Key Parameter
Linear	`KernelType.LINEAR`	Simple dot product similarity	None
Polynomial	`KernelType.POLYNOMIAL`	Hierarchical structure	`degree` (2=quadratic, 3=cubic), `coef0`
Global Alignment (GAK)	`KernelType.GAK`	Plot structure (handles stretching)	Based on Cuturi (2011) soft-DTW
Composite	`KernelType.COMPOSITE`	Weighted multi-kernel combination	Weights per component kernel

The novelty grading system. The `SurprisalAnalyzer` compares each book's actual novelty curve against its `SurprisalGoal` contract and produces a letter grade:

Grade	Score	Interpretation
A	$\geq 85\%$	Book meets or exceeds its novelty contract
B	$\geq 70\%$	Minor deviations from contract
C	$\geq 50\%$	Significant deviations — revision recommended
F	$< 50\%$	Fails to meet contract — structural issues

Four diagnostic codes identify specific issues:

Code	Diagnostic	Meaning
SCA001	Low compression progress	Text may not be teaching the reader effectively
SCA002	Flat novelty run	Extended monotone passage — reader may lose engagement
SCA003	High terminal/initial ratio	Text doesn't reward sustained reading — ending as unpredictable as beginning
SCA004	No novelty spikes	Expected dramatic moments absent — text may be monotonous

Five profile types define expected novelty curve shapes for different book types:

Profile	Trend	Spike Frequency	Description
`annotated_primary_source`	Descending	Moderate	Reader learns domain conventions; spikes at key events
`analytical_essay`	Ascending then resolving	Low	Building argument with periodic synthesis
`narrative_history`	Sawtooth	High	Tension/resolution cycles
`intelligence_analysis`	Stepped descent	Moderate	Progressive reframing through revelations
`reference_material`	Flat	None	Independent entries; low compression progress is normal

The .rkhs.json universe file format (documented in Ch 21) stores the output of the pipeline: embeddings, kernel similarities, operator results, and metadata in a human-readable JSON structure that can be loaded by both the Python pipeline and the Swift Multiverse app.

22.11 Zero-Cost Operations After Initial Build

A critical feature of the architecture: **all operations after the one-time build are free.** No API calls, no cloud services, no subscription fees. The embedding model runs locally. The kernel computations are matrix operations. The operators are mathematical functions. The viewers are local applications.

This zero-marginal-cost architecture means that exploration is unlimited. An analyst can run thousands of queries, apply hundreds of operators, and explore every corner of the universe — all on a standard laptop, with no metered costs. The only cost is the initial build time (8-10 hours for 28,000 books), which is a one-time investment.

For organizations considering the platform, this means the total cost of ownership is: developer time to integrate + compute time for initial build + hardware (a

standard laptop). There are no ongoing API fees, no per-query charges, and no data egress costs. All data stays on the local machine.

Bottom Line

The software exists, is modular, and runs locally. The most expensive operation (building the initial universe) is one-time. All subsequent operations are instant and free. The stack uses standard, well-maintained libraries with no proprietary dependencies.

CHAPTER 23

Building Your First Universe



Figure 23.1: Building your first universe: a 30-minute tutorial from text to navigable space

What's In It for You

A step-by-step guide to creating your first RKHS universe from any collection of texts. In 30 minutes, you will have an embedded, navigable, transformable content universe.

23.1 Step 1: Prepare Your Texts

Collect your content as text files, one per item (book, article, document, etc.).

23.2 Step 2: Install Dependencies

```
uv init my-rkhs-project
cd my-rkhs-project
uv add sentence-transformers numpy
```

23.3 Step 3: Generate Embeddings

```
from sentence_transformers import SentenceTransformer
import json, numpy as np

model = SentenceTransformer('all-mpnet-base-v2')

texts = [open(f).read()[:5000] for f in your_files]  # First 5000 chars
embeddings = model.encode(texts, normalize_embeddings=True)
```

23.4 Step 4: Build the Universe

```
nodes = {}
for i, (file, text, emb) in enumerate(zip(your_files, texts, embeddings)):
    nodes[f"node-{i}"] = {
        "id": f"node-{i}",
        "position": [0, 0, 0],  # Computed by viewer
        "content": {"title": file.stem, "description": text[:200]},
        "kernel_features": emb.tolist(),
        "timestamp": "2026-01-27T00:00:00Z",
        "parent_ids": [],
        "children_ids": []
    }

# Add similarity edges
for i in range(len(embeddings)):
    sims = embeddings[i] @ embeddings.T
    top_k = np.argsort(sims)[-6:-1][::-1]  # Top 5 (excluding self)
    nodes[f"node-{i}"]["children_ids"] = [f"node-{j}" for j in top_k]
    for j in top_k:
        if f"node-{i}" not in nodes[f"node-{j}"]["parent_ids"]:
            nodes[f"node-{j}"]["parent_ids"].append(f"node-{i}")

universe = {
    "id": "my-first-universe",
    "name": "My First RKHS Universe",
    "description": "Built from my content",
```

```
    "dimension": 768,
    "kernel_type": "cosine",
    "kernel_params": {"gamma": 1.0},
    "version": "1.0",
    "nodes": nodes,
    "edges": []
}

with open("my_universe.rkhs.json", "w") as f:
    json.dump(universe, f, indent=2)
```

23.5 Step 5: Explore

Open in the Streamlit viewer or the Multiverse Mac/iOS app. Navigate, discover, and transform.

23.6 Before You Begin: What You Need

This tutorial assumes you have:

- A computer with Python 3.10 or later installed
- The `uv` package manager (install with `curl -LsSf https://astral.sh/uv/install.sh | sh`)
- A collection of text files you want to explore (at least 20; ideally 100+)
- Basic familiarity with the command line

You do *not* need: - A GPU (CPU is sufficient for small universes) - Any API keys or cloud accounts - Prior experience with machine learning or RKHS mathematics

The entire process runs locally and costs nothing beyond your electricity bill.

23.7 Step 1: Set Up Your Project (5 minutes)

```
# Create a new project
uv init my-story-universe
cd my-story-universe

# Add dependencies
uv add sentence-transformers numpy

# Create directories
mkdir texts output
```

Place your text files in the `texts/` directory. Each file should be a `.txt` file containing the content of one item (book, article, document, etc.). The file name will become the item's title in the universe.

What kinds of content work? Anything in English text. Books, articles, blog posts, research papers, policy documents, song lyrics, poetry collections, legal briefs, medical case studies, patent descriptions, product reviews. The embedding model handles any English text.

How much text per item? The embedding model uses the first 5,000 characters (roughly 800-1,000 words). Longer texts are truncated. This is usually sufficient — the first few pages of a book capture its genre, topic, style, and tone.

23.8 Step 2: Generate Embeddings (5-15 minutes)

```python
# embed.py
from sentence_transformers import SentenceTransformer
from pathlib import Path
import numpy as np
import json

# Load the embedding model (downloads ~400 MB on first run)
print("Loading model...")
model = SentenceTransformer('all-mpnet-base-v2')

# Read all text files
text_dir = Path("texts")
files = sorted(text_dir.glob("*.txt"))
print(f"Found {len(files)} text files")

texts = []
titles = []
for f in files:
    content = f.read_text(encoding='utf-8', errors='replace')[:5000]
    texts.append(content)
    titles.append(f.stem)  # Use filename without extension as title

# Generate embeddings
print("Generating embeddings...")
embeddings = model.encode(texts, normalize_embeddings=True, show_progress_bar=True)
print(f"Generated {len(embeddings)} embeddings of dimension {embeddings.shape[1]}")

# Save for later use
np.save("output/embeddings.npy", embeddings)
with open("output/titles.json", "w") as f:
    json.dump(titles, f)

print("Done! Embeddings saved to output/")
```

Run with: `uv run python embed.py`

On a standard laptop (no GPU), this takes: - 100 texts: ~10 seconds - 500 texts: ~50 seconds - 1,000 texts: ~2 minutes - 5,000 texts: ~10 minutes

The first run downloads the model (~400 MB), which is cached for future use.

23.9 Step 3: Build the Universe (5 minutes)

```
# build_universe.py
import numpy as np
import json
from datetime import datetime

# Load embeddings and titles
embeddings = np.load("output/embeddings.npy")
with open("output/titles.json") as f:
    titles = json.load(f)

n = len(titles)
print(f"Building universe from {n} items...")

# Compute PCA for 3D visualization positions
from numpy.linalg import svd
centered = embeddings - embeddings.mean(axis=0)
U, S, Vt = svd(centered, full_matrices=False)
positions_3d = U[:, :3] * S[:3]  # First 3 principal components

# Build nodes
nodes = {}
for i in range(n):
    node_id = f"node-{i:04d}"
    nodes[node_id] = {
        "id": node_id,
        "position": positions_3d[i].tolist(),
        "content": {
            "title": titles[i],
            "description": titles[i],  # Replace with actual text excerpt if desired
            "properties": {"index": i}
        },
        "kernel_features": embeddings[i].tolist(),
        "timestamp": datetime.now().isoformat() + "Z",
        "parent_ids": [],
        "children_ids": [],
        "isTraversed": False,
        "isForkPoint": False,
        "metadata": {}
    }
```

```
# Add similarity edges (k=5 nearest neighbors)
k = min(5, n - 1)
print(f"Computing {k}-nearest neighbors...")
similarity_matrix = embeddings @ embeddings.T

for i in range(n):
    sims = similarity_matrix[i].copy()
    sims[i] = -1  # Exclude self
    top_k = np.argsort(sims)[-k:][::-1]

    node_id = f"node-{i:04d}"
    for j in top_k:
        child_id = f"node-{j:04d}"
        # Add bidirectional relationship
        if child_id not in nodes[node_id]["children_ids"]:
            nodes[node_id]["children_ids"].append(child_id)
        if node_id not in nodes[child_id]["parent_ids"]:
            nodes[child_id]["parent_ids"].append(node_id)

# Build edges array
edges = []
for node_id, node in nodes.items():
    for child_id in node["children_ids"]:
        i = int(node_id.split("-")[1])
        j = int(child_id.split("-")[1])
        edges.append({
            "source_id": node_id,
            "target_id": child_id,
            "weight": 1.0,
            "kernel_similarity": float(similarity_matrix[i][j]),
            "transition_type": "semantic",
            "metadata": {}
        })

# Assemble universe
universe = {
    "id": "my-first-universe",
    "name": "My First Story Operator Universe",
    "description": f"Built from {n} texts on {datetime.now().strftime('%Y-%m-%d')}",
    "dimension": 768,
    "kernel_type": "cosine",
    "kernel_params": {"gamma": 1.0},
    "version": "1.0",
    "created_at": datetime.now().isoformat() + "Z",
    "modified_at": datetime.now().isoformat() + "Z",
    "domain_type": "general",
    "nodes": nodes,
    "edges": edges,
    "metadata": {
```

```
        "source": "my-story-universe tutorial",
        "embedding_model": "all-mpnet-base-v2"
    }
}

# Write output
output_path = "output/my_universe.rkhs.json"
with open(output_path, "w") as f:
    json.dump(universe, f, indent=2)

import os
size_mb = os.path.getsize(output_path) / (1024 * 1024)
print(f"\nUniverse saved to {output_path}")
print(f"File size: {size_mb:.1f} MB")
print(f"Nodes: {len(nodes)}")
print(f"Edges: {len(edges)}")
```

Run with: `uv run python build_universe.py`

23.10 Step 4: Validate Your Universe (1 minute)

Before exploring, validate that the file is well-formed:

```
# validate.py
import json

with open("output/my_universe.rkhs.json") as f:
    data = json.load(f)

nodes = data["nodes"]
errors = []

for node_id, node in nodes.items():
    # Check ID consistency
    if node["id"] != node_id:
        errors.append(f"Node key '{node_id}' != node id '{node['id']}'")

    # Check bidirectional relationships
    for child_id in node.get("children_ids", []):
        if child_id not in nodes:
            errors.append(f"Node {node_id}: child {child_id} not found")
        elif node_id not in nodes[child_id].get("parent_ids", []):
            errors.append(f"Node {node_id} -> {child_id}: missing reverse link")

    for parent_id in node.get("parent_ids", []):
        if parent_id not in nodes:
            errors.append(f"Node {node_id}: parent {parent_id} not found")
        elif node_id not in nodes[parent_id].get("children_ids", []):
```

```
            errors.append(f"Node {node_id} <- {parent_id}: missing reverse link")

    # Check dimension consistency
    kf = node.get("kernel_features", [])
    if len(kf) != data.get("dimension", 768):
        errors.append(f"Node {node_id}: features length {len(kf)} != {data.get('dimension

if errors:
    print(f"VALIDATION FAILED: {len(errors)} errors")
    for e in errors[:10]:
        print(f"  {e}")
else:
    print(f"VALIDATION PASSED: {len(nodes)} nodes, all relationships bidirectional")
```

23.11 Step 5: Explore Your Universe

You now have a fully valid `.rkhs` file. Three ways to explore it:

Option A: Multiverse App (Mac/iOS). Copy the `.rkhs.json` file to the Multiverse app's Resources directory. The app will auto-discover it and provide 3D visualization, browsing, search, and forking.

Option B: Streamlit Viewer (Web). Use the Streamlit-based viewer for web-based exploration with interactive Plotly visualizations.

Option C: Python Analysis. Write Python scripts that load the universe and perform custom analysis — clustering, operator application, gap detection, and more.

23.12 Going Further: Adding Operators

Once your universe is built, you can apply operators to create new content:

```
# Simple operator: find the midpoint between two items
def midpoint(universe, node_id_1, node_id_2):
    """Compute the semantic midpoint between two nodes."""
    import numpy as np
    n1 = universe["nodes"][node_id_1]
    n2 = universe["nodes"][node_id_2]
    v1 = np.array(n1["kernel_features"])
    v2 = np.array(n2["kernel_features"])
    mid = (v1 + v2) / 2
    mid = mid / np.linalg.norm(mid)  # Normalize
    return mid.tolist()
```

This midpoint vector represents the "average" of two items — the concept that bridges them. You can find its nearest neighbors in the universe to discover

what real content exists at that midpoint, or generate new content targeting that embedding.

23.13 Troubleshooting Common Issues

Problem	Likely Cause	Solution
Model download fails	Network/firewall	Download model manually from HuggingFace
Out of memory	Too many texts at once	Process in batches of 1,000
Viewer shows disconnected graph	Bidirectional links missing	Run validate.py and fix
Nodes cluster in one area	Texts too similar	Add more diverse content
File too large to open	Universe too big	Use compact embeddings (8D)

23.14 What You Have Built

At the end of this tutorial, you have:

1. **A permanent semantic asset.** Your content collection is now embedded in a 768-dimensional space where relationships are measurable and navigable. This asset does not degrade, does not require ongoing maintenance, and does not incur ongoing costs.

2. **A valid `.rkhs` file.** This file can be opened in the Multiverse app, analyzed with Python scripts, shared with colleagues, and federated with other universes. It follows the specification in Chapter 24 and is interoperable with every tool in the Story Operators ecosystem.

3. **A foundation for analysis.** With the embeddings computed, you can now apply any of the 34 operators described in this book, run spectral analysis to discover the principal dimensions of your content, compute optimal transport distances for adaptation planning, and identify sparse regions that represent content opportunities.

4. **A starting point for expansion.** As you add new content, you can embed it and append it to your universe incrementally. Each addition enriches the graph, creates new connections, and potentially reveals new structure. Your universe grows organically as your content collection grows.

The total investment: approximately 30 minutes of setup time, zero ongoing cost, and 30 lines of Python code. The return: a permanent, navigable, transformable representation of your entire content collection.

Bottom Line

Building a universe from your own content takes 30 minutes and zero cost beyond a laptop. Once built, you have a permanent, navigable, transformable content space. The barrier to entry is writing 30 lines of Python.

CHAPTER 24

The RKHS Format Specification — A Complete Reference



Figure 24.1: The complete .rkhs format specification: field-by-field reference for developers

What's In It for You

The `.rkhs` file is the universal container for Story Operator data — the equivalent of `.mp3` for music or `.pdf` for documents. Understanding this format means you can create, validate, exchange, and build on any Story Operator universe. Every tool in the ecosystem reads and writes this single format.

The `.rkhs` file format is a JSON document that encodes an entire navigable universe of content. Whether it contains 28,000 books or 50 decision nodes, the structure is identical.

24.1 Universe-Level Structure

```
{
  "id": "unique-universe-id",
  "name": "Universe Display Name",
  "description": "What this universe contains",
  "dimension": 768,
  "kernel_type": "cosine",
  "kernel_params": {"gamma": 1.0},
  "version": "1.0",
  "created_at": "2026-01-27T10:00:00Z",
  "modified_at": "2026-01-27T10:00:00Z",
  "domain_type": "fiction",
  "nodes": { /* Node objects keyed by ID */ },
  "edges": [ /* Edge objects */ ],
  "metadata": {}
}
```

Field	Type	Required	Description
`id`	String	Yes	Unique universe identifier
`name`	String	Yes	Human-readable name
`dimension`	Integer	Yes	Length of all kernel_features arrays (8 for compact, 768 for full)
`kernel_type`	String	Yes	One of: `cosine`, `rbf`, `linear`, `polynomial`
`domain_type`	String	No	Content domain: `biography`, `decision`, `history`, `fiction`, `education`, `business`, `science`, `game`
`nodes`	Object	Yes	**Must be an object (dict), NOT an array**
`edges`	Array	Yes	Array of edge objects

□ **The #1 Mistake:** Encoding `nodes` as a JSON array instead of an object. Nodes must be keyed by their ID: `"nodes": {"node-1": {...}, "node-2": {...}}`.

□ **Plain English:** Think of a `.rkhs` file as a map. The universe-level fields are the map's legend. Nodes are the locations. Edges are the roads between them. And `kernel_features` are GPS coordinates in meaning-space.

24.2 Node Structure

Each node represents a single element — a book, a document, a decision point, a story beat:

```
{
  "id": "pg19_00042",
  "position": [0.234, -1.456, 0.892],
  "content": {
    "title": "Pride and Prejudice",
    "description": "It is a truth universally acknowledged...",
    "properties": {"year": "1813", "word_count": 120000}
  },
  "kernel_features": [0.123, -0.456, 0.789, /* ... 768 total */],
  "timestamp": "2026-01-27T10:00:00Z",
  "parent_ids": ["pg19_00041", "pg19_00138"],
  "children_ids": ["pg19_00043", "pg19_00256"],
  "isTraversed": false,
  "isForkPoint": false,
  "metadata": {}
}
```

Field	Type	Required	Description
`id`	String	Yes	Must match its key in the `nodes` object
`position`	Array[3]	Yes	3D visualization coordinates `[x, y, z]`
`content.title`	String	Yes	Display title (under 100 characters)
`content.description`	String	Yes	Full text description
`kernel_features`	Array[Float]	Yes	Feature vector — length MUST match universe `dimension`
`parent_ids`	Array[String]	**CRITICAL**	IDs of nodes pointing TO this node
`children_ids`	Array[String]	**CRITICAL**	IDs of nodes this node points TO

24.3 The Bidirectionality Rule

This is the single most important rule in the entire specification:

```
If Node A lists Node B in children_ids,
then Node B MUST list Node A in parent_ids.
```

Failure to maintain bidirectional relationships is the #1 cause of display errors in the Multiverse viewer. The graph will appear disconnected, navigation will break, and fork points won't be detected.

> □ **Plain English:** If you write "Chapter 1 leads to Chapter 2," then Chapter 2 must also know "I came from Chapter 1." Every road goes both ways on the map.

24.4 Edge Structure

Edges carry additional metadata about relationships between nodes:

```json
{
  "source_id": "pg19_00042",
  "target_id": "pg19_00137",
  "weight": 1.0,
  "kernel_similarity": 0.856,
  "transition_type": "semantic",
  "metadata": {"rank": 1}
}
```

Transition types describe the nature of the connection:

Type	Meaning	Example
`temporal`	Sequential progression	Chapter 1 → Chapter 2
`fork`	Branching decision point	Choose your own adventure
`semantic`	Similarity-based connection	Two related books
`causal`	Cause and effect	Decision → Consequence
`counterfactual`	"What if" alternate	Historical turning point → Alternative history

24.5 Timestamps

The format accepts two timestamp styles:

- **ISO 8601 (recommended):** `"2026-01-27T10:00:00Z"`
- **Numeric (Swift native):** `787972552.025954` — seconds since January 1, 2001 (Apple reference date)

24.6 Validation Tools

Python relationship validator — run this before loading any `.rkhs` file:

```python
import json

def validate_relationships(rkhs_file):
    with open(rkhs_file) as f:
        data = json.load(f)

    nodes = data['nodes']
    errors = []

    for node_id, node in nodes.items():
        # Check children
        for child_id in node.get('children_ids', []):
            if child_id not in nodes:
                errors.append(f"Node {node_id} references non-existent child {child_id}")
            elif node_id not in nodes[child_id].get('parent_ids', []):
                errors.append(f"Node {node_id} → {child_id}: missing reverse reference")

        # Check parents
        for parent_id in node.get('parent_ids', []):
            if parent_id not in nodes:
                errors.append(f"Node {node_id} references non-existent parent {parent_id}")
            elif node_id not in nodes[parent_id].get('children_ids', []):
                errors.append(f"Node {node_id} ← {parent_id}: missing reverse reference")

        # Check dimension consistency
        kf = node.get('kernel_features', [])
        if len(kf) != data.get('dimension', 0):
            errors.append(f"Node {node_id}: kernel_features length {len(kf)} != dimension

    return errors
```

Edge generator from node relationships:

```python
def generate_edges_from_nodes(nodes):
    """Generate edges from existing parent/child relationships."""
    edges = []
    for node_id, node in nodes.items():
        for child_id in node.get('children_ids', []):
            edges.append({
                "source_id": node_id,
```

```
                "target_id": child_id,
                "weight": 1.0,
                "kernel_similarity": 0.9,
                "transition_type": "temporal",
                "metadata": {}
            })
    return edges
```

24.7 Size Guidelines

Scale	Nodes	File Size	Use Case
Small	10–50	< 1 MB	Testing, tutorials
Medium	50–200	1–10 MB	Single projects
Large	200–500	10–50 MB	Complex narratives
Very Large	500+	50+ MB	Full libraries (use sampling for viz)

24.8 Validation Checklist

Before deploying any `.rkhs` file:

- ☐ `nodes` is an object (dict), not an array
- ☐ Every node `id` matches its key in the `nodes` object
- ☐ Every `kernel_features` array has length equal to `dimension`
- ☐ All `parent_ids` / `children_ids` references exist in `nodes`
- ☐ All relationships are bidirectional
- ☐ Root nodes have `parent_ids: []`
- ☐ Leaf nodes have `children_ids: []`
- ☐ All edge `source_id` and `target_id` values exist in `nodes`

24.9 Design Rationale: Why JSON, Not Binary?

The choice of JSON over a binary format like Protocol Buffers, MessagePack, or HDF5 was deliberate and reflects the current stage of the ecosystem.

Arguments for JSON: - Human-readable: critical during development and debugging - Universal support: every language and platform can read JSON - Git-friendly: text diffs show exactly what changed between versions - No dependencies: no special libraries needed to parse - Self-documenting: field names are visible in the file

Arguments against JSON (acknowledged limitations): - Verbose: a 768-element float array in JSON is ~15,000 characters; in binary, ~3,072 bytes (5x more compact) - Slow parsing: JSON parsing is CPU-intensive for large files; binary formats are faster - No random access: to read one node, you must parse the entire file; binary formats can support seeking

The trade-off: For universes up to ~50,000 nodes, JSON is practical (load times under 60 seconds). Beyond that scale, a binary format or database-backed storage will be necessary. Version 3.0 of the format may introduce a binary companion format for large-scale deployments, while maintaining JSON as the interchange format.

24.10 Field-by-Field Specification

This section provides the complete specification for every field in the `.rkhs` format, with constraints, defaults, and examples.

Universe-Level Fields (Complete)

Field	Type	Required	Default	Constraints	Example
`id`	String	Yes	—	Unique, URL-safe, max 128 chars	`"codexspace-v1-pg19"`
`name`	String	Yes	—	Max 200 chars	`"CodexSpace v1: PG19 Literary Universe"`
`description`	String	No	`""`	Max 5,000 chars	`"28,602 pre-1919 English-language books"`
`dimension`	Integer	Yes	—	Must be > 0; typical values: 8, 384, 768	`768`
`kernel_type`	String	Yes	—	One of: `cosine`, `rbf`, `linear`, `polynomial`	`"cosine"`
`kernel_params`	Object	No	`{}`	Depends on kernel_type	`{"gamma": 1.0}`

Field	Type	Required	Default	Constraints	Example
`version`	String	No	`"1.0"`	Semantic version string	`"1.1"`
`created_at`	String	No	—	ISO 8601 or numeric timestamp	`"2026-01-27T10:00:00Z"`
`modified_at`	String	No	—	ISO 8601 or numeric timestamp	`"2026-01-27T10:00:00Z"`
`domain_type`	String	No	`"general"`	One of standard domain types or custom	`"fiction"`
`nodes`	Object	Yes	—	**MUST be object, NOT array**	`{"node-1": {...}}`
`edges`	Array	Yes	—	Array of edge objects	`[{"source_id": ...}]`
`metadata`	Object	No	`{}`	Arbitrary key-value pairs	`{"source": "PG19"}`

Kernel parameters by type:

Kernel Type	Parameters	Default	Description
`cosine`	`gamma` (Float)	1.0	Scaling factor (usually 1.0)
`rbf`	`gamma` (Float)	0.1	Bandwidth: smaller = tighter clusters
`linear`	(none)	—	Simple dot product
`polynomial`	`degree` (Int), `coef0` (Float)	3, 1.0	Polynomial degree and offset

Node-Level Fields (Complete)

Field	Type	Required	Default	Constraints
`id`	String	Yes	—	Must match its key in `nodes` object
`position`	Array[3 Floats]	Yes	`[0, 0, 0]`	3D coordinates for visualization
`content`	Object	Yes	—	Must contain at least `title`
`content.title`	String	Yes	—	Max 200 chars
`content.description`	String	Yes	—	Full text content, no max
`content.properties`	Object	No	`{}`	Domain-specific key-value pairs
`kernel_features`	Array[Float]	Yes	—	Length MUST equal universe `dimension`
`timestamp`	String or Number	No	—	ISO 8601 or Apple reference date numeric
`parent_ids`	Array[String]	Yes	`[]`	IDs of nodes pointing TO this node
`children_ids`	Array[String]	Yes	`[]`	IDs of nodes this node points TO
`isTraversed`	Boolean	No	`false`	UI state: has user visited this node?
`isForkPoint`	Boolean	No	`false`	Does this node have multiple children from forking?
`metadata`	Object	No	`{}`	Arbitrary domain-specific data

Edge-Level Fields (Complete)

Field	Type	Required	Default	Constraints
`source_id`	String	Yes	—	Must exist in `nodes`
`target_id`	String	Yes	—	Must exist in `nodes`
`weight`	Float	No	1.0	Edge importance for visualization
`kernel_similarity`	Float	No	—	Cosine similarity between source and target
`transition_type`	String	No	`"semantic"`	One of standard transition types
`metadata`	Object	No	`{}`	Arbitrary edge metadata

24.11 Domain Extensions: Structured Metadata for Specific Domains

The `metadata` field on nodes and universes can contain domain-specific extensions. Here are the standard extensions for each supported domain:

Domain: `fiction`

```
{
  "metadata": {
    "author": "Jane Austen",
    "year": 1813,
    "word_count": 120000,
    "genre": "romance",
    "characters": ["Elizabeth", "Darcy", "Jane", "Bingley"],
    "setting": "Regency England",
    "narrative_pov": "third_person_limited"
  }
}
```

Domain: `history`

```
{
  "metadata": {
```

```
    "date": "1942-06-04",
    "location": "Midway Atoll",
    "participants": ["USN", "IJN"],
    "commander": "ADM Nimitz",
    "outcome": "US victory",
    "counterfactual_branches": ["what_if_carriers_missed"],
    "graybook_references": ["GB-1942-0604-001"]
  }
}
```

Domain: `doctrine`

```
{
  "metadata": {
    "originator": "Carl von Clausewitz",
    "original_date": "1832",
    "domain": "land_warfare",
    "operator_applied": "temporal_shift",
    "operator_params": {"target_era": "2025"},
    "novelty_score": 0.817,
    "validated": true
  }
}
```

24.12 Error Recovery: Common Issues and Fixes

The most common issues with `.rkhs` files, their symptoms, and their fixes:

Issue 1: Nodes encoded as array instead of object - Symptom: Viewer shows "Invalid format" or crashes on load - Cause: `"nodes": [{...}, {...}]` instead of `"nodes": {"id1": {...}, "id2": {...}}` - Fix: Convert array to object, using each node's `id` as its key

Issue 2: Missing bidirectional relationships - Symptom: Navigation is broken — clicking "next" works but "back" does not. Graph appears disconnected. - Cause: Node A lists B as child, but B does not list A as parent - Fix: Run the validation script; add missing reverse references

Issue 3: Dimension mismatch - Symptom: Similarity computations return NaN or unexpected values - Cause: Some nodes have `kernel_features` arrays of different lengths than the universe `dimension` - Fix: Re-embed affected nodes or pad/truncate to match dimension

Issue 4: Orphaned references - Symptom: Clicking on a link leads to "node not found" error - Cause: A node references a parent or child that does not exist in the `nodes` object - Fix: Either add the missing node or remove the dangling reference

Bottom Line

The `.rkhs` format is a single, validated, portable container for any Story Operator universe. If you can produce valid JSON following these rules — especially bidirectional relationships — you can create content that works across every tool in the ecosystem: Streamlit viewers, the Multiverse Mac/iOS app, Python analysis scripts, and federation hubs.

CHAPTER 25

From 768 Dimensions to Your Screen — The Architecture Pipeline



Figure 25.1: The architecture pipeline: from 768-dimensional embeddings to interactive visualization

What's In It for You

Getting 28,000 books from raw text to an interactive 3D visualization requires a three-stage pipeline: embed, convert, explore. The first two stages run once. The third runs forever. Total cost: zero (beyond your own hardware). Total time to first exploration: about 8 hours of compute, mostly unattended.

25.1 The Three-Stage Pipeline



□ **Plain English:** Stage 1 reads every book and converts it to 768 numbers that capture its meaning. Stage 2 arranges those numbers into a navigable map. Stage 3 is you, exploring that map forever.

25.2 Stage 1: Building the Semantic Space

The embedding model (all-mpnet-base-v2, a Sentence-BERT variant) reads the first 5,000 characters of each book and produces a 768-dimensional vector. Books that are semantically similar end up near each other in this space.

What "768 dimensions" means: Each dimension captures some aspect of meaning. No single dimension maps to a simple concept like "romance" or "war." Instead, the 768 numbers together create a fingerprint so precise that cosine similarity between two fingerprints reliably predicts human judgments of relatedness.

The kernel matrix records the similarity between every pair of books:

Cosine kernel:

$$K(A, B) = \langle A, B \rangle / (\|A\| \times \|B\|)$$

RBF kernel (alternative, for tighter clustering):

$$K(A, B) = \exp(-\gamma \times \|A - B\|^2)$$

□ **Plain English:** The cosine kernel asks "how much do these two books point in the same direction in meaning-space?" A result of 0.85 means

they're very similar. The RBF kernel asks the same question but is more forgiving of small differences and harsher on large ones.

25.3 Stage 2: Converting to RKHS Format

The conversion pipeline:

1. **PCA Projection** — Reduces 768 dimensions to 3 for visualization, preserving as much structure as possible (~2 minutes)
2. **Node Construction** — Creates an RKHSNode for each book with position, kernel_features, and content
3. **Edge Construction** — Connects each book to its 10 nearest neighbors by cosine similarity
4. **Bidirectional Linking** — Ensures every parent-child relationship goes both ways
5. **JSON Export** — Writes the complete universe

25.4 Node Anatomy

Each node lives in two spaces simultaneously:

```
┌─────────────────────────────────────────────────┐
│ Node: "Pride and Prejudice"                     │
├─────────────────────────────────────────────────┤
│                                                 │
│  VISUALIZATION (3D)         SEMANTIC (768D)     │
│  position: [0.23, -1.4, 0.8] kernel_features: [0.12, -0.45, ...]│
│  For human eyes              For machine computation│
│                                                 │
│  CONTENT                    GRAPH               │
│  title, author, description  parent_ids, children_ids│
│  For human reading           For navigation     │
│                                                 │
└─────────────────────────────────────────────────┘
```

The 3D position is a *lossy projection* — it captures the broad structure but loses fine detail. The 768D kernel_features are the *lossless* representation. All mathematical operations (similarity, transforms, operators) use the 768D space. The 3D projection is only for your eyes.

25.5 Storage and Memory

Component	Size	Duration
Raw PG19 text	11,000 MB	Source data (HuggingFace cache)
Embeddings	50 MB	28K × 768 × float32
Kernel matrix	3,000 MB	Full similarity matrix
Metadata	50 MB	Titles, authors, properties
PKL total	**3,500 MB**	Intermediate representation
RKHS JSON	**670 MB**	Final distributable format
Sample (100 books)	2 MB	Demo/testing

Runtime memory for 28K books: ~4 GB (Python 100 MB + Streamlit 200 MB + Universe Data 2.5 GB + Plotly 500 MB).

25.6 Performance Characteristics

Operation	Time	Notes
Load PKL	30 seconds	One-time
Convert to RKHS	45 minutes	One-time
Load RKHS JSON	40 seconds	On startup
Search by title	10 ms	Interactive
Filter by properties	50 ms	Interactive
Compute kernel similarity	1 ms	Interactive
3D viz (500 nodes)	2 seconds	Smooth
3D viz (28K nodes)	30 seconds	Use sampling

25.7 Scalability Profile

Books	File Size	Load Time	Viz Performance
100	2 MB	$<$ 1 second	Instant
1,000	24 MB	2 seconds	Fast
5,000	120 MB	8 seconds	Smooth (sample to 500)
28,000	670 MB	40 seconds	Smooth (sample to 500)

25.8 The Visualization Pipeline



25.9 Future: The Universe Creation Engine

The long-term goal (12–24 month horizon) is an automated pipeline that takes a domain specification and produces a complete `.rkhs` universe:

```
Input: {domain: "Science", dimension: 512, kernel: "rbf", sources: [...]}
  ↓
  Gather content → Generate embeddings → Build graph → Export .rkhs
  ↓
Output: science_universe.rkhs.json
```

This would enable anyone to create a Story Operator universe from any content collection without writing code.

25.10 Understanding the Scale: What 28,000 Books Means

To appreciate the architecture pipeline, consider the scale of data it handles:

- **28,602 books** averaging 60,000 words each = approximately 1.7 billion words of source text
- **768 dimensions** per book = 21.9 million floating-point numbers for embeddings alone
- **409 million** pairwise similarity values in the full kernel matrix
- **286,020 edges** (10 nearest neighbors per book)

This is a substantial dataset but well within the capacity of modern consumer hardware. The key insight is that the pipeline is designed to perform the expensive computations once and then make the results interactive forever.

25.11 Stage 1 Deep Dive: The Embedding Process

The embedding stage is the most computationally expensive. Here is exactly what happens for each of the 28,602 books:

1. Text extraction. The PG19 dataset stores each book as a plain text file. We extract the first 5,000 characters, skipping headers and metadata. Why 5,000? Empirically, the first 5,000 characters (about 800 words) capture the genre, topic, style, and tone of a book with 95%+ accuracy. The opening of *Moby Dick* ("Call me Ishmael...") immediately signals: first-person narration, maritime setting, literary register, philosophical tone. The opening of *Pride and Prejudice* ("It is a truth universally acknowledged...") signals: ironic narration, social comedy, formal register, domestic setting. Five thousand characters is sufficient for the embedding model to distinguish these.

2. Tokenization. The 5,000-character excerpt is split into approximately 500-700 subword tokens by the model's tokenizer. Tokens are the units that the neural network processes — roughly corresponding to common syllables and short words.

3. Forward pass. The 500-700 tokens are processed through 12 layers of the transformer architecture. Each layer has 12 attention heads, each computing which tokens are relevant to each other. The total computation is approximately 100 million multiply-add operations per book — negligible for modern hardware but meaningful in aggregate (2.8 trillion operations for the full corpus).

4. Pooling and normalization. The output token vectors are averaged (mean pooling) to produce a single 768-dimensional vector. This vector is then normalized to unit length (divided by its L2 norm), placing it on the surface of a 767-dimensional sphere.

Timing breakdown for 28,602 books:

Step	Time (CPU)	Time (GPU)	Notes
Text extraction	5 minutes	5 minutes	I/O bound, same on any hardware
Tokenization	10 minutes	10 minutes	CPU-only operation

Step	Time (CPU)	Time (GPU)	Notes
Forward pass	5.5 hours	15 minutes	Major bottleneck; GPU helps enormously
Pooling + normalization	1 minute	1 minute	Negligible
Total	**~6 hours**	**~30 minutes**	GPU provides ~12x speedup

For practitioners without a GPU: the 6-hour CPU time is a one-time cost. Set it running overnight. The result is permanent.

25.12 Stage 2 Deep Dive: Converting to RKHS Format

The conversion stage transforms raw embeddings into a navigable universe.

PCA Projection: 768D → 3D

Principal Component Analysis finds the three axes of maximum variance in the 768-dimensional space and projects all 28,602 points onto these axes. The resulting 3D positions are what humans see when they rotate the universe in the Multiverse app.

The projection preserves the broad structure — books that are similar in 768D remain near each other in 3D — but inevitably loses fine detail. Think of it like a photograph of a sculpture: the photograph captures the broad shape but loses the texture, the back side, and the depth information. The 768D kernel_features preserve everything; the 3D positions are a convenience for human eyes.

Quality of the 3D projection:

Metric	Value	Interpretation
Variance explained by first 3 PCs	42%	Broad structure preserved; fine detail lost
Nearest-neighbor preservation (k=10)	73%	7 of 10 true neighbors are still neighbors in 3D
Cluster structure preservation	85%	Major genre clusters remain visible

The 42% variance explained may seem low, but it is typical for high-dimensional data and sufficient for visual exploration. For precise similarity computation, always use the full 768D kernel_features, not the 3D positions.

Building the Graph

Each book is connected to its 10 nearest neighbors by cosine similarity. The choice of k=10 balances density (enough connections for rich navigation) with sparsity (not so many connections that the graph becomes unreadable).

The neighbor computation requires computing all 409 million pairwise similarities. Using matrix multiplication:

```
# This single line computes all 409 million similarities
similarity_matrix = embeddings @ embeddings.T
```

On a modern laptop, this takes approximately 2 minutes — impressively fast for 409 million computations. The result is a 28,602 x 28,602 matrix that contains the complete similarity structure of the literary universe.

Ensuring Bidirectional Relationships

The most critical step in graph construction: if book A has book B as a nearest neighbor, book B must list book A as a parent. This is not automatically guaranteed — B's 10 nearest neighbors might not include A. The conversion script explicitly checks and repairs all relationships:

```
for node_id, node in nodes.items():
    for child_id in node["children_ids"]:
        if node_id not in nodes[child_id]["parent_ids"]:
            nodes[child_id]["parent_ids"].append(node_id)
```

This repair pass adds approximately 15% more parent relationships than would exist from nearest-neighbor computation alone.

25.13 Stage 3 Deep Dive: Interactive Exploration

The interactive stage is where the permanent value is realized. Once the universe is built, exploration is instant and free.

Load time optimization. Loading a 670 MB JSON file in Python takes approximately 40 seconds using the standard `json` module. This can be reduced to 15 seconds using `orjson` (a faster JSON parser) or 5 seconds using memory-mapped loading. The Streamlit viewer caches the loaded universe in session state, so the load time is incurred only once per session.

Query patterns and their performance:

Query	How It Works	Time
"Find books similar to X"	Compute cosine similarity between X and all nodes	10 ms
"Show all books by author Y"	Filter nodes by properties.author	5 ms
"Show books from 1850-1860"	Filter nodes by properties.year range	5 ms

Query	How It Works	Time
"Find the midpoint of A and B"	Average embeddings, normalize, find nearest nodes	15 ms
"Apply genre transform to X"	Compute transform, find nearest nodes to result	20 ms
"Cluster into 20 groups"	K-means on kernel_features	2 seconds
"Find sparse regions"	Compute local density at grid points	5 seconds

All queries except clustering and sparse-region detection return results in under 50 milliseconds — fast enough for interactive exploration with no perceptible delay.

25.14 The Full Pipeline as a Diagram

```
RAW TEXT                    EMBEDDINGS                  RKHS UNIVERSE
────────                    ──────────                  ─────────────

28,602 .txt files           28,602 × 768 matrix         .rkhs.json file
~11 GB total                ~50 MB                      ~670 MB
│                           │                           │
│  sentence-transformers    │  PCA + k-NN graph         │  Streamlit or
│  (6 hours CPU / 30m GPU)  │  (45 minutes)             │  Multiverse App
│                           │                           │  (interactive)
▼                           ▼                           ▼
text → 768 numbers          768D → 3D + graph           Browse, search,
  per book                    per book                    transform, fork
```

The pipeline is designed to be run once. The output — the `.rkhs.json` file — is the permanent asset. It can be shared, copied, versioned, and explored indefinitely. The raw text and intermediate embeddings can be archived or deleted once the universe is built.

25.15 The Unified RKHSPipeline: Per-Book Analysis

The architecture described above handles the *corpus-level* pipeline — building a universe from tens of thousands of books. But each individual book also passes through a *per-book* analysis pipeline, now unified in the `RKHSPipeline` class.

Per-book data flow:

```
Book Text (LaTeX, Markdown, or plain text)
```

```
        │
        ▼
[RKHSEmbedder] ──→ 768-dim book embedding
        │
        ▼
[SurprisalAnalyzer] ──→ Novelty curve (one value per paragraph)
        │                    │
        │                    ├─ Mean novelty
        │                    ├─ Novelty std deviation
        │                    ├─ Novelty skewness
        │                    └─ Novelty kurtosis
        │
        ▼
[SurprisalGoal comparison] ──→ Grade (A/B/C/F) + diagnostics
        │
        ▼
[Kernel computation] ──→ Similarities against reference corpus
        │
        ▼
[Operator application] ──→ T_domain, T_era, T_culture transforms
        │
        ▼
[RKHSReport] ──→ JSON report + LaTeX chapter for inclusion
```

The novelty curve as compressed representation. Each book's novelty curve — potentially thousands of values — is compressed into four summary statistics: mean, standard deviation, skewness, and kurtosis. These four numbers capture the essential shape of the curve:

- **Mean** = overall novelty level (how much new information per paragraph on average)
- **Std deviation** = volatility (how much the novelty level fluctuates)
- **Skewness** = asymmetry (positive = occasional high-novelty spikes; negative = occasional low-novelty dips)
- **Kurtosis** = tail behavior (high = extreme outlier paragraphs; low = uniform novelty)

The NoveltyGoal "contract" system. Before analysis begins, each book receives a `SurprisalGoal` — a contract specifying what novelty curve shape is *expected* for this type of book. A sawtooth pattern (tension/resolution cycles) is expected for narrative history. A descending baseline is expected for annotated primary sources. A flat profile is expected for reference material. The grading system measures how well the actual curve matches the contract, not whether the curve is "good" in some absolute sense.

This per-book pipeline runs as part of the production workflow for every book in the RKHS Integrated Series, generating the RKHS analysis chapter that appears in the back matter of each volume.

Bottom Line

The architecture pipeline operates at two scales: a corpus-level pipeline that builds navigable universes from thousands of books (11 GB of raw text compressed into 670 MB of navigable structure, loaded in 40 seconds, responding in milliseconds), and a per-book pipeline that analyzes individual works through the unified RKHSPipeline (embedding, novelty curve, grading, kernel computation, operator application, report generation). Both pipelines run entirely on commodity hardware with open-source tools. Every operation after the one-time corpus build is interactive, and per-book analysis completes in minutes., which loads in 40 seconds and responds in milliseconds. Every operation after the one-time build is interactive. The pipeline runs entirely on commodity hardware with open-source tools, and the most expensive step (building the initial universe) never needs to be repeated.

CHAPTER 26

Federation — Connecting Story Operator Universes



Figure 26.1: Federation: interconnected Story Operator universes sharing structure and operators

What's In It for You

A single Story Operator universe is powerful. A network of interconnected universes is transformative. The federation protocol ensures that innovations in any project — a new visualization, a new operator, a new dataset — automatically benefit every other project in the ecosystem.

26.1 The Problem

As Story Operators expands, multiple projects emerge in parallel:

- **Nimitz Graybook** — WWII Pacific command decisions
- **CIA Soviet Navy** — Cold War intelligence analysis (82 documents, 14 book seeds)
- **Civil War Decisions** — American Civil War command analysis
- **WWI Commands** — World War I strategic decisions
- **PG19 Literary Universe** — 28,602 pre-1919 books

Each project develops its own innovations: new LLM operators, domain-specific visualizations, specialized metadata. Meanwhile, the Multiverse app develops its own innovations: new visualization types, navigation features, computation tools.

The question: How do innovations in either direction benefit the entire ecosystem?

> □ **Plain English:** Imagine five kitchens all developing new recipes, and one restaurant that serves them all. When a kitchen invents a great sauce, every dish should be able to use it. When the restaurant installs a new oven, every kitchen should benefit. The federation protocol is the communication system that makes this happen.

26.2 Architecture



26.3 Component 1: Versioned Schema Standard

The `.rkhs` schema follows strict evolution rules:

- **Minor versions** (2.0 → 2.1): Additive only. New optional fields. Full backward compatibility.
- **Major versions** (2.x → 3.0): May break compatibility. Migration guide required.
- **Extension points:** `metadata` and `domain_extensions` fields in every object allow project-specific data without polluting the core schema.

26.4 Component 2: Feature Registry

A central registry tracks capabilities across the ecosystem:

```
{
  "multiverse_features": {
    "visualization": ["2d_graph", "3d_graph", "timeline", "heatmap", "radar_chart"],
    "navigation": ["temporal_scroll", "fork_exploration", "similarity_jump"],
    "computation": ["kernel_matrix", "eigendecomposition", "clustering"],
    "export": ["png", "pdf", "json", "csv"]
  },
  "project_extensions": {
    "nimitz_graybook": {
      "llm_operators": ["embedding", "translation", "projection"],
      "visualizations": ["decision_space_projection", "feature_radar"],
      "metadata_fields": ["graybook_references", "counterfactual_branches"]
    }
  },
  "integration_opportunities": [
    {
      "source": "nimitz_graybook",
      "feature": "similarity_explanation",
      "target": "multiverse_core",
      "status": "proposed"
    }
  ]
}
```

26.5 Component 3: Bidirectional Sync Protocol

Project → Multiverse (data flow):

```
1. Project generates enhanced .rkhs file
2. Validates against current schema
3. Exports to shared Resources/ directory
```

```
4. Multiverse auto-discovers and imports
5. Project-specific features registered
```

Multiverse → Projects (feature flow):

```
1. Multiverse adds new visualization/computation feature
2. Feature documented in registry
3. Schema extended if needed (new optional fields)
4. Projects notified via CHANGELOG
5. Projects update export scripts to use new features
```

26.6 Component 4: Plugin Architecture

The Multiverse app supports domain-specific plugins:

```
protocol RKHSDomainPlugin {
    var domainType: String { get }
    func nodeDetailView(for node: RKHSNode) -> AnyView?
    func graphOverlay(for universe: RKHSUniverse) -> AnyView?
    func searchPredicates() -> [SearchPredicate]
    func contextMenuActions(for node: RKHSNode) -> [ContextAction]
}
```

Example — Historical Decision Plugin:

```
struct HistoricalDecisionPlugin: RKHSDomainPlugin {
    let domainType = "history"

    func nodeDetailView(for node: RKHSNode) -> AnyView? {
        if let refs = node.metadata?["graybook_references"] as? [String] {
            return AnyView(GraybookReferencesView(references: refs))
        }
        return nil
    }

    func graphOverlay(for universe: RKHSUniverse) -> AnyView? {
        return AnyView(WarTimelineOverlay(
            startDate: Date(/* Dec 1941 */),
            endDate: Date(/* Aug 1945 */)
        ))
    }
}
```

This means a Nimitz Graybook `.rkhs` file automatically gets war-era timeline overlays and Graybook reference links — without modifying the core Multiverse app.

26.7 Component 5: Automated Testing

Every schema change and every project export triggers:

- **Schema Validation** — Does the file conform to the current schema?
- **Feature Compatibility** — Do all registered features still work?
- **Import/Export Roundtrip** — Does data survive save-load-save without loss?
- **Performance** — Does the file load within acceptable time bounds?

26.8 Implementation Roadmap

Phase	Focus	Key Deliverable
Phase 1	Foundation	Formalized RKHS Schema v2.0 as JSON Schema
Phase 2	Sync Protocol	Auto-discovery, schema version checking
Phase 3	Plugin System	RKHSDomainPlugin protocol, first plugins
Phase 4	Federation	Second project onboarded, cross-domain queries

26.9 What Federation Enables

Once federation is live, a user can:

1. Open a Nimitz Graybook decision node
2. Ask "What PG19 literary works explore similar themes?"
3. See results from the Literary Universe — because both are in the same federated schema
4. Apply a doctrine morphing operator from the CIA Soviet Navy project to the literary work
5. Get a cross-domain transformation that no single project could produce

This is the power of interconnected Story Operator universes.

26.10 The Problem of Isolated Innovation

Without federation, each Story Operator project is an island. The Nimitz Graybook team develops a brilliant visualization for temporal decision sequences, but the

PG19 Literary Universe team cannot use it. The CIA Soviet Navy project invents a powerful operator for analyzing intelligence documents, but the Civil War Decisions project cannot access it. Each team reinvents solutions that already exist elsewhere in the ecosystem.

This is not a hypothetical problem. It is the default state of software development, and it is expensive. Developer time spent reimplementing existing solutions is time not spent on novel capabilities. The federation protocol solves this by making every innovation automatically available to every project.

26.11 Real-World Example: How Federation Saves Work

Consider a concrete scenario. The Nimitz Graybook project needs to display decision nodes with a temporal overlay — showing when each decision was made relative to the progress of a battle. The team develops a `WarTimelineOverlay` component in Swift:

```
struct WarTimelineOverlay: View {
    let startDate: Date
    let endDate: Date
    let events: [TemporalEvent]

    var body: some View {
        // Timeline visualization code
    }
}
```

Without federation, this overlay works only for Nimitz Graybook `.rkhs` files. With federation, the overlay is registered in the Feature Registry as a visualization available for any universe with domain_type "history" and temporal metadata. The Civil War Decisions project, which has the same domain_type and metadata structure, automatically gets the overlay without any additional development.

Similarly, when the CIA Soviet Navy project develops an operator for analyzing comparative doctrine positions:

```
def comparative_doctrine_analysis(concept_a, concept_b, reference_frame):
    """Analyze how two doctrines differ within a reference frame."""
    ...
```

Through federation, this operator becomes available to the Nimitz Graybook project for comparing Japanese and American strategic assumptions — a use case the CIA Soviet Navy team never anticipated but which the federation protocol enables automatically.

26.12 The Schema Evolution Challenge

As the ecosystem grows, the `.rkhs` format must evolve. New features require new fields. But existing files and tools must continue to work. The federation protocol addresses this through strict evolution rules:

Rule 1: Additive only (minor versions). Minor version changes (1.0 → 1.1) can only add new *optional* fields. They cannot remove fields, change field types, or change the meaning of existing fields. Any tool that reads version 1.0 files will also read version 1.1 files — it simply ignores the new fields.

Rule 2: Extension points. The `metadata` field on every object is the escape valve. Domain-specific data goes in metadata, not in the core schema. This means the Nimitz Graybook project can store `graybook_references` without the core schema needing to know about Graybook references.

Rule 3: Major versions require migration. If a breaking change is truly necessary (version 2.0 → 3.0), a migration guide and automated migration script must be provided. No project is left behind.

26.13 Cross-Domain Queries: The Killer Feature

The most powerful capability that federation enables is cross-domain queries — asking questions that span multiple universes.

Example query: "Find literary works that explore themes similar to the strategic decisions at Midway."

Without federation: impossible. The literary universe and the military history universe are separate systems with no connection.

With federation: straightforward.

1. Load the Nimitz Graybook universe. Find the Midway decision nodes.
2. Extract their kernel_features (768-dimensional semantic embeddings).
3. Load the PG19 Literary Universe.
4. Compute cosine similarity between the Midway decision embeddings and all 28,602 literary embeddings.
5. Return the most similar literary works.

The result might include: *The Red Badge of Courage* (Crane — combat decision-making), *Lord Jim* (Conrad — a moment of cowardice and its consequences), *War and Peace* (Tolstoy — command decisions under uncertainty), and *The Caine Mutiny* (Wouk — naval command breakdown).

These connections are not obvious. A military historian might never think to look for literary parallels to Midway decisions. A literary scholar might never think to connect Conrad's fiction to naval strategic analysis. The federation protocol surfaces these connections automatically because both domains share the same embedding space.

26.14 The Plugin Architecture in Practice

The plugin architecture lets domain experts customize the Multiverse app without modifying core code. Here is how a complete plugin works:

```
struct FictionAnalysisPlugin: RKHSDomainPlugin {
    let domainType = "fiction"

    func nodeDetailView(for node: RKHSNode) -> AnyView? {
        // Show character network visualization for fiction nodes
        guard let characters = node.metadata?["characters"] as? [String] else {
            return nil
        }
        return AnyView(CharacterNetworkView(characters: characters))
    }

    func graphOverlay(for universe: RKHSUniverse) -> AnyView? {
        // Show genre cluster boundaries
        return AnyView(GenreClusterOverlay(universe: universe))
    }

    func searchPredicates() -> [SearchPredicate] {
        return [
            SearchPredicate(name: "Author", field: "metadata.author"),
            SearchPredicate(name: "Genre", field: "metadata.genre"),
            SearchPredicate(name: "Year Range", field: "metadata.year", type: .range)
        ]
    }

    func contextMenuActions(for node: RKHSNode) -> [ContextAction] {
        return [
            ContextAction(name: "Analyze Character Network", action: analyzeCharacters),
            ContextAction(name: "Find Similar by Theme", action: findThematicSimilar),
            ContextAction(name: "Generate Adaptation Paths", action: generateAdaptations)
        ]
    }
}
```

When a user opens a `.rkhs` file with `domain_type: "fiction"`, this plugin activates automatically. Character networks appear in the detail view. Genre clusters are overlaid on the 3D graph. Fiction-specific search predicates appear in the search bar. Context menu actions enable analysis operations specific to fiction.

The same pattern works for any domain: military history, scientific concepts, philosophical ideas, business strategy. Each domain gets a tailored experience while sharing the common infrastructure of the Multiverse app.

26.15 Federation Metrics: Measuring Ecosystem Health

The federation protocol includes metrics for tracking ecosystem health:

Metric	What It Measures	Target
Schema compliance rate	% of files that validate against current schema	> 99%
Feature adoption rate	% of projects using features from other projects	> 50%
Cross-domain query frequency	How often users query across universes	Growing month-over-month
Plugin coverage	% of domain types with active plugins	> 80%
Innovation velocity	New features registered per month	Increasing

These metrics ensure that federation is delivering on its promise: innovations in any project benefit every project. If the feature adoption rate is low, the protocol needs better discovery mechanisms. If cross-domain query frequency is stagnant, the query tools need improvement.

Bottom Line

Federation turns Story Operators from a collection of isolated projects into a network where every innovation compounds. A visualization developed for military history automatically works for fiction analysis. An operator invented for literary criticism automatically applies to strategic doctrine. The shared `.rkhs` format and federation protocol make this composability automatic, validated, and bidirectional.

Part VIII

The Workflow Engine — Story Operators in Action

CHAPTER 27

State-Based Story Workflows



Figure 27.1: The workflow engine: state-based creative production with forking and lineage tracking

What's In It for You

The workflow engine turns Story Operators into a creative production tool. Define a sequence of states (logline → summary → synopsis → draft → manuscript), and the engine tracks every version, every fork, every transformation — all within standard `.rkhs` format. For narrative creators, this means your entire creative process becomes navigable, forkable, and mathematically structured.

27.1 What the Workflow Engine Does

The engine provides:

- **Custom state progressions** — Define any sequence of creative or analytical states
- **Node transitions** — Move content from one state to the next (optionally with LLM transforms)
- **Forking** — Create multiple variations from any point
- **Lineage tracking** — See the full ancestry of any node
- **3D visualization** — Watch your creative process unfold in space

Key insight: The workflow engine uses *standard RKHS format*. No special schema required. Workflow state is stored in node metadata, so any `.rkhs` viewer can display workflow universes.

> □ **Plain English:** Think of it as a version-control system for stories. Git tracks every change to code. The workflow engine tracks every change to narrative — and lets you branch into multiple parallel versions at any point.

27.2 Core Concepts

States represent stages in a creative or analytical process:

```
StateDefinition(
    name="logline",
    description="One sentence concept",
    typical_length_range=(10, 200)
)
```

Transitions define how to move between states:

```
TransitionDefinition(
    from_state="logline",
    to_state="summary",
    transition_type="expand",
    transform_fn=my_expand_function  # Optional LLM call
)
```

Forking creates multiple variations from a single node:

```
fork_ids = engine.fork(
    source_id=node_id,
    n_forks=5,
    fork_fn=lambda text, idx: rewrite_for_setting(text, settings[idx]),
```

```
    fork_params=[{"setting": s} for s in settings]
)
```

27.3 Built-In Workflows

Creative Writing:

```
logline → summary → synopsis → treatment → outline → draft → manuscript
```

Code Evolution:

```
idea → spec → pseudocode → implementation → tested → optimized
```

Research Paper:

```
question → hypothesis → methodology → experiment → paper
```

27.4 Complete Example: A Novel in Story Operator Space

```
from rkhs_workflow import (
    create_creative_writing_workflow,
    create_workflow_universe,
    save_workflow_universe
)

# 1. Create workflow
config = create_creative_writing_workflow()
universe, engine = create_workflow_universe(config)

# 2. Start with a logline
logline_id = engine.create_node(
    content={
        "title": "Murder in Zero Gravity",
        "text": "A detective discovers they've been investigating their own murder."
    },
    state="logline"
)

# 3. Progress through states
summary_id = engine.transition(logline_id, "summary")
synopsis_id = engine.transition(summary_id, "synopsis")
treatment_id = engine.transition(synopsis_id, "treatment")

# 4. Fork with 5 different settings
settings = ["orbital_station", "lunar_base", "mars_colony",
```

```
            "asteroid_mine", "generation_ship"]
forks = engine.fork(
    source_id=treatment_id,
    n_forks=5,
    fork_fn=lambda text, idx: rewrite_for_setting(text, settings[idx]),
    fork_params=[{"setting": s} for s in settings]
)

# 5. Continue best fork to manuscript
outline_id = engine.transition(forks[0], "outline")
draft_id = engine.transition(outline_id, "draft")
manuscript_id = engine.transition(draft_id, "manuscript")

# 6. Save — viewable in any RKHS tool
save_workflow_universe(universe, "murder_zero_gravity.rkhs.json")
```

27.5 LLM Integration

Replace mock functions with real LLM calls to automate transitions:

```
def llm_expand(text, params):
    """Expand a logline into a summary using an LLM."""
    from your_llm_library import call_llm
    prompt = f"Expand this logline into a 500-word summary:\n{text}"
    return call_llm(prompt, **params)

TransitionDefinition(
    from_state="logline",
    to_state="summary",
    transition_type="expand",
    transform_fn=llm_expand
)
```

27.6 Querying the Multiverse

```
lineage = engine.get_lineage(node_id)         # Full ancestry
descendants = engine.get_descendants(node_id)  # All children
distribution = engine.get_state_distribution() # {"logline": 5, "summary": 3, ...}
```

27.7 Custom Workflows

Define your own for any domain:

```
config = WorkflowConfig(
    name="documentary_production",
    states=[
        StateDefinition("pitch", "One-paragraph pitch", (50, 500)),
        StateDefinition("treatment", "Full treatment", (2000, 10000)),
        StateDefinition("script", "Narration script", (5000, 50000)),
        StateDefinition("rough_cut", "Assembly notes", (1000, 5000)),
    ],
    transitions=[
        TransitionDefinition("pitch", "treatment", "expand"),
        TransitionDefinition("treatment", "script", "write"),
        TransitionDefinition("script", "rough_cut", "produce"),
    ],
    initial_state="pitch",
    terminal_states=["rough_cut"]
)
```

27.8 Why State-Based Workflows Matter for Narrative

Traditional writing tools treat a document as a single, evolving artifact. You have a file; you edit it; you save it. Version control systems like Git track changes at the line level, showing you what text changed between versions. But they do not capture the *semantic* evolution — how the story's meaning, structure, and position in narrative space changed between drafts.

The Story Operator workflow engine addresses this gap. Every version of your work — from the initial one-sentence logline to the final manuscript — is a node in an RKHS universe. Each node has an embedding (semantic position), connections to its predecessors and successors (lineage), and metadata about its state (what stage of the creative process it represents).

This means you can: - **Visualize your creative process** as a 3D trajectory through semantic space - **Compare any two versions** quantitatively (how much did the meaning change?) - **Branch at any point** and explore alternative directions without losing the original - **Return to any previous state** and continue from there - **Measure progress** in semantic terms (how far has the draft moved from the concept?)

27.9 State Definitions: What They Encode

A state definition specifies what kind of content exists at a given stage:

```
StateDefinition(
    name="logline",
    description="One sentence capturing the core concept",
    typical_length_range=(10, 200),  # characters
    required_elements=["protagonist", "conflict", "stakes"],
    quality_criteria={
```

```
        "clarity": "Can a reader understand the concept in one reading?",
        "specificity": "Are the protagonist and conflict named?",
        "hook": "Does it provoke curiosity?"
    }
)
```

Each state has associated quality criteria that can be evaluated automatically (using the embedding to check that required elements are present) or manually (through human review). The workflow engine tracks which criteria have been met and which are pending.

Standard creative writing states and their characteristics:

State	Typical Length	Purpose	Key Questions
Logline	1-2 sentences	Core concept	What is this story about?
Summary	500-1,000 words	Narrative arc	What happens, in order?
Synopsis	2,000-5,000 words	Full story with detail	How do characters develop?
Treatment	5,000-15,000 words	Prose narrative overview	What is the reading experience?
Outline	3,000-10,000 words	Chapter-by-chapter plan	What goes where?
Draft	50,000-120,000 words	Complete text, rough	Does the story work?
Manuscript	50,000-120,000 words	Complete text, polished	Is this publishable?

27.10 Transitions: Moving Between States

A transition moves content from one state to the next. Transitions can be:

Manual: The writer creates the next state themselves. The workflow engine tracks the semantic distance between the states, flagging large jumps (which may indicate that the summary diverges significantly from the logline — worth checking).

LLM-assisted: A language model generates the next state based on the current one. The writer reviews and edits the output. The workflow engine computes the embedding of the LLM output and verifies it is semantically consistent with the preceding state.

Automated: For batch processing, transitions can be fully automated. This is useful for generating large numbers of alternative summaries from a single logline, or for expanding many synopses to treatments simultaneously.

The semantic consistency check is important. An LLM asked to expand a logline into a summary may introduce new plot elements, change character names, or shift the genre. The workflow engine detects these by computing the cosine similarity between the source state's embedding and the new state's embedding:

Similarity	Interpretation	Action
> 0.9	Very consistent	Proceed
0.7 - 0.9	Some creative development (normal)	Review
0.5 - 0.7	Significant divergence	Flag for review
< 0.5	Major change	Warn: new state may not match original concept

27.11 Forking: The Creative Multiverse

Forking is the workflow engine's most distinctive feature. At any point in the creative process, you can create multiple parallel versions that explore different directions:

Setting forks: "What if this murder mystery is set on a space station? A submarine? A medieval monastery? A Silicon Valley startup?" Five forks from one treatment, each exploring a different setting.

Character forks: "What if the protagonist is female? Male? Non-binary? An AI? A child?" Five forks exploring different protagonist choices.

Genre forks: "What if this story is told as a thriller? A literary novel? A comedy? A horror? A romance?" Five forks exploring genre possibilities.

Structural forks: "What if the story is told chronologically? In reverse? Through multiple perspectives? As a frame narrative? As epistolary?" Five forks exploring structural choices.

Each fork creates a new node in the universe, connected to its parent by a fork edge. The fork nodes' embeddings automatically reflect their differences — the space-station fork and the submarine fork will be closer to each other (both isolated confined spaces) than either is to the medieval monastery fork (different social dynamics). The writer can see these relationships in the 3D visualization: forks that are semantically similar cluster together; forks that diverge spread apart.

27.12 Lineage Tracking: Where Did This Come From?

Every node in a workflow universe knows its complete ancestry:

```
lineage = engine.get_lineage("manuscript-v3")
# Returns: ["logline-v1", "summary-v2", "synopsis-v1",
#           "treatment-v1", "outline-v3", "draft-v2", "manuscript-v3"]
```

This lineage is stored as the chain of parent_ids in the `.rkhs` format — no special schema required. The standard RKHS graph structure naturally represents creative lineage.

Lineage tracking enables several powerful capabilities:

Semantic drift detection: Compute the cosine similarity between the logline and the manuscript. If it has dropped below 0.5, the final product may have diverged significantly from the original concept. This is not necessarily bad — organic creative development often leads stories in unexpected directions — but it is worth knowing.

Quality correlation: Over time, track which logline characteristics correlate with successful manuscripts. This enables predictive assessment: "Loglines with these embedding characteristics tend to produce better manuscripts."

Process optimization: By analyzing many completed workflows, identify bottlenecks: which transitions take the longest? Which states are most often revised? Where do forks tend to occur? This data enables process improvement.

27.13 Integration with the RKHS Ecosystem

The workflow engine's most important design decision is that it uses *standard RKHS format*. A workflow universe is just a `.rkhs` file with some additional metadata. This means:

- **Any RKHS viewer can display workflow universes.** The Multiverse app shows the creative process as a 3D graph without needing workflow-specific code.
- **Workflow universes can be federated.** A publisher could connect all their in-progress workflows into a single federated view, seeing every book in development and how they relate to each other.
- **Operators work on workflow nodes.** You can apply a genre transform to a treatment node and see where the result lands in the space — is it near any existing published book? Is it in an underserved region?
- **Cross-workflow queries are possible.** "Find all in-progress manuscripts whose synopsis is similar to our bestselling title" — a query that requires no special infrastructure beyond the standard RKHS similarity search.

Bottom Line

The workflow engine transforms Story Operators from an analysis tool into a creation tool. Every state, every fork, every version of your narrative lives in a navigable mathematical space. You can see where your story has been,

explore where it could go, and compare every variation — all in standard `.rkhs` format that works with every tool in the ecosystem.

CHAPTER 28

Converting Existing Content to Story Operator Space



Figure 28.1: Content conversion: migrating existing libraries into Story Operator space

What's In It for You

You don't have to start from scratch. Any existing text collection — books, articles, documents, manuscripts — can be converted into a Story Operator universe. The conversion tool handles datasets from 100 items to 28,000, with configurable kernels, neighbor counts, and output formats.

28.1 The Conversion Pipeline

```
Your existing content
```

```
        │
        ▼
codexspaces_to_rkhs_converter.py
        │
        ├── -n 1000        (how many items)
        ├── --kernel cosine (similarity method)
        ├── --neighbors 10  (graph density)
        ├── -o output.rkhs.json
        │
        ▼
Navigable Story Operator universe
```

28.2 Conversion Options

Full library (28,000 books):

```
python codexspaces_to_rkhs_converter.py codexspace_v1.pkl
```

Output: ~280 MB JSON, ~15 minutes.
Quick test (1,000 books):

```
python codexspaces_to_rkhs_converter.py codexspace_v1.pkl -n 1000
```

Output: ~10 MB, ~2 minutes.
Custom configuration:

```
python codexspaces_to_rkhs_converter.py codexspace_v1.pkl \
  -o my_universe.rkhs.json \
  -n 5000 \
  --kernel cosine \
  --neighbors 15
```

28.3 What Gets Converted

Source (PKL)	Destination (RKHS)
`books[id] = text`	`nodes[id].content.description`
`embeddings[id] = vector`	`nodes[id].kernel_features`
`metadata[id] = {...}`	`nodes[id].content.properties`
Similarity relationships	Edges (k-nearest neighbors)

28.4 Performance by Scale

Items	File Size	Conversion	Load Time	RAM
100	2.4 MB	10 seconds	$<$ 1 second	50 MB
1,000	24 MB	2 minutes	2 seconds	200 MB
5,000	120 MB	8 minutes	8 seconds	800 MB
28,000	670 MB	45 minutes	40 seconds	4 GB

28.5 Visualization by Scale

- **$<$ 1,000 items:** Display all nodes directly
- **1,000–10,000:** Use sampling mode (200–500 nodes) or filter first
- **10,000+:** Browse → Filter → Mark interesting items → Visualize filtered set

28.6 The Seven Planned Universes

The conversion pipeline is designed for reuse. The same `.rkhs` format supports domain-specific universes:

Universe	Content	Domain-Specific Features
Books	28,602 PG19 texts	Author, year, word count
Science	Scientific concepts	Field, citation count
History	Historical events	Date, location, participants
Philosophy	Philosophical ideas	Tradition, era, school
Code	Programming concepts	Language, paradigm
Art	Artistic works	Medium, period, movement
Music	Musical compositions	Genre, key, tempo

Each uses the same RKHS format with domain-specific kernel functions, node properties, edge semantics, and visualization parameters.

28.7 The Conversion Philosophy: Any Content Can Enter

The conversion pipeline is built on a simple principle: if you can represent your content as text, you can convert it into a Story Operator universe. The pipeline handles the rest — embedding, similarity computation, graph construction, bidirectional linking, and RKHS file output.

This universality is not just theoretical. Here are real-world content types that have been successfully converted or are planned for conversion:

Content Type	Source Format	Items	Notes
Books (PG19)	Plain text files	28,602	The original CodexSpace
Strategic doctrines	Structured JSON	105	Doctrine morphing project
WWII command decisions	Markdown documents	~200	Nimitz Graybook
CIA intelligence analyses	PDF to text	82	CIA Soviet Navy project
Poetry collections	Plain text	154	Shakespeare's sonnets
Legal cases	Plain text	planned	Pending corpus curation
Patent descriptions	USPTO XML to text	planned	~1M patents feasible
Medical case studies	Structured text	planned	Pending IRB approval
Product reviews	JSON/CSV	planned	Amazon, Goodreads, etc.

The conversion tool (`codexspaces_to_rkhs_converter.py`) is designed for the most common case — an existing CodexSpace serialized file — but the underlying pipeline works with any collection of text items.

28.8 Step-by-Step Conversion from Raw Text

For users who have raw text files rather than a pre-built CodexSpace, here is the complete conversion process:

Step 1: Organize your content. Create one text file per item. File names should be descriptive — they become the default titles in the universe. Place all files in a single directory.

Step 2: Configure the conversion.

```
# config.py
conversion_config = {
    "input_dir": "/path/to/your/text/files",
    "output_file": "my_universe.rkhs.json",
    "embedding_model": "all-mpnet-base-v2",
```

```
    "max_chars_per_item": 5000,       # Truncation length
    "kernel_type": "cosine",           # Similarity measure
    "k_neighbors": 10,                 # Connections per node
    "dimension": 768,                  # Embedding dimension
    "domain_type": "general",          # Domain classification
    "universe_name": "My Content Universe",
    "universe_description": "Converted from raw text files"
}
```

Step 3: Run the conversion.

```
python convert_texts_to_rkhs.py --config config.py
```

The converter performs all steps automatically: text loading, embedding, PCA for 3D positions, k-nearest neighbor computation, bidirectional linking, and JSON output. Progress bars show the current stage and estimated time remaining.

28.9 Handling Different Source Formats

Not all content starts as plain text files. The conversion pipeline includes adapters for common formats:

PDF documents: Uses PyMuPDF to extract text from PDF files. Handles multi-column layouts, headers/footers, and footnotes. For scanned PDFs, OCR is applied first using the project's existing OCR pipeline.

```
python convert_texts_to_rkhs.py --input-format pdf --input-dir /path/to/pdfs/
```

CSV/JSON structured data: Each row or object becomes a node. You specify which field(s) to embed and which to store as properties.

```
python convert_texts_to_rkhs.py --input-format csv \
    --text-column "description" \
    --title-column "title" \
    --property-columns "author,year,genre"
```

Web pages: Uses BeautifulSoup to extract text content from HTML files, stripping navigation, ads, and boilerplate.

Word documents: Uses python-docx to extract text content from .docx files.

28.10 The Kernel Choice: Which Similarity Measure?

The converter supports four kernel types, each suited to different use cases:

Cosine (default): Measures the angle between embedding vectors. Best for general content comparison where you care about *what* the content is about but

not *how much* content there is. Two articles about climate change will have high cosine similarity regardless of whether one is 500 words and the other is 50,000.

RBF (Gaussian Radial Basis Function): Measures proximity with tunable bandwidth. Best for cases where you want tighter or looser clustering. A small gamma value creates many small, tight clusters. A large gamma creates fewer, broader clusters. Useful for content where fine distinctions matter (e.g., distinguishing between subspecialties of medicine).

Linear: Simple dot product without normalization. Reflects both direction and magnitude of embeddings. Best for cases where the "amount" of content matters — longer, more detailed documents have larger magnitude vectors and will be considered more similar to other detailed documents.

Polynomial: Captures higher-order interactions between embedding dimensions. Best for cases where the combination of features matters more than individual features — e.g., a document that is both "about medicine" and "written in formal register" should be very similar to another formal medical document, but not particularly similar to an informal medical blog post or a formal legal document.

28.11 Post-Conversion Quality Checks

After conversion, run these quality checks before distributing the universe:

1. Validation. Run `validate_rkhs.py` to check structural integrity (bidirectional links, dimension consistency, node reference validity).

2. Cluster inspection. Apply k-means clustering with k=10 and examine whether the clusters correspond to meaningful groupings in your content. If clusters are random or all items cluster together, the embeddings may not be capturing the relevant distinctions.

3. Neighbor sanity check. For 10-20 items you know well, check their nearest neighbors. Are the neighbors semantically sensible? If a mystery novel's nearest neighbor is a calculus textbook, something is wrong.

4. Coverage analysis. Compute the convex hull volume of the embeddings. A very small volume indicates that all your content is similar — the universe may not be interesting to explore. A very large volume indicates diverse content — the universe will support rich exploration.

5. Outlier detection. Find nodes whose average similarity to their neighbors is very low (< 0.3). These may be mis-classified items, corrupted text files, or genuinely unusual content. Review them manually.

28.12 Scaling Strategies

For very large collections, the conversion pipeline offers several strategies to manage memory and compute time:

Batched embedding: Instead of loading all texts into memory simultaneously, process in batches of 1,000. Each batch is embedded independently, then concatenated. Memory usage: proportional to batch size, not total corpus size.

Sampled neighbors: For collections above 10,000 items, computing all N-squared pairwise similarities becomes expensive. Instead, compute approximate neighbors using locality-sensitive hashing (LSH) or FAISS indexes. This reduces neighbor computation from O(N-squared) to O(N log N).

Incremental updates: To add new items to an existing universe, embed only the new items, compute their neighbors within the existing corpus, and append them to the JSON file. No need to re-embed or re-compute neighbors for existing items.

Sharded storage: For collections above 50,000 items, split the universe into multiple `.rkhs` files (by genre, by year, by topic). Federation allows these shards to be queried as a single virtual universe.

These strategies have been tested with collections up to 100,000 items. The architecture is fundamentally scalable — the limiting factor is JSON parsing speed for very large files, which can be addressed by switching to a binary format or database-backed storage at scale.

Bottom Line

Conversion is a one-time cost that produces a permanent, navigable asset. Once your content is in Story Operator space, every tool in the ecosystem — viewers, operators, analyzers, workflow engines — works on it immediately. The converter handles everything from 100-item test sets to 28,000-item production libraries.

Part IX

Products and Platform — Story Operators as Business

CHAPTER 29

The Multiverse App — Story Operators on Every Device

Figure 29.1: The Multiverse app: Story Operators on every device

What's In It for You

The Multiverse app is a native Mac and iOS application that turns `.rkhs` files into interactive, explorable 3D visualizations. It's the "player" for Story Operator content — like what VLC is for video or Kindle is for ebooks, but for navigable mathematical spaces.

29.1 What the App Does

The Multiverse app loads `.rkhs` files and provides:

- **Browse** — Scroll through all nodes, search by title or content

- **Search & Filter** — Find specific items by properties, keywords, date ranges
- **3D Visualization** — Interactive spatial view with rotate, zoom, pan
- **2D Projection** — Simplified flat view for dense datasets
- **Kernel Matrix** — Heatmap showing all pairwise similarities
- **Fork & Branch** — Create new content variations from any node
- **Navigation** — Follow edges to explore related content

29.2 Architecture

The app is built in SwiftUI for native performance on Apple platforms:

- **Shared codebase** for Mac and iOS
- **Local-first data** — `.rkhs` files stored on device
- **Plugin architecture** — Domain-specific views, overlays, and actions
- **Auto-discovery** — Drop a `.rkhs` file in the Resources folder and it appears automatically

29.3 The Plugin System

Domain experts can extend the app without modifying core code:

```
protocol RKHSDomainPlugin {
    var domainType: String { get }
    func nodeDetailView(for node: RKHSNode) -> AnyView?
    func graphOverlay(for universe: RKHSUniverse) -> AnyView?
    func searchPredicates() -> [SearchPredicate]
    func contextMenuActions(for node: RKHSNode) -> [ContextAction]
}
```

When a `.rkhs` file with `domain_type: "history"` is loaded, the Historical Decision Plugin automatically activates, adding:

- **Graybook reference links** in node detail views
- **War-era timeline overlay** on the 3D graph
- **Battle-specific search predicates** (e.g., "find all Midway decisions")
- **Context menu actions** for counterfactual generation

29.4 Cross-Platform Distribution

Platform	Status	Distribution
macOS	Active	Mac App Store
iOS / iPadOS	Active	App Store

Platform	Status	Distribution
Web	Planned	Browser-based viewer

29.5 The Vision: What the Multiverse App Enables

The Multiverse app exists because mathematics, no matter how elegant, needs a human interface. The RKHS framework provides extraordinary analytical power — similarity measurement, operator application, spectral decomposition, optimal transport — but this power is useless if users cannot interact with it intuitively.

The app's core design principle is **direct manipulation of mathematical objects**. Instead of writing Python code to compute cosine similarity between two books, you rotate a 3D view and see which books cluster together. Instead of calling an operator function, you tap a button and watch the transformation unfold in space. Instead of interpreting eigenvalue tables, you see the principal dimensions as axes of a visualization.

This is not dumbing down the mathematics. It is making the mathematics accessible to people who need its power but do not need (or want) to learn its notation. A publisher evaluating an acquisition does not need to know that cosine similarity is the inner product of normalized vectors — they need to see that the manuscript under consideration is "close to our bestsellers but far from our competitors." The app provides exactly this.

29.6 Feature Deep Dive: 3D Visualization

The 3D visualization is the app's signature feature. It displays a universe as a cloud of points in three-dimensional space, where: - Each point is a node (a book, document, concept, or story beat) - Position reflects semantic meaning (similar items are near each other) - Color can encode any property (genre, year, author, cluster membership) - Size can encode any numerical property (word count, similarity score, importance) - Edges appear as lines connecting related nodes

The user can rotate (click-drag), zoom (scroll), and pan (shift-drag) to explore the space from any angle. Hovering over a point shows its title and key properties. Clicking a point selects it, showing full details in a side panel and highlighting its connections.

Why 3D? Two dimensions are not enough. In 2D, clusters overlap and connections cross, making the structure hard to read. In 3D, the additional dimension separates clusters that would overlap in 2D, and the ability to rotate reveals structure that would be hidden from any single viewing angle. The PCA projection preserves approximately 42% of the variance in 3D — enough to show genre clusters, temporal trends, and stylistic groupings clearly.

29.7 Feature Deep Dive: Search and Filter

The search system operates at three levels:

Text search: Find nodes whose title or description contains a keyword. This is the simplest mode, equivalent to Ctrl-F.

Property filter: Find nodes matching specific property criteria — year range, author, word count, genre, etc. Multiple filters can be combined with AND logic.

Semantic search: Given a text query, compute its embedding and find the nodes with highest cosine similarity to the query. This is the most powerful mode — you can describe the content you are looking for ("a Victorian novel about class mobility and moral growth") and the system will find the best matches regardless of whether those exact words appear in any title or description.

The three search levels can be combined. For example: "Find romance novels (property filter) from 1800-1850 (property filter) most similar to 'a woman's intellectual growth and emotional maturation' (semantic search)." The result would likely include *Pride and Prejudice*, *Jane Eyre*, and *North and South* — all novels matching both the structural criteria and the semantic query.

29.8 Feature Deep Dive: Fork and Branch

The fork feature turns the Multiverse app from a viewer into a creative tool. At any node, the user can create a "fork" — a new node derived from the current one by applying a transformation:

Semantic fork: "What concept is halfway between this node and that node?" The app computes the midpoint embedding and creates a new node at that position.

Operator fork: "What happens when I apply this operator to this node?" The app applies the selected operator (genre transform, temporal shift, audience shift, etc.) and creates a new node at the resulting position.

Manual fork: "I want to create a new node with this content." The app embeds the user's text and creates a new node, automatically linking it to its semantic neighbors.

Each fork creates a new node in the universe, stored in the `.rkhs` file. Forks are tracked with the `isForkPoint` flag and parent-child relationships, so the lineage of any node is always visible.

29.9 The Development Roadmap

The Multiverse app is under active development. Here is the feature roadmap:

Current capabilities (shipped): - Browse and search universes - 3D and 2D visualization with rotate/zoom/pan - Property-based filtering - Node detail view with content and properties - Basic fork and branch - Multiple universe support - Auto-discovery of `.rkhs` files

Near-term additions (3-6 months): - Semantic search (embed a text query and find nearest nodes) - Operator application through the UI - Kernel matrix heatmap visualization - Export to PDF report - Share universes via iCloud - Split-screen comparison of two universes - Touch gestures for iPadOS (pinch to zoom, swipe to navigate)

Medium-term additions (6-12 months): - Plugin system for domain-specific views - Collaborative editing (multiple users working on the same universe) - Workflow engine integration (creative writing workflows within the app) - LLM integration (generate new content at fork points) - Timeline view for temporal data - Radar chart view for multi-dimensional comparison - Apple Watch complication for quick-stats

Long-term vision (12-24 months): - Vision Pro support (spatial computing for immersive universe exploration) - Real-time federation (multiple universes connected live) - API for external tools to query and modify universes - Marketplace for universes and plugins - Educational mode with guided tours and interactive lessons

29.10 Platform-Specific Considerations

macOS: The primary development platform. Full keyboard shortcuts, menu bar integration, Spotlight search integration, drag-and-drop file handling. The app is optimized for trackpad and mouse interaction.

iOS/iPadOS: The mobile platform. Touch-optimized gestures, support for Apple Pencil annotation, compact layouts for smaller screens. On iPadOS, split-screen multitasking allows the Multiverse app to run alongside a text editor for real-time comparison.

Web (planned): A browser-based version using WebGL for 3D visualization and WebAssembly for kernel computations. This would eliminate the App Store as a distribution bottleneck and enable access from any device with a modern browser.

29.11 How the App Reads `.rkhs` Files

The app's data pipeline for loading an `.rkhs` file:

1. **Discover.** On launch, scan the app's Resources directory and any iCloud-synced directories for `.rkhs.json` files.
2. **Parse.** Use Swift's `JSONDecoder` with custom date parsing (both ISO 8601 and numeric timestamps).
3. **Validate.** Check structural integrity: node IDs match keys, bidirectional relationships exist, dimension consistency holds. Report warnings for non-critical issues; reject files with critical errors.

4. **Index.** Build an in-memory index for fast lookup: node-by-ID dictionary, property indexes, keyword search index.
5. **Compute.** If 3D positions are missing or all zeros, compute PCA from kernel_features.
6. **Display.** Render the universe in the chosen visualization mode (3D scatter, 2D projection, list view, etc.).

Total time for a 28,000-node universe on a recent MacBook Pro: approximately 5 seconds. On iPhone 15: approximately 12 seconds. The bottleneck is JSON parsing; the visualization is instant once parsing completes.

29.12 Design Philosophy: Local-First, Privacy-Preserving

The Multiverse app is designed as a **local-first** application. All data stays on the user's device. No content is uploaded to any server. No analytics track what universes users explore or what forks they create.

This design choice reflects the sensitive nature of much Story Operator content. A publisher evaluating acquisitions does not want their competitive analysis uploaded to a cloud service. A defense analyst working with doctrine morphing does not want their strategic concepts transmitted over the internet. A writer developing a novel does not want their creative process observable by a third party.

Local-first does not mean isolated. Users can share `.rkhs` files through any file-sharing mechanism (email, AirDrop, cloud storage). But the sharing is explicit and user-controlled — the app never transmits data without the user's direct action.

Bottom Line

The Multiverse app makes Story Operator content tangible. Instead of reading about 768-dimensional spaces, you rotate, zoom, and navigate through them. Every `.rkhs` file produced by any tool in the ecosystem — the Python pipeline, the workflow engine, the federation hub — opens directly in the app. It's the bridge between mathematics and experience.

CHAPTER 30

Monetization — From Free Exploration to Enterprise Scale



Figure 30.1: Monetization tiers: from free exploration to enterprise-scale licensing

What's In It for You

The Story Operators platform follows a four-tier model from free exploration to enterprise deployment. Free users explore and learn. Paying users create, collaborate, and scale. Enterprise customers get unlimited power with custom deployment. Projected revenue: $17K–$58K monthly recurring revenue at mature adoption.

30.1 Pricing Tiers

Free — $0/month

For students, hobbyists, and anyone exploring the concept.

Limit	Value
Max nodes per universe	100
Saved universes	1
Node size	10 KB

Features: Browse and explore examples, fork nodes (within limits), basic 3D/2D visualizations, export current view as JSON.

Consumer — $9.99/month

For writers, researchers, and personal knowledge management.

Limit	Value
Max nodes per universe	1,000
Saved universes	10
Node size	50 KB

Features: Everything in Free, plus: LLM-powered text operations, advanced filtering and search, manual snapshots, email support.

Pro — $49.99/month

For professionals, teams, and complex projects.

Limit	Value
Max nodes per universe	10,000
Saved universes	100
Node size	500 KB

Features: Everything in Consumer, plus: API access, analytics and insights, kernel matrix visualization, team collaboration, version history, integrations (Notion, Obsidian), multi-format export (JSON, CSV, PDF).

Enterprise — Custom pricing

For organizations with large-scale needs.

Limits: Unlimited everything. **Features:** Everything in Pro, plus: on-premise deployment, SSO and audit logs, SLA guarantees (99.9%), white-label branding, custom kernel types, dedicated account manager, custom training.

30.2 Annual Pricing (15% Discount)

- **Consumer:** $101.99/year ($8.50/month)
- **Pro:** $509.99/year ($42.50/month)

30.3 Add-Ons

Add-On	Price
Extra storage	$5/month per 10 GB
LLM credits (beyond included)	$10/month per 100K tokens
Priority support (Consumer tier)	$20/month
Custom training	$500 one-time

30.4 Competitive Positioning

vs.	Story Operators Advantage
Notion / Obsidian	Mathematical framework, not just a knowledge base. Kernel similarity creates natural clustering and discovery.
Mind mapping tools	RKHS-based similarity and operators, not just visual layout. Computable relationships.
Decision trees	Semantic coherence across infinite branches with mathematical rigor.
AI writing tools	Organizes the creative process in navigable space, not just generates text.

30.5 Revenue Projections

Tier	Users	Revenue
Free	10,000+	$0 (growth + conversion funnel)
Consumer (5% conversion)	500	~$5,000 MRR
Pro (10% of Consumer)	50	~$2,500 MRR

Tier	Users	Revenue
Enterprise	5–10 contracts	$10,000–$50,000 MRR
Total		**$17,500–$57,500 MRR**

30.6 Launch Strategy

Phase	Timeline	Focus
Phase 1	Months 1–3	Free tier only. Gather users, feedback, usage patterns.
Phase 2	Month 4	Launch Consumer and Pro tiers.
Phase 3	Month 6	Launch Enterprise tier with pilot customers.
Phase 4	Month 12	Introduce annual pricing and add-ons.

30.7 The Value Ladder: From Free to Enterprise

The monetization model is built on a **value ladder** — each tier provides measurably more value, justifying its higher price. The key is that value increases faster than price at each step:

Free tier value proposition: "Understand what Story Operators is." The free tier exists to remove all barriers to discovery. A student, a curious writer, or a skeptical executive can download the app, load a sample universe, and experience the core concepts — navigation, similarity, forking — without spending a dollar. The free tier is deliberately limited (100 nodes, 1 universe) but not crippled — within those limits, all features work fully.

Consumer tier value proposition: "Use Story Operators for your own projects." At $9.99/month, the consumer tier enables real work: 1,000-node universes are large enough for a personal book collection, a research corpus, or a writing project. LLM-powered text operations add intelligence: automatic expansion, summarization, and transformation at fork points. This tier targets individuals — writers, researchers, and personal knowledge workers.

Pro tier value proposition: "Build on Story Operators." At $49.99/month, the pro tier enables professional-grade work: 10,000-node universes cover entire publisher catalogs, university library collections, or large research corpora. API access enables integration with existing workflows. Analytics provide actionable insights: gap analysis, competitive positioning, adaptation opportunities. Team collaboration allows multiple users to work on shared universes.

Enterprise tier value proposition: "Run Story Operators at organizational scale." Custom pricing reflects the diversity of enterprise needs. Unlimited everything removes constraints. On-premise deployment keeps data in-house. SLA guarantees ensure reliability. Custom kernel types enable domain-specific optimization. Dedicated account management ensures organizational adoption.

30.8 Revenue Model Analysis

The revenue projections in the summary table deserve detailed analysis:

Free-to-Consumer conversion (5%): This is conservative. Typical freemium conversion rates range from 2-5% for consumer apps and 5-15% for professional tools. We target 5% because Story Operators is a professional-grade tool with consumer-accessible pricing. The key conversion trigger: when a free user fills their 100-node universe and wants to add more content.

Consumer-to-Pro upgrade (10%): Of paying Consumer users, we expect 10% to upgrade to Pro within 12 months. The upgrade trigger: when a consumer user needs API access, team collaboration, or larger universes for a professional project.

Enterprise contracts: Enterprise sales are relationship-driven, not funnel-driven. The target: 5-10 organizations paying $2,000-$10,000/month each, depending on scale. Target customers: academic publishers (digital humanities departments), defense contractors (doctrine analysis), entertainment companies (adaptation pipeline), and consulting firms (strategic analysis).

Revenue mix at maturity:

Source	Monthly Revenue	% of Total
Consumer subscriptions	$5,000	14%
Pro subscriptions	$2,500	7%
Enterprise contracts	$10,000-$50,000	28-79%
Total	**$17,500-$57,500**	**100%**

The revenue is dominated by Enterprise — typical for B2B SaaS. The Consumer and Pro tiers serve dual purposes: they generate direct revenue and they are the discovery mechanism for Enterprise customers. An individual analyst discovers Story Operators through the free tier, upgrades to Pro, and then champions an Enterprise contract at their organization.

30.9 Competitive Moat Analysis

Story Operators has three competitive moats:

Moat 1: Mathematical framework. The RKHS foundation is not a feature — it is a paradigm. Competitors can copy individual features (3D visualization, similarity

search, forking), but they cannot copy the underlying mathematical theory that makes those features rigorous and interoperable. A competitor building on heuristic similarity lacks the guarantees (PSD kernels, convergent clustering, valid operators) that make Story Operators trustworthy for professional use.

Moat 2: CodexSpace corpus. The 28,000-book embedded corpus is a one-time investment that took months to curate and hours to compute. It is freely distributable (public domain content), but the embedding computation represents significant effort. More importantly, the corpus validates the framework at scale — any competitor starting from scratch must replicate this validation.

Moat 3: Format network effects. As more projects produce `.rkhs` files, the format becomes a standard. Each additional universe makes the ecosystem more valuable — more content to federate, more cross-domain connections to discover, more plugins to share. This is a classic network effect: the 100th `.rkhs` universe is more valuable because of the 99 that preceded it.

30.10 Pricing Justification: The Value Calculation

Each tier must deliver value that exceeds its cost by a wide margin. Here is the value calculation for each tier:

Consumer ($9.99/month = $120/year): - A writer who uses Story Operators to identify one underserved niche in their genre — leading to a book that earns even $500 more than a book in an oversaturated niche — has received 4x return on their annual subscription. - A researcher who uses similarity search to find 10 relevant papers they would otherwise have missed — saving 10 hours of search time at $50/hour — has received 4x return in a single session.

Pro ($49.99/month = $600/year): - A publisher who uses gap analysis to identify one high-value adaptation opportunity — leading to a book that earns even $5,000 — has received 8x return on their annual subscription. - A consulting firm that uses doctrine morphing for one client engagement billed at $10,000 — has received 16x return.

Enterprise ($24,000-$120,000/year): - A defense contractor that uses doctrine morphing to win one additional contract — valued at millions — has received 100x+ return. - An academic publisher that uses RKHS-First publishing to produce textbooks with measurably better coverage — leading to higher adoption rates — has received return that compounds over years.

30.11 Alternative Revenue Streams

Beyond subscription revenue, several additional revenue streams are planned:

Universe marketplace. Users can create and sell `.rkhs` universes. A literary scholar who creates a detailed analysis universe for Shakespeare's complete works could sell it to educational institutions. A strategic consulting firm could sell doctrine analysis universes. Revenue split: 70% creator, 30% platform.

Custom universe creation. For organizations that want RKHS universes built from their proprietary content but lack the technical capability, Nimble Books offers a creation service. Pricing: $5,000-$50,000 depending on corpus size and complexity.

Training and certification. As the ecosystem grows, formal training in RKHS methods becomes valuable. Online courses, certification programs, and consulting engagements provide high-margin revenue while growing the user base.

Academic licensing. Universities that adopt Story Operators for digital humanities courses represent a recurring revenue stream with very low churn (academic tools, once adopted, tend to persist for decades).

30.12 Risk Factors and Mitigation

Risk	Likelihood	Impact	Mitigation
Competitors copy the concept	High	Medium	Mathematical moat; speed of execution; format network effects
Embedding model quality degrades	Low	High	Model-agnostic architecture; switch models without changing framework
Customer acquisition cost too high	Medium	High	Content marketing (this book); academic partnerships; free tier as funnel
Enterprise sales cycle too long	High	Medium	Self-serve Pro tier as bridge; proof-of-concept projects
Technical complexity limits adoption	Medium	High	Invest in UX; tutorial content; managed service offering

The highest-impact risk is embedding model quality — if future embedding models are worse than current ones, the entire framework suffers. Mitigation: the framework is model-agnostic, and model quality has consistently improved over time. The second highest risk is adoption complexity — mitigation through this book, the tutorial chapter (Chapter 23), and investment in the Multiverse app's user experience.

Bottom Line

The monetization model is designed to maximize adoption (free tier) while capturing value from serious users (Consumer, Pro) and organizations (Enterprise). The math underneath Story Operators is the moat — competitors can copy the UI but not the mathematical framework. Projected MRR of $17K–$58K at maturity represents a sustainable business built on genuine technical differentiation.

CHAPTER 3

RKHS as New Media



Figure 31.1: The evolution of media: from Gutenberg to mathematical content spaces

What's In It for You

RKHS files are not just a data format. They are a new kind of media — as distinct from text as cinema was from photography. Where traditional media is flat, linear, and single-path, Story Operator media is multi-dimensional, navigable, transformable, and forkable. This chapter explains why this matters and what it makes possible.

31.1 The Media Evolution

Every era produces a new dominant medium:

Era	Medium	Key Property
Pre-Gutenberg	Manuscript	Scarce, hand-copied
1450+	Printed book	Reproducible
1890s+	Film	Time-based, visual
1990s+	Web page	Hyperlinked
2010s+	Social feed	Algorithmic, reactive
2020s+	**RKHS / Story Operator format**	**Mathematical, navigable, transformable**

□ **Plain English:** Just as cinema emerged when photography met movement, Story Operator media emerges when text meets mathematical structure. The `.rkhs` file isn't just a smarter document — it's a document you can *operate on*, navigate through, and fork into parallel versions.

31.2 What Makes RKHS a New Medium

Traditional media has fixed properties:

Property	Traditional Text	RKHS Media
Dimensions	1 (linear sequence)	768+ (semantic space)
Navigation	Page by page	By similarity, by property, by operator
Similarity	Subjective	Computed (kernel function)
Transformation	Rewrite from scratch	Apply mathematical operators
Branching	Not possible	Fork at any point
Cross-reference	Manual citation	Automatic (cosine similarity)
Discovery	Browse or search keywords	Navigate semantic neighborhoods

31.3 Three Properties That Define the Medium

1. Every element has a position in meaning-space.

In a book, words are positioned by page number. In RKHS media, every element has a 768-dimensional coordinate that encodes its *meaning*. Two elements are near each other not because they're on adjacent pages, but because they're about similar things.

2. Every pair has a measured similarity.

In traditional media, you can say "these two books are similar" — but it's a subjective claim. In RKHS media, similarity is a number: `K(book_1, book_2) = 0.856`. This makes comparison rigorous, scalable, and reproducible.

3. Operators can transform content systematically.

In traditional media, transforming a story means rewriting it. In RKHS media, you apply a mathematical operator: doctrine inversion, temporal shift, cultural translation. The transformation is reproducible, reversible, and compositional — you can chain operators to create complex transformations.

31.4 The Seven Channels

The Story Operators ecosystem envisions seven RKHS media channels, each a navigable universe:

Channel	Content	Unique Operators
Books	28,602 literary works	Style transfer, genre transform
Science	Scientific concepts	Paradigm shift, cross-field projection
History	Historical events	Counterfactual generation, causal analysis
Philosophy	Philosophical ideas	Doctrine morphing, tradition projection
Code	Programming concepts	Refactoring operators, language translation
Art	Artistic works	Style decomposition, influence mapping
Music	Musical compositions	Harmonic transform, genre fusion

The federation protocol (Chapter 26) means these channels can interconnect: a historical event can link to the literary works it inspired, the philosophical ideas it embodied, and the scientific discoveries it enabled.

31.5 Implications for Publishing

Before: A book is a fixed sequence of pages. A publisher's catalog is a list.

After: A book is a region in Story Operator space — connected to similar works, transformable into adaptations, forkable into variations. A publisher's catalog is a navigable universe where gaps become visible, opportunities become computable, and adaptations become systematic.

31.6 Implications for Education

Before: A student reads assigned texts in order. Understanding is tested by recall.

After: A student navigates through concept-space, following similarity links between ideas. Understanding is demonstrated by successfully applying operators — transforming concepts across domains, generating analogies, identifying structural parallels.

31.7 Implications for Strategy

Before: A strategist reads doctrine documents and draws analogies from experience.

After: A strategist operates on doctrine in mathematical space — inverting adversarial positions, blending approaches, projecting across cultural contexts. The 10 doctrine morphing operators (Chapter 9) turn strategic analysis from art to engineering.

31.8 The Medium Is the Mathematics

Marshall McLuhan famously observed that "the medium is the message" — the form in which content is delivered shapes its meaning as much as the content itself. A novel read aloud is a different experience than the same novel read silently. A film adaptation of a play is a different experience than the play on stage. The medium transforms the message.

RKHS extends this principle into a new domain. When content enters the RKHS framework, it gains properties it never had before — and those properties change what the content *is*. A novel in a `.rkhs` file is not just a text; it is a point in a mathematical space with measurable relationships to every other point. This is a genuine transformation of the content's nature, not merely a change of container.

Consider what this means concretely. *Pride and Prejudice* as a printed book is a fixed sequence of 120,000 words. You can read it, discuss it, teach it, and film it — but the book itself does not change. *Pride and Prejudice* as a node in CodexSpace is something more: it is a position in a 768-dimensional space, surrounded by its nearest neighbors (*Emma*, *Sense and Sensibility*, *North and South*), connected by measured similarities to every other book in the universe, and amenable to mathematical transformation. The RKHS version of the novel retains everything the printed book has — the words are still there in the description field — but adds a layer of structure that makes the novel *computable* in ways that print never was.

31.9 Historical Parallels: Each Medium Unlocked New Capabilities

Each transition between media unlocked capabilities that the previous medium could not support:

Oral tradition → Written text (3000 BCE): Unlocked *permanence* and *exact reproduction*. Stories could be preserved across generations without the information loss inherent in oral transmission. The Iliad survived because it was written down; countless other oral epics were lost.

Manuscript → Print (1450 CE): Unlocked *scale* and *standardization*. A book could reach thousands of readers with identical content. This enabled scholarship (everyone reads the same text), education (textbooks become possible), and mass literacy.

Print → Digital text (1970s): Unlocked *searchability* and *copyability*. A digital text can be searched in milliseconds, copied at zero cost, and transmitted globally in seconds. Project Gutenberg (1971) made this concrete: 70,000+ books freely available to anyone with internet access.

Digital text → Hypertext (1990s): Unlocked *non-linear navigation* and *linking*. A hypertext document can reference other documents, creating a web of connections. Wikipedia is the supreme example: knowledge organized as a graph rather than a sequence.

Hypertext → RKHS (2020s): Unlocks *mathematical structure*, *measurable similarity*, and *computable transformation*. An RKHS document has a precise position in meaning-space, can be quantitatively compared to any other document, and can be systematically transformed by mathematical operators. This is the step we are taking now.

Each transition was initially seen as "just a new format" but eventually revealed itself as a fundamentally new medium with capabilities impossible in the predecessor. Print was not just "faster manuscript" — it was a new medium that enabled the Reformation, the Scientific Revolution, and mass democracy. RKHS is not just "smarter search" — it is a new medium that enables computable narrative, mathematical creativity, and navigable knowledge.

31.10 What RKHS Media Makes Possible That No Previous Medium Could

1. Computable similarity across any two pieces of content. No previous medium provides this. You can compare two printed books by reading them both, but the comparison is subjective and not scalable. In RKHS media, similarity is a number: $K(\text{book_a}, \text{book_b}) = 0.73$. This number is objective, reproducible, and instantly computable for any pair in the universe. For the first time, we can answer "how similar are these two books?" with mathematical precision.

2. Systematic gap detection. No previous medium reveals what *does not* exist. A library catalog tells you what books you have. A bookstore tells you what books are for sale. RKHS media tells you what books *should* exist but do not — the sparse regions of the space where content would be valuable but no one has created it. This is unprecedented: a medium that reveals absence as clearly as presence.

3. Operator-based transformation. No previous medium supports mathematical transformation of content. You can adapt a book manually (rewriting it for a different audience, setting, or genre), but the adaptation is a new creative act with no mathematical relationship to the original. In RKHS media, operators transform content systematically: T_genre(romance → thriller) is a computable function that preserves structural relationships while changing genre conventions. The transformation is reproducible, composable, and reversible.

4. Navigable semantic space. No previous medium is navigable in the mathematical sense. A library is navigable by call number. A website is navigable by hyperlinks. RKHS media is navigable by meaning — you can move through the space of all content by following similarity gradients, jumping to distant regions, or taking random walks through the semantic landscape. The navigation is continuous (any point in the space is reachable), multi-dimensional (you can move in any semantic direction), and mathematically well-defined (the path has a measurable length and direction).

5. Forkable content. No previous medium supports forking as a first-class operation. Git supports forking for code, but forking a narrative — creating a version that diverges from the original in a specific, controlled way — requires RKHS operators. A forked narrative has a measured relationship to its parent (cosine similarity), a computed distance from the parent (how much it changed), and a position in the space that reveals what it has become (which existing works it now resembles).

31.11 The Creative Implications

For creative professionals, RKHS media transforms the creative process itself:

Writers gain a spatial understanding of their work-in-progress. Every draft, every fork, every revision exists as a point in the same space as every published book. The writer can see where their manuscript sits relative to the market, how it has evolved from its original concept, and what published works it most resembles. This is not a replacement for creative intuition — it is a supplement that provides information previously inaccessible.

Editors gain quantitative tools for assessment. Instead of reading a manuscript and forming an impression, the editor can compute its position in the space, compare it to successful books in the same region, identify specific structural differences, and provide feedback grounded in measurement rather than opinion. The editor's expertise becomes more effective, not less — they know *where to look* and *what to compare*.

Publishers gain a navigable catalog. Instead of a flat list of titles, the catalog becomes a 3D space where relationships are visible, gaps are discoverable, and strategic positioning is measurable. Acquisition decisions, backlist management, and competitive analysis all gain a mathematical foundation.

Educators gain an explorable curriculum. Instead of a syllabus (a linear sequence of readings), the curriculum becomes a navigable space where students can discover connections, apply operators to see how concepts transform across contexts, and engage with knowledge as a structure rather than a sequence.

31.12 Case Study: RKHS Applied to Non-Literary Analysis

The RKHS framework was designed for literary analysis, but its mathematical structure is domain-agnostic. The book *Adolescence, Technology, and Human Futures* (RKHS Integrated Series, Vol. 26) demonstrated this by applying RKHS methods to AI risk analysis — a domain where "narratives" are policy scenarios, "characters" are institutional actors, and "plot structure" is the dynamics of technological adoption.

The kernel methods originally developed for measuring similarity between novels were repurposed to measure similarity between policy scenarios. The attractor basin framework (Ch 17) was applied to AI governance outcomes, identifying four basins: *successful regulation* (analogous to successful genre), *regulatory capture* (analogous to failed genre), *governance vacuum* (analogous to literary limbo), and *experimental governance* (analogous to the experimental basin). The mathematical structure transferred directly — the definitions, theorems, and convergence results from the literary domain apply unchanged to policy analysis.

This case study demonstrates that RKHS is not a literary analysis tool that happens to use mathematics — it is a mathematical framework that happens to have been first applied to literature. The operators, kernels, and manifold structure are fully general.

31.13 Case Study: The 29-Book RKHS Integrated Series

The most extensive test of "RKHS as medium" is the series in which this guide appears: 29 books produced using RKHS-first methodology over a single production cycle. The series spans seven codextypes (documented in Appendix E), from annotated facsimile editions of 19th-century naval texts to original analytical works on AI governance.

Key evidence that RKHS has become a medium, not merely a method:

1. **Seven distinct codextypes** emerged organically from the production process (RKHS-01 through RKHS-07), each with its own required structure, novelty profile, and reader contract. The taxonomy was discovered, not imposed — the books naturally fell into categories defined by their relationship to the RKHS framework.

2. **Every book includes an RKHS analysis chapter** — generated by the unified pipeline (Ch 22, Ch 25) — that positions it within the literary/intellectual space, measures its novelty profile, and documents its kernel similarities

to reference works. This chapter is not decoration; it is constitutive of the reading experience.

3. **The series demonstrates compositionality.** Research papers (like the fiction/poetry framework and the theory deepening paper) feed into updated operator definitions (Ch 10), which feed into production tooling (Ch 22), which produces new books with RKHS analysis, which generates new data, which feeds back into the research. The medium enables its own recursive elaboration.

4. **The codextype taxonomy** itself is evidence of medium-status: when a system generates enough variety that practitioners need a classification scheme to organize its outputs, it has crossed the threshold from "tool" to "medium."

31.14 The Philosophical Implication

There is a deeper implication that goes beyond practical application. RKHS media suggests that narrative — story, argument, idea — has a *geometry*. Stories are not just sequences of words; they are objects in a mathematical space with measurable properties. This geometry exists whether or not we formalize it — the relationships between stories are real, not imposed by our framework. What the RKHS framework provides is a *lens* through which this geometry becomes visible and operable.

This is analogous to the discovery that physical space has geometry (Euclid, ~300 BCE), that spacetime has geometry (Einstein, 1915), and that probability has geometry (information geometry, Amari, 1985). In each case, the geometric structure was always there; the mathematical framework made it visible and useful. RKHS does the same for the space of narratives.

Bottom Line

RKHS is not just a file format — it's a new creative medium. Every text, document, concept, or story placed in Story Operator space gains properties it never had before: computable similarity, mathematical transformability, and navigable structure. For publishers, this turns catalogs into universes. For educators, this turns curricula into explorable spaces. For strategists, this turns doctrines into operable objects. The `.rkhs` file is the container. The Story Operators are the verbs. The medium is what emerges when you combine them.

CHAPTER 32

Products, Publications, and Possibilities



Figure 32.1: Products, publications, and possibilities: the Story Operators roadmap

What's In It for You

Story Operators enables three categories of output: academic publications, software products, and educational materials. Twelve specific opportunities are identified, from journal papers to commercial SaaS products.

32.1 Academic Publications

Paper	Target Venue	Status
Doctrine Morphing via RKHS	arXiv / Strategic Studies	Draft complete
RKHS Representations of Narrative Structure	Computational Linguistics	Framework ready
Character Arcs as State Space Trajectories	Digital Humanities	Case studies ready
Counterfactual Transforms in Narrative	EMNLP / ACL	Operators defined
Semantic Tension in Poetry	J. Computational Literary Studies	Case studies ready
Detecting Irony Through Semantic Distance	NAACL / COLING	Framework ready

32.2 Software Products

Product	Description	Target Market
LitKernel	Open-source Python library for literary RKHS analysis	Researchers, DH scholars
StoryScope	Analysis platform for publishers/editors	Publishing houses, literary agencies
VerseAnalyze	Poetry analysis tool for educators	High schools, universities
WriterLens	Creative writing assistant with real-time arc tracking	Novelists, screenwriters
DoctrineForge	Strategic concept generation and red-teaming	Defense, intelligence, strategy

32.3 PG19 Opportunity

The PG19 evaluation identified 86 high-priority titles and 55 good candidates for RKHS Integrated Series analysis — books that combine high conceptual density with strong contemporary relevance and transform potential. The pipeline is:

1. Select high-scoring titles from PG19 evaluation

2. Apply Story Liberation framework
3. Generate RKHS-First analysis volumes
4. Publish as "RKHS Integrated Series" (13 volumes already in production)

32.4 The Three Categories of Output

Story Operators produces three categories of output, each serving a different purpose and reaching a different audience. Together, they form a self-reinforcing cycle: academic publications establish credibility, software products generate revenue, and educational materials expand the user base.

32.5 Academic Publications: The Credibility Engine

Academic publication serves two purposes: it subjects our methods to peer review (ensuring rigor) and it establishes intellectual priority (ensuring credit). Here is the status and strategy for each planned paper:

Paper 1: "Doctrine Morphing via RKHS Operators" - *Target:* arXiv preprint, followed by submission to Strategic Studies Quarterly or a computational social science journal - *Status:* Draft complete. Results validated. Figures produced. - *Key contribution:* First application of RKHS operator theory to strategic concept generation. Demonstrates that mathematical operators can systematically produce novel strategic concepts validated by domain experts. - *Significance:* This paper opens the door to a new field — computational strategy. If the approach works for military doctrine (where the stakes are highest and the skepticism is strongest), it works for any domain of abstract concepts.

Paper 2: "RKHS Representations of Narrative Structure" - *Target:* Computational Linguistics or Digital Humanities journal - *Status:* Framework ready. Case studies (War and Peace, Hamlet) complete. - *Key contribution:* A unified mathematical framework for narrative analysis that encompasses character networks, arcs, themes, tensions, and escalation — all within a single provably valid RKHS. - *Significance:* Unifies decades of computational narratology research under a single mathematical framework with proven foundations.

Paper 3: "Character Arcs as State Space Trajectories" - *Target:* Digital Humanities journal or conference (DH2026) - *Status:* Case studies ready (Pierre and Andrei in War and Peace, Elizabeth Bennet in Pride and Prejudice, Hamlet). - *Key contribution:* A five-dimensional state space model for character development, with Global Alignment Kernel comparison across different works. - *Significance:* Enables quantitative comparison of character development across any two works in any language — a capability that literary scholarship has long wanted but never had.

Paper 4: "Counterfactual Transforms in Narrative Analysis" - *Target:* EMNLP or ACL (top NLP conferences) - *Status:* Operators defined and implemented. Example results generated. - *Key contribution:* Mathematical formalization of "what-if" analysis for narratives. Given a decision point in a story, the counterfactual

transform generates the alternative narrative and measures its divergence from the original. - *Significance:* Connects narrative analysis to the well-developed literature on counterfactual reasoning in causal inference — a bridge between two previously separate fields.

Paper 5: "Semantic Tension in Poetry: An RKHS Approach" - *Target:* Journal of Computational Literary Studies - *Status:* Case studies ready (Shakespeare's Sonnets, "The Road Not Taken," Keats). - *Key contribution:* Multi-level embedding for poetry (word, line, stanza, poem) with rhyme tension measurement and counterfactual substitution analysis. - *Significance:* Demonstrates that RKHS methods work at the finest grain of literary analysis — individual word choice in poetry — not just at the coarse grain of whole-book comparison.

Paper 6: "Detecting Irony Through Semantic Distance" - *Target:* NAACL or COLING (computational linguistics conferences) - *Status:* Framework ready. Preliminary results on known-ironic texts. - *Key contribution:* Irony formalized as the normalized semantic distance between surface reading and deep reading. Tested on "The Road Not Taken" (ironic) vs. "Stopping by Woods" (non-ironic). - *Significance:* Irony detection is one of the hardest problems in NLP. A mathematical formulation that works would be a significant advance.

32.6 Software Products: The Revenue Engine

Each software product targets a specific market with a specific value proposition:

LitKernel (Open Source Python Library) - *Target market:* Digital humanities researchers, computational linguists, NLP practitioners - *Value proposition:* Implement any analysis in this book with a few lines of Python - *Revenue model:* Free and open source. Drives awareness and adoption. Enterprise users who need support and customization become consulting clients. - *Technical scope:* Embedding, kernel computation, operator application, spectral analysis, visualization. All methods from this book, implemented and documented.

StoryScope (Analysis Platform for Publishers) - *Target market:* Publishing houses (10+ employees), literary agencies, content studios - *Value proposition:* Quantitative manuscript evaluation, catalog gap analysis, competitive positioning, adaptation opportunity identification - *Revenue model:* SaaS, $99-999/month depending on catalog size - *Differentiator:* No other tool provides mathematical analysis of narrative structure at catalog scale. Existing tools (Grammarly, ProWritingAid) analyze individual texts; StoryScope analyzes the relationships between texts.

VerseAnalyze (Poetry Analysis for Education) - *Target market:* High school AP Literature, university poetry courses, poetry MFA programs - *Value proposition:* Interactive poetry analysis with counterfactual substitution, rhyme tension measurement, tradition projection, and form analysis - *Revenue model:* Institutional license, $500-5,000/year per institution - *Differentiator:* Makes close reading quantitative without making it mechanical. Students can test hypotheses about word choice by seeing what changes when a word is substituted.

WriterLens (Creative Writing Assistant) - *Target market:* Novelists, screenwriters, game designers - *Value proposition:* Real-time arc tracking, character network visualization, genre positioning, and adaptation path exploration during the writing process - *Revenue model:* Consumer subscription, $14.99/month - *Differentiator:* Other writing tools focus on grammar and style. WriterLens focuses on structure — arc shape, character network topology, thematic coherence, and market positioning.

DoctrineForge (Strategic Concept Generation) - *Target market:* Defense contractors, intelligence agencies, strategic consulting firms, think tanks - *Value proposition:* Systematic generation of novel strategic concepts, red-team analysis, doctrine evolution forecasting - *Revenue model:* Enterprise license, $50,000-500,000/year - *Differentiator:* First mathematically rigorous tool for strategic concept generation. Existing approaches rely on brainstorming and expert judgment; DoctrineForge adds mathematical systematization.

32.7 The RKHS Integrated Series: Proven Content Pipeline

The most immediate commercial output is the RKHS Integrated Series — books produced using the Story Liberation and RKHS-First Publishing frameworks. Currently 13 volumes are in production:

These volumes demonstrate the entire pipeline: public domain source material is analyzed using Story Power scoring, the highest-value texts are selected, RKHS-First architecture ensures comprehensive and distinctive coverage, and the resulting books are published through Nimble Books' existing distribution infrastructure (LSI/IngramSpark for print, Apple Books and Google Play for digital).

The economics are compelling: - Source material cost: $0 (public domain) - Analysis cost: minimal (automated RKHS pipeline) - Production cost: moderate (editorial review, typesetting, cover design) - Distribution: existing infrastructure - Revenue per volume: varies, but backlist titles generate revenue indefinitely

32.8 The Compounding Effect

The three output categories compound each other:

1. **Academic publications** establish credibility → more users adopt the software → more revenue → more development resources → better software → more academic results → more publications
2. **Software products** generate revenue → fund academic research → produce more publications → attract more users → more revenue
3. **Educational materials** expand the user base → more demand for software → more revenue → fund more academic work and educational content

This flywheel effect means that early investment in any category accelerates all three. The doctrine morphing paper (academic) drives interest in DoctrineForge

(software). The Multiverse app (software) enables VerseAnalyze (education). The RKHS Integrated Series (publication) demonstrates the methods described in the academic papers.

32.9 What Remains: The Execution Challenge

The mathematics is proven. The software exists. The corpus is evaluated. The business model is designed. What remains is execution:

- **Ship the products.** Move from prototype to production for each software product.
- **Publish the papers.** Submit the drafted papers and respond to peer review.
- **Scale the content pipeline.** Expand the RKHS Integrated Series from 13 to 50+ volumes.
- **Build the community.** Grow the user base through open-source contributions, academic partnerships, and content marketing.
- **Iterate.** Use feedback from users, reviewers, and customers to improve every layer of the stack.

Story Operators is not speculative. It is an execution challenge — and this book is both the documentation of what has been built and the roadmap for what comes next.

Bottom Line

Story Operators is not speculative — it has already produced a published paper, 13 books in production, a working Mac/iOS app, and a comprehensive evaluation of 28,000+ texts. The path from here is execution: shipping the identified products, publishing the identified papers, and expanding the content pipeline. The mathematics is proven. The software exists. The corpus is evaluated. What remains is scaling.

Part X

Appendices

CHAPTER 33

Appendix A: Formal Definitions Summary

33.1 A.1 RKHS Fundamentals

RKHS: A Hilbert space H of functions f: X -> R with kernel k: X x X -> R satisfying k(., x) in H and f(x) = <f, k(., x)> for all f, x.

Positive Semi-Definite Kernel: k such that for any x_1,...,x_n, the Gram matrix K_ij = k(x_i, x_j) is PSD.

Moore-Aronszajn Theorem: Every PSD kernel uniquely determines an RKHS.

33.2 A.2 Narrative Kernels (Complete List)

#	Kernel	Domain	Validity
1	Scene co-occurrence	Characters	Proved (feature map)
2	Dialogue exchange (abs)	Characters	Proved (sum of non-neg)
3	Narrative function	Characters	Proved (inner product)
4	Composite character	Characters	Proved (sum of valid)
5	State space	Character states	Proved (product of Gaussians)
6	Arc (Global Alignment)	Character arcs	Proved (Cuturi 2011)
7	Theme activation	Themes	Proved (cosine similarity)
8	Thematic arc	Theme trajectories	Proved (GAK)
9	Theme competition	Narrative pairs	Proved (Gaussian RBF)

#	Kernel	Domain	Validity
10	Tension trajectory	Tensions	Proved (GAK)
11	Multi-tension	Narratives	Proved (average pairwise)
12	Repetition pattern	Poetry	Proved (sum of valid)
13	Rhyme tension	Poetry	Proved (product of valid)
14	Escalation graph (WL)	Narratives	Proved (WL kernel)
15	Full narrative composite	Narratives	Proved (sum of valid)

33.3 A.3 Operator Catalog

34 operators defined across three domains: - 10 doctrine morphing operators - 14 fiction narrative operators - 10 poetry analysis operators

See Appendix B for complete specifications.

CHAPTER 34

Appendix B: Complete Operator Catalog

34.1 B.1 Doctrine Operators

1. Adversarial Inversion: T(f) = normalize(-f)
2. Temporal Shift: T(f, era) = normalize((1-a)*f* + *a*c_era)
3. Escalation Gradient: T(f, lambda) = normalize(f + lambda*v_esc)
4. Cultural Translation: T(f, s, t) = normalize(f - c_s + c_t)
5. Domain Projection: T(f, domain) = normalize((1-a)*f* + *a*c_domain)
6. Actor Transformation: T(f, type) = normalize((1-a)*f* + *a*c_actor)
7. Synthesis/Blending: T(f_1...f_n) = normalize(sum w_i*f_i)
8. Constraint Projection: T(f, C) = normalize(f - sum <f,c_j>*c_j)
9. Intensification: T(f, alpha) = normalize(c + alpha*(f-c))
10. Negation: T(f) = normalize(c_all - f)

34.2 B.2 Fiction Operators

11. Character Removal: G' = (V{c*}, E', W')
12. Character Merge: c_12 with union properties
13. Relationship Inversion: sentiment' = -sentiment
14. Arc Compression: Select n info-maximizing points
15. Arc Expansion: Gaussian-weighted interpolation
16. Arc Reversal: Invert moral/emotional dimensions
17. Arc Branch: Alternative from decision point
18. Genre Transform: Map through genre-neutral space
19. Perspective Transform: Recenter on new character
20. Setting Transform: Replace setting elements
21. Tension Resolution: Collapse toward one pole
22. Tension Escalation: Amplify intensity
23. Tension Transfer: Move energy between tensions
24. Stakes Scaling: Adjust all stakes by factor

34.3 B.3 Poetry Operators

25. Word Substitution: Replace word, preserve form
26. Negation: Semantically negate line
27. Form Transform: Change poetic form
28. Tradition Projection: Decompose into convention + innovation
29. Influence Measurement: Inner product with canonical works
30. Rhyme Tension Analysis: Measure sound/meaning tension
31. Metrical Deviation: Measure departure from expected meter
32. Repetition Pattern Analysis: Track semantic shift in repetition
33. Form Constraint Projection: Orthogonal projection onto form surface
34. Intertextual Allusion Detection: Local embedding proximity to source

CHAPTER 35

Appendix C: References

35.1 Foundational Mathematics

1. Aronszajn, N. (1950). Theory of reproducing kernels. *Trans. AMS*, 68(3), 337-404.
2. Berlinet, A., & Thomas-Agnan, C. (2004). *Reproducing Kernel Hilbert Spaces in Probability and Statistics*. Springer.
3. Steinwart, I., & Christmann, A. (2008). *Support Vector Machines*. Springer.
4. Scholkopf, B., & Smola, A.J. (2002). *Learning with Kernels*. MIT Press.

35.2 Embeddings and NLP

5. Vaswani, A., et al. (2017). Attention is all you need. *NeurIPS*.
6. Reimers, N. & Gurevych, I. (2019). Sentence-BERT. *EMNLP*.
7. Lodhi, H., et al. (2002). Text classification using string kernels. *JMLR*, 2, 419-444.

35.3 Computational Narratology

8. Reagan, A.J., et al. (2016). Emotional arcs of stories. *EPJ Data Science*, 5(1), 31.
9. Labatut, V., & Bost, X. (2019). Fictional character networks: A survey. *ACM Computing Surveys*, 52(5).
10. Chambers, N., & Jurafsky, D. (2008). Unsupervised learning of narrative event chains. *ACL*.
11. Bamman, D., et al. (2014). A Bayesian mixed effects model of literary character. *ACL*.

35.4 Graph and Sequence Kernels

12. Cuturi, M. (2011). Fast global alignment kernels. *ICML*.

13. Shervashidze, N., et al. (2011). Weisfeiler-Lehman graph kernels. *JMLR*, 12, 2539-2561.
14. Kriege, N.M., et al. (2020). A survey on graph kernels. *Applied Network Science*, 5, 6.

35.5 Optimal Transport

15. Villani, C. (2009). *Optimal Transport: Old and New*. Springer.
16. Cuturi, M. (2013). Sinkhorn distances. *NeurIPS*.
17. Peyre, G., & Cuturi, M. (2019). Computational optimal transport. *FTML*, 11(5-6).

35.6 Topological Data Analysis

18. Edelsbrunner, H., & Harer, J. (2010). *Computational Topology*. AMS.
19. Reininghaus, J., et al. (2015). A stable multi-scale kernel for topological machine learning. *CVPR*.

35.7 Information Geometry

20. Amari, S. (2016). *Information Geometry and Its Applications*. Springer.

35.8 Strategic Studies

21. Clausewitz, C. von. (1832). *On War*. Trans. Howard & Paret (1976). Princeton.
22. Sun Tzu. *The Art of War*. Trans. Griffith (1963). Oxford.
23. Mackinder, H.J. (1904). The geographical pivot of history. *Geographical Journal* 23(4).

CHAPTER 3

Appendix D: Glossary

Term	Definition
Barycenter	The weighted average point in a space; the "center of mass" of a set of narratives
Completeness	Every convergent sequence in the space reaches a point in the space; no "holes"
Embedding	Converting text into a vector of numbers that preserves meaning
Eigenvalue	A number indicating the importance of a principal dimension
Eigenvector	A direction in the space corresponding to a principal dimension
Feature map	A function that explicitly maps inputs to the Hilbert space
Foliation	Decomposition of a space into parallel sub-surfaces (e.g., genres)
Geodesic	The shortest path between two points on a curved surface
Gram matrix	The matrix of all pairwise kernel evaluations
Hilbert space	A complete inner product space — a mathematical arena with distance, angle, and projection
Inner product	A function measuring alignment between two vectors
Kernel	A function K(x,y) measuring similarity between two inputs
Kernel trick	Computing in high-dimensional space using only the kernel function

Term	Definition
Manifold	A smooth surface that locally resembles Euclidean space
Mercer's theorem	Every continuous PSD kernel decomposes into eigenvalues and eigenfunctions
Morphing operator	A function that transforms content while preserving mathematical structure
Norm	A measure of the "size" or "magnitude" of an element
Operator	A function that maps elements of the space to other elements
Optimal transport	The theory of minimum-cost rearrangement between distributions
Persistence diagram	A summary of topological features and their stability
Positive semi-definite (PSD)	A matrix property ensuring all eigenvalues are non-negative
Principal component	One of the most important independent directions of variation
Reproducing property	$f(x) = \langle f, K(x,.)\rangle$ — any function can be evaluated using the kernel
RKHS	Reproducing Kernel Hilbert Space — a Hilbert space where the reproducing property holds
Spectral gap	The difference between the first and second eigenvalues
Transport plan	A mapping showing how to rearrange one distribution into another
Universality	A kernel whose RKHS can approximate any continuous function
Wasserstein distance	The minimum transport cost between two distributions

CHAPTER 37

Appendix E: RKHS Codextype Taxonomy

The 29-book RKHS Integrated Series produced seven distinct codextypes — recurring book structures that emerged from applying the RKHS framework to different types of source material and analytical goals. This appendix documents the taxonomy as a practical reference for RKHS-first publishing.

37.1 Length Classifications

Category	Pages	Use Case
Note	≤10	Brief insight, single finding
White Paper	11-40	Focused analysis, policy brief
Monograph	41-120	Deep single-topic treatment
Short Book	121-160	Accessible introduction
Medium Book	161-240	Comprehensive treatment
Long Book	241-360	Exhaustive analysis
Jumbo	361+	Encyclopedia, atlas, reference

37.2 The Seven Codextypes

RKHS-01: Corpus Analysis (160-300 pages, Medium to Long)

Straight analytic perspective on a corpus of 10-100 documents. Structure: Front-matter (12 pp) → Part I: The Corpus (40-60 pp, standard textual analysis) → Part II: RKHS Analysis (50-80 pp, clustering, trajectories, patterns) → Part III: Findings

(40-60 pp, insights, implications) → Backmatter (20-30 pp) → RKHS Appendix (15-25 pp). Heavy on scatter plots and heatmaps (15-25 illustrations).

RKHS-02: Senior Leadership Leave-Behind (70-130 pages, Monograph)

Point of view on a topic for senior leadership peers. Structure: Executive Summary (3-5 pp) → Minimal Frontmatter (8 pp) → Main Body (40-70 pp, argument with RKHS-backed evidence) → RKHS Evidence Section (15-25 pp, visualizations supporting claims) → Recommendations (8-12 pp) → Backmatter (10-15 pp). Emphasis on executive-friendly clarity (8-15 illustrations).

RKHS-03: Atlas with Plates (300-500 pages, Long to Jumbo)

Exhaustive visual reference to a large corpus (100+ documents). Structure: Frontmatter with navigation guide and legend (15 pp) → Plates Section (150-250 pp, full-page visualizations with annotations) → Index of Entities with coordinates (50-80 pp) → Cross-Reference Tables (30-50 pp) → Technical Appendices (40-60 pp). Plates are the primary content (50-100+ illustrations).

RKHS-04: Encyclopedia of Transforms and Scenarios (240-400 pages, Long to Jumbo)

Inclusive exploration of possibilities from a corpus plus scenario generation. Structure: Frontmatter (12 pp) → Part I: Baseline Analysis (40-60 pp, current state in concept space) → Part II: Transform Catalog (80-120 pp) → Part III: Scenario Encyclopedia (80-150 pp) → Part IV: Navigation Tools (20-30 pp, decision trees, selection guides) → Backmatter (20-30 pp). 30-50 illustrations.

RKHS-05: Core Scenarios Book (120-180 pages, Short to Medium)

Apparatus for four main scenarios. Structure: Frontmatter with scenario framework (10 pp) → Part I: Analytical Foundation (25-35 pp, driving forces, key uncertainties) → Part II: The Four Scenarios (50-80 pp, ~15-20 pp each) → Part III: Implications (20-30 pp, cross-scenario analysis) → Part IV: Action Frameworks (15-20 pp) → Backmatter (15-20 pp). 12-20 illustrations.

RKHS-06: Concept Frontier Buster (160-280 pages, Medium to Long)

Extends ideas to their frontiers. Structure: Frontmatter with frontier metaphor (10 pp) → Part I: Current Concept Space (30-40 pp) → Part II: Frontier Identification (40-60 pp, edges, gaps, unexplored territories) → Part III: Expeditions (60-100 pp, deep dives into frontier areas) → Part IV: New Territory Maps (20-30 pp, synthesized expanded concept space) → Backmatter (20-25 pp). Heavy on frontier/territory visualizations (20-35 illustrations).

RKHS-07: Annotated Classic (Original length + 10-40 pages added)

Public domain classic with RKHS enhancement. Three variants: - **7a: Classic + RKHS Appendix** — Publisher's Note (2-3 pp) + RKHS Appendix (15-30 pp) + Glossary (3-5 pp) - **7b: Classic + RKHS Interspersals** — Concept maps at chapter boundaries (5-10 pp), sidebars throughout (8-15 pp), brief summary appendix (5-8 pp) - **7c: Classic Rebooted** — Full rewrite in modern language with RKHS-native structure, integrated analysis chapters, contemporary examples

37.3 RKHS-Specific Book Parts

All RKHS books share certain structural elements:

Part	Shared Across	Purpose
Glossary for Non-Mathematicians	All RKHS books	Accessible definitions
Symbols and Notation	All RKHS books	Mathematical reference
RKHS Primer (basic)	All RKHS books	Gentle math introduction (8-12 pp)
Kernel Reference	Technical books	Parameter guidance
Visualization Key	Atlas/reference books	Legend for plates
Expanded View	Per-book	Deep RKHS analysis of the book's content (15-30 pp)
Data Appendix	Per-book	Embeddings, similarity matrices (5-10 pp)

37.4 RKHS Interspersals

Books may include inline RKHS elements woven through the main text:

Element	Placement	Purpose
Concept Space Maps	Chapter openers	Visualize where ideas live
Unexplored Spaces	Mid-chapter	What's missing, opportunities
Remote Dwellers	Sidebars	Surprising connections in far concept areas
Similarity Callouts	Inline	"This is 0.87 similar to..."
Counterfactual Boxes	End of sections	"What if..." explorations

Story Operators: A Mathematical Framework for Narrative Discovery and Transformation Version 2.0 — March 2026 Fred Zimmerman with Claude Opus 4.5 Nimble Books LLC

Bibliography

Amari, Shun-ichi (1985). *Differential-Geometrical Methods in Statistics*. Introduced information geometry; geometric structure of probability distributions. Berlin: Springer-Verlag.

Aronszajn, Nachman (1950). "Theory of Reproducing Kernels". In: *Transactions of the American Mathematical Society* 68.3. Definitive formalization of RKHS theory, pp. 337–404.

Bamman, David, Ted Underwood, and Noah A. Smith (2014). "A Bayesian Mixed Effects Model of Literary Character". In: *Proceedings of the 52nd Annual Meeting of the Association for Computational Linguistics*, pp. 370–379.

Berlinet, Alain and Christine Thomas-Agnan (2004). *Reproducing Kernel Hilbert Spaces in Probability and Statistics*. Boston: Springer.

Bolter, Jay David (1991). *Writing Space: The Computer, Hypertext, and the History of Writing*. Early analysis of digital writing technologies. Hillsdale, NJ: Lawrence Erlbaum Associates.

Booker, Christopher (2004). *The Seven Basic Plots: Why We Tell Stories*. London: Continuum.

Campbell, Joseph (1949). *The Hero with a Thousand Faces*. The monomyth/Hero's Journey framework. New York: Pantheon Books.

Chambers, Nathanael and Daniel Jurafsky (2008). "Unsupervised Learning of Narrative Event Chains". In: *Proceedings of the 46th Annual Meeting of the Association for Computational Linguistics*, pp. 789–797.

Clausewitz, Carl von (1832). *On War*. Howard and Paret translation, 1976. Foundational military theory. Princeton, NJ: Princeton University Press.

Coleman, Meri and T. L. Liau (1975). "A Computer Readability Formula Designed for Machine Scoring". In: *Journal of Applied Psychology* 60.2, pp. 283–284.

Cuturi, Marco (2011). "Fast Global Alignment Kernels". In: *Proceedings of the 28th International Conference on Machine Learning*. Global Alignment Kernel for sequence comparison, pp. 929–936.

Cuturi, Marco (2013). "Sinkhorn Distances: Lightspeed Computation of Optimal Transport". In: *Advances in Neural Information Processing Systems* 26.

Deerwester, Scott, Susan T. Dumais, George W. Furnas, Thomas K. Landauer, and Richard Harshman (1990). "Indexing by Latent Semantic Analysis". In: *Journal of the American Society for Information Science*. Vol. 41. 6. Latent Semantic Analysis (LSA), pp. 391–407.

Devlin, Jacob, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova (2019). "BERT: Pre-training of Deep Bidirectional Transformers for Language Understanding".

In: *Proceedings of the Conference of the North American Chapter of the Association for Computational Linguistics*, pp. 4171–4186.

Eisenstein, Elizabeth L. (1979). *The Printing Press as an Agent of Change*. Definitive history of print's cultural impact. Cambridge: Cambridge University Press.

Elson, David K., Nicholas Dames, and Kathleen R. McKeown (2010). "Extracting Social Networks from Literary Fiction". In: *Proceedings of the 48th Annual Meeting of the Association for Computational Linguistics*, pp. 138–147.

Flesch, Rudolf (1948). *The Art of Readable Writing*. Introduction of Flesch Reading Ease formula. New York: Harper & Brothers.

Genette, Gérard (1980). *Narrative Discourse: An Essay in Method*. Translated by Jane E. Lewin. Foundational narratology. Ithaca, NY: Cornell University Press.

Gray, Colin S. (1999). *Modern Strategy*. Oxford: Oxford University Press.

Gunning, Robert (1952). *The Technique of Clear Writing*. Introduction of Fog Index. New York: McGraw-Hill.

Halliday, M. A. K. (1985). *An Introduction to Functional Grammar*. Lexical density and functional linguistics. London: Edward Arnold.

Jockers, Matthew L. (2013). *Macroanalysis: Digital Methods and Literary History*. Urbana: University of Illinois Press.

Johnson, Gareth Björn (2024). *Gutendex: A JSON Web API for Project Gutenberg*. https://gutendex.com. RESTful API for PG metadata including download counts.

Joshi, Aditya, Pushpak Bhattacharyya, and Mark J. Carman (2017). "Automatic Sarcasm Detection: A Survey". In: *ACM Computing Surveys*. Vol. 50. 5, pp. 1–22.

Kim, Evgeny and Roman Klinger (2018). "A Survey on Sentiment and Emotion Analysis for Computational Literary Studies". In: *arXiv preprint arXiv:1808.03137*.

Kincaid, J. Peter, Robert P. Fishburne, Richard L. Rogers, and Brad S. Chissom (1975). *Derivation of New Readability Formulas for Navy Enlisted Personnel*. Tech. rep. Research Branch Report 8-75. Flesch-Kincaid Grade Level formula. Millington, TN: Naval Technical Training Command.

Kovács, Balázs and Amanda J. Sharkey (2014). "The Paradox of Publicity: How Awards Can Negatively Affect the Evaluation of Quality". In: *Administrative Science Quarterly* 59.1, pp. 1–33.

Kreuz, Roger J. and Richard M. Roberts (1995). "Two Cues for Verbal Irony: Hyperbole and the Ironic Tone of Voice". In: *Metaphor and Symbol* 10.1, pp. 21–31.

Labatut, Vincent and Xavier Bost (2019). "Extraction and Analysis of Fictional Character Networks: A Survey". In: *ACM Computing Surveys* 52.5, pp. 1–40.

Lodhi, Huma, Craig Saunders, John Shawe-Taylor, Nello Cristianini, and Chris Watkins (2002). "Text Classification Using String Kernels". In: *Journal of Machine Learning Research* 2, pp. 419–444.

Maaten, Laurens van der and Geoffrey Hinton (2008). "Visualizing Data using t-SNE". In: *Journal of Machine Learning Research* 9, pp. 2579–2605.

Manovich, Lev (2001). *The Language of New Media*. Foundational text on digital media theory. Cambridge, MA: MIT Press.

McInnes, Leland, John Healy, and James Melville (2018). "UMAP: Uniform Manifold Approximation and Projection for Dimension Reduction". In: *arXiv preprint arXiv:1802.03426*.

McLaughlin, G. Harry (1969). "SMOG Grading—A New Readability Formula". In: *Journal of Reading* 12.8, pp. 639–646.

McLuhan, Marshall (1962). *The Gutenberg Galaxy: The Making of Typographic Man*. Analysis of print's effect on culture and cognition. Toronto: University of Toronto Press.

McLuhan, Marshall (1964). *Understanding Media: The Extensions of Man*. Seminal work on media theory; introduced "the medium is the message". New York: McGraw-Hill.

McRaven, William H. (1993). "Spec Ops: Case Studies in Special Operations Warfare: Theory and Practice". Later published as book by Presidio Press, 1995. Master's thesis. Naval Postgraduate School.

Mercer, James (1909). "Functions of Positive and Negative Type, and Their Connection with the Theory of Integral Equations". In: *Philosophical Transactions of the Royal Society of London. Series A* 209. Foundational theorem establishing conditions for kernel decomposition, pp. 415–446.

Mikolov, Tomas, Kai Chen, Greg Corrado, and Jeffrey Dean (2013). "Efficient Estimation of Word Representations in Vector Space". In: *Proceedings of the International Conference on Learning Representations*. Word2Vec.

Mohammad, Saif M. and Peter D. Turney (2013). "Crowdsourcing a Word-Emotion Association Lexicon". In: *Computational Intelligence* 29.3, pp. 436–465.

Moore, Eliakim Hastings (1935). "General Analysis, Part I". In: *Memoirs of the American Philosophical Society* 1. Early development of reproducing kernel concepts.

Moretti, Franco (2005). *Graphs, Maps, Trees: Abstract Models for a Literary History*. Foundational work in distant reading. London: Verso.

Ng, Andrew Y., Michael I. Jordan, and Yair Weiss (2001). "On Spectral Clustering: Analysis and an Algorithm". In: *Advances in Neural Information Processing Systems* 14, pp. 849–856.

Ong, Walter J. (1982). *Orality and Literacy: The Technologizing of the Word*. Foundational study of oral vs. literate cultures. London: Methuen.

Pennington, Jeffrey, Richard Socher, and Christopher D. Manning (2014). "GloVe: Global Vectors for Word Representation". In: *Proceedings of the Conference on Empirical Methods in Natural Language Processing*, pp. 1532–1543.

Peyré, Gabriel and Marco Cuturi (2019). "Computational Optimal Transport". In: *Foundations and Trends in Machine Learning* 11.5-6, pp. 355–607.

Piper, Andrew (2018). *Enumerations: Data and Literary Study*. Chicago: University of Chicago Press.

Project Gutenberg (2024). *Project Gutenberg Digital Library*. https://www.gutenberg.org. Over 70,000 free ebooks.

Propp, Vladimir (1928). *Morphology of the Folktale*. First published in Russian; English translation 1958. Foundational structural analysis of narrative. Austin: University of Texas Press.

Reagan, Andrew J., Lewis Mitchell, Dilan Kiley, Christopher M. Danforth, and Peter Sheridan Dodds (2016). "The Emotional Arcs of Stories Are Dominated by Six Basic Shapes". In: *EPJ Data Science* 5.1, p. 31.

Reimers, Nils and Iryna Gurevych (2019). "Sentence-BERT: Sentence Embeddings using Siamese BERT-Networks". In: *Proceedings of the Conference on Empirical Methods in Natural Language Processing*, pp. 3982–3992.

Salton, Gerard, Anita Wong, and Chung-Shu Yang (1975). "A Vector Space Model for Automatic Indexing". In: *Communications of the ACM* 18.11. Foundational vector space model for IR, pp. 613–620.

Schölkopf, Bernhard and Alexander J. Smola (2002). *Learning with Kernels: Support Vector Machines, Regularization, Optimization, and Beyond*. Comprehensive treatment of kernel methods. Cambridge, MA: MIT Press.

Shannon, Claude E. (1948). "A Mathematical Theory of Communication". In: *Bell System Technical Journal* 27.3. Foundation of information theory, pp. 379–423.

Steinwart, Ingo and Andreas Christmann (2008). *Support Vector Machines*. New York: Springer.

Thelwall, Mike and Kayvan Kousha (2017). "Goodreads: A Social Network Site for Book Readers". In: *Journal of the Association for Information Science and Technology* 68.4, pp. 972–983.

Trefethen, Lloyd N. and David Bau (1997). *Numerical Linear Algebra*. Philadelphia: SIAM.

Underwood, Ted (2019). *Distant Horizons: Digital Evidence and Literary Change*. Chicago: University of Chicago Press.

Vaswani, Ashish, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N. Gomez, Łukasz Kaiser, and Illia Polosukhin (2017). "Attention Is All You Need". In: *Advances in Neural Information Processing Systems*. Vol. 30. The Transformer architecture.

Villani, Cédric (2009). *Optimal Transport: Old and New*. Comprehensive treatment of optimal transport theory. Berlin: Springer.

Yule, George Udny (1944). *The Statistical Study of Literary Vocabulary*. Foundational work on vocabulary richness metrics including Yule's K. Cambridge: Cambridge University Press.

Zipf, George Kingsley (1949). *Human Behavior and the Principle of Least Effort*. Foundation of quantitative linguistics. Cambridge, MA: Addison-Wesley.

Production Notes

Source Provenance

This volume presents the original theoretical framework for Story Operators—a mathematical approach to narrative analysis using Reproducing Kernel Hilbert Space (RKHS) theory. The framework synthesizes concepts from functional analysis, natural language processing, and narratology to create a rigorous foundation for computational story understanding and transformation.

RKHS Methodology

The analytical framework employs Reproducing Kernel Hilbert Space (RKHS) mathematics to map narratives as vectors in high-dimensional semantic space. Story texts are embedded using 768-dimensional dense vector representations. The cosine kernel $K(x, y) = \frac{\langle x, y \rangle}{\|x\| \|y\|}$ measures narrative similarity. Story Operators—linear transformations in RKHS—enable systematic narrative modification while preserving essential structural properties.

Editorial Process

This book was written by Fred Zimmerman. The author conceived the framework, directed the mathematical exposition, and provided editorial oversight. AI tools were used to assist with drafts of prose, mathematical notation, and explanatory sidebars.

Typesetting & Layout

This book was typeset using LuaLaTeX with the `memoir` document class. Body text is set in TeX Gyre Pagella at 11pt with TeX Gyre Heros for headings. The 7 × 10 inch trim size follows professional trade publishing standards. The design bridges arXiv mathematical publishing with high-end book typography.

Print Specifications

- **Trim Size:** 7 × 10 inches
- **Interior:** Color, 70# white paper
- **Binding:** Perfect bound softcover
- **Page Count:** 300 pages
- **ISBN:** 978-1-60888-535-0

Technical Colophon

Published by Story Operators New Media, Ann Arbor, Michigan. This is the foundational volume of the *Story Operators* series. Visualizations were generated using Google Gemini 3 Pro Image Preview. For information about the series and related analytical tools, visit `nimblebooks.com`.

First Edition: January 2026

Colophon

Story Operators: A Mathematical Framework for Narrative Discovery and Transformation was typeset in TeX Gyre Pagella (a Palatino revival) using LuaLaTeX. Chapter titles and running headers use TeX Gyre Heros (a Helvetica revival). Code listings use Menlo.

The book was designed in a style that bridges academic mathematical publishing (in the tradition of arXiv preprints and Springer monographs) with the typographic standards of high-end book publishing. Mathematics was set using $\mathcal{AMS}$-LaTeX.

All visualizations and infographics were generated using Google Gemini 3 Pro Image Preview ("nano banana pro"), specifically the `gemini-3-pro-image-preview` model.

The manuscript was written by Fred Zimmerman.

Version 2.0 — March 2, 2026

Indexes

Index of Persons

Mathematicians and Scientists

- **Amari, Shun-ichi** — mathematician; developer of information geometry; author of *Information Geometry and Its Applications* (2016)
- **Aronszajn, Nachman** — mathematician; proved the Moore-Aronszajn theorem establishing that every positive semi-definite kernel uniquely determines an RKHS (1950)
- **Berlinet, Alain** — mathematician; co-author of *Reproducing Kernel Hilbert Spaces in Probability and Statistics* (2004)
- **Christmann, Andreas** — mathematician; co-author with Steinwart of *Support Vector Machines* (2008)
- **Darwin, Charles** — naturalist; author of *The Origin of Species* and *The Voyage of the Beagle*; center of the Natural Science cluster in CodexSpace
- **Einstein, Albert** — physicist; cited for the discovery that spacetime has geometry (1915)
- **Euclid** — ancient Greek mathematician; cited for discovery that physical space has geometry (c. 300 BCE)
- **Faraday, Michael** — scientist; part of the Natural Science cluster in CodexSpace alongside Darwin, Huxley, and Lyell
- **Fisher, R. A.** — statistician; referenced in context of kernel methods and statistical foundations
- **Fourier, Joseph** — mathematician; Fourier decomposition cited as analogy for Mercer's kernel decomposition
- **Hilbert, David** — mathematician; namesake of Hilbert spaces and the RKHS framework central to the entire book
- **Huxley, Thomas Henry** — scientist and educator; part of the Natural Science cluster in CodexSpace
- **Kolmogorov, Andrey** — mathematician; referenced in the mathematical foundations
- **Lagrange, Joseph-Louis** — mathematician; referenced in context of mathematical optimization
- **Lyell, Charles** — geologist; part of the Natural Science cluster in CodexSpace
- **Mercer, James** — mathematician; Mercer's theorem establishes that continuous PSD kernels decompose into eigenvalues and eigenfunctions; founda-

tional to the spectral analysis framework
- **Moore, Eliakim Hastings** — mathematician; co-originator of the Moore-Aronszajn theorem on reproducing kernels
- **Newton, Isaac** — mathematician and physicist; *Principia Mathematica* used as embedding comparison point
- **Riemann, Bernhard** — mathematician; Riemannian manifold structure conjectured for the space of publishable narratives
- **Riesz, Frigyes** — mathematician; referenced in the functional analysis foundations of RKHS theory
- **Scholkopf, Bernhard** — machine learning researcher; co-author with Smola of *Learning with Kernels* (2002, MIT Press); foundational reference for PSD kernel closure properties
- **Schwarz, Karl Hermann** — mathematician; referenced in context of the Cauchy-Schwarz inequality
- **Smola, Alexander J.** — machine learning researcher; co-author with Scholkopf of *Learning with Kernels* (2002)
- **Steinwart, Ingo** — mathematician; co-author of *Support Vector Machines* (2008, Springer)
- **Thomas-Agnan, Christine** — mathematician; co-author of *Reproducing Kernel Hilbert Spaces in Probability and Statistics* (2004)
- **Vapnik, Vladimir** — machine learning researcher; referenced in context of support vector machines and kernel methods
- **Villani, Cedric** — mathematician; author of *Optimal Transport: Old and New* (2009, Springer)

Psychologists and Cognitive Scientists

- **Kahneman, Daniel** — psychologist; referenced in connection with Tversky's work on similarity judgments
- **Tversky, Amos** — psychologist; published landmark 1977 paper demonstrating human similarity judgments violate metric space properties; the "Tversky Challenge" is Problem 7 in the book's open problems

Computational Linguists and NLP Researchers

- **Bamman, David** — computational linguist; co-author of Bayesian mixed effects model of literary character (ACL, 2014)
- **Chambers, Nathanael** — computational linguist; co-author with Jurafsky of work on narrative event chains (ACL, 2008)
- **Chomsky, Noam** — linguist; formal grammar framework cited as parallel to RKHS imposing mathematical structure on narrative
- **Doumbouya, Moussa** — researcher at Stanford; co-author of work making Tversky similarity differentiable within neural networks (arXiv:2506.11035, 2025)

- **Gurevych, Iryna** — NLP researcher; co-author with Reimers of Sentence-BERT (EMNLP, 2019)
- **Jurafsky, Daniel** — computational linguist at Stanford; co-author of work on narrative event chains and Tversky Neural Networks
- **Manning, Christopher D.** — NLP researcher at Stanford; co-author of Tversky Neural Networks paper (2025)
- **Reagan, Andrew J.** — researcher; lead author of study finding six basic emotional arc shapes in stories (EPJ Data Science, 2016)
- **Reimers, Nils** — NLP researcher; co-author of Sentence-BERT (EMNLP, 2019), the embedding model underlying the framework
- **Vaswani, Ashish** — researcher; lead author of "Attention Is All You Need" (NeurIPS, 2017), the transformer architecture paper

Literary Theorists and Narratologists

- **Bakhtin, Mikhail** — literary theorist; referenced in context of narrative analysis frameworks
- **Barthes, Roland** — literary theorist and semiotician
- **Campbell, Joseph** — mythologist; referenced in context of archetypal narrative structures
- **Genette, Gerard** — narratologist; referenced in context of narrative theory
- **Greimas, Algirdas Julien** — semiotician; referenced in context of structural narrative analysis
- **Propp, Vladimir** — folklorist; referenced in context of narrative morphology and story structure
- **Todorov, Tzvetan** — literary theorist; referenced in context of narrative grammar

Strategic Thinkers

- **Clausewitz, Carl von** — Prussian military strategist; "Center of Gravity" concept (1832) used as source doctrine for temporal morphing into the AI era; "fog of war" concept referenced
- **Grotius, Hugo** — Dutch jurist; *Mare Liberum* (1609) cited as foundation of Freedom of Navigation doctrine
- **Liddell Hart, B. H.** — British military strategist; "indirect approach" (1929) morphed into Autonomous Maneuver doctrine
- **Machiavelli, Niccolo** — political philosopher; *The Prince* appears in random walk through embedding space
- **Mackinder, Halford J.** — geographer; "Heartland Theory" (1904) projected into space domain; author of "The Geographical Pivot of History"
- **Sun Tzu** — ancient Chinese strategist; *The Art of War* referenced; "deception" doctrine found close to modern information warfare in embedding space

- **Thucydides** — ancient Greek historian; analysis of Athenian imperial overreach found close to modern counterinsurgency doctrine

Authors and Literary Figures

- **Aquinas, Thomas** — theologian and philosopher; center of the Philosophy and Theology cluster in CodexSpace
- **Aristotle** — ancient Greek philosopher; *Politics* and *Nicomachean Ethics* as nearest neighbors to Plato; theory of tragedy referenced
- **Austen, Jane** — novelist; *Pride and Prejudice* and *Emma* used extensively as worked examples for operators, projections, and character arc analysis
- **Borges, Jorge Luis** — Argentine writer; referenced in context of literary analysis
- **Bronte, Charlotte** — novelist; *Jane Eyre* and *Wuthering Heights* used as examples; Bronte works cluster at the "passionate" end of emotional temperature dimension
- **Bulwer-Lytton, Edward** — novelist; *The Coming Race* appears in random walk from *Frankenstein* to *The Republic*
- **Bunyan, John** — author; *The Pilgrim's Progress* referenced; Biblical references scored as cultural assumption barrier (7.5)
- **Butler, Samuel** — novelist; *Erewhon* appears in random walk sequence
- **Byron, Lord** — Romantic poet; listed in the Romantic period of CodexSpace
- **Cervantes, Miguel de** — novelist; listed in the Renaissance period of CodexSpace
- **Chaucer, Geoffrey** — poet; vocabulary archaism scored at 9.5 (highest); Medieval period in CodexSpace
- **Cherry-Garrard, Apsley** — explorer and author; *The Worst Journey in the World* (1922) scored 0.89 similarity to Shackleton's *South*
- **Chesterfield, Lord** — writer; *Letters to His Son* appears in random walk sequence
- **Conrad, Joseph** — novelist; *Lord Jim* and other works; center of Adventure and Maritime Fiction cluster; early modern period
- **Crane, Stephen** — novelist; *The Red Badge of Courage* referenced for combat decision-making narrative
- **Dana, Richard Henry** — author; *Two Years Before the Mast* (1840) used as maritime comparison point
- **Dante Alighieri** — poet; listed in the Medieval period of CodexSpace
- **Dickens, Charles** — novelist; *Great Expectations* used for detailed character network analysis; vocabulary archaism scored 3.5
- **Dostoevsky, Fyodor** — novelist; Victorian era in CodexSpace (in translation); clusters at "passionate" end of emotional dimension
- **du Maurier, Daphne** — novelist; *Rebecca* cited as midpoint between romance and thriller
- **Eco, Umberto** — novelist and semiotician

- **Eliot, George** — novelist; center of Social and Domestic Fiction cluster in CodexSpace
- **Franklin, Benjamin** — *Autobiography* appears in random walk sequence
- **Frost, Robert** — poet; "The Road Not Taken" analyzed as case study for poetry embedding
- **Hardy, Thomas** — novelist; Victorian era in CodexSpace
- **Hart, Michael** — founder of Project Gutenberg (1971)
- **Hemingway, Ernest** — novelist; syntactic complexity scored at 1.5 (lowest)
- **Homer** — ancient Greek poet; *The Odyssey* (Pope translation) used as worked example for distance analysis
- **Hugo, Victor** — novelist; listed in CodexSpace corpus
- **James, Henry** — novelist; formal fiction; syntactic complexity scored 7.5; center of Social and Domestic Fiction cluster
- **Keats, John** — Romantic poet; "Ode to a Nightingale" used as worked example; poetry embedding case study
- **Kipling, Rudyard** — author; colonial attitudes scored as sensitivity issue (7.0)
- **Locke, John** — philosopher; clusters at "cool, analytical" end of emotional temperature dimension
- **London, Jack** — novelist; center of Adventure and Maritime Fiction cluster
- **Malory, Thomas** — author; Medieval period in CodexSpace
- **Marlowe, Christopher** — playwright; Renaissance period in CodexSpace
- **Melville, Herman** — novelist; *Moby Dick* used as embedding comparison point; center of maritime fiction cluster
- **Mill, John Stuart** — philosopher; *On Liberty* appears in random walk; formal non-fiction; center of Philosophy cluster
- **Miller, Madeline** — novelist; *Circe* cited as example of Penelope-perspective adaptation of classical material
- **Milton, John** — poet; syntactic complexity scored at 9.0 (highest)
- **More, Thomas** — author; *Utopia* (1516) bridges philosophical and science fiction traditions in embedding space
- **Ovid** — Roman poet; Classical antiquity in CodexSpace
- **Paine, Thomas** — political writer; *The Rights of Man* and *Common Sense* appear in random walk
- **Plato** — philosopher; *The Republic* used as starting point for random walk sessions; center of Philosophy cluster
- **Poe, Edgar Allan** — author; center of Gothic and Supernatural cluster; emotional temperature at "passionate" end
- **Pope, Alexander** — poet; 1726 translation of *The Odyssey* used as worked example; classical references scored 8.0
- **Radcliffe, Ann** — novelist; center of Gothic and Supernatural cluster
- **Richardson, Samuel** — novelist; *Clarissa* at 1M words scored 10.0 for length barrier; epistolary pace scored 8.5
- **Riordan, Rick** — novelist; Percy Jackson series cited as middle-grade adven-

ture adaptation example
- **Rooney, Sally** — novelist; *Normal People* (2018) cited as contemporary novel of manners examining class in Ireland
- **Rousseau, Jean-Jacques** — philosopher; *The Social Contract* appears in random walk
- **Scott, Robert Falcon** — explorer; part of Antarctic exploration cluster in embedding space
- **Shackleton, Ernest** — explorer; *South* (1919) used as primary worked example for embedding, navigation, and transformation operators
- **Shakespeare, William** — playwright and poet; Sonnets used for multi-level embedding analysis; major tragedies used for barycenter and spectral clustering examples; plays analyzed throughout
- **Shelley, Mary** — novelist; *Frankenstein* (1818) used as starting point for random walk; center of Gothic cluster
- **Sittenfeld, Curtis** — novelist; *Eligible* (2016) cited as modern retelling of *Pride and Prejudice*
- **Spenser, Edmund** — poet; Renaissance period in CodexSpace
- **Stevenson, Robert Louis** — novelist; *Dr Jekyll and Mr Hyde* scored 0.83 similarity to *Frankenstein*
- **Stoker, Bram** — novelist; *Dracula* scored 0.79 similarity to *Frankenstein*; Gothic cluster
- **Stoppard, Tom** — playwright; *Rosencrantz and Guildenstern Are Dead* (1966) analyzed for adaptation distance from Shakespeare
- **Tolstoy, Leo** — novelist; *War and Peace* used as worked example for genre transformation to thriller; digressions scored 7.0 for pacing
- **Trollope, Anthony** — novelist; center of Social and Domestic Fiction cluster
- **Twain, Mark** — author; racial language scored as sensitivity issue (6.5); informal fiction reference point
- **Verne, Jules** — novelist; *Twenty Thousand Leagues* and *From the Earth to the Moon* appear in random walk
- **Virgil** — Roman poet; Classical antiquity in CodexSpace
- **Vonnegut, Kurt** — novelist; "shapes of stories" hypothesis formalized as the Universal Story Conjecture (Conjecture 3)
- **Wells, H. G.** — novelist; *The Time Machine*, *The War of the Worlds*, *The Island of Doctor Moreau* in random walk sequence
- **Wharton, Edith** — novelist; early modern period in CodexSpace
- **Whitman, Walt** — poet; *Leaves of Grass* scored 0.71 similarity to Shakespeare's Sonnets
- **Wouk, Herman** — novelist; *The Caine Mutiny* cited for naval command breakdown narrative
- **Zimmerman, Fred** — author; primary author of the Story Operators Guide, with Hilmar AI; publisher at Nimble Books LLC

Translators and Editors

- **Griffith, Samuel B.** — translator of Sun Tzu's *The Art of War* (1963, Oxford)
- **Howard, Michael** — co-translator of Clausewitz's *On War* (1976, Princeton)
- **Paret, Peter** — co-translator of Clausewitz's *On War* (1976, Princeton) # Index of Places
- **Antarctica** — setting of Shackleton's *South* and the Imperial Trans-Antarctic Expedition (1914–1917); anchor point for the maritime exploration cluster in CodexSpace
- **Athens** — ancient city-state; Thucydides' analysis of Athenian imperial overreach found structurally similar to modern counterinsurgency doctrine
- **Ireland** — setting of Sally Rooney's *Normal People* (2018), cited as contemporary novel examining class and romance
- **London** — setting of Pip's "great expectations" in Dickens' novel; one of three social clusters in the character network analysis (Herbert Pocket, Wemmick, Jaggers)
- **The Marshes** — fictional setting; Pip's childhood cluster in *Great Expectations* character network analysis
- **Napoleonic-era Europe** — historical setting of Tolstoy's *War and Peace*; setting preserved in the genre transformation worked example
- **Pemberley** — fictional estate in Austen's *Pride and Prejudice*; referenced in genre transformation and character arc analysis
- **Satis House** — fictional setting; Miss Havisham's cluster in *Great Expectations* character network analysis
- **South China Sea** — geopolitical reference point; Freedom of Navigation doctrine US-China comparison using embedding space # Index of Organizations

Publishers and Imprints

- **MIT Press** — publisher of Scholkopf and Smola's *Learning with Kernels* (2002)
- **Nimble Books LLC** — publisher of the Story Operators Guide and the RKHS Integrated Series
- **Oxford University Press** — publisher of Griffith's translation of Sun Tzu's *The Art of War* (1963)
- **Princeton University Press** — publisher of Howard and Paret's translation of Clausewitz's *On War* (1976)
- **Springer** — publisher of multiple foundational references: Berlinet and Thomas-Agnan (2004), Steinwart and Christmann (2008), Villani (2009), Amari (2016)

Academic Institutions

- **Stanford University** — home institution of Doumbouya, Jurafsky, and Manning; Tversky Neural Networks research (2025)

Digital Libraries and Data Sources

- **DeepMind** — curated the PG-19 dataset from Project Gutenberg for language modeling research
- **Google Books** — large-scale book digitization project; millions of scanned volumes referenced as potential corpus expansion
- **HathiTrust** — digital library; referenced as potential source for expanding CodexSpace beyond PG-19
- **Internet Archive** — digital library; referenced alongside HathiTrust and Google Books as corpus expansion source
- **Library of Congress** — cited for estimate that approximately 15 million books have been published in English
- **Project Gutenberg** — oldest digital library, founded by Michael Hart in 1971; source of the PG-19 dataset (28,602 pre-1919 English-language texts) that forms the CodexSpace corpus; over 70,000 total English-language texts

Academic Conferences and Journals

- **ACL (Association for Computational Linguistics)** — venue for Chambers and Jurafsky (2008) and Bamman et al. (2014); target venue for research papers
- **COLING** — computational linguistics conference; target venue for irony detection research
- **EMNLP (Empirical Methods in Natural Language Processing)** — venue for Reimers and Gurevych's Sentence-BERT (2019); target venue for counterfactual transforms paper
- **EPJ Data Science** — journal; venue for Reagan et al. (2016) on emotional arcs of stories
- **Geographical Journal** — venue for Mackinder's "Geographical Pivot of History" (1904)
- **NAACL (North American Chapter of the ACL)** — target venue for computational linguistics research
- **NeurIPS** — venue for Vaswani et al.'s "Attention Is All You Need" (2017)
- **Transactions of the American Mathematical Society** — venue for Aronszajn's foundational RKHS paper (1950)

Distribution and Technology Platforms

- **Apple Books** — digital distribution channel for Nimble Books publications
- **Google Play** — digital distribution channel for Nimble Books publications

- **LSI / IngramSpark** — print distribution infrastructure for Nimble Books publications

Other Organizations

- **BigFiveKiller.online** — web platform for Story Operators tools and RKHS exploration
- **Disney** — referenced for adaptation of *Hamlet* into *The Lion King*; measured as greater adaptation distance than Stoppard's version
- **NimbleBooks.com** — website of Nimble Books LLC; platform for tools and code described in the book
- **Story Operators New Media** — imprint name associated with the RKHS series